



✓ [Xâu Ký Tự Cơ Bản]. Bài 6. Sắp xếp chữ số

C

C++ CB NC

C++ NC

DSA

JAVA OOP

 View
as PDF

Cho số nguyên không âm **N**, hãy tiến hành sắp xếp các chữ số của **N** theo thứ tự tăng dần rồi in ra màn hình, trong trường hợp số sau khi sắp xếp xuất hiện các chữ số 0 ở đầu thì ra không in những chữ số 0 vô nghĩa này.

[Submit solution](#)

Đầu vào

Dòng duy nhất chứa số nguyên dương **N**

Giới hạn

 $0 \leq N \leq 10^{18}$

Đầu ra

In ra số **N** sau khi sắp xếp

Ví dụ :

Input 01

999968677

Copy

Output 01

667789999

Copy

Input 02

[My submissions](#)[All submissions](#)[Best submissions](#)✓ **Points:** 1.00 (partial)🕒 **Time limit:** 1.0s📄 **Memory limit:** 256M💻 **Input:** stdin🖨️ **Output:** stdout📝 **Problem source:**
28Tech➤ **Problem type**▼ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



Output 02

2288

Copy

Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.

^
-1
v



zXCczxvzxv

commented 7:13:39 pm, 22/01/2026

**include <bits/stdc++.h>**

```
using namespace std; int main(){ iosbase::syncwith_stdio(false);
cin.tie(NULL); string n; cin>>n; sort(n.begin(),n.end()); long long val =
stoll(n); cout<< val << "\n"; return 0; }
```

^
-1
v



nguyen_duc_lam_348

commented 1:42:12 am, 31/12/2025

← edited

**include<stdio.h>**
include<stdlib.h>
include<ctype.h>
include<string.h>

```
void bai6(char c[]){ int n=strlen(c); char tmp; for (int i=0;i<n;i++){ int
min=i; for (int j=i+1;j<n;j++){ if (c[j]<=c[min]){ min=j; } } tmp=c[i];
c[i]=c[min]; c[min]=tmp; } printf("%lld",atoll(c)); } int main(){ char
c[10005]; fgets(c,sizeof(c),stdin); c[strlen(c)-1]='\0'; bai6(c); return 0; }
```



Hello, Nguyễn Bảo Toàn.

-2
▼

theguy777_jaboi



ae nếu input: 0 thì output ntn?

^
-2
▼

commented 3:45:33 pm, 14/11/2025



skjafirjmm

include <bits/stdc++.h>

using namespace std;

```
using ll=long long; int main(){ string s; cin>>s; multiset<ll> se;
for(int i=0; i<s.size(); i++){ if(s[i]!='0') continue; se.insert(s[i]-'0'); }
if(se.empty()){ cout<<0; return 0; } for(auto x:se){ cout<<x; } }
```

^
-2
▼

commented 3:52:15 pm, 06/09/2025



bengokyeuanh99

Full AC

include <iostream>
include <string>
include <algorithm>

using namespace std;

```
string sortDigitsAscending(const string& number) { string
sortedNumber = number; sort(sortedNumber.begin(),
sortedNumber.end()); return sortedNumber; }
```

```
string removeLeadingZeros(const string& number) { size_t
firstNonZero = number.findfirstnotof('0'); if (firstNonZero ==
string::npos) return "0"; return number.substr(firstNonZero); }
```

```
string processNumber(const string& number) { string sorted =
sortDigitsAscending(number); return removeLeadingZeros(sorted); }
```

```
int main() { ios::syncwithstdio(false); cin.tie(nullptr);
```



Hello, Nguyễn Bảo Toàn.

```
cin >> inputNumber;

cout << processNumber(inputNumber) << '\n';
return 0;
```

}

^
-2
v



Kaybe

commented 6:44:28 am, 31/03/2025



```
include <stdio.h>
include <stdlib.h>
include <string.h>
include <ctype.h>
```

```
int cmp(const void *a, const void *b){ char *x = (char *)a; char *y =
(char *)b; return *x - *y; } int main(){ char c[10005]; scanf("%s", c);
qsort(c, strlen(c), sizeof(char), cmp); int i = 0; while(c[i] == '0' && i <
strlen(c) - 1){ ++i; } for(int j = i; j < strlen(c); j++){ printf("%c", c[j]); } }
```

^
-12
v



Malaze_KL

commented 5:56:21 am, 08/06/2024



This comment is hidden due to too much negative feedback. [Show it anyway.](#)



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**