



✓ [Xâu Ký Tự]. Bài 10. Liệt kê từ

[View
as PDF](#)

Cho một xâu kí tự **S** bao gồm các chữ cái và dấu cách, một từ được định nghĩa là các kí tự liên tiếp không chứa dấu cách, hãy liệt kê các từ **khác nhau** trong xâu **S**, đầu tiên hãy liệt kê các từ khác nhau theo **thứ tự từ điển tăng dần**, sau đó liệt kê các từ theo **thứ tự xuất hiện trong xâu**.

[Submit solution](#)[My submissions](#)[All submissions](#)[Best submissions](#)

Đầu vào

Dòng duy nhất chứa xâu **S**.

Giới hạn

 $1 \leq \text{len}(S) \leq 100000$

Đầu ra

Dòng đầu tiên in ra các từ trong xâu theo thứ tự từ điển.

Dòng thứ hai in ra các từ theo thứ tự xuất hiện trong xâu.

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

🖨 **Input:** stdin

🖨 **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

✓ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch

Ví dụ :

Input 01

```
python java php php java python
```

[Copy](#)

Output 01

```
java php python  
python java php
```

[Copy](#)

[report an issue](#)

COMMENTS

Please read the [guidelines](#) before commenting.

^
-4
v



commented 10:19:02 am, 09/04/2025



Kaybe

```
include <stdio.h>  
include <string.h>  
include <ctype.h>  
include <stdlib.h>
```

```
int cmp(const void *a, const void *b){ char *x = (char *)a; char *y =  
(char *)b; return strcmp(x, y); } char a[10000][50]; char b[10000][50];  
int main(){ char c[100005]; fgets(c, 100005, stdin); c[strlen(c) - 1] =  
'\0'; char *token = strtok(c, " "); int n = 0; while(token != NULL){ int  
check = 1; for(int j = 0; j < n; j++){ if(strcmp(a[j], token) == 0){ check  
= 0; break; } } if(check){ strcpy(a[n], token); strcpy(b[n], token); ++n; }  
token = strtok(NULL, " "); } qsort(a, n, sizeof(a[0]), cmp); for(int i = 0; i  
< n; i++){ printf("%s", a[i]); if(i != n - 1){ printf(" "); } } printf("\n");  
for(int i = 0; i < n; i++){ printf("%s", b[i]); if(i != n - 1){ printf(" "); } } }
```



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**