





✓ [Xâu Ký Tự]. Bài 12. Sắp xếp từ 2

[View
as PDF](#)

Cho một xâu kí tự **S** bao gồm các chữ cái và dấu cách, một từ được định nghĩa là các kí tự liên tiếp không chứa dấu cách, hãy sắp xếp các từ **thuận nghịch khác nhau** trong xâu theo thứ tự từ **chiều dài tăng dần**, nếu 2 từ thuận nghịch có cùng chiều dài thì từ nào **xuất hiện trước sẽ được in ra trước**.

[Submit solution](#)[My submissions](#)[All submissions](#)[Best submissions](#)

Đầu vào

Dòng duy nhất chứa xâu **S**.

Giới hạn

 $1 \leq \text{len}(S) \leq 100000$

Đầu ra

In ra các từ theo thứ tự sắp xếp yêu cầu, các từ được in cách nhau một dấu cách.

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

⌨ **Input:** stdin

🖨 **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

✓ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch

Ví dụ :

Input 01

```
php aba aaaa nguyen huu hoc pop
```

[Copy](#)

Output 01

```
php aba pop aaaa
```

[Copy](#)



Please read the [guidelines](#) before commenting.



Khanh_Vy_NN_2007

commented 12:00:55 am, 14/05/2026



<https://onecompiler.com/cpp/44p6qbywt>



tuong_706

commented 1:02:28 pm, 13/10/2025



```
include <stdio.h>  
include <string.h>  
include <ctype.h>  
include <stdlib.h>
```

```
// Ham check co phai xau thuan nghich khong  
int isreverse(char c[]){  
    int l = 0, r = strlen(c) - 1; while (l <= r){ if (c[l] != c[r]){ return 0; } l++;  
    r--; } return 1; }
```

```
// Ham comp so sanh chieu dai cua 2 xau ki tu  
int lencomp(const void *a, const void *b){  
    char *x = (char *)a; char *y = (char *)b; if (strlen(x) != strlen(y)){  
        return strlen(x) - strlen(y); } else{ // Neu co cung chieu dai se in ra xau co dia chi be hon, tuc la xuat hien truoc  
        return x-y; } }
```

```
int main(){ // Nhap xau ki tu  
    char c[100001]; fgets(c, 100001, stdin);  
    c[strlen(c) - 1] = '\0'; // Tach cac tu thuan nghich ra va luu vao mang  
    char memo[10000][100] = {0}; int n=0; char *word = strtok(c, " ");  
    while (word != NULL){ if (isreverse(word)){ // Kiem tra tu do da xuat hien chua?  
        int checker = 1; for (int j=0; j<n; j++){ if (strcmp(memo[j], word) == 0){ checker=0; } }  
        if (checker == 1){ strcpy(memo[n++], word); } } word = strtok(NULL, " "); }  
    qsort(memo, n, sizeof(memo[0]), lencomp);  
    for (int i=0; i<n; i++){ printf("%s ", memo[i]); } return 0; }
```



-2
▼



Kaybe

```
include <stdio.h>  
include <string.h>  
include <ctype.h>  
include <stdlib.h>
```

```
int tn(char c[]){ int l = 0, r = strlen(c) - 1; while(l <= r){ if(c[l] != c[r]){  
return 0; } ++l, --r; } return 1; } void sx(char a[][50], int n){ for(int i = 0;  
i < n; i++){ int pos = i - 1; char tmp[100]; strcpy(tmp, a[i]); while(pos  
>= 0 && strlen(tmp) < strlen(a[pos])){ strcpy(a[pos + 1], a[pos]); --  
pos; } strcpy(a[pos + 1], tmp); } } char c[100001]; int main(){ fgets(c,  
100001, stdin); c[strlen(c) - 1] = '\0'; char a[10000][50]; int n = 0; char  
*token = strtok(c, " "); while(token != NULL){ if(tn(token)){ int check  
= 1; for(int j = 0; j < n; j++){ if(strcmp(a[j], token) == 0){ check = 0;  
break; } } if(check){ strcpy(a[n], token); ++n; } } token = strtok(NULL, "  
"); } sx(a, n); for(int i = 0; i < n; i++){ printf("%s ", a[i]); } }
```

New comment

Post!