



[Lý Thuyết Số - Toán Học]. Bài 21. Số chính phương trong đoạn

[C](#)[C++ CB NC](#)[C++ NC](#)[DSA](#)[JAVA OOP](#)[PYTHON](#)[View as PDF](#)

In ra các số chính phương trong đoạn từ **a** tới **b**.

Gợi ý : Số chính phương có dạng $i^2 \Rightarrow a \leq i^2 \leq b \Rightarrow \sqrt{a} \leq i \leq \sqrt{b} \Rightarrow$ Bạn chỉ cần duyệt từ $\sqrt{a}$ tới $\sqrt{b}$ và in ra bình phương của số i , khi đó sẽ không bị quá thời gian.

Đầu vào

2 số nguyên dương **a**, **b**

Giới hạn

$1 \leq a \leq b \leq 10^{12}$

Đầu ra

In ra các số chính phương trong đoạn giữa 2 số **a**, **b** trên một dòng. Các số cách nhau một khoảng trắng.

Ví dụ :

Input 01

10 20

[Copy](#)

Output 01

[Copy](#)[Submit solution](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

💻 **Input:** stdin

🖨️ **Output:** stdout

📄 **Problem source:**
28Tech

➤ **Problem type**


✓ **Allowed languages**
C, C#, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.



emsinhvien


commented 6:17:28 pm, 14/06/2025



```
include<stdio.h>  
include<math.h>
```

```
int cp(int n){ if( n < 0 ) return 0; int can = sqrt(n); return (can * can  
== n); }
```

```
int main(){ long long a , b; scanf("%lld%lld",&a, &b); if(a < b){ for(int i  
= a ; i <= b ; i++){ if(cp(i)) printf("%d ",i); } } else if ( a > b ){ for(int i =  
b ; i <= a ; i++){ if(cp(i)) printf("%d ",i); } } }
```



emsinhvien

commented 6:17:16 pm, 14/06/2025



```
include<stdio.h>  
include<math.h>
```

```
int cp(int n){ if( n < 0 ) return 0; int can = sqrt(n); return (can * can  
== n); }
```

```
int main(){ long long a , b; scanf("%lld%lld",&a, &b); if(a < b){ for(int i  
= a ; i <= b ; i++){ if(cp(i)) printf("%d ",i); } } else if ( a > b ){ for(int i =  
b ; i <= a ; i++){ if(cp(i)) printf("%d ",i); } } }
```



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**