



✓ [Sắp Xếp - Tìm Kiếm]. Bài 7. Sắp xếp chèn

C

C++ CB NC

C++ NC

DSA

JAVA OOP

View as PDF

Cho mảng số nguyên **A[]** có **N** phần tử, hãy in ra các bước của thuật toán sắp xếp chèn

[Submit solution](#)

Đầu vào

Dòng đầu tiên là số nguyên dương **N**.

Dòng thứ 2 là **N** phần tử trong mảng, các phần tử viết cách nhau một dấu cách.

Giới hạn

 $1 \leq N \leq 10^3$ $0 \leq A[i] \leq 10^9$

Đầu ra

In ra các bước của thuật toán sắp xếp chèn

Ví dụ :

Input 01

```
7
56 73 15 64 86 61 50
```

[Copy](#)

Output 01

[Copy](#)[My submissions](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

⌨ **Input:** stdin

🖨 **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

▼ **Allowed languages**
C, C#, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



Buoc 2: 15 56 73 64 86 61 50
 Buoc 3: 15 56 64 73 86 61 50
 Buoc 4: 15 56 64 73 86 61 50
 Buoc 5: 15 56 61 64 73 86 50
 Buoc 6: 15 50 56 61 64 73 86

Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.

^
-3
v



Sam_430

commented 4:01:47 pm, 06/05/2025



include "stdio.h"
include "string.h"

```
//in mang void printf_array(int a[], int n) { for(int i = 0; i < n; i++) {
printf("%d ", a[i]); }
printf("\n"); }
```

```
//doi cho void swap(int *a, int *b) { int tmp = *a; *a = *b; *b = tmp; }
```

```
//O(n^2) -> chen ptu dan duoc xet vaof mang da duoc sap xep void
insertionsort(int arr[], int n) { for(int i = 1; i < n; i++) { int indexmin =
i; //can xac dinh vi tri tk nho nhat for(int j = i-1; j >= 0; j--) { if(arr[j] >
arr[indexmin]) { swap(&arr[indexmin], &arr[j]); index_min = j; //thay
doi index sau moi lan doi } }
```

```
printf("Buoc %d: ", i);
printf_array(arr, n);
}
```

Copy

```
}
```

```
int main() { int n; scanf("%d", &n); int arr[n]; for(int i = 0; i < n; i++) {
scanf("%d", &arr[i]); }
```



Hello, Nguyễn Bảo Toàn.

```
return 0;
```

```
}
```

^
-3
v



commented 8:44:57 am, 17/03/2025

**Kaybe**

```
include <stdio.h>  
include <stdlib.h>  
include <math.h>
```

```
void insertionSort(int a[], int n){ for(int i = 1; i < n; i++){ int pos = i -  
1, value = a[i]; while(pos >= 0 && value < a[pos]){ a[pos + 1] =  
a[pos]; --pos; } a[pos + 1] = value; printf("Buoc %d: ", i); for(int i = 0; i  
< n; i++){ printf("%d ", a[i]); } printf("\n"); } }
```

```
int main(){ int n; scanf("%d", &n); int a[n]; for(int i = 0; i < n; i++){  
scanf("%d", &a[i]); } insertionSort(a, n); return 0; }
```

New comment

Post!

