



✓ [Xâu Ký Tự Cơ Bản]. Bài 25. Phone number check



CB NC



NC



OOP

[View
as PDF](#)

Một số điện thoại được coi là hợp lệ nếu nó có 10 hoặc 11 chữ số và bắt đầu bằng chữ số 0.

Ngoài ra nó không được chứa bất cứ một ký tự đặc biệt nào ngoài các chữ số. Cho 1 loạt các số điện thoại, bạn hãy in ra xem số điện thoại nào hợp lệ và không hợp lệ?

[Submit solution](#)

Đầu vào

- Dòng 1 là **T** : số lượng số điện thoại
- **T** dòng tiếp theo mỗi dòng là một số điện thoại

Giới hạn

 $1 \leq T \leq 1000$

Đầu ra

In ra **YES** hoặc **NO** với mỗi số điện thoại tùy thuộc vào nó có hợp lệ hay không?

Ví dụ :

Input 01

[Copy](#)[My submissions](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

⌨ **Input:** stdin

🖨 **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

▼ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



```
k20472090a
20400855kk8
k0k02d0078
0sks0s0k0
160080955800
0965303260
```

Output 01

```
NO
NO
NO
NO
NO
YES
```

Copy

Comments

Report an issue

Please read the [guidelines](#) before commenting.



dquan0337

commented 11:17:23 pm, 04/11/2025



```
include <bits/stdc++.h>
define FOR(i,a,b) for(int i = a; i < b; i++)
```

```
using namespace std; const int nmax = 1e6+5; bitset<nmax + 1>
prime; void DANGBAONGHI(){ prime.set(); prime[0] = prime[1] =
false; for (int i = 4; i <= nmax; i += 2) prime[i] = false; for (int i = 3; i
* i <= nmax; i += 2){ if (prime[i]){ for (int j = i * i; j <= nmax; j += 2 *
i) prime[j] = false; } } } bool PhoneNumber(string s){ if (s[0] != '0')
return false; if (s.size() < 10 || s.size() > 11) return false; for (size_t i =
1; i < s.size(); i++){ if (s[i] < '0' || s[i] > '9') return false; } return true; }
int n,cnt = 0,Max = 0,sum = 0,MaxSum = 0,idx = -1,PreSum; string s;
```



Hello, Nguyễn Bảo Toàn.

```
cin >> s; cout << (PhoneNumber(s) ? "YES" : "NO") << '\n'; } return 0; }
```



commented 9:05:29 am, 08/04/2025



Kaybe

```
include <stdio.h>  
include <string.h>  
include <ctype.h>
```

```
int check(char c[]){ if(strlen(c) != 10 && strlen(c) != 11){ return 0; }  
if(c[0] != '0'){ return 0; } for(int i = 0; i < strlen(c); i++){ if(!isdigit(c[i])){  
return 0; } } return 1; } int main(){ int t; scanf("%d", &t);  
while(getchar() != '\n'); char c[10005]; while(t--){ scanf("%s", c);  
if(check(c)){ printf("YES\n"); } else printf("NO\n"); } }
```

New comment

Post!

Được phát triển bởi **28TECH.COM.VN**