



✓ [Xâu Ký Tự]. Bài 23. Ghép xâu

[View
as PDF](#)

Cho các từ chỉ bao gồm chữ cái in hoa và in thường, bạn được yêu cầu ghép các từ này lại với nhau sao cho từ được ghép lại sau cùng có thứ tự từ điển lớn nhất.

Gợi ý : Không phải sắp xếp giảm dần xong in ra đâu nhé, cần nối 2 xâu vào với nhau và chọn thứ tự từ điển lớn hơn

Đầu vào

Dòng đầu tiên là số nguyên dương **N** - số lượng từ

Dòng thứ 2 gồm **N** từ, mỗi từ cách nhau một dấu cách.

Giới hạn

$1 \leq N \leq 1000$

Đầu ra

In ra xâu sau khi ghép.

Ví dụ :

Input 01

```
4
28tech dsa cpp learn
```

[Copy](#)

Output 01

[Copy](#)[Submit solution](#)[My submissions](#)[All submissions](#)[Best submissions](#)

✓ **Points:** 1.00 (partial)

🕒 **Time limit:** 1.0s

📄 **Memory limit:** 256M

⌨ **Input:** stdin

🖨 **Output:** stdout

📝 **Problem source:**
28Tech

➤ **Problem type**

▼ **Allowed languages**
C, C++, Java, Kotlin,
Pascal, PyPy, Python,
Scratch



Comments

[Report an issue](#)

Please read the [guidelines](#) before commenting.

0



Khanh_Vy_NN_2007

commented 10:24:18 pm, 15/05/2026



<https://onecompiler.com/cpp/44pcj7wj6>

-2



Quan_Pham

commented 9:05:34 pm, 06/10/2025



$a + b > b + a$

-3



Kaybe

commented 10:31:14 am, 12/04/2025



```
include <stdio.h>
include <string.h>
include <ctype.h>
include <stdlib.h>
```

```
int cmp(const void *a, const void *b){ char *x = (char *)a; char *y =
(char *)b; char xy[1000], yx[1000]; strcpy(xy, x), strcat(xy, y); strcpy(yx,
y), strcat(yx, x); return strcmp(yx, xy); }
```

```
int main(){ int n; scanf("%d", &n); char a[n][100]; for(int i = 0; i < n;
i++){ scanf("%s", a[i]); } qsort(a, n, sizeof(a[0]), cmp); for(int i = 0; i <
n; i++){ printf("%s", a[i]); } }
```



Hello, Nguyễn Bảo Toàn.

Post!

Được phát triển bởi **28TECH.COM.VN**