

Stop bad data at the keystroke.

The **Universal Field Validator** adds five action tags to REDCap that catch typos, contradictions, omissions and duplicates while the field is still being typed — no server-wide admin request required.



ReAnalytics & Consulting
Data Consulting, BI & Computerized
Accounting Services

The five action tags

LIMITATION → RESOLUTION

ACTION TAG	REDCAP LIMITATION	HOW THE MODULE SOLVES IT
@UVALIDATE	Stock validation checks the shape of data only — never a single-character typo or digit swap inside an ID. Custom regex normally needs a server-wide administrator.	Recomputes check-character algorithms (ISO 7064, Verhoeff) live as the user types, and lets project designers set custom regex per field without an admin.
@UVASSERT	Nothing blocks a bad relationship between fields at entry: branching logic only hides fields, and range checks give non-binding warnings.	Enforces cross-field logic — an end date after its start date — as data is typed, with an optional hard block until it is corrected.
@UVREQUIRED	The native required flag is unconditional and raises only a soft warning that users can dismiss in one click.	Adds conditional requirements that switch on and off with live data, and upgrades the warning to a compulsory save block .
@UVUNIQUE	No real-time, field-level uniqueness check exists, so duplicate records surface later as retrospective cleanup.	Runs a live AJAX check against every record in the project — or a scope such as a DAG — stopping duplicate identifiers before they save.
@UVCHOICES	Native @HIDECHOICE is static and cannot respond to live form changes, so designers add redundant fields and branching to surface the right options.	Filters radio, dropdown and checkbox options dynamically — cascading menus inside one field, no duplication, a simpler data dictionary.

AND AFTER THE FACT

Validation scan — the retrospective sweep

Re-runs every configured rule across the whole project to surface violations that predate a rule or arrived by API or Data Import Tool. Opened from the left-hand menu with design rights; the report and its CSV name record, event, instance and field — never the stored value.



INSTALL THE MODULE

Universal Field Validator

github.com/NghaReformer/redcap-universal-validator



MINT THE IDENTIFIERS

ID Minter

Generate check-character IDs the validator verifies — idminter.com



ReAnalytics & Consulting
Data Consulting, BI & Computerized
Accounting Services

CONTRIBUTE • TEST • GIVE FEEDBACK

Pilot the module in your own project, open an issue or pull request on GitHub, or write with feedback and enquiries — contributors and test sites are welcome.

Ngha Ndze Mbuh
+237 676 651 837 · ngha.mbuh@gmail.com

Catch the typo before it becomes a record.

Five action tags that validate REDCap data *while it is still being typed* — check characters, cross-field logic, conditional requirements, live uniqueness and dynamic choices. Drop the module into a project; no server-wide administrator request required.

LIVE CHECK CHARACTERS
HARD SAVE BLOCKS
NO ADMIN REQUIRED

ACTION TAG	REDCAP LIMITATION	HOW IT IS RESOLVED
@UVALIDATE	Stock validation checks the shape of data only — never a single-character typo or digit swap inside an ID. Custom regex needs a server admin.	Recomputes check-character algorithms (ISO 7064, Verhoeff) live as the user types, and allows custom regex per field with no admin.
@UVASSERT	Nothing blocks a bad relationship between fields: branching logic only hides fields; range checks give non-binding warnings.	Enforces cross-field logic — end date after start date — as data is typed, with an optional hard block on saving.
@UVREQUIRED	The native required flag is unconditional and raises only a soft warning users dismiss in one click.	Adds conditional requirements driven by live data and upgrades the warning to a compulsory save block .
@UVUNIQUE	No real-time, field-level uniqueness check exists, so duplicates surface later as retrospective cleanup.	Runs a live AJAX check across every record — or a scope such as a DAG — stopping duplicate identifiers before they save.
@UVCHOICES	Native @HIDECHOICE is static , so designers add redundant fields and branching to surface the right options.	Filters radio, dropdown and checkbox options dynamically — cascading menus in one field, a simpler data dictionary.

Validation scan

The retrospective sweep across records already collected

Re-runs every configured rule across the whole project to surface violations that predate a rule or arrived by API or Data Import Tool. Opened from the left-hand menu with design rights; the report and its CSV name record, event, instance and field — never the stored value.

CONTRIBUTE • TEST • GIVE FEEDBACK Pilot it in your own project, open an issue or pull request on GitHub, or write with feedback — contributors and test sites are welcome.



INSTALL

The module on GitHub

github.com/NghaReformer/redcap-universal-validator



MINT IDS

ID Minter

idminter.com

ENQUIRIES & CONTRIBUTIONS

Ngha Ndze Mbuh

+237 676 651 837

ngha.mbuh@gmail.com

Five tags. Zero bad *records.*

Validation that runs on every keystroke: check characters, cross-field assertions, conditional requirements, live uniqueness and dynamic choices — installed per project, no server-wide admin request.

TYPOS CAUGHT LIVE
DUPLICATES STOPPED
SAVES BLOCKED ON ERROR

ACTION TAG	LIMITATION IN REDCAP	RESOLUTION
@UVALIDATE	Checks the shape of data only — never a single-character typo or digit swap in an ID; custom regex needs a server admin.	Recomputes check-character algorithms (ISO 7064, Verhoeff) live, plus per-field regex with no admin.
@UVASSERT	Nothing blocks a bad relationship between fields: branching only hides, range checks only warn.	Enforces cross-field logic (end date after start date) as data is typed, with an optional hard block .
@UVREQUIRED	The required flag is unconditional and raises a soft warning users dismiss in one click.	Adds conditional requirements from live data and a compulsory save block .
@UVUNIQUE	No real-time uniqueness check at field level, so duplicates become retrospective cleanup.	A live AJAX check across all records — or a DAG scope — stops duplicate identifiers before saving.
@UVCHOICES	Native @HIDECHOICE is static , forcing redundant fields and branching to show the right options.	Filters choices dynamically — cascading menus in a single field, a simpler data dictionary.

Validation scan

The retrospective sweep across records already collected

Re-runs every configured rule across the whole project to surface violations that predate a rule or arrived by API or Data Import Tool. Opened from the left-hand menu with design rights; the report and its CSV name record, event, instance and field — never the stored value.



INSTALL THE MODULE

Universal Field Validator

github.com/NghaReformer/redcap-universal-validator



MINT THE IDENTIFIERS

ID Minter

Check-character IDs the validator verifies — idminter.com

CONTRIBUTE • TEST • GIVE FEEDBACK

Pilot the module, open an issue or pull request on GitHub, or write with feedback — contributors and test sites welcome.

Ngha Ndze Mbuh
+237 676 651 837 · ngha.mbuh@gmail.com
ReAnalytics & Consulting



ReAnalytics &
Consulting
Data Consulting, BI &
Computerized Accounting
Services

REDCAP EXTERNAL MODULE

Universal Field Validator

Five action tags that validate data on every keystroke — catching typos, contradictions, omissions and duplicates before a record is ever saved.

CHECK CHARACTERS

CROSS-FIELD LOGIC

LIVE UNIQUENESS

NO ADMIN REQUIRED



INSTALL
Module on GitHub
github.com/NghaReformer/redcap-universal-validator



MINT IDS
ID Minter
Check-character IDs —
idminter.com

CONTRIBUTE • TEST • GIVE FEEDBACK

Pilot it in your project, open an issue or pull request, or write with feedback — contributors and test sites welcome.

Ngha Ndze Mbuh

+237 676 651 837

ngha.mbuh@gmail.com

What each tag fixes

REDCAP LIMITATION

HOW IT IS RESOLVED

@UVALIDATE

Stock validation checks the **shape** of data only — never a single-character typo or digit swap in an ID, and custom regex needs a server admin.

Recomputes **check-character algorithms** (ISO 7064, Verhoeff) live as the user types, and sets **custom regex per field** without an admin.

@UVASSERT

Nothing **blocks** a bad relationship between fields at entry: branching logic only hides fields, and range checks give non-binding warnings.

Enforces **cross-field logic** — an end date after its start date — as data is typed, with an optional **hard block** on saving.

@UVREQUIRED

The native required flag is **unconditional** and raises only a soft warning that users can dismiss in a single click.

Adds **conditional requirements** that switch with live data and upgrades the warning to a **compulsory save block**.

@UVUNIQUE

No **real-time, field-level uniqueness** check exists, so duplicate records only surface later as retrospective cleanup.

Runs a **live AJAX check** against every record — or a scope such as a DAG — stopping **duplicate identifiers** before they save.

@UVCHOICES

Native **@HIDECHOICE** is **static** and cannot respond to live form changes, so designers add redundant fields and branching.

Filters radio, dropdown and checkbox options **dynamically** — cascading menus inside one field, a simpler data dictionary.

Validation scan the retrospective sweep

Re-runs every configured rule across the whole project to surface violations that predate a rule or arrived by API or Data Import Tool. Opened from the left-hand menu with design rights; the report and its CSV name record, event, instance and field — never the stored value.