

Artificial Neural Networks

Artificial Neural Networks

- A general, practical method for **learning** real-valued, discrete-valued, and vector-valued functions from examples
- **Robust** to errors in training data
- **Applications**: speech recognition, robot control strategies, handwritten recognition, etc.

Biological Motivation

- Human brain has about 100 billion neurons
- Each connected to 10^4 others
- Switching time = 10^{-3} seconds (quite slow compared to computer switching speeds of 10^{-10} seconds)
- Scene recognition time 10^{-1} seconds
 - highly parallel and distributed processes


Biological Motivation

- ANN model is **not the same as** that of biological neural systems
- Two research directions:
 - Using ANNs to **study and model biological learning processes**
 - Obtaining highly **effective machine learning algorithms**


When to Consider Neural Networks

- Instances have many attribute-value pairs
- Target function output may be discrete-valued, real-valued, or a vector of several real- or discrete-valued attributes
- Training examples may contain errors
- Long training times are acceptable
- Fast evaluation of the learned target function may be required
- The ability for humans to understand the learned target function is not important


ANN Representation



Perceptron




Perceptron




$$o(x_1, \dots, x_n) = \begin{cases} 1 & \text{if } w_0 + w_1 x_1 + \dots + w_n x_n > 0 \\ -1 & \text{otherwise.} \end{cases}$$

Perceptron



(a)



(b)

Perceptron training rule

$$w_i \leftarrow w_i + \Delta w_i$$

where

$$\Delta w_i = \eta(t - o)x_i$$

Where:

- $t = c(\vec{x})$ is target value
- o is perceptron output
- η is small constant (e.g., .1) called *learning rate*

Gradient Descent

To understand, consider simpler *linear unit*, where


$$o = w_0 + w_1x_1 + \cdots + w_nx_n$$

Let's learn w_i 's that minimize the squared error

$$E[\vec{w}] \equiv \frac{1}{2} \sum_{d \in D} (t_d - o_d)^2$$

Where D is set of training examples

Gradient Descent



Gradient

$$\nabla E[\vec{w}] \equiv \left[\frac{\partial E}{\partial w_0}, \frac{\partial E}{\partial w_1}, \dots, \frac{\partial E}{\partial w_n} \right]$$

Training rule:

$$\Delta \vec{w} = -\eta \nabla E[\vec{w}]$$

i.e.,

$$\Delta w_i = -\eta \frac{\partial E}{\partial w_i}$$

Gradient Descent

$$\begin{aligned}\frac{\partial E}{\partial w_i} &= \frac{\partial}{\partial w_i} \frac{1}{2} \sum_d (t_d - o_d)^2 \\ &= \frac{1}{2} \sum_d \frac{\partial}{\partial w_i} (t_d - o_d)^2 \\ &= \frac{1}{2} \sum_d 2(t_d - o_d) \frac{\partial}{\partial w_i} (t_d - o_d) \\ &= \sum_d (t_d - o_d) \frac{\partial}{\partial w_i} (t_d - \vec{w} \cdot \vec{x}_d) \\ \frac{\partial E}{\partial w_i} &= \sum_d (t_d - o_d) (-x_{i,d})\end{aligned}$$

GRADIENT-DESCENT(*training_examples*, η)

Each training example is a pair of the form $\langle \vec{x}, t \rangle$, where \vec{x} is the vector of input values, and t is the target output value. η is the learning rate (e.g., .05).

- Initialize each w_i to some small random value
- Until the termination condition is met, Do
 - Initialize each Δw_i to zero.
 - For each $\langle \vec{x}, t \rangle$ in *training_examples*, Do
 - * Input the instance \vec{x} to the unit and compute the output o
 - * For each linear unit weight w_i , Do

$$\Delta w_i \leftarrow \Delta w_i + \eta(t - o)x_i$$

- For each linear unit weight w_i , Do

$$w_i \leftarrow w_i + \Delta w_i$$

Gradient Descent

Perceptron training rule guaranteed to succeed if

- Training examples are linearly separable
- Sufficiently small learning rate η

Linear unit training rule uses gradient descent

- Guaranteed to converge to hypothesis with minimum squared error
- Given sufficiently small learning rate η
- Even when training data contains noise
- Even when training data not separable by H

Stochastic Approximation

Batch mode Gradient Descent:

Do until satisfied

1. Compute the gradient $\nabla E_D[\vec{w}]$
 2. $\vec{w} \leftarrow \vec{w} - \eta \nabla E_D[\vec{w}]$
-

Incremental mode Gradient Descent:

Do until satisfied

- For each training example d in D
 1. Compute the gradient $\nabla E_d[\vec{w}]$
 2. $\vec{w} \leftarrow \vec{w} - \eta \nabla E_d[\vec{w}]$
-

$$E_D[\vec{w}] \equiv \frac{1}{2} \sum_{d \in D} (t_d - o_d)^2$$


$$E_d[\vec{w}] \equiv \frac{1}{2} (t_d - o_d)^2$$

Incremental Gradient Descent can approximate
Batch Gradient Descent arbitrarily closely if η
made small enough


Multilayer Networks

- Single perceptrons can express only **linear** decision surfaces
- A multilayer network can represent highly **nonlinear** decision surfaces

Multilayer Networks



Sigmoid Unit



Sigmoid Unit

$\sigma(x)$ is the sigmoid function

$$\frac{1}{1 + e^{-x}}$$

Nice property: $\frac{d\sigma(x)}{dx} = \sigma(x)(1 - \sigma(x))$

We can derive gradient decent rules to train

- One sigmoid unit
- *Multilayer networks* of sigmoid units \rightarrow Backpropagation

Sigmoid Unit

$$\begin{aligned}\frac{\partial E}{\partial w_i} &= \frac{\partial}{\partial w_i} \frac{1}{2} \sum_{d \in D} (t_d - o_d)^2 \\ &= \frac{1}{2} \sum_d \frac{\partial}{\partial w_i} (t_d - o_d)^2 \\ &= \frac{1}{2} \sum_d 2(t_d - o_d) \frac{\partial}{\partial w_i} (t_d - o_d) \\ &= \sum_d (t_d - o_d) \left(-\frac{\partial o_d}{\partial w_i} \right) \\ &= - \sum_d (t_d - o_d) \frac{\partial o_d}{\partial net_d} \frac{\partial net_d}{\partial w_i}\end{aligned}$$

But we know:

$$\begin{aligned}\frac{\partial o_d}{\partial net_d} &= \frac{\partial \sigma(net_d)}{\partial net_d} = o_d(1 - o_d) \\ \frac{\partial net_d}{\partial w_i} &= \frac{\partial (\vec{w} \cdot \vec{x}_d)}{\partial w_i} = x_{i,d}\end{aligned}$$

So:

$$\frac{\partial E}{\partial w_i} = - \sum_{d \in D} (t_d - o_d) o_d (1 - o_d) x_{i,d}$$

Backpropagation Algorithm

Initialize all weights to small random numbers.

Until satisfied, Do

- For each training example, Do
 1. Input the training example to the network and compute the network outputs
 2. For each output unit k

$$\delta_k \leftarrow o_k(1 - o_k)(t_k - o_k)$$

3. For each hidden unit h

$$\delta_h \leftarrow o_h(1 - o_h) \sum_{k \in \text{outputs}} w_{h,k} \delta_k$$

4. Update each network weight $w_{i,j}$

$$w_{i,j} \leftarrow w_{i,j} + \Delta w_{i,j}$$

where

$$\Delta w_{i,j} = \eta \delta_j x_{i,j}$$

Backpropagation Algorithm


- Gradient descent over entire *network* weight vector
- Easily generalized to arbitrary directed graphs
- Will find a local, not necessarily global error minimum
 - In practice, often works well (can run multiple times)

- Often include weight *momentum* α

$$\Delta w_{i,j}(n) = \eta \delta_j x_{i,j} + \alpha \Delta w_{i,j}(n-1)$$

- Minimizes error over *training* examples
 - Will it generalize well to subsequent examples?
- Training can take thousands of iterations \rightarrow slow!
- Using network after training is very fast

Learning Hidden Layer Representations




A target function:

Input	Output
10000000	→ 10000000
01000000	→ 01000000
00100000	→ 00100000
00010000	→ 00010000
00001000	→ 00001000
00000100	→ 00000100
00000010	→ 00000010
00000001	→ 00000001

Learning Hidden Layer Representations

A network:



Learned hidden layer representation:

Input		Hidden Values		Output
10000000	→	.89 .04 .08	→	10000000
01000000	→	.01 .11 .88	→	01000000
00100000	→	.01 .97 .27	→	00100000
00010000	→	.99 .97 .71	→	00010000
00001000	→	.03 .05 .02	→	00001000
00000100	→	.22 .99 .99	→	00000100
00000010	→	.80 .01 .98	→	00000010
00000001	→	.60 .94 .01	→	00000001

Training

