

Lab 09

Laboratory Exercise

Part 1: Deploy Single Container POD in Kubernetes

LAB EXERCISE

This LAB exercise shows you how to deploy a sample application in kubernetes.

Time to Complete

Approximately 15 Minutes

What You Need

Kubernetes Cluster should be running. If not start the cluster using the command “minikube start”

Question: What is the main difference between Kubernetes and Minikube?


For YAML Basic Syntax and Meaning, please read

https://docs.ansible.com/ansible/latest/reference_appendices/YAMLSyntax.html

Republic Polytechnic - School of Infocomm

From your machine logged-in to RP VPN, run Remote Desktop Connection to connect to the ubuntu Linux Virtual Machine (VM). Please login based on your assigned VM as shown below:

S/N	Name	VM	IP Address	User Name	Password
1	ABDUL SALIM BIN ABDUL RASHITH	LABC03 - 172.20.115.50	172.20.115.50	dockeradm	docker!2
2	CASPER LEOW YU HAN (LIAO YU HANG)	LABC03 - 172.20.115.51	172.20.115.51	dockeradm	docker!2
3	CHAN JUN ZHI, GLENN	LABC03 - 172.20.115.52	172.20.115.52	dockeradm	docker!2
4	CHIA WAI TAT	LABC03 - 172.20.115.53	172.20.115.53	dockeradm	docker!2
5	HOI WAI TECK	LABC03 - 172.20.115.54	172.20.115.54	dockeradm	docker!2
6	KOH JIN CAI DAEMIAN	LABC03 - 172.20.115.55	172.20.115.55	dockeradm	docker!2
7	KYAW KYAW OO	LABC03 - 172.20.115.56	172.20.115.56	dockeradm	docker!2
8	LUM YOKE FAI	LABC03 - 172.20.115.57	172.20.115.57	dockeradm	docker!2
9	MUHAMMAD FADHLI BIN MOHAMED NOOR	LABC03 - 172.20.115.58	172.20.115.58	dockeradm	docker!2
10	MUHAMMAD HILMEE BIN MD ALI	LABC03 - 172.20.115.59	172.20.115.59	dockeradm	docker!2
11	NG SAY WEE	LABC03 - 172.20.115.60	172.20.115.60	dockeradm	docker!2
12	NGUI WEILY	LABC03 - 172.20.115.61	172.20.115.61	dockeradm	docker!2
13	NU'MAN HARITH BIN NORRAIMI	LABC03 - 172.20.115.62	172.20.115.62	dockeradm	docker!2
14	RULY JANUAR FACHMI	LABC03 - 172.20.115.76	172.20.115.76	dockeradm	docker!2
15	SEAH SHIH WEI GEROME	LABC03 - 172.20.115.64	172.20.115.64	dockeradm	docker!2
16	SEAN CHENG ZHI WEI	LABC03 - 172.20.115.65	172.20.115.65	dockeradm	docker!2
17	SEY KOK SIONG	LABC03 - 172.20.115.66	172.20.115.66	dockeradm	docker!2
18	TAN JOON YEE DOUGLAS	LABC03 - 172.20.115.67	172.20.115.67	dockeradm	docker!2
19	WU WAI TENG VANESSA	LABC03 - 172.20.115.68	172.20.115.68	dockeradm	docker!2
20	YAP KOON SING	LABC03 - 172.20.115.69	172.20.115.69	dockeradm	docker!2
21	YE CHENG LIM	LABC03 - 172.20.115.70	172.20.115.70	dockeradm	docker!2
22	SHAIFUL BIN ABDUL KARIM	LABC03 - 172.20.115.71	172.20.115.71	dockeradm	docker!2
23	CHAI RU YI	LABC03 - 172.20.115.72	172.20.115.72	dockeradm	docker!2
24	JWAY HWEE LING JULIE	LABC03 - 172.20.115.73	172.20.115.73	dockeradm	docker!2
25	SAMANTHA TEO XING YEE	LABC03 - 172.20.115.74	172.20.115.74	dockeradm	docker!2
26	ZIL AZZA HILMIAH BINTE RADUAN	LABC03 - 172.20.115.75	172.20.115.75	dockeradm	docker!2



Replace **xx** with the IP address of the VM that you have been assigned.

Republic Polytechnic - School of Infocomm**Deploy the Application**

1. Save below db-pod.yml file in the directory ~/lab09 i.e. /home/dockeradm/lab09

```
apiVersion: v1
kind: Pod
metadata:
  name: mysql
  labels:
    name: mysql
    app: demo
spec:
  containers:
  - name: mysql
    image: mysql:latest
    ports:
    - containerPort: 3306
      protocol: TCP
    env:
    - name: "MYSQL_ROOT_PASSWORD"
      value: "password"
```

2. Create a POD with single container using the command :
cd /home/dockeradm/lab09
kubectl create -f db-pod.yml
3. Check the PODs via the below command
kubectl get pods
4. Login to the Kubernetes Dashboard and analyze the POD
5. Get the complete details of POD using the command
kubectl describe pod mysql

Republic Polytechnic - School of Infocomm

Part 2: Deploy multiple PODs and communication between PODs in Kubernetes

LAB EXERCISE

This LAB exercise demonstrates the concept of packaging containers into a pod and communication between pods.

Time to Complete

Approximately 30 Minutes

What You Need

- Lab 9 - Part 1 to be completed successfully.
- Execute the command: `sudo apt install docker-compose`
- Kubernetes Cluster should be running. If not start the cluster using the command “minikube start”
- Register a free account on Docker hub <https://www.docker.com/>

Build a Docker image and push it to docker hub

1. Sign in to the Docker Hub (Browser) <https://www.docker.com/>
 - Using the same credentials launch a new terminal to login into docker: `docker login`
2. Git clone all the files from the Folder **PODLab** from the provided git url <https://github.com/KeyonGenesis/K8Exercises> and edit the below files in the **Docker** folder as per your docker hub username.

```
soi-sddo@sddo-vm:~$ git clone https://github.com/KeyonGenesis/K8Exercises
```

```
soi-sddo@sddo-vm:~$ cd K8Exercises/lab03/PODLab/Docker
```

Edit the following 2 files. Replace the username/repository from keyongenesi/web to your username/ in docker hub.

- Build.sh
- docker-compose.yml

3. From the docker directory, build the image using the below command.

```
docker build -t <DOCKER_HUB_USERNAME>/web .
```

```
soi-sddo@sddo-vm:~/K8Exercises/lab03/PODLab/Docker$ docker build -t keyongenesi/web .
Sending build context to Docker daemon 6.144kB
Step 1/3 : FROM python:2.7-onbuild
# Executing 3 build triggers
--> Using cache
--> Using cache
--> Using cache
--> 825850e79e72
Step 2/3 : EXPOSE 5000
--> Using cache
--> ac0b8b9cdb0f
Step 3/3 : CMD [ "python", "app.py" ]
--> Using cache
--> cbd35aedffc8
Successfully built cbd35aedffc8
Successfully tagged keyongenesi/web:latest
```

Republic Polytechnic - School of Infocomm

4. Once the build is successful, push the image to your docker hub.


Need to login to your docker hub account first

```
docker login
```

Username:

Password:

```
docker push <DOCKER_HUB_USERNAME>/web
```



5. To check if the build image is working properly, use the docker compose file to create the container using below command.

```
docker-compose up -d
```

```
soi-sddo@sddo-vm:~/K8Exercises/lab02/PODLab/Docker$ docker-compose up -d
redis is up-to-date
docker_web_1 is up-to-date
```

6. Check the container using the below command.

```
docker ps -a
```


Republic Polytechnic - School of Infocomm

```
soi-sddo@sddo-vm:~/K8Exercises/lab02/PODLab/Docker$ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	NAMES	PORTS
112b1df0aacd	keyongenes/web	"python app.py"	2 days ago	Up 2 days	docker_web_1	0.0.0.0:3000->5000/tcp, :3000->5000/tcp
692a9fa2b780	redis:latest	"docker-entrypoint.s..."	2 days ago	Up 2 days	redis	6379/tcp
7160b3c6b877	gcr.io/k8s-minikube/kicbase:v0.0.27	"/usr/local/bin/entr..."	2 weeks ago	Up 2 days	minikube	127.0.0.1:49167->22/tcp, 127.0.0.1:49166->2376/tcp, 127.0.0.1:49165->5000/tcp, 127.0.0.1:49164->8443/tcp, 127.0.0.1:49163->32443/tcp

7. Test the application using the url <http://localhost:3000/> and the output will be as :

Hello Container World! I have been seen 1 times.



Now your build image is ready to deploy in Kubernetes.

Republic Polytechnic - School of Infocomm




Part 3: Deploy the Application in Kubernetes

LAB EXERCISE

This LAB exercise demonstrates the concept of packaging containers into a pod and communication between pods.

Before starting part 3, you need to clean up the services and pods created in part 2. You may clean them up via `minikube dashboard`

Click on each pod or service, and then click on the bin icon.



Time to Complete

Approximately 30 Minutes

1. Copy all the files from the Folder PODLab from git Location and store it locally.
<https://github.com/KeyonGenesis/K8Exercises>

2. Edit the below files in the folder **Kubernetes** as per your docker hub username.
 Edit the following files. Replace the username/repository from keyongenesis/web to your username/web in docker hub.

- web-pod.yml
- web-rc.yml

Republic Polytechnic - School of Infocomm

4. Open the command prompt as administrator and create POD service as below

```
cd K8Exercises/lab03/PodLab/Kubernetes/
```

```
kubectl create -f db-pod.yml
```

```
kubectl create -f db-svc.yml
```

```
kubectl create -f web-pod.yml
```

```
kubectl create -f web-svc.yml
```

```
kubectl create -f web-rc.yml
```

<Insert screen capture of results>

5. Open the command prompt as administrator and create POD service as below

```
kubectl get pods
```

<Insert screen capture of results>

6. Get the list of exposed services.

```
kubectl get svc
```

<Insert screen capture of results>

7. Get service url for web application using below command.

```
minikube service web --url
```

8. Access the url listed above from the browser and verify the result.
Hello Container World! I have been seen 1 times.

Republic Polytechnic - School of Infocomm


Part 4: Deployment in Kubernetes

LAB EXERCISE

This LAB exercise demonstrates the concept of how to use the service deployment and expose it.

Before starting part 4, you need to clean up the services and pods created in part 3. You may clean them up via `minikube dashboard`

Click on Deployment, Pods and Services, and then click on the bin icon.



Time to Complete

Approximately 30 Minutes

What You Need

- Lab 01 to be completed successfully.
- Kubernetes Cluster should be running. If not start the cluster using the command “minikube start”

1. Deploy the Application

1.1 Save this below *deployment.yaml* file in local storage directory

K8Exercises/lab03/Deployment

```
apiVersion: apps/v1
```


Republic Polytechnic - School of Infocomm

```

kind: Deployment
metadata:
  name: tomcat-deployment
spec:
  selector:
    matchLabels:
      app: tomcat
  replicas: 2
  template:
    metadata:
      labels:
        app: tomcat
    spec:
      containers:
        - name: tomcat
          image: tomcat:9.0
          ports:
            - containerPort: 8080

```

2. Create a POD service using the command:
`kubectl create -f deployment.yaml`
3. Check the PODs using the below command:
`kubectl get pods`



NAME	READY	STATUS	RESTARTS	AGE
busybox-logs	0/1	Completed	0	2d8h
my-multi-app	1/2	CrashLoopBackOff	664 (5m8s ago)	2d8h
my-single-app	0/1	CrashLoopBackOff	665 (87s ago)	2d8h
nginx	1/1	Running	0	2d9h
nginx-6799fc88d8-b4gfv	1/1	Running	0	2d9h
redis	1/1	Running	0	31m
tomcat-deployment-7594d999c8-8rv87	1/1	Running	0	8m19s
tomcat-deployment-7594d999c8-t9lmg	1/1	Running	0	8m19s
web	1/1	Running	0	28m
web-qmlgr	1/1	Running	0	28m

Once the tomcat POD is running, then expose the service.

4. Expose the service using the command:
`kubectl expose deployment tomcat-deployment --type=NodePort`
- 4.1. Verify the Service is created and is available on a node port:
`kubectl get service tomcat-deployment`
5. Get the minikube service url for this tomcat service using the command:
`minikube service tomcat-deployment --url`
6. Open the browser and access the service URL.

Republic Polytechnic - School of Infocomm

Check the tomcat home page is loading and version.

Upgrade the Application with different tomcat version

7. Update deployment of object tomcat to version 8.0 using the command:

```
kubectl set image deployment/tomcat-deployment tomcat=tomcat:8.0
```

8. Check the PODs are running using the below command:

```
kubectl get pods
```

It will take some time, since the image of the 8.0 version of tomcat needs to be pulled. Once the tomcat POD is running, then expose the service.

9. Expose the service using the command

```
kubectl expose deployment tomcat-deployment --type=NodePort
```

10. Get the minikube service url for this tomcat service using the command:

```
minikube service tomcat-deployment --url
```

Open the browser and access the service URL. Check the tomcat home page is loading.

Rollout the previous deployed version

11. Rollout the changes applied to the deployment object using the below command.

```
kubectl rollout undo deployment/tomcat-deployment
```

12. Get the minikube service url for this tomcat service.

13. Open the browser and access the service URL.
Check the tomcat home page is loading and version.

--End of Lab Exercise --

External documentations

Those documentations can help you to go further in this topic :

- Kubernetes official documentation of [the command line](#)
- Kubernetes official [command line cheat sheet](#)
- Kubernetes official documentation of [namespace](#)
- Kubernetes official documentation of [labels](#)
- Kubernetes official documentation of [recommended labels](#)
- Kubernetes [API reference](#) documentation
- [Kubectl official Reference](#) documentation
- Kubernetes official documentation on [declarative object management](#)
- Kubernetes official documentation on [imperative object management](#)