MATERIAL SAFETY DATA SHEET *According to regulation GB/T16483, GB/T17519*

ZHANCHEN

SECTION 1 - Product and company identification

Product Code	:	ZP76011
Product Description	:	White paste
Intended Use	:	Wood Coatings
Revision date	:	2-NOV-2025
Company name	:	VISION NEW MATERIALS VIETNAM COMPANY LIMITED
Address	:	FACTORY N2-A1, N2-A2, N2-C1, N2-C2, LOT N2, 5 ROAD, VIET HUONG 2 INDUSTRIAL PARK, TAY NAM WARD, HO CHI MINH CITY, VIET NAM.
Telephone	:	0274 3555 208
Fax	:	0274 3555 209
Emergency telephone	:	0274 3555 208
E-mail address	:	zhanchengroup@gmail.com

SECTION 2 - Hazards identification

Emergency summary : Liquid. Flammable, its vapor and air mixture can form explosive mixture. May cause serious lung damage if swallowed. Irritating to skin. Risk of serious damage to eyes. Irritating to respiratory system. Vapours may cause drowsiness and dizziness.

Hazard classification according to GHS : According to series standards of GB 30000-2013: Rules for classification and labelling of chemicals. Hazard classification as following: Flammable liquid, Category 3; Aspiration hazard, Category 1; Skin corrosion/Irritation, Category 2; Serious eye damage/Irritation, Category 1; Specific target organ toxicity-single exposure: Criteria for respiratory tract irritation, Category 3; Specific target organ toxicity-single exposure: Criteria for narcotic effects, Category 3; Germ cell mutagenicity, Category 1.

Label elements

-Hazard pictogram :



-Signal word : Danger

-Hazard statements : Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness or dizziness.

-Supplemental Hazard Statements : Repeated exposure may cause skin dryness or cracking.

Precautionary statements

-Prevention : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

-Response : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

-Storage : Store in a well-ventilated place. Keep container tightly closed.

SECTION 3 - Composition/information on ingredients

Substance/Mixture : Mixture

Ingredients	CAS No.	Weight (%)
Xylene	1330-20-7	15-25
Propylene glycol monomethyl ether acetate	108-65-6	10-20
Alkyd resin	63148-69-6	10-20
Titanium	13463-67-7	40-70

SECTION 4 - First aid measures

Skin Exposure : To remove the contaminated clothes, need to clean with a lot of cleaning agent and soap,or clean with gauze or cotton cloth impregnated with vegetable oil.

Eye Exposure : In case of contact, flush with copious amount of water for at least 15minutes.Assure adequate flushing by separating the eyelids with fingers. IF irritation persists, call a physician.

Inhalation Exposure : If inhaled, remove to fresh air. If necessary, get medical attention.

Oral Exposure : If swallowed, wash out mouth with water provided person is conscious. Call a physician.

SECTION 5 - Firefighting measures

Hazard characteristics : Flammable, its steam and air can form an explosive mixture, and it is very easy to burn and explode in the light of fire and high heat. It can react strongly with the oxidizing agent. It is easy to produce and gather static electricity, and there is a danger of burning and explosion.

Extinguishing Media : Dry chemical powder, carbon dioxide or appropriate foam.

Precautions and measures for Firefighting : Firefighters must wear self-contained breathing apparatus, wear whole body fireproof and antitoxic clothes, and put out the fire in the upper wind. Water spray cooling containers, if possible, move the container from the fire field to the open space. If the container in the fire field has changed color or

produces sound from the safety pressure relief device, it must be evacuated immediately. Water extinguishing is not effective.

Prevent secondary disasters : Eliminating point fire sources and preventing leaks from entering the sewer.

SECTION 6 - Accidental release measures

Procedures of Personal Precautions : Exercise appropriate precautions to minimize direct contact with skin or eyes and prevent inhalation of dust.

Environmental protection measures : Prevent leaks from entering water, sewer, basement, or confined space.

Methods for Cleaning up

-Leak on land : Small leak, mix with inert material (eg. Dry sand, vermiculite)and transfer to sealed container for disposal.
Large leak, Build an embankment or dig a hole for shelter.Cover with foam to reduce vapor hazard.Transfer to tank truck or special collector with explosion-proof pump for recovery or transport to waste disposal site.

-Leak in water : If there is no danger, action can be taken to stop the leak, immediately spilled oil fence limit range, Pull from the surface, warning other ships.

Refer to Section 8 for additional personal protection information.
Refer to Section 13 for disposal considerations.

SECTION 7 - Handling and storage

Handling Measures : Wear appropriate protective clothing and safety gloves. Avoid contact with eyes, skin. Avoid inhalation. Mechanical exhaust required. Keep away from ignition sources, hest and flame. Incompatibilities: strong oxidizing agents and foods. No smoking at working site.At the time of filling, the flow rate should be controlled and the grounding device is used to prevent the accumulation of static electricity. Light load should be loaded lightly to prevent the damage of packaging and container. The empty container may remain harmful.

Storage Measures : Store in a cool, ventilated storeroom. Stay away from fire and heat. Keep the container sealed. It should be stored separately with oxidant and edible chemicals, and avoid mixed storage. The use of explosion-proof lighting, ventilation facilities. It is forbidden to use mechanical equipment and tools that easily generate sparks. The storage area should be equipped with leakage emergency treatment equipment and suitable collection materials.

SECTION 8 - Exposure controls/personal protection

Contact limit value：

Component name	Reference standard	PC-TWA (mg/m^3)	PC-STEL (mg/m^3)

Xylene	GBZ 2.1-2019	50	100
Propylene glycol monomethyl ether acetate	GBZ 2.1-2019	200	300

Engineering Control	:	Ensure adequate ventilation on workstation. Provide safety shower and eyewash equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Set up emergency exit and necessary risk-elimination area.
General Protective Measures	:	Avoid contact with eyes and skin.
Hygiene Measure	:	Wash hand before and after work. Use skin barrier cream.
Personal Protective Equipment		
- Respiratory Protection	:	Suitable portable respiratory protective equipment should be worn during spray application, emergency rescue or evacuation.
- Hand Protection	:	Compatible chemical-resistant gloves.
- Eye Protection	:	Safety glasses.
- Skin Protection	:	Wear appropriate protective clothing.
Other Protect	:	No smoking, drinking and eating at working site. Wash thoroughly after handling. Carry out pre-employment physical examination and regular physical examination.

SECTION 9 - Physical and chemical properties

Appearance	:	Colored viscous liquid
Flash point (℃)	:	24
Boiling point (℃)	:	>35
Ignition point(℃)	:	38
Relative vapor density(Air=1)	:	>1
Relative density (Water=1)	:	1.1 (±0.05)
Upper limit of explosion(V/V)	:	8.5%
Lower limit of explosion(V/V)	:	1%
Solubility	:	Insoluble in water

SECTION 10 - Stability and reactivity

Stability	:	Stable under recommendation storage and handling condition.
Hazardous Reaction	:	Highly reactive or incompatible with the following materials: oxidizing materials, strong base or acid.
Avoid contact conditions		open fire, high heat.
Hazardous Decomposition Products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 - Toxicological information

Toxicity Data	:	No data available.but it has been Preparations Directive to evaluate and classify their

		poison danger.
Skin irritation/corrosion	:	Causes skin irritation.
Eye irritation/corrosion	:	Cause serious eye damage.
Skin sensitization	:	No data available.
Respiratory sensitization	:	No data available.
Reproductive toxicity	:	No data available.
Specific target organ toxicity-single exposure	:	May cause respiratory irritation.
Aspiration hazard	:	May be fatal if swallowed and enters airways.

SECTION 12 - Ecological information

Ecotoxicity	:	No data available.
Biological degradability	:	No data available.
Mobility in soil	:	No data available.
Other deleterious effect	:	No data available.

SECTION 13 -Disposal considerations

The national and local regulations should be referred to before the disposal of waste. it is not allowed to be dumped into sewers or drains, nor disposed of in places where soil or groundwater may be affected.

Waste chemicals	:	To be recycled as much as possible, if it can not be recycled then send to a licensed waste management company.
Contaminated packaging		No reuse can be repeated or empty containers filled with this product. If we want to reuse and dispose of contaminated empty containers, they should be thoroughly cleaned. The cleaning solution should be conduct harmless treatment.

SECTION 14 - Transport information

In Accordance with ADR/IMDG/IATA

- UN No.	:	1263
- UN proper shipping name	:	PAINT RELATED MATERIAL
- UN Classification of Hazards	:	3
- EMS No.	:	F-E, S-C
- IMO Class	:	3
- Package group	:	III
- Label	:	

Marine pollutants (yes / no)	:	No
Packing method	:	Gland opening metal drum; threaded bottles, iron cover mouth glass bottles,

		plastic bottles or metal barrels (cans) ordinary wooden case.
Other Special Transportation Protective Measures	:	The railway transportation should be installed in strict accordance with the dangerous goods distribution form in the railway ministry's "dangerous goods transportation rules". Transportation vehicles should be equipped with the corresponding variety and quantity of fire-fighting equipment and leakage emergency treatment equipment. It is best to ship morning and evening in summer. With no oxidant, edible chemicals, such as mixed mixed transport. In transit, insolation, rain, and high temperature should be prevented. It should stay away from fire, heat and high temperature. The vehicle exhaust pipe that carries the goods must be equipped with a fire resistance device, which prohibits the use of mechanical equipment and tools that easily generate sparks. Road transportation should be driven in accordance with the prescribed route, and do not stay in residential areas and densely populated areas. It is strictly prohibited to use wooden and cement ships in bulk.

SECTION 15 - Regulatory information

Related regulatory information	:	-General rules for preparation of chemical safety data sheet (GB/T16483-2008) - Guidance on the compilation of safety data sheet for chemical products(GB/T 17519-2013) -Rules for classification and labelling of chemicals(GB 30000-2013) -Classification and package when delivery dangerous goods (GB/T15098-2008) -Occupational Exposure Limits for Hazardous Agents in the Workplace: Chemical Hazardous Agents. (GBZ 2.1-2019)

SECTION 16 - Other information

Reference	:	- Transport regulations according to ADR, IMDG, and IATA (UN). - MSDS from 3rd parties/suppliers.
Abbreviation and Acronyms		
-PC-TWA	:	Permissible Concentration-Time Weighted Average.(8h)
-PC-STEL	:	Permissible Concentration-Short Term Exposure Limit.(15min)
-ADR	:	European Agreement concerning the international carriage of Dangerous goods by Road.
-IMDG	:	International Maritime Code for Dangerous Goods.
-IATA	:	International Air Transport Association.
-UN	:	United Nations.
-GHS	:	Globally Harmonized System of Classification and Labeling of Chemicals.
-Cas No.	:	Chemical abstracts registration number.
-EMS No.	:	Emergency measures for shipping dangerous goods.
-UN No.	:	United Nations Numbers for Dangerous Goods.

-IMO : International Maritime Organization

Disclaimer

The information presented here is based on our current best understanding and data from reputable third party sources. This document is neither a contract nor a guarantee. The conditions and the way our customer handle, store, use and disposal of these products is not controlled by the supplier. We will not accept any loss, damage or relative expense caused by your improper disposal, storage, use and discard of these products. This MSDS can only be used for the products listed in the title. It is not acceptable to use this MSDS for a product which contains this material or any material listed in the document.