

Nhập Môn CNTT – Thực Hành

Shell commands

Streams, Redirection

AGENDA


- Useful shell commands (wc, more, less, grep)
- Standard in, Standard out
- Input/output redirection
- Pipes

FILE EXAMINATION

Command	description
cat	Print contents of a file
less	Output file contents, one page
more	Output file contents, one page
head	Output number of lines of start of file
tail	Output number of lines of end of file
wc	Count words, characters, lines in a file

SEARCHING AND SORTING

Command	description
grep	Search given file for pattern
sort	Sort input or file, line based
uniq	Strip duplicate adjacent lines
find	Search filesystem
cut	Remove section from each line of file



You're working on a project and have been leaving comments with the text "TODO" near all the things you still need to finish. Your project is stored in the project directory in your current directory.

Write a command to find and print all of the lines that have a TODO on them in the project folder.

Hint: Use the "wildcard" to select all files as part of a path.

```
$ grep "TODO" project/*
```

C AND THE COMMAND LINE

Command	description
<code>gcc filename.c</code>	Compile C file
<code>./a.out</code>	Run the c program
<code>python, ruby, perl, go, etc</code>	Run or compile other files in different languages!



What is the command to compile all C files in the current directory?

Hint: How can you use wildcards to find all C files?


```
$ gcc -Wall *.c -o sayhello
```

STANDARD STREAMS

- Every unix process has three *streams*, which are abstract locations that tell a program where to read input from and where to write output to.
- There are three standard streams:
 - `stdin` (Standard Input)
 - `stdout` (Standard Output)
 - `stderr` (Standard Error)
- By default, all of these default to the console (they print to the terminal and read from user input into the terminal). However, this can be easily changed.

STANDARD STREAMS

int	stream
0	stdin
1	stdout
2	stderr



STDIN VS PARAMETERS

- One of **the most important distinctions in this class** is the difference between *stdin* and a command's *parameters*.
- A *parameter* is an argument you give on the command line, like so
 - `$ ls dir1`
 - `dir1` is a parameter, it does not come from standard input
- Standard input comes from the user, either from a file or from the console
 - `$ grep "a"`
 - Once you type this command, it accepts input from your keyboard until you close the stream using Ctrl + D

OUTPUT REDIRECTION


command > filename

- Execute **command** and redirect its standard output to the given **filename**
 - If the file *does not* exist, create the given file.
 - If the file *does* exist, it will **overwrite the given file (BE CAREFUL!!)**
 - To append to a file instead of overwrite it, use >> instead of >
- Examples:
 - Output contents of current directory to files.txt: `ls -l > files.txt`
 - Append output of `wc -l veggies.txt` to files.txt: `wc -l veggies.txt >> files.txt`

INPUT REDIRECTION

command < filename

- Execute **command** and read its standard input from the contents of **filename** instead of from the console.
 - If a program usually accepts from user input, such as a console Scanner in Java, it will instead read from the file.
- Notice that this affects user input, not parameters.



Write a command to store all of the lines in `fruits.txt` that contain the letter **a** into a file called `a.txt`

```
$ grep "a" fruits.txt > a.txt
```

STDERR REDIRECTION

command 2> filename

- Execute **command** and redirect its standard error to the given **filename**

command 2>&1

- Execute **command** and redirect **standard error** to **standard output**

command 2>&1 filename

- Execute **command**, redirect **standard error** to **standard output**, and redirect **standard output** to **filename**


PIPES

command1 | **command2**

- Execute **command1** and send its standard output as standard input to **command2**.
- This is essentially shorthand for the following sequence of commands:

```
command1 > filename  
command2 < filename  
rm filename
```

- This is one of the most powerful aspects of unix - being able to chain together simple commands to achieve complex behavior!



Suppose we have a file `berries.txt` where each line is the name of a different berry. Write a command that outputs how many berries have names that contain **both** the letter **a** and the letter **e**.

```
$ grep "a" berries.txt | grep "e" | wc -l
```


COMBINING COMMANDS

command1 ; command2

- Execute **command1**, then execute **command2**.

command1 && command2

- Execute **command1**, and if it succeeds, then execute **command2**.

FIND

- **find** is a program for searching your filesystem for certain files.
- For example, to list all java files in the current directory and all subdirectories, recursively, we would run the following
 - `$ find -name "*.c"`
- This is commonly used with **xargs**. For instance, to compile all c files in the current directory and all subdirectories recursively
 - `$ find -name "*.c" | xargs gcc`
- Note that find has a plethora of options and flags, but we will most commonly use find with the `-name` and `-type` flags

COMMAND SUBSTITUTION

`$(command)`

- Another powerful tool is command substitution. It executes the given command and places that string literally into the given context.
- For example, to compile all C files in the current directory and subdirectories recursively, we can run the following
 - `$ gcc $(find -name "*.c")`

STDERR REDIRECTION

- We've learned that we can redirect standard error using the `2>` operator.
- Sometimes, however, we want standard error and standard out to go to the same location. We can do that with the following syntax:
 - `$ command > out.txt 2>&1`
- To understand this command, this reads as “redirect standard out to `out.txt`, redirect standard error to the same place as standard out”

TEE

- Sometimes, we want to redirect the output of a command to both a file and to the console. To do this, we can pipe the output of a command to tee
 - `$ command | tee file.txt`
- To redirect both standard output and standard error to a file, and to the console, we use the following
 - `$ command 2>&1 | tee file.txt`

CUT

cut -d<DELIMITER> -f<FIELD>

- cut is a simple program to split lines based on a given delimiter.
- For example, to split the string “a,b,c,d,e” on commas and get the second entry, we would use the following:
 - `$ echo “a,b,c,d,e” | cut -d, -f2`
 - Note: the echo program simply prints the given string to standard out

LOGS

- A common exercise in daily software development and operations is looking at log files - basically a status report of what is going on inside the program.
- We can look at the logs for a service by using: `$ journalctl`
- For example, to actively watch the log file and only look for access to our own course website, we could use the following

```
$ sudo journalctl -u <some-name> -f | grep "503"
```