

AI Provider Connection Verification

Establish AI provider connection for the chatbot

Provider Configuration

The current YAF backend has support for many AI providers such as Mock, OpenAI, xAI, and Pinecone. For local testing purposes, Mock AI provider was used.

Configuration for local use:

AI_PROVIDERS=mock

The Mock AI provider was chosen since the credentials for the external provider were unavailable.

Environment Setup

Setup has been completed successfully:

- Environment variables were generated locally according to the .env.example file.
- Backend environment configuration was checked for successful loading.
- The AI provider was found to be initialized while starting the application.
- The backend operates locally via:

go run ./cmd/api

Chatbot Endpoint Verification

The current endpoint of the chatbot was tested:

POST http://localhost:8080/api/ai/chat

Request:

```
{  
  "content": "Hello, can you help me plan my accessible flight?"  
}
```

Response:

provider: mock

model: mock-chat

content: This is a mock AI response.

Result

The chatbot has been able to process the existing AI request flow:

User Request -> /api/ai/chat -> AI Handler -> AI Service -> AI Provider -> Response

The configured fallback provider is working properly.

Limitations and Outstanding Requirements

- Mock provider will always return a pre-set development time response.
- API credentials are necessary for a production AI provider.
- The choice of final AI provider for Sprint 2 is yet to be confirmed.
- The real provider testing will need access to credentials for OpenAI, xAI, or Pinecone.
- The retrieval of information in relation to the YAF airport, airlines, and equipment is a different task.