



Nguyen Tat Thanh Institute of
International Education (NIIE)

DATABASE MANAGEMENT SYSTEMS

(Credits 3)

MSc. Luong Tran Ngoc Khiet
May - 2021

Chap 1. Overview

Chap 2. Data storage management

Chap 3. Programming with Cursors

Chap 4. Query optimization

Chap 5. Continuous transaction processing



Chap 3.

Programming with Cursors

MSc. Luong Tran Ngoc Khiet


NTT Institute of International Education (NIIE)

- ❑ A cursor is a database object used by an application to manipulate rows of data instead of collections of data.
- ❑ Pointers are used **Procedure** and **Trigger**

❑ With pointers we can:

- Allows positioning of specified rows of a result set.
- Gets a single row or set of rows from the current position of the result set.
- Supports modifying the row's data at the current position in the result set.
- Supports multiple levels of visibility into changes made by other users on the result set data.

Cursors handling process



Declare cursor



- ❑ Command **DECLARE** used to create a cursor.
- ❑ It contains **SELECT** command to include records from the table.
- ❑ Syntax:

DECLARE <Cursor_Name> **CURSOR**

FOR <Select Statements>

[FOR UPDATE [OF Column_name[,....N]]]

Declare cursor



❑ Full syntax :

DECLARE <Cursor_Name> **CURSOR**

[LOCAL | GLOBAL]

[FORWARD ONLY | SCROLL]

[STATIC | KEYSET | DYNAMIC | FAST_FORWARD]

[READ_ONLY | SCROLL_LOCKS | OPTIMISTIC]

[TYPE_WARNING]

FOR <Select Statements>

[**FOR UPDATE** [**OF** Column_name[,....N]]]

Declare cursor parameter



- ❑ Scope: [LOCAL | GLOBAL]
 - Local :chỉ sử dụng trong phạm vi khai báo(mặc định)
 - Global :sử dụng chung cho cả kết nối

- ❑ Move: [FORWARD ONLY | SCROLL]
 - ForWard_Only :chỉ di chuyển một hướng từ trước ra sau(mặc định)
 - Scroll : di chuyển tùy ý

Declare cursor parameter



❑ Status: [STATIC | KEYSET | DYNAMIC]

- Static : dữ liệu trên Cursor không thay đổi mặt dù dữ liệu trong bảng nguồn thay đổi (mặc định)
- Dynamic : dữ liệu trên Cursor sẽ thay đổi khi dữ liệu trong bảng nguồn thay đổi
- KeySet : giống Dynamic nhưng chỉ thay đổi những dòng bị cập nhật

Declare cursor parameter



- ❑ Process: [READ_ONLY | SCROLL_LOCKS]
 - Read_Only : chỉ đọc (mặc định)
 - Scroll_Lock : đọc/ghi
- ❑ The select statement: does not contain Into, Compute, Compute by clauses
- ❑ Updated column list: is a list of columns that will be changed

Steps to use cursors



❑ Mở con trỏ:

OPEN <Cursor_name>

❑ Duyệt và xử lý dữ liệu trong cursor :

FETCH <Cursor_name>

❑ Đóng con trỏ:

CLOSE <Cursor_name>

❑ Xoá các tham chiếu tới con trỏ:

DEALLOCATE <Cursor_name>

Retrieve and traverse the cursor

❑ For example:

FETCH direction **From** cursor_name **Into** list variable

```
declare Cur_MatHang CurSor
for select MaMH,tenmh from MatHang
open Cur_MatHang
declare @maMH char(4), @tenMH varchar(100)
while 0=0
    begin
        fetch next from Cur_MatHang into @maMH, @tenMH
        if @@fetch_status<>0 break
        print 'Mã mặt hàng :' + @maMH + ' Tên mặt hàng :' +
            @tenMH
    end
close Cur_MatHang
deallocate Cur_MatHang
```

Retrieve and traverse the cursor



- ❑ **FETCH FIRST:** Retrieve the first row.
- ❑ **FETCH NEXT:** Retrieve the next row of the previous row.
- ❑ **FETCH PRIOR:** Retrieve the previous row of the previous retrieved row.
- ❑ **FETCH LAST:** Retrieve the last row.

Retrieve and traverse the cursor

- ❑ **FETCH ABSOLUTE** *n*: Move to the *n*-th record from the first record
 - If *n* is a positive integer, it will retrieve *n* rows in the cursor.
 - If *n* is a negative integer, the *n* rows before the last row in the cursor are retrieved.
 - If *n* is 0, no rows are retrieved.
 - Example: **FETCH Absolute 2** will display the second record of a table.
- **FETCH RELATIVE** *n*: Move to the *n*th record from the current record
 - If *n* is negative, *n* rows before the previously retrieved row are retrieved.
 - If *n* is 0, the current row is received.

- ❑ **@@FETCH_STATUS**: This variable returns an integer representing the result of the last access of the cursor..
 - **@@FETCH_STATUS** return $\neq 0$ if failed
 - **@@FETCH_STATUS** return = 0 if successful
- ❑ **@@CURSOR_ROWS**: This variable returns the total number of rows currently in the open cursor.

- A cursor is a database object used by an application to manipulate rows of data instead of collections of data. Using cursors, multiple operations can be performed row-by-row on the result set, which may or may not require the presence of the original table.

- ❑ The cursor is created using the **DECLARE** command.
First the pointer is declared and created in memory. Only then will it be opened..
- ❑ The **OPEN** command opens the cursor. Retrieving records from a cursor is called fetching. A user can only receive one record at a time.
- ❑ The **FETCH** instruction is used to read records from the cursor.

- ❑ By default, a cursor is **forward only**. It can retrieve records sequentially from the first record to the last record. It cannot directly retrieve the 1st or last row in a table.
- ❑ When a pointer is temporarily not needed, it can be closed with the **CLOSE** command.
- ❑ Whenever the pointer is not used, references to it should be removed with the **DEALLOCATE** command

STORED PROCEDURE

Stored Procedure



- ❑ Allows module-oriented programming
- ❑ Execute faster, reduce network connection usage
- ❑ Security
- ❑ Processing functions and sharing with other applications

□ *Syntax:*

```
CREATE PROCEDURE proc_name  
AS  
BEGIN  
    sql_statement1  
    sql_statement2  
END
```

Stored Procedure Syntax



```
CREATE PROCEDURE StoredName
@Parameter1 DataType [=DefaultValue,]
@Parameter2 DataType OUTPUT,
@Parameter3 DataType OUTPUT
AS
BEGIN
    BEGIN TRANSACTION
        {T-SQL Statement1}
        If @Error <> 0
            Goto Err_Handle
        {T-SQL Statement2}
        If @Error <> 0
            Goto Err_Handle
    COMMIT TRANSACTION
    Return(0)
Err_Handle:
    ROLLBACK TRANSACTION
    Return(@Error)
END
```


Example 1 – Store procedure without parameters



```
CREATE PROCEDURE sp_XemDSSV  
AS  
BEGIN  
    PRINT N'DANH SÁCH SINH VIÊN'  
    SELECT MSSV, HoLot, Ten, NgaySinh,  
        NoiSinh, DiaChi  
    FROM SinhVien  
END
```

Example 1 – Store procedure with parameters



```
CREATE PROCEDURE sp_XemSV  
    @MaSV nvarchar(11)  
AS  
BEGIN  
    PRINT N'SINH VIÊN'  
    SELECT HoLot, Ten, NgaySinh,  
        NoiSinh, DiaChi  
    FROM SinhVien  
    WHERE MSSV = @MaSV  
END
```

See Store Procedure content



- *Syntax:*

sp_helptext proc_name

For example:

- *Open Query Analyzer, typing:*

*sp_helptext **sp_XemDSSV***

*sp_helptext **sp_XemSV***

- *Check spelling and procedure content.*

Execute Stored Procedure



- **Syntax:**

EXECUTE proc_name parameter_list

or

EXEC proc_name parameter_list

or

proc_name parameter_list

Tips: Each parameter is separated by a comma

For example



- **Open Query Analyzer, typing:**
EXECUTE sp_XemDSSV
EXECUTE sp_XemSV 'K29.103.010'
or
EXEC sp_XemDSSV
EXEC sp_XemSV 'K29.103.010'
or
sp_XemDSSV
sp_XemSV 'K29.103.010'
- **Press *F5* to execute**

Discussion

