


**CSE 265:  
System & Network Administration**

- DNS – The Domain Name System
  - What does DNS do?
  - The DNS namespace
  - BIND software
  - How DNS works
  - DNS database
  - Testing and debugging (tools)

Source: Internet Systems Consortium ([www.isc.org](http://www.isc.org))

# What uses DNS?

- Any application that operates over the Internet
- Such as
  - email
  - Spam filters
  - WWW
  - FTP
  - IRC, IM
  - Windows update
  - telnet, ssh



# What does DNS do?

- Provides hostname – IP lookup services
  - `www.lehigh.edu` = 128.180.2.57
- DNS defines
  - A hierarchical namespace for hosts and IP addresses
  - A distributed database of hostname and address info
  - A “resolver” – library routines that query this database
  - Improved routing for email
  - A mechanism for finding services on a network
  - A protocol for exchanging naming information
- DNS is essential for any org using the Internet



## How DNS works


- A client calls `gethostbyname()`, which is part of the resolver library
- The resolver library sends a lookup request to the first nameserver that it knows about (from `/etc/resolv.conf`)
- If the nameserver knows the answer, it sends it back to the client
- If the nameserver doesn't know, it either
  - asks the next server, or
  - returns a failure, and suggests that the client contact the next server

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Resolving process



Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Selecting a domain name



- Most good (short) names in .com and other old gTLDs are already in use
- Domain names are up to 63 characters per segment (but a 12 character length limit is recommended), and up to 255 chars overall
- Identify two authoritative name servers
- Select a registrar, and pay ~\$1-\$35/year for registration

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## BIND software


- Berkeley Internet Name Domain system
  - By far, the most popular nameserver  
[[Measurement Factory 2010 study](#)]
- Three components
  - a daemon called named that answers queries
  - library routines that resolve host queries by contacting DNS servers
  - command-line utilities (nslookup, dig, host)

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Example resolution




Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Delegation



- Impractical for high-level servers to know about all hosts (or even sub-domains) below
- Servers delegate specific zones to other servers
- Names and addresses of authoritative servers for the relevant zone are returned in referrals

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Types of name servers

- Recursive vs. nonrecursive servers
  - Servers that allow recursive queries will do all the work
  - Nonrecursive servers will only return referrals or answers
- Authoritative vs. caching-only servers
  - Authoritative servers have the original data
  - Caching servers retain data previously seen for future use

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## What servers know

- All servers know about the 13 root servers
  - hardcoded (rarely changes!), or in hint file
  - a.root-servers.net ... m.root-servers.net
- Each root server knows about servers for every top-level domain (.com, .net, .uk, etc.)
- Each top-level domain knows the servers for each second-level domain within the top-level domain
- Authoritative servers know about their hosts

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## BIND client configuration

- Each host has `/etc/resolv.conf` which lists DNS servers
  - Can be set manually, or via DHCP
  - Example from sunlab:
 

```
search cse.lehigh.edu eeecs.lehigh.edu
nameserver 128.180.120.6
nameserver 128.180.120.4
nameserver 128.180.2.9
```
- Servers must be recursive, and should have a cache
- Servers are contacted in order, only after timing out previous attempt

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## BIND server issues


- named is typically started at boot time
- Configured using `/etc/named.conf`
- Can decide between
  - caching vs. authoritative
  - slave vs. master (per zone)
  - answering recursive or only iterative queries
- Lots more options
  - Who can access, what port, etc.

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Caching reduces DNS load




Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## IP-to-hostname resolution

- IP resolution works essentially the same as hostname resolution
- Query for 15.16.192.152
  - Rendered as query for 152.192.16.15.in-addr.arpa
  - Each layer can delegate to the next



Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Resource record: name

---

### **[name]** [ttl] [class] type data

- name is host or domain for the record
- Absolute names must end with a dot
- Relative names do not – the current domain is added (sometimes causing mistakes!)
  - www.cse.lehigh.edu.cse.lehigh.edu

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## DNS on Linux

---

- Linux uses /etc/nsswitch.conf to determine what sources to use for name lookups

```
# /etc/nsswitch.conf
#
passwd: files nisplus
shadow: files nisplus
group: files nisplus
hosts: files dns
```

- Configuration is in /etc/named.conf
- Other files in /var/named

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Resource record: ttl

---

### **[name]** **[ttl]** [class] type data

- The time to live (ttl) field specifies in seconds the time that the data item may still be cached
- Increasing the ttl (say to a week) decreases traffic and DNS load substantially
- Setting a value too low can hurt web site performance
- Typical values are in days or weeks

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## DNS database

---

- Exactly what data is stored?
- Resource records
  - Specify nameservers
  - Name to address translation
  - Address to name translation
  - Host aliases
  - Mail routing
  - Free text, location, etc.
- Format
  - [name] [ttl] [class] type data

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## SOA record

```
cs.colorado.edu 86400 IN SOA ns.cs.colorado.edu. hostmaster.cs.colorado.edu.  
(
```

```
    2001111300 ; serial number  
    7200      ; refresh (2 hours)  
    1800      ; retry (30 minutes)  
    604800    ; expire (1 week)  
    7200 )    ; minimum (2 hours)
```

- refresh = how often slave servers must check master
- retry = when the slave will try again after failure
- expire = how long data can be considered valid without master
- minimum = TTL for cached negative answers

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Resource record: class

[name] [ttl] [class] type data

- Three values of class are supported
  - IN: Internet
    - default (and only one modern systems care about)
  - CH: ChaosNet
    - obsolete protocol used by obsolete machines
  - HS: Hesiod
    - database service built on top of BIND (from MIT)

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## NS record

```
lehigh.edu.      86400 IN  NS   cerberus.CC.lehigh.edu.  
lehigh.edu.      86400 IN  NS   spot.CC.lehigh.edu.  
lehigh.edu.      86400 IN  NS   rover.CC.lehigh.edu.  
  
cse.lehigh.edu.  86400 IN  NS   kato.eecs.lehigh.edu.  
cse.lehigh.edu.  86400 IN  NS   rosie.eecs.lehigh.edu.  
cse.lehigh.edu.  86400 IN  NS   cerberus.cc.lehigh.edu.  
cse.lehigh.edu.  86400 IN  NS   spot.cc.lehigh.edu.  
cse.lehigh.edu.  86400 IN  NS   rover.cc.lehigh.edu.
```

- Can't tell whether the nameserver is master or slave (but it is definitely authoritative, not caching)

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Resource record: type

[name] [ttl] [class] type data

- Many DNS record types
  - Zone
    - SOA: Start of authority (define a zone)
    - NS: Name server
  - Basic
    - A: IPv4 address (name to address translation)
    - AAAA: IPv6 address (name to address translation)
    - PTR: address-to-name translation
    - MX: Mail exchanger
  - Other
    - CNAME: Canonical name (implements aliases)

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison



## Dynamic updates to DNS

- DNS was originally designed for an environment in which hostnames (and other DNS info) changed slowly, if at all
- DHCP breaks this assumption
- Recent versions of BIND allow DHCP to notify BIND of address assignments

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## A and PTR records

- ```
rover.cc.lehigh.edu. 45355 IN A 128.180.2.9
spot.cc.lehigh.edu. 45355 IN A 128.180.1.3
cerberus.cc.lehigh.edu. 45355 IN A 69.7.224.17
kato.eecs.lehigh.edu. 86400 IN A 128.180.120.6
rosie.eecs.lehigh.edu. 86400 IN A 128.180.120.4

6.120.180.128.in-addr.arpa. 7200 IN PTR kato.eecs.lehigh.edu.
4.120.180.128.in-addr.arpa. 7200 IN PTR rosie.eecs.lehigh.edu.
```
- lehigh.edu and 180.128.in-addr.arpa are different zones
    - each has own SOA and resource records
  - Some apps require that A and PTR records match (for authentication)

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## Testing and debugging (tools)

- named supports lots of logging options
- typical BIND tools
  - nslookup (old, possibly deprecated)
  - host
  - dig
- whois — find domain and network registration info

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison

## MX and CNAME records

- ```
piper          IN MX 10 piper
               IN MX 20 mailhub
xterm1         IN MX 50 boulder.colorado.edu.
               IN MX 10 mailhub

ftp            IN CNAME anchor
www            IN CNAME anchor

www.cse.lehigh.edu. 6754 IN CNAME telstar.eecs.lehigh.edu.
```
- Every host should have MX records
  - Machines that accept mail for others need to be configured to do so (e.g., mailhub)
  - CNAMEs can nest eight deep in BIND

Spring 2016

CSE 265: System and Network Administration

©2004-2016 Brian D. Davison



## Other Issues

---

- Many aspects of DNS haven't been covered in lecture
  - Lots of details!
  - Security issues
  - IPv6
  - Internationalization – now supported!
- DNS is generally case-insensitive
- VeriSign Site Finder product
  - See <http://cyber.law.harvard.edu/tlds/sitefinder/>