

## Model Name:GA-G41MT-S2P

Revision 1.31

SHEET

TITLE

01	COVER SHEET
02	BLOCK DIAGRAM
03	BOM & PCB MODIFY HISTORY
04	P4_LGA775_A
05	P4_LGA775_B,D
06	P4_LGA775_C
07	P4_LGA775_E,F,G,H
08	G41_HOST
09	G41_DDRII
10	G41_PCI E, DMI
11	G41_VGA
12	G41_GND
13	G41_PWR
14	PCI EXPRESS*16 SLOT
15	DDR3 CHANNEL A
16	DDR3 CHANNEL B
17	DDR3 TERMINATION
18	ICH7 PCI, USB, DMI, LAN
19	ICH7 IDE, GPIO, SATA, CTRL
20	ICH7 VCC, GND
21	CK505 CLOCK.
22	PCI SLOT 1,PCIE*1,2
23	IDE/FLOPPY/F_USB/R_USB
24	ITE 8718 GB
25	COM_LPT
26	CI,HWM,KB/MS,DUALBIOS
27	VIA VT2021

SHEET


TITLE

28	REAR AUDIO JACK
29	DISCRETE POWER
30	VCORE PWM_ISL6312
31	ATX, OTHERS POWER
32	FRONT PANEL
33	ARTHEROS AR8151

**Gigabyte Technology**

Title		
Cover Sheet		
Size	Document Number	Rev
Custom	GA-G41MT-S2P	1.31
Date:	Thursday, December 23, 2010	Sheet 1 of 33




BLOCK DIAGRAM





**Version: 1.31**

2010/12/23


[illegible][illegible]



中間値0.9V




### LGA775-39-2





Gigabyte Technology




Title			
P4_LGA775-A			
Size	Document Number	Rev	
B	GA-G41MT-S2P	1.3	
Date:	Thursday, December 23, 2010	Sheet	4 of 33



VCCA & VCOREPLL  
define doesn't same as  
old P4 design kit




Place outside of CPU socket




## Gigabyte Technology

Title			
P4_LGA775-C			
Size B	Document Number	GA-G41MT-S2P	Rev 1.3
Date:	Thursday, December 23, 2010	Sheet 6 of 33	


PECI:Platform Environment Control Interface




CPU-SK/775/S/GF



CPU-SK/775/S/GF



CPU-SK/775/S/GF



CPU-SK/775/S/GF


Gigabyte Technology

Title			
P4_LGA775-E,F,G,H			
Size B	Document Number		Rev
	GA-G41MT-S2P		1.3
Date:	Thursday, December 23, 2010	Sheet 7 of 33	












Gigabyte Technology


Title				
GMCH-PCI E & DMI				
Size Custom	Document Number			Rev
	GA-G41MT-S2P			1.3
Date:	Thursday, December 23, 2010		Sheet 10 of 33	






<b><i>Gigabyte Technology</i></b>			
Title			
GMCH-GND			
Size Custom	Document Number		Rev
	<b>GA-G41MT-S2P</b>		<b>1.31</b>
Date:	Thursday, December 23, 2010	Sheet	12 of 33
















## DDR TERMINATION CHANNEL A




## DDR TERMINATION CHANNEL B

### DDR18V Decouple



### DDRVTT Decouple





**Gigabyte Technology**

Title			DDRII TERMINATOR
Size	Document Number	GA-G41MT-S2P	
Custom		Rev	1.31
Date:	Thursday, December 23, 2010	Sheet	17 of 33










# PCI1,2 SLOT







AD\_16/-PIRQ(E-D-C-A)/-REQ0/-GNT0

[18] A\_D[0..31] ↔ A\_D[0..31]


-PCIRST ↔ -PCIRST [18]

Place close to PCI1




[14,15,16,19,21] SMBCLK ↔ PCI\_A40  
[14,15,16,19,21] SMBDATA ↔ PCI\_A41



# PCIEX1,2




WHITE



Gigabyte Technology			
PCI SLOT 1, 2/PCIEX1			
GA-G41MT-S2P			
Size	Document Number	Rev	
Custom		1.31	
Date:	Thursday, December 23, 2010	Sheet	22 of 33

IDE/SATA LED



IDE RESET

N/A


FLOPPY

N/A




IDE

N/A

FRONT USB1





FRONT USB2






RTS2- ==LOW CPU FAN 50%  
==HIGH 100%  
**DEFAULT 50%**



**FOR AR8161**




**EUP** [29] EUP\_N




**Dual BIOS:**  
GB logo :Pin 61 (GP15/CSA)  
GB logo :Pin 59 (GP17/CSB)

Pin 59 Dual BIOS ,Power On Strapping:  
H ==>Dual BIOS function Enable  
L ==>Dual BIOS function Disable

1.2V or 3.3V tolerance select.  
1.2V OUTPUT 接 VTT\_GMCH  
3.3V OUTPUT 接 3.3V  
LPCPD# =VIDVCC




**JP7 : HIGH DUAL BIOS ENABLE  
LOW DUAL BIOS DISABLE**








## TEMP H/W MONITOR




## CASE OPEN




Case Open Circuits


## KB/MS



## VOLTAGE-- H/W MONITOR




## DUAL BIOS



**Gigabyte Technology**


Title			
HW-MONITOR/CI/KB/MS/BIOS			
Size	Document Number	Rev	
Custom	GA-G41MT-S2P	1.31	
Date:	Thursday, December 23, 2010	Sheet	26 of 33

	ALC888B	ALC888 -VA	ALC889A	ALC888 -VD	ALC892
CR59	X	O	O	O	O
CR53,58	X	X	O	X	X
CR56	O	O	O	O	X
CR63	X	X	X	X	O
CR34	20K/1%	20K/1%	20K/0.1%	20K/1%	20K/1%



Can Support Amp Out



# CODEC POWER/EMI PAD




# CD IN N/A

# SPDIF IN N/A


# AZALIA JACK



# LINE-OUT




# LINE-IN




VIA 不SUPPORT

# MIC-IN




# AZALIA FRONT PANEL




Gigabyte Technology

AUDIO JACK			
Title	Document Number	GA-G41MT-S2P	Rev
Size	Custom		1.31
Date:	Thursday, December 23, 2010	Sheet	28 of 33


VTT\_PWRGD





3VDUAL




PWR\_SEQ




DDRVTT




VCC1\_5




DDR18V




VTT\_GMCH






















VCC1\_1



5VDUAL




FOR HEAT/OC DDR3 1333










<b>Gigabyte Technology</b>			
Title			
VRD 11.1 ISL6334			
Size	Document Number	<b>GA-G41MT-S2P</b>	Rev
Custom			1.3
Date:	Thursday, December 23, 2010	Sheet	30 of 33

# ATX POWER CONNECTOR



## FIX PWR AcBel(ATX-400C-A2ADB)




**Gigabyte Technology**

**ATX POWER CONNECTOR**


**GA-G41MT-S2P**

Title		Rev	
Size		1.31	
Date: Thursday, December 23, 2010		Sheet 31 of 33	


CPU SMART FAN	SMART FAN
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100




PROCESSOR HOT




## INTEL FRONT PANEL



## SYS\_FAN



## BUZZER






## PCIE-1G LAN


AR8131/AR8132 SWR:  
LL1,LBC27,LBC16(O),LR30(X)

```
AR8152 LDO OUTPUT(PIN4):LL1(X)
```


- 1.AL1A:LR30(O),LBC27,26(O)  
2.BL1A:LR30(O),LBC27,26(X)




CHOK4U7-500MA-1



FOR INTERNAL SWR  
AR8151:LR36(O),LR38(X)  
AR8161:LR38(O),LR36(X)




Single Color LED



LED0 (ACT)    LED1 (LINK)    LED2 (LINK1G)


CLKREQ# PULL-UP FOR EFUSE:

- 1.AR8151:LR31(O),LR32(X)
- 2.AR8152:LR31(X),LR32(O)



## USB\_LAN CONNECTOR



```
1G :USB+LAN/1G/GO,Y/OS/RA/D/1
100M:USB+LAN/100/GO,Y/OS/RA/D/1
```



LR25:AR8151(X),AR8152(O)

因100M LAN  
CONNECTOR差異

## USB\_LAN



P4+ ↔ +USBP4 [18]  
P4- ↔ -USBP4 [18]  
P5+ ↔ +USBP5 [18]  
P5- ↔ -USBP5 [18]