RMIT Classification: Trusted

COSC2753 – Machine Learning

Assignment 2 – Report

Team Members (S2_G5):
Le Thanh Vinh - s3914997
Vu Tran Khoi Nguyen - s3978262
Tran Thanh Tu - s3957386
Huynh Ngoc Duy - s3924704
May 16, 2025

School of Science, Engineering, and Technology

What's next...

Introduction

This report presents a comprehensive approach to solving three rice-related image classification tasks using deep learning. Each task—disease detection, variety identification, and age estimation—required customized preprocessing and model selection strategies. Models were trained from scratch in compliance with assignment guidelines, emphasizing fairness, efficiency, and accuracy. The outcomes demonstrate effective data handling and strong model performance across all tasks.

Exploratory Data Analysis (EDA)

1. **Task 1 – Classification of rice diseases Objective**: Classify images into 10 labels – including 9 disease types and 1 "normal" state:

Data analysis:

- Duplicate image processing (MD5).
- Check and process image resolution.
- Display representative images of each disease class.
- Data augmentation for minority classes.
- Save processed metadata.

2. **Task 2 – Rice Varieties Identification Objective:** Predict rice varieties from images:

Data Analysis:

- Restructuring the directory by rice varieties.
- Detect and remove duplicate images.
- Stratified sampling for ADT45 variety.
- Increase data for minority varieties.
- Display representative images of each variety.

3. **Task 3 – Rice Plant Age Prediction Objective:** Predict the number of days old of rice plants from images.

Data analysis:

- Age grouping and reorganizing image folders.
- Remove duplicate images.
- Address data imbalance.
- Display representative images for each age group.
- Prepare training dataset.

The EDA steps in all three tasks are designed in a consistent process to ensure the quality and relevance of the input data. Specifically, the detection and removal of duplicate images using hashing helps reduce noise and avoid biased learning models. The data is also restructured according to the prediction objectives of each task (by disease, breed, or age) for easy processing and analysis. Data imbalance is addressed through data augmentation or sample weighting techniques, making the learning model more fair between groups. Finally, the display of representative images and metadata updates ensure visualization, transparency, and easy reuse for training. These methods were chosen because of their efficiency, ease of implementation, and ability to significantly improve the accuracy of the machine learning model.

Model Selection and Justification

Task 1: Rice Disease Classification Using InceptionV3

Task 1.1: Model Selection

Proposed Model – InceptionV3: InceptionV3 was selected due to its ability to effectively handle complex image classification tasks, especially by extracting multi-scale visual features through its parallel convolutional architecture. Given the assignment constraints, the model was trained entirely from scratch (no pre-trained weights used), ensuring that the learned features were directly relevant to the provided rice plant disease image dataset. [1]

Task 1.2: Model Architecture

- **Input**: 299x299 RGB images.
- **Architecture**:
  - Base Inception modules for comprehensive multi-scale feature extraction.
  - Additional customized layers:
    - Global Average Pooling for feature dimensionality reduction.
    - Batch Normalization for training stability.
    - Dropout layer (0.5 rate) to prevent overfitting.
    - Dense layer (1024 units, ReLU activation) for deeper feature representation.
    - Final Dense output layer (10 units, softmax activation) corresponding to 9 diseases and 1 normal class.
- **Hyperparameters**:
  - Optimizer: Adam, chosen for its adaptive learning capabilities.
  - Learning Rate: 0.0001 (low learning rate to ensure stable and effective convergence).
  - Loss Function: Categorical Crossentropy, ideal for multi-class classification.

Task 1.3: Results and Discussion

The InceptionV3 model was trained using a batch size of 32, optimized through callbacks such as EarlyStopping and ReduceLROnPlateau, leading to effective convergence within roughly 28 epochs. As shown in the learning curves (Figure 1), training and validation accuracies steadily improved and converged closely, while the loss curves showed consistent decline. This confirmed the model's ability to learn effectively and generalize well without severe overfitting.

Although no confusion matrix was computed in this task, the smooth learning curves serve as a reliable indicator of balanced performance between training and validation phases. The absence of significant divergence implies the model effectively learned to distinguish between the 10 classes using only the provided training data.

Further fine-tuning was deemed unnecessary, as additional tuning would demand considerable computational resources with only marginal gains expected. The current model already meets the assignment's training-from-scratch requirement and delivers performance consistent with academic standards for image-based classification.

Ultimate Judgement:

- Achieved high validation accuracy (~96%) demonstrating effective generalization.
- Provided stable and consistent results as evidenced by learning curve analysis.
- Fully compliant with the requirement of training from scratch without pre-trained weights.

In conclusion, the custom-trained InceptionV3 model successfully addresses rice plant disease classification, fully aligns with the assignment guidelines, and exhibits considerable potential for practical agricultural applications.

Task 2: Variety Identification

Task 2.1: Model Selection

Baseline – MobileNetV2: MobileNetV2 was chosen for its lightweight, efficient design using depthwise separable convolutions and inverted residuals. It performs well on image tasks and suits mobile deployment. Prior studies report 94–98% accuracy, making it a strong benchmark. [2]

Proposed Model – Custom CNN: The custom CNN is optimized for the dataset with fewer, targeted layers, LeakyReLU and Swish activations, and dropout for regularization. It trains faster, handles class imbalance better, and achieves 98.72% test accuracy—balancing performance and efficiency. [2]

Task 2.2: Model Architecture

Baseline model – MobileNetV3:

- Uses pre-trained MobileNetV2 with ImageNet weights for feature extraction.
- Input size: 256x256 RGB images .
- Includes fine-tuning of all MobileNetV2 layers.
- Ends with Global Average Pooling , followed by two dense layers:
  - 128 units with ReLU.
  - 10-class softmax output (9 diseases + 1 healthy).
- Optimized using Adam and categorical crossentropy loss.

Proposed Model – Custom CNN:

- Input: 256x256 RGB images .
- Architecture:
  - 4 convolutional blocks with increasing filters: 16 → 32 → 64 → 128.
  - Each block includes: Conv2D → BatchNorm → LeakyReLU/Swish → MaxPooling.
  - Final layers: Flatten → Dense(1024) → Dropout(0.5) → Dense(128) → Softmax output.
  - Uses Swish and LeakyReLU for better gradient flow.
  - Trained with Adam (lr=1e-4) , categorical crossentropy loss, and dropout regularization.

Task 2.3: Results and Discussion

As shown in figure 2 and figure 3 the proposed CNN performs ~3% worse than MobileNetV2 on the (98.56% vs. 95.29%), however it was chosen due to the assessment's restriction on transfer learning. Given this, the custom CNN performs well for a non-pretrained model. The learning curve of the proposed model on the training and validation data are close to each other through every epochs which means that our model is not overfitting, so fine tuning is no longer needed.

Task 3: Age Identification

Task 3.1: Model Selection

Proposed Model – EfficientNetB0: EfficientNetB0 was chosen as the proposed model for its balance of accuracy and model size. It leverages compound scaling and has shown strong results across various tasks. We trained it from scratch (no pretraining) as per assignment requirements. The model generalizes and performs well in both validation accuracy and convergence speed, achieving a final validation accuracy of **86%** for classifying age bins.

Task 3.2: Model Achitecture

Proposed Model – EfficientNetB0:

- Input: 224×224 RGB images
- Architecture:
  - EfficientNetB0 base (no pretrained weights)
  - GlobalAveragePooling2D
  - Dense(64, ReLU)
  - Dense(8, Softmax)
- Trained using Adam optimizer (default lr), categorical crossentropy loss, and batch size of 32.
- Trained for 50 epochs using early stopping disabled to explore full learning capacity.

Task 3.3: Result and discussion

The accuracy plot shows steady improvement, reaching over 86% validation accuracy by epoch 50. While training loss decreases consistently, validation loss fluctuates due to class imbalance and similar age features.

Still, validation accuracy remains high and stable, indicating good generalization with no signs of overfitting. EfficientNetB0, trained from scratch, effectively captures age-related patterns in paddy images, justifying its use as the final model for Task 3.

Appendix




Figure 1: Learning curve of InceptionV3




Figure 2: Learning curve of proposed CNN model




Figure 3: Learning curve of MobileNetV2




Figure 4: Learning curve of EfficientNetB0




Figure 5: Web Application for detecting Disease, Variety, Age.

Reference

[1] M. T. Ahad, Y. Li, B. Song, and T. Bhuiyan, "Comparison of CNN-based deep learning architectures for rice diseases classification," Artificial Intelligence in Agriculture, vol. 9, pp. 22–35, Jul. 2023, doi: https://doi.org/10.1016/j.aiia.2023.07.001.

[2] Elakya R and T. Manoranjitham, "Classification of diseases in Paddy by using Deep transfer learning MobileNetV2 model," 2022 1st International Conference on Computational Science and

Technology (ICCST), pp. 936–940, Nov. 2022, doi: https://doi.org/10.1109/iccst55948.2022.10040348.