

Category	Function	Description	Syntax	Example of function	Possible result
Collection	contains	Check whether a collection has a specific item.	contains('<collection>', '<value>') OR contains([<collection>], '<value>')	contains('hello world', 'world')	true
Collection	empty	Check whether a collection is empty.	empty('<collection>') OR empty([<collection>])	empty('abc')	true
Collection	first	Return the first item from a collection.	first('<collection>') OR first([<collection>])	first('hello')	"h"
Collection	intersection	Return a collection that has <i>only</i> the common items across the specified collections.	intersection([<collection1>], [<collection2>], ...)	intersection(createArray(1, 2, 3), createArray(101, 2, 1, 10), createArray(6, 8, 1, 2))	[1, 2]
Collection	join	Return a string that has <i>all</i> the items from an array, separated by the specified character.	join([<collection>], '<delimiter>')	join(createArray('a', 'b', 'c'), '.')	"a.b.c"
Collection	last	Return the last item from a collection.	last('<collection>') OR last([<collection>])	last('abcd')	"d"
Collection	length	Return the number of items in a string or array.	length('<collection>') OR length([<collection>])	length('abcd')	4
Collection	skip	Remove items from the front of a collection, and return <i>all the other</i> items.	skip([<collection>], <count>)	skip(createArray(0, 1, 2, 3), 1)	[1, 2, 3]
Collection	take	Return items from the front of a collection.	take('<collection>', <count>) OR take([<collection>], <count>)	take('abcde', 3)	"abc"
Collection	union	Return a collection that has <i>all</i> the items from the specified collections.	union('<collection1>', '<collection2>', ...) OR union([<collection1>], [<collection2>], ...)	union(createArray(1, 2, 3), createArray(1, 2, 10, 101))	[1, 2, 3, 10, 101]
Conversion	array	Return an array from a single specified input. For multiple inputs, see createArray.	array('<value>')	array('hello')	["hello"]
Conversion	base64	Return the base64-encoded version for a string.	base64('<value>')	base64('hello')	"aGVsbG8="
Conversion	base64ToBinary	Return the binary version for a base64-encoded string.	base64ToBinary('<value>')	base64ToBinary('aGVsbG8=')	"01100001010001110101..."
Conversion	base64ToString	Return the string version for a base64-encoded string.	base64ToString('<value>')	base64ToString('aGVsbG8=')	"hello"
Conversion	binary	Return the binary version for an input value.	binary('<value>')	binary('hello')	"0110100001100101011011..."
Conversion	bool	Return the Boolean version for an input value.	bool(<value>)	bool(1)	true
Conversion	coalesce	Return the first non-null value from one or more parameters.	coalesce(<object_1>, <object_2>, ...)	coalesce(null, true, false)	true
Conversion	createArray	Return an array from multiple inputs.	createArray('<object1>', '<object2>', ...)	createArray('h', 'e', 'l', 'l', 'o')	["h", "e", "l", "l", "o"]
Conversion	dataUri	Return the data URI for an input value.	dataUri('<value>')	dataUri('hello')	"data:text/plain;charset=utf-8;base64,aGVsbG8="
Conversion	dataUriToBinary	Return the binary version for a data URI.	dataUriToBinary('<value>')	dataUriToBinary('data:text/plain;charset=utf-8;base64,aGVsbG8=')	"011001000110000101110100011..."
Conversion	dataUriToString	Return the string version for a data URI.	dataUriToString('<value>')	dataUriToString('data:text/plain;charset=utf-8;base64,aGVsbG8=')	"hello"
Conversion	decodeBase64	Return the string version for a base64-encoded string.	decodeBase64('<value>')	decodeBase64('aGVsbG8=')	"hello"
Conversion	decodeDataUri	Return the binary version for a data URI.	decodeDataUri('<value>')	decodeDataUri('data:text/plain;charset=utf-8;base64,aGVsbG8=')	"011001000110000101110100..."
Conversion	decodeUriComponent	Return a string that replaces escape characters with decoded versions.	decodeUriComponent('<value>')	decodeUriComponent('http%3A%2F%2Fcontoso.com')	"https://contoso.com"
Conversion	encodeUriComponent	Return a string that replaces URL-unsafe characters with escape characters.	encodeUriComponent('<value>')	encodeUriComponent('https://contoso.com')	"http%3A%2F%2Fcontoso.com"
Conversion	float	Return a floating point number for an input value.	float('<value>')	float('10.333')	10.333
Conversion	int	Return the integer version for a string.	int('<value>')	int('10')	10
Conversion	json	Return the JavaScript Object Notation (JSON) type value or object for a string or XML.	json('<value>')	json('[1, 2, 3]')	[1, 2, 3]
Conversion	string	Return the string version for an input value.	string(<value>)	string(10)	"10"

Data Factory Expression Language Functions – Sorted by Function Name (with hyperlinks)

Category	Function	Description	Syntax	Example of function	Possible result
Conversion	uriComponent	Return the URI-encoded version for an input value by replacing URL-unsafe characters with escape characters.	uriComponent('<value>')	uriComponent('https://contoso.com')	"http%3A%2F%2Fcontoso.com"
Conversion	uriComponentToBinary	Return the binary version for a URI-encoded string.	uriComponentToBinary('<value>')	uriComponentToBinary('http%3A%2F%2Fcontoso.com')	"0010001001101000011101..."
Conversion	uriComponentToString	Return the string version for a URI-encoded string.	uriComponentToString('<value>')	uriComponentToString('http%3A%2F%2Fcontoso.com')	"https://contoso.com"
Conversion	xml	Return the XML version for a string.	xml('<value>')	xml(json('{ \"name\": \"Sophia Owen\" }'))	<name>Sophia Owen</name>
Conversion	xpath	Check XML for nodes or values that match an XPath (XML Path Language) expression, and return the matching nodes or values.	xpath('<xml>', '<xpath>')	xpath(xml(parameters('items')), 'sum(/produce/item/count)')	30
Dates	addDays	Add a number of days to a timestamp.	addDays('<timestamp>', <days>, '<format>?')	addDays('2018-03-15T13:00:00Z', 10)	"2018-03-25T00:00:000000Z"
Dates	addHours	Add a number of hours to a timestamp.	addHours('<timestamp>', <hours>, '<format>?')	addHours('2018-03-15T00:00:00Z', 10)	"2018-03-15T10:00:000000Z"
Dates	addMinutes	Add a number of minutes to a timestamp.	addMinutes('<timestamp>', <minutes>, '<format>?')	addMinutes('2018-03-15T00:10:00Z', 10)	"2018-03-15T00:20:00.000000Z"
Dates	addSeconds	Add a number of seconds to a timestamp.	addSeconds('<timestamp>', <seconds>, '<format>?')	addSeconds('2018-03-15T00:00:00Z', 10)	"2018-03-15T00:00:10.000000Z"
Dates	addToTime	Add a number of time units to a timestamp. See also getFutureTime.	addToTime('<timestamp>', <interval>, '<timeUnit>', '<format>?')	addToTime('2018-01-01T00:00:00Z', 1, 'Day')	"2018-01-02T00:00:00.000000Z"
Dates	convertFromUtc	Convert a timestamp from Universal Time Coordinated (UTC) to the target time zone.	convertFromUtc('<timestamp>', '<destinationTimeZone>', '<format>?')	convertFromUtc('2018-01-01T08:00:00.000000Z', 'Pacific Standard Time')	"2018-01-01T00:00:00Z"
Dates	convertTimeZone	Convert a timestamp from the source time zone to the target time zone.	convertTimeZone('<timestamp>', '<sourceTimeZone>', '<destinationTimeZone>', '<format>?')	convertTimeZone('2018-01-01T08:00:00.000000Z', 'UTC', 'Pacific Standard Time')	"2018-01-01T00:00:00.000000Z"
Dates	convertToUtc	Convert a timestamp from the source time zone to Universal Time Coordinated (UTC).	convertToUtc('<timestamp>', '<sourceTimeZone>', '<format>?')	convertToUtc('01/01/2018 00:00:00', 'Pacific Standard Time')	"2018-01-01T08:00:00.000000Z"
Dates	dayOfMonth	Return the day of the month component from a timestamp.	dayOfMonth('<timestamp>')	dayOfMonth('2018-03-15T13:27:36Z')	15
Dates	dayOfWeek	Return the day of the week component from a timestamp.	dayOfWeek('<timestamp>')	dayOfWeek('2018-03-15T13:27:36Z')	3
Dates	dayOfYear	Return the day of the year component from a timestamp.	dayOfYear('<timestamp>')	dayOfYear('2018-03-15T13:27:36Z')	74
Dates	formatDateTime	Return the timestamp as a string in optional format.	formatDateTime('<timestamp>', '<format>?')	formatDateTime('03/15/2018 12:00:00', 'yyyy-MM-ddTHH:mm:ss')	"2018-03-15T12:00:00"
Dates	getFutureTime	Return the current timestamp plus the specified time units. See also addToTime.	getFutureTime(<interval>, <timeUnit>, <format>?)	getFutureTime(5, 'Day')	"2018-03-06T00:00:00.000000Z"
Dates	getPastTime	Return the current timestamp minus the specified time units. See also subtractFromTime.	getPastTime(<interval>, <timeUnit>, <format>?)	getPastTime(5, 'Day')	"2018-01-27T00:00:00.000000Z"
Dates	startOfDay	Return the start of the day for a timestamp.	startOfDay('<timestamp>', '<format>?')	startOfDay('2018-03-15T13:30:30Z')	"2018-03-15T00:00:00.000000Z"
Dates	startOfHour	Return the start of the hour for a timestamp.	startOfHour('<timestamp>', '<format>?')	startOfHour('2018-03-15T13:30:30Z')	"2018-03-15T13:00:00.000000Z"
Dates	startOfMonth	Return the start of the month for a timestamp.	startOfMonth('<timestamp>', '<format>?')	startOfMonth('2018-03-15T13:30:30Z')	"2018-03-01T00:00:00.000000Z"
Dates	subtractFromTime	Subtract a number of time units from a timestamp. See also getPastTime.	subtractFromTime('<timestamp>', <interval>, '<timeUnit>', '<format>?')	subtractFromTime('2018-01-02T00:00:00Z', 1, 'Day')	"2018-01-01T00:00:00.000000Z"
Dates	ticks	Return the ticks property value for a specified timestamp.	ticks('<timestamp>')	ticks('2018-03-15T13:30:30Z')	636566556300000000
Dates	utcNow	Return the current timestamp as a string.	utcNow('<format>')	utcNow()	"2018-04-15T13:00:00.000000Z"
Logical	and	Check whether all expressions are true.	and(<expression1>, <expression2>)	and(false, true)	false
Logical	equals	Check whether both values are equivalent.	equals('<object1>', '<object2>')	equals(true, 1)	true
Logical	greater	Check whether the first value is greater than the second value.	greater(<value>, <compareTo>) OR greater('<value>', '<compareTo>')	greater(10, 5)	true

Category	Function	Description	Syntax	Example of function	Possible result
Logical	greaterOrEquals	Check whether the first value is greater than or equal to the second value.	greaterOrEquals(<value>, <compareTo>) OR greaterOrEquals('<value>', '<compareTo>')	greaterOrEquals(5, 5)	true
Logical	if	Check whether an expression is true or false. Based on the result, return a specified value.	if(<expression>, <valueIfTrue>, <valueIfFalse>)	if(equals(1, 1), 'yes', 'no')	"yes"
Logical	less	Check whether the first value is less than the second value.	less(<value>, <compareTo>)	less(5, 10)	true
Logical	lessOrEquals	Check whether the first value is less than or equal to the second value.	lessOrEquals(<value>, <compareTo>)	lessOrEquals(10, 10)	true
Logical	not	Check whether an expression is false.	not(<expression>)	not(false)	true
Logical	or	Check whether at least one expression is true.	or(<expression1>, <expression2>)	or(true, false)	true
Mathematical	add	Return the result from adding two numbers.	add(<summand_1>, <summand_2>)	add(1, 1.5)	2.5
Mathematical	div	Return the result from dividing two numbers.	div(<dividend>, <divisor>)	div(10, 5)	2
Mathematical	max	Return the highest value from a set of numbers or an array.	max(<number1>, <number2>, ...)	max(1, 2, 3)	3
Mathematical	min	Return the lowest value from a set of numbers or an array.	min(<number1>, <number2>, ...)	min(1, 2, 3)	1
Mathematical	mod	Return the remainder from dividing two numbers.	mod(<dividend>, <divisor>)	mod(3, 2)	1
Mathematical	mul	Return the product from multiplying two numbers.	mul(<multiplicand1>, <multiplicand2>)	mul(1, 2)	2
Mathematical	rand	Return a random integer from a specified range.	rand(<minValue>, <maxValue>)	rand(1, 5)	4
Mathematical	range	Return an integer array that starts from a specified integer.	range(<startIndex>, <count>)	range(1, 4)	[1, 2, 3, 4]
Mathematical	sub	Return the result from subtracting the second number from the first number.	sub(<minuend>, <subtrahend>)	sub(10.3, .3)	10
Strings	concat	Combine two or more strings, and return the combined string.	concat('<text1>', '<text2>', ...)	concat('Hello', 'World')	"HelloWorld"
Strings	endsWith	Check whether a string ends with the specified substring.	endsWith('<text>', '<searchText>')	endsWith('hello world', 'world')	true
Strings	guid	Generate a globally unique identifier (GUID) as a string.	guid()	guid('P')	"(c2ecc88d-88c8-4096-912c-d6f2e2b138ce)"
Strings	indexOf	Return the starting position for a substring.	indexOf('<text>', '<searchText>')	indexOf('hello world', 'world')	6
Strings	lastIndexOf	Return the starting position for the last occurrence of a substring.	lastIndexOf('<text>', '<searchText>')	lastIndexOf('hello world', 'world')	6
Strings	replace	Replace a substring with the specified string, and return the updated string.	replace('<text>', '<oldText>', '<newText>')	replace('the old string', 'old', 'new')	"the new string"
Strings	split	Return an array that contains substrings, separated by commas, from a larger string based on a specified delimiter character in the original string.	split('<text>', '<delimiter>')	split('a_b_c', '_')	["a", "b", "c"]
Strings	startsWith	Check whether a string starts with a specific substring.	startsWith('<text>', '<searchText>')	startsWith('hello world', 'hello')	true
Strings	substring	Return characters from a string, starting from the specified position.	substring('<text>', <startIndex>, <length>)	substring('hello world', 6, 5)	"world"
Strings	toLower	Return a string in lowercase format.	toLower('<text>')	toLower('Hello World')	"hello world"
Strings	toUpper	Return a string in uppercase format.	toUpper('<text>')	toUpper('Hello World')	"HELLO WORLD"
Strings	trim	Remove leading and trailing whitespace from a string, and return the updated string.	trim('<text>')	trim(' Hello World ')	"Hello World"