GROUP-IB

Threat intelligence

Web portal manual

Content

Integrations

Starting Guide 5
Initial Steps 5
Steps to Get Started 5
URLs and IP Addresses for Access 5
API key generation 5
IP access list 7
Test API Configuration 9
Request 9
Response 9
Troubleshooting 10
Troubleshooting and Error Codes 12
HTTP Response Codes 12
Important Points to Avoid Errors 12
API Limitations 15
Quantity Requests Limitations 15
Records limits 15
IP Access List 17
POC and Partner Access Limitations 18
API Ticket Creation Guide 19
Navigate to the Service Desk 19
Click “Create Request” 19
Choose category and fill out the form 20
API and Integration Support 21
Integration development request 96
Collections Overview 98
Threats and Actors 98
Malware 98
Darkweb 99
Compromises 99
Banking 100
Suspicious Indicators 100
Not presented in the interface 101
Utility & Analysis Endpoints 102
Legend 103
Collections Details - Utilities 105
User Granted Collections 105
Sequence List 109
Search 113
IMC API 118

Collections Details - Feeds 134
Threats and Actors - APT Threat Actors 134
Threats and Actors - APT Threat Reports 145
Threats and Actors - HI Threat Actors 157
Threats and Actors - HI Threat Reports 167
Threats and Actors - Open Threats 179
Threats and Actors - Analyst Reports 188
IOC Primary 195
IOC Common 206
Malware - C2 212
Malware - Config 218
Malware - Reports 224
Malware - Suricata 231
Malware - Yara 237
Malware - Vulnerability 242
Malware - Phishing Kit 250
Darkweb - Discord 257
Darkweb - Telegram 261
Darkweb - Shops 269
Darkweb - Forums 274
Compromises - Account 280
Compromises - Git Repository 290
Compromises - Public Leak 294
Compromises - Breached DB 302
Banking - Cards 309
Banking - Masked cards 314
Banking - SPD 319
Suspicious indicators - Deface 327
Suspicious indicators - DDoS 334
Suspicious indicators - Open Proxies IP 343
Suspicious indicators - Phishing 348
Suspicious indicators - Scanning IP 361
Suspicious indicators - Socks Proxy IP 366
Suspicious indicators - TOR IP 371
Suspicious indicators - VPN IP 376
Collections Details - Analysis 382
Domain Whois 382
IP Whois 388
IP Scoring 395
Domain Scoring 399
Deprecated Collections 403
Overview 403
Collections: 403

Reference: 403
Custom and native integrations 404
List of integrations 404
Explanatory notes 406
Google SecOps 407
Overview 407
Installation 407
Configuration 408
Step 1. App configuration 408
Step 2. Connectors configuration 409
Step 3. Alerts configuration 412
Usage 413
Data filtering 417
Troubleshooting 417
Common errors 418
Download logs 418
Common errors solution 418
LogRhythm 420
Installation 420
Configuration 420
Run the script 420
Automation 421
Configuration script steps 421
Troubleshooting 421
MISP 422
Installation 422
Configuration 422
Troubleshooting 425
FAQ 425
ThreatConnect 426
Installation 426
Configuration 427
Step 1. Add new Job 427
Step 2. Collections configuration 428
Usage 430
Data filtering 433
Troubleshooting 440
Enable Debug Logging 440
Log Collection 440
Testing API Connectivity via cURL 441
Common Errors and Solutions 441
Data Input Error Code (HTTP) in TC 442
ArcSight SIEM Connector 443

ArcSight SIEM Connector 443
Requirements 443
Configuration 443
Deploy 444
ArcSight FlexConnector Setup 444
Working with the Integration 445
Available Collections 446
Troubleshooting 448
Custom API tools 453
TI Data Export Utility 453
Glossary 454
Introduction 455
Use Cases 456
Installation 457
Running the Utility 458
CLI Menu Structure Overview 459
Data Export Utility Options 459
Tips and Best Practices 466
TI Python library 467
ciaops 467
License 467
Installation 467
Usage 467
Parsing 470
Records limits 470
Troubleshooting 470
TI Postman configuration 471
Prerequisites 471
Installation 471
Configuration 471
Usage 471
Example Requests 472
Additional Notes 473
Developer Guide 474
Common Dev info 474
API Logic Explanation 479
API logic 479
Sequence Update logic 480
Search logic 481

Starting Guide
Initial Steps

API is a powerful interface designed to seamlessly integrate Group-IB Threat Intelligence with your internal security and anti-fraud systems. It operates using the RESTful protocol, with all data returned in JSON format for easy parsing and integration.

Steps to Get Started

- IP Access List Provide your public IP addresses, and we'll add them to the API access list.
- Generate API Key Log in to your account, navigate to your profile, and generate an API_KEY. Be sure to save this key, as it will be required for API access. For API authorization, use your email and the generated API key instead of your portal password.
- Start Using API Tools Once the previous steps are completed, you can test your API connection by following the steps outlined in the Test API Configuration article. Then, begin utilizing the API with tools such as Custom TI Data Export, Postman, and other integration utilities.

Developing your own integration? Before you start building, review the ciaops Python library and the TI Postman collection. The ciaops library handles authentication, pagination, and rate limiting for you, and the Postman collection lets you explore the endpoints interactively - both are the recommended starting points for any custom integration.

URLs and IP Addresses for Access

To ensure the API and web interface function properly (this list is applicable for both API and web-interface), add the following URLs and IP addresses to your internal security access list:

URLs:

- tap.group-ib.com - Base domain for web portal and API access
- sso.group-ib.com - Required for web portal


IP-addresses

- 148.251.50.14
- 144.76.117.21
- 138.201.56.157
- 88.99.105.142
- 94.130.70.148
- 88.99.167.51


API key generation

To generate the API_KEY follow these steps:


- Navigate to Group-IB Threat Intelligence
- Click your name in the upper-right corner and select Profile




- Go to Security and Access -> Personal token



- Click GENERATE TOKEN



- Enter your password, then click Save button to save API KEY and exit the settings.




NOTE: Don’t forget to save all changes during API key generation!


IP access list

You can add your external IP addresses through your profile settings. Follow the steps below:


- Navigate to Group-IB Threat Intelligence
- Click your name in the upper-right corner, select Profile.
- Go to Security and Access -> IP white list.
- Click the Edit button and enter your trusted IP address.



- Before entering another IP, click the “Create ‘X.X.X.X.’” line. Repeat this process for each IP address you want to add.



- Click Save to confirm and apply the changes, adding all IP addresses to your access list.



NOTE: If you need to add a large number of IP addresses, or configure an access list for an entire company or cloud system, please create a ticket through the Service Desk for assistance.

Test API Configuration

Request


Once you've configured the API, you can verify that everything is working correctly by using the following curl request in your terminal:

curl -u login:api_key https://tap.group-ib.com/api/v2/user/granted_collections


Alternatively, you can verify everything in Postman as shown in the screenshot below: Request: GET https://tap.group-ib.com/api/v2/user/granted_collections


For the password field enter the API key you have generated. This key is required for successful authentication.

If you haven't generated an API key yet, please refer to the Initial Steps article for step-by-step instructions on how to create one.



Response





This request will help ensure that your API setup is functioning as expected. If you receive a successful response, your API is correctly configured.

Troubleshooting

Make sure you follow all the steps in the Initial Steps. If you receive an error response (e.g., 401 Unauthorized or 403 Forbidden), ensure that:

- Your login and API key are correct.
  - Your IP address is whitelisted in the access list.
  - You are using the correct API endpoint.
  - The Authorization header is properly formatted.

Then refer to the Troubleshooting and error codes article for further details.

Troubleshooting and Error Codes


HTTP Response Codes

- 400: Bad Request A bad request usually stems from incorrect request formatting. Check the error details in the response JSON and adjust the request accordingly.
- 401: Unauthorized This code indicates a failed authentication attempt. Make sure you're using Basic Authentication with the correct username and API key. Verify that these credentials are accurate and included in the request header.
- 403: Forbidden Access issues, such as IP restrictions or invalid API keys, can cause this error. Confirm that your IP address is allowed, the API key is valid, and you have permission to access the requested feed. Check your settings or contact Group-IB support if necessary.
- 404: Not Found The requested resource does not exist on the server. Double-check that the URL is correct and that the resource is available.
- 429: Too Many Requests This response means you've exceeded the allowable request rate. Reduce your request frequency or adjust the limit parameter to stay within the acceptable range.
- 500: Internal Server Error This error indicates a server-side problem while processing your request. Wait and try again later.
- 504: Gateway Timeout or Timeout The request took too long to process. Try reducing the limit parameter when making API requests to decrease the load and avoid timeouts.


Note: If these response codes don't resolve your issue or if further troubleshooting is needed, you can reach out to our support team via the Service Desk for additional assistance. For detailed steps on how to create a Service Desk ticket, please refer to API Ticket Creation Guide.

Important Points to Avoid Errors


- Avoid Using DF and DT Parameters with seqUpdate In the updated endpoint /updated, do not use the DF (date from) and DT (date to) parameters along with the seqUpdate parameter. This is because the seqUpdate already acts as a timestamp for filtering data, and including DF and DT will introduce conflicting date filters. For example, avoid using the endpoint in this format: /api/v2/ioc/common/updated?sequpdate=15995952916289&df=2024-01-01&dt=2024-09-09 Using both date filters (DF/DT) alongside seqUpdate will result in errors, and while the API might return a response, the data will be inaccurate and inconsistent with the expected results as shown in the screenshot below: The screenshot below illustrates the proper configuration for sending a GET request using Postman:



The following screenshot highlights a common mistake that should be avoided:



- Do Not Use Your Account Password as the API Key Ensure that you do not mistakenly use your account password as the API key. API keys are designed to authenticate your requests securely, and using your password could not only cause errors but also expose your credentials to unauthorized access, compromising account security.


GET Get updated items (IOC
No environment
Group-IB Threat Intelligence APIv2 / api/v2 / ioc / common / Get updated items (IOC.Common)
Save
Share
GET
https://tap.group-ib.com/api/v2/ioc/common/updated?seqUpdate=1599595291628 9
Send
Params
Authorization
Headers (8)
Body
Scripts
Settings
Cookies
Auth Type
Basic Auth
Username
Password
The authorization header will be automatically generated when you send the request. Learn more about Basic Auth authorization.
Body
Cookies
Headers (18)
Test Results
403 Forbidden
541 ms
852 B
Save Response
Pretty
Raw
Preview
Visualize
JSON
{
"message": "Permission denied"
}
Online
Find and replace
Console
Postbot
Runner
Start Proxy
Cookies
Vault
Trash

API Limitations

Quantity Requests Limitations

Due to technical constraints, the API has several request rate limitations:

You are allowed 1 request per 1 second per company per feed per route. This means you can only poll a specific feed from one account. For instance, while you cannot poll the feed at /api/v2/hi/threat/updated more frequently than once per 1 second, you can simultaneously poll different feeds such as /api/v2/ioc/primary/updated and /api/v2/hi/threat/updated

Records limits

Default limit is 100 records per request. Due to different size of feeds there are different limits for getting data:

Feed	Limit
osi/vulnerability/updated	500
osi/public_leak/updated	100
osi/git_repository/updated	100
compromised/account_group/updated	500
compromised/breacheddb/updated	100
compromised/bank_card_group/updated	500
compromised/masked_card/updated	500
compromised/spd/updated	500
compromised/access/updated	500
compromised/messenger/updated	100
compromised/discord/updated	100
darkweb/forums/updated	100

Feed	Limit
hi/threat/updated	10
hi/threat_actor/updated	100
hi/open_threats/updated	100
apt/threat/updated	10
apt/threat_actor/updated	100
suspicious_ip/tor_node/updated	100
suspicious_ip/open_proxy/updated	5000
suspicious_ip/socks_proxy/updated	5000
suspicious_ip/vpn/updated	100
suspicious_ip/scanner/updated	5000
malware/config/updated	100
malware/malware/updated	100
malware/cnc/updated	1000
malware/yara/updated	5000
malware/signature/updated	5000
ioc/primary/updated	2500
ioc/common/updated	5000
attacks/ddos/updated	5000
attacks/phishing_kit/updated	1000

Feed	Limit
attacks/phishing_group/updated	1000
attacks/deface/updated	100

IP Access List

The API is only accessible from trusted IP addresses. During validation, we check the following IP lists:

1. User's IP List You can set up your own allowed IP list by navigating to your Profile page -> Security and Access -> Allowed IP list.

2. Company's IP List You can find the IP assets of your company on the Company page -> Assets -> (IP v4 addresses | IP v6 addresses) Note: The Company's IP list is fixed. If you need to add new IP addresses to your assets, please submit a request via the Service Desk.

3. Global IP addresses list These IP addresses belong to vendors with whom we have integrations. If you use one of these vendors, their IPs are already in our access list. Here is the list of these IPs:

Vendor	IP Address(es)
Anomali	54.208.4.186, 105.184.118.114, 194.46.126.6, 197.101.51.179, 197.101.53.127, 216.38.139.26, 34.227.3.92, 34.231.7.29, 35.168.197.59, 35.172.241.145, 35.173.107.231, 50.1.114.34, 50.1.114.40, 52.23.133.33, 52.34.112.37, 52.37.145.253, 52.73.15.50, 54.147.241.218, 54.87.172.249, 54.87.192.13, 81.128.219.20, 94.204.8.39, 3.225.1.124, 52.24.86.178, 52.37.145.25, 52.158.28.64/28, 20.50.68.128/29, 51.144.56.96/28, 40.113.178.32/29
EclecticIQ	34.247.181.230, 3.75.187.123
Splunk Cloud	34.225.9.69, 52.70.128.234, 3.225.120.176, 34.231.205.169, 122.179.137.12, 122.169.101.20, 34.193.4.124, 52.21.139.207, 103.108.207.48/28, 122.179.137.12/32, 122.169.101.20/32
ThreatConnect	54.159.242.168

Vendor	IP Address(es)
Microsoft Sentinel	40.68.209.23, 40.68.222.65, 20.193.17.32, 20.197.219.106, 20.48.128.36, 20.199.186.58, 40.80.86.109, 52.158.170.36, 20.52.212.85, 52.251.70.29, 20.74.12.78, 20.194.150.139, 20.194.17.254, 51.13.75.153, 102.133.139.160, 20.197.113.87, 40.123.207.43, 51.11.168.197, 20.71.8.176, 40.64.106.65
Cortex XSOAR	35.244.250.18, 35.227.237.180, 34.120.31.199, 34.120.87.77, 35.241.28.254, 34.117.211.129, 34.120.229.65, 34.98.68.183, 35.186.207.80, 34.111.6.153, 34.117.240.208, 34.160.28.41, 35.190.0.180, 34.111.134.57, 34.111.129.144, 35.222.81.194, 34.90.67.58, 35.203.82.121, 34.89.56.78, 34.84.125.129, 34.87.83.144, 35.189.18.208, 34.107.57.23, 35.200.158.164, 34.65.248.119, 34.116.216.55, 35.234.8.249, 34.18.46.240, 34.155.222.152, 34.165.156.139, 35.222.81.194, 34.90.67.58, 35.203.82.121, 34.89.56.78, 34.84.125.129, 34.87.83.144, 35.189.18.208, 34.107.57.23, 35.200.158.164, 34.65.248.119, 34.116.216.55, 35.234.8.249, 34.18.46.240, 34.155.222.152, 34.165.156.139, 35.225.156.101, 34.69.88.119, 34.147.67.188, 34.90.16.31, 35.203.57.162, 35.203.90.79, 34.142.3.42, 34.142.44.136, 34.146.60.215, 34.84.93.160, 35.240.144.192, 35.240.255.15, 35.244.73.76, 35.201.22.63, 34.107.83.197, 34.159.53.97, 34.93.118.113, 35.244.5.205, 34.65.233.60, 34.65.222.25, 34.116.223.119, 34.118.92.214, 104.199.223.229, 34.81.38.132, 34.18.39.0, 34.18.32.96, 34.155.197.131, 34.155.5.100, 34.165.33.165, 34.165.27.131
Filigran, OpenCTI	5.135.76.0/27 141.95.234.96/28 164.132.148.32/27 135.148.64.32/27 51.89.91.160/27
Liberty91	35.210.22.235

If you are missing your vendor IP, please inform us via Service Desk.

POC and Partner Access Limitations

For users with a Proof of Concept (POC) license or a trial, feed consumption is limited to data from the last 30 days. This same 30-day data access restriction also applies to partner accounts. Ensure that your use cases align with these limitations to effectively leverage the available data within the set timeframe.

API Ticket Creation Guide


This guide will walk you through the steps required to create a ticket in the service desk system. Follow these instructions to ensure proper reporting and tracking of issues.

Disclaimer#1: When creating an API support ticket, it is crucial to select the correct category and provide all necessary information and data required for issue resolution. Failure to do so may result in your inquiry not being addressed. Choosing the wrong category or omitting essential details can delay or prevent effective troubleshooting and support.

Disclaimer#2: Coins are not charged for requests related to integrations.


Navigate to the Service Desk

- From the TI Portal Dashboard, locate and click on the Service Desk tab in the left-side panel.



Click “Create Request”


- In the Service Desk section, click on the Create Request button to begin a new support ticket



Choose category and fill out the form


From the menu, select the most appropriate category for your issue:

- API and Integration Support: Use this category if you require assistance with existing native integrations, REST API functionalities, or STIX/TAXII 2.x protocols.
- Integration development request: Select this option when you need to request the development of a new integration.



API and Integration Support

- Choose sub category for your request:



.

Rest APIv2

All questions related to use of JSON API

.

STIX/TAXII 2.x

Questions related to STIX/TAXII 2.x

.


Native integration applications

Installation and troubleshooting of native applications

.

- Fill out the Required Information:

  For Rest APIv2:



.

User name

User’s email, where API token is established

.

Public IP

External IP of your instance, used for API communication

.

Used API routes


All API endpoints are listed here. Specify “None” if there is no any

.

Description

Add comments if you want to provide additional information

For STIX/TAXII 2.x:



User name

User’s email, where API token is established

.

Public IP

External IP of your instance, used for STIX/TAXII integration

.

Application


Application used for STIX/TAXII integration

.

Description

Add comments if you want to provide additional information

For Native integration applications:



User name

User’s email, where API token is established

.

Public IP

External IP of your instance, used for integration

.

Application

3rd party vendor application name


.

Description

Add comments if you want to provide additional information


.

- Submit the request Click the Send button to submit the request




Integration development request

- Describe the case
- Drag and drop the necessary files



- Submit the request Click the Send button to submit the request



By selecting the correct request type, you streamline the process and reduce the time it takes for our support team to resolve issues or respond to your inquiries.

Collections Overview

Threats and Actors

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Actors	Common + Individual	apt/threat_actor/updated	360	None	9	Supported
		hi/threat_actor/updated	360	None	9	Supported
Last threats	Common + Individual	apt/threat/updated	360	Can differ	9	Supported
		hi/threat/updated	360	Can differ	9	Supported
Open Threats	Common	hi/open_threats/updated	None	Mostly B3	5	Supported
Analytic Reports	Common	hi/analytic/updated	None	A1	N/A	N/A

Note: For Last threats submodule reports can be found at the threat actor profile on the left side. Threats are mostly in the “Common” category, but some of them can be individual for clients. TTL is not provided in the API for the endpoints in this table.

Malware

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Configs	Individual	malware/config/updated	30	A1	9	N/A
Reports	Common	malware/malware/updated	None	None	9	N/A
Signatures (Suricata)	Common	malware/signature/updated	None	None	8	N/A

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Yara rules	Common	malware/yara/updated	None	None	8	N/A
Phishing Kits	Common	attacks/phishing_kit/updated	30	mostly B2	9	Supported
Vulnerabilities	Common	osi/vulnerability/updated	30	A1	9	Supported

Darkweb

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Comment	Hunting Rules
Instant messengers (Telegram)	Individual	compromised/messenger/updated	None	None	N/A	TTL not provided in API	N/A
Discord	Individual	compromised/discord/updated	None	None	N/A	TTL not provided in API	N/A
Shops	Individual	compromised/access/updated	90	A2	N/A	TTL not provided in API	N/A
Forums	Individual	darkweb/forums/updated	None	None	N/A	TTL not provided in API	N/A

Compromises

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Accounts	Individual	compromised/account_group/updated	90	A2	N/A	N/A
Public leaks	Individual	osi/public_leak/updated	30	C3	N/A	N/A
Git Leaks	Individual	osi/git_repository/updated	30	A1	N/A	N/A
Breached DB	Individual	compromised/breacheddb/updated	N/A	C3	N/A	N/A

Banking

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Bank cards	Individual	compromised/bank_card_group/updated	90	A2	N/A	N/A
		compromised/masked_card/updated	90	A2	N/A	N/A
Suspicious Payment Details	Common	compromised/spd/updated	90	A2	N/A	N/A

Suspicious Indicators

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Hunting Rules
Tor	Common	suspicious_ip/tor_node/updated	30	A1	3	Supported
Open proxy	Common	suspicious_ip/open_proxy/updated	15	C3	3	Supported
Socks proxy	Common	suspicious_ip/socks_proxy/updated	2	A1	3	Supported
VPN	Common	suspicious_ip/vpn/updated	30	A2	1	Supported
Scanning IP	Common	suspicious_ip/scanner/updated	15	C3	1	Supported
DDoS	Common	attacks/ddos/updated	30	A2	3	Supported
Phishing	Common	attacks/phishing_group/updated	30	A2-A3	6	Supported
Deface	Common	attacks/deface/updated	30	B2	3	N/A

Not presented in the interface

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Comment	Hunting Rules
Malware	Common	malware/cnc/updated	90	None	9	TTL not provided in API	N/A

Submodule	Individual/Common	APIv2 Endpoint	TTL (Days)	Admiralty	Severity	Comment	Hunting Rules
IOC	Common	ioc/primary/updated	Per record (365-14600)	Per record	Derive from riskScore	Replaces ioc/common. Network (IP, domain, URL) and file (hash) indicators with risk score, malware and threat actor attribution. Includes malware/cnc indicators.	N/A

Utility & Analysis Endpoints

Module	APIv2 Endpoint	Type	Description	Hunting Rules
General	user/granted_collections	Utility	Retrieve list of collections available to authenticated user. Also serves as a health check endpoint.	N/A
General	sequence_list	Utility	Get sequence update numbers for all collections based on a specific date.	N/A

Module	APIv2 Endpoint	Type	Description	Hunting Rules
General	search	Utility	Global search across all available collections for indicators, domains, IPs, hashes, and other data types.	N/A
Graph	utils/graph/domain	Analysis	Domain WHOIS information endpoint providing registration and ownership data for second-level domain names.	N/A
Graph	utils/graph/ip	Analysis	IP address WHOIS information endpoint providing registration and ownership data.	N/A
Scoring	scoring/ip	Analysis	Returns a 0-100 risk score for one or more IPv4 addresses.	N/A
Scoring	scoring/domain	Analysis	Returns a 0-100 risk score for one or more domains.	N/A
IMC	imc/incidents	Utility	Retrieve Incident Management Center incidents, their aggregated events, and Prevyn AI insights.	N/A

Legend

- Common - collections, which consist of data that is displayed to all users.
- Individual - collections, which consist of only user-related data. For example, if the client is a bank, he will receive only cards with the BIN numbers provided by his bank.
- APIv2 Endpoint - the designation of the collection endpoint in Group-IB TI APIv2.
-

TTL (**Time To Live**) - maximum length of time indicator a dataset (package) can exist. Calculated in days. During this period, we ensure that this data is IoC.

- Admiralty - Approximate Admiralty Code. You can learn more about calculating all types of risk scores in the article Data Classification.
- Severity - refers to the level or degree of seriousness, commonly used in the context of cybersecurity to assess the importance of a vulnerability or incident. This measure helps cybersecurity professionals and administrators evaluate the necessity and urgency of taking actions to prevent or mitigate threats. Severity is typically assessed on a scale, for example, from 0 to 9, where 1 is low, and 9 - the highest.
- Hunting Rules - refers to the request parameter apply_hunting_rules (set to 1 to enable or 0 to disable). Supported = the collection accepts this parameter. N/A = not applicable: either by nature of the collection (e.g. utilities, combined feeds, or collections where the parameter is not used) or because filtering by hunting rules is usually applied by default; the flag can still be used technically where applicable (for example, in search requests).
- General Modules are common and available for all types of licenses.

Collections Details - Utilities User Granted Collections

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint retrieves a list of all collections that are granted/available to the authenticated user. It serves as both a health check endpoint and a way to discover which collections your account has access to. This is useful for programmatically determining which collection endpoints you can query.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/user/granted_collections
Collection Name	Granted Collections
Type	Utility
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Utility endpoint to retrieve list of collections available to the authenticated user. Also serves as a health check endpoint.

Request

Request URL
GET /api/v2/user/granted_collections
Query Parameters

This endpoint does not accept any query parameters.

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json

Header	Type	Required	Description	Example
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
[{ "collection": string, "label": string, "route": string, "huntingRulesUsed": boolean }, ...]
The response is an array of collection objects.

Collection Object

Field	Type	Required	Description
collection	string	Yes	Collection identifier (e.g., “apt/threat”, “malware/malware”)

Field	Type	Required	Description
label	string	Yes	Human-readable label for the collection (e.g., “Threats & Actors :: Nation-State :: Report”)
route	string	Yes	Route identifier for the collection. May be “NO_ROUTE” for collections without a direct route
huntingRulesUsed	boolean	Yes	Whether hunting rules are used for this collection. If true, the apply_hunting_rules parameter can be used when querying this collection

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/user/granted_collections' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

[{ "collection": "apt/threat", "label": "Threats & Actors :: Nation-State :: Report", "route": "apt/report", "huntingRulesUsed": true }, { "collection": "apt/threat_actor", "label": "Threats & Actors :: Nation-State", "route": "apt/threat_actor", "huntingRulesUsed": true }, { "collection": "hi/threat", "label": "Threats & Actors :: Cybercriminals :: Report", "route": "human_intel/threats", "huntingRulesUsed": true }, { "collection": "hi/threat_actor", "label": "Threats & Actors :: Cybercriminals", "route": "human_intel/threat_actor", "huntingRulesUsed": true }, { "collection": "hi/open_threats", "label": "Threats & Actors :: Open Threats", "route": "ta/open-threats", "huntingRulesUsed": true }, { "collection": "hi/analytic", "label": "Threats & Actors :: Analytics", "route": "__NO_ROUTE__", "huntingRulesUsed": false }, { "collection": "malware/malware", "label": "Malware/Source", "route": "malware/reports", "huntingRulesUsed": false }, { "collection": "malware/cnc", "label": "Malware/Source :: C2", "route": "__NO_ROUTE__", "huntingRulesUsed": false }, { "collection": "malware/config", "label": "Malware/Source", "route": "malware/configs", "huntingRulesUsed": true }, { "collection": "malware/signature", "label": "Malware :: Suricata signatures", "route": "__NO_ROUTE__", "huntingRulesUsed": false }, { "collection": "malware/yara", "label": "Malware :: Yara rules", "route": "__NO_ROUTE__", "huntingRulesUsed": false }, { "collection": "attacks/ddos", "label": "Attack :: DDoS", "route": "attacks/ddos", "huntingRulesUsed": true }, { "collection": "attacks/phishing_group", "label": "Attack :: Phishing", "route": "attacks/phishing_group", "huntingRulesUsed": true }, { "collection": "attacks/phishing_kit", "label": "Malware :: Phishing kits", "route": "attacks/phishing_kit", "huntingRulesUsed": true }, { "collection": "compromised/account_group", "label": "Compromise & leaks :: Accounts", "route": "__NO_ROUTE__", "huntingRulesUsed": true }, { "collection": "compromised/bank_card_group", "label": "Compromise & leaks :: Bank cards", "route": "__NO_ROUTE__", "huntingRulesUsed": true }, { "collection": "compromised/messenger", "label": "Threats & Actors :: Instant Messengers", "route": "__NO_ROUTE__", "huntingRulesUsed": true }, { "collection": "compromised/discord", "label": "Threats & Actors :: Discord Messenger", "route": "__NO_ROUTE__", "huntingRulesUsed": true }, { "collection": "suspicious_ip/vpn", "label": "Suspicious IP :: VPN", "route": "suspicious/vpn", "huntingRulesUsed": true }, { "collection": "suspicious_ip/tor_node", "label": "Suspicious IP :: Tor Nodes", "route": "suspicious/tor", "huntingRulesUsed": true }, { "collection": "osi/vulnerability", "label": "Malware :: Vulnerabilities", "route": "osi/vulnerabilities", "huntingRulesUsed": true }, { "collection": "osi/public_leak", "label": "Compromise & leaks :: Public Leaks", "route": "osi/public_leak", "huntingRulesUsed": true }, { "collection": "osi/git_repository", "label": "Compromise & leaks :: Code repositories", "route": "osi/git_repository", "huntingRulesUsed": true }, { "collection": "ioc/common", "label": "IOC :: Common", "route": "__NO_ROUTE__", "huntingRulesUsed": false }]

Usage Patterns

Health Check

This endpoint can be used as a health check to verify: - API authentication is working - API connectivity is available - User account is active and has granted collections

```
curl 'https://tap.group-ib.com/api/v2/user/granted_collections' \   -u 'LOGIN:API_KEY'
```

Discovering Available Collections

Use this endpoint to programmatically discover which collections your account can access:

```
# Get all granted collections curl 'https://tap.group-ib.com/api/v2/user/granted_collections' \   -u 'LOGIN:API_KEY' | jq '.[].collection'
```

Filtering Collections by Hunting Rules Support

To find collections that support hunting rules:

```
curl 'https://tap.group-ib.com/api/v2/user/granted_collections' \   -u 'LOGIN:API_KEY' | jq '.[] | select(.huntingRulesUsed == true) | .collection'
```

Related Endpoints

- Get sequence update numbers: GET /api/v2/sequence_list?date=

Sequence List

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint retrieves a list of sequence update numbers for all available collections based on a specified date. This is useful for determining the starting seqUpdate value when you want to begin iterating through feeds from a specific date, rather than starting from the beginning (seqUpdate=0).

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/sequence_list
Collection Name	Sequence List
Type	Utility
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Utility endpoint to retrieve sequence update numbers for all collections based on a specific date.

Request

Request URL
GET /api/v2/sequence_list
Query Parameters

Parameter	Type	Required	Default	Description	Example
date	string	Yes	-	Date for which the sequence list is requested. Format: YYYY-MM-DD	2024-10-14

Parameter	Type	Required	Default	Description	Example
collection	string	No	-	Optional collection name to filter results for a specific collection. If provided, returns only the sequence update number for that collection.	apt/threat

Query Parameter Details:

- date:
  - Required parameter
  - Format: YYYY-MM-DD (e.g., 2024-10-14)
  - Returns sequence update numbers for all collections as of this date
- collection:
  - Optional parameter
  - If specified, returns only the sequence update number for the specified collection
  - Collection name format: module/submodule (e.g., apt/threat, malware/malware)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)

Header	Type	Required	Description	Example
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "list": { "collection_name": integer, ... } }

Field	Type	Required	Description
list	object	Yes	Object containing collection names as keys and their corresponding sequence update numbers as values

List Object

The list object contains key-value pairs where: - Key: Collection name (e.g., "apt/threat", "malware/malware", "suspicious_ip/vpn") - Value: Sequence update number (integer) for that collection as of the specified date

Example structure:

{ "list": { "apt/threat": 17287776262152, "apt/threat_actor": 17286912357507, "attacks/ddos": 1728853572756170, "malware/malware": 17287232595059, "suspicious_ip/vpn": 1728863618842723 } }

Example Request

Basic Request (All Collections)

```
curl -X GET 'https://tap.group-ib.com/api/v2/sequence_list?date=2024-10-14' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```

Request for Specific Collection

```
curl -X GET 'https://tap.group-ib.com/api/v2/sequence_list?date=2024-10-14&collection=apt/threat' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```

Example Response

Success Response (200 OK) - All Collections

{ "list": { "apt/threat": 17287776262152, "apt/threat_actor": 17286912357507, "attacks/ddos": 1728853572756170, "attacks/deface": 1728159944011312, "attacks/phishing_group": 1728863999999999, "attacks/phishing_kit": 1728861626744927, "compromised/account_group": 1720706185734061, "compromised/bank_card_group": 1719857916092329, "compromised/masked_card": 1728845300540036, "compromised/messenger": 1728853200000000, "compromised/discord": 1727905789379160, "hi/threat": 17288283676769, "hi/threat_actor": 17288283685184, "hi/open_threats": 1728834812506702, "ioc/common": 17288526154476, "malware/cnc": 1728777672644977, "malware/config": 17288510093459, "malware/malware": 17287232595059, "malware/signature": 17288479212942, "malware/yara": 17219413666444, "osi/git_repository": 1728734319944338, "osi/public_leak": 1728863904288975, "osi/vulnerability": 17288546508036, "suspicious_ip/open_proxy": 1728863532650054, "suspicious_ip/scanner": 1728863423033642, "suspicious_ip/socks_proxy": 1728863966244699, "suspicious_ip/tor_node": 1728846278012000, "suspicious_ip/vpn": 1728863618842723 } }

Success Response (200 OK) - Specific Collection

If the collection parameter is provided, the response will contain only that collection:

{ "list": { "apt/threat": 17287776262152 } }

Usage Patterns

Getting Sequence Update for a Specific Date

To start iterating through feeds from a specific date:

- Get sequence update for the desired date:
  ```
  curl 'https://tap.group-ib.com/api/v2/sequence_list?date=2024-10-14&collection=apt/threat' \ -u 'LOGIN:API_KEY'
  ```
- Extract the sequence update number from the response:
  { "list": { "apt/threat": 17287776262152 } }
- Use this sequence update number in your first request to the collection endpoint:
  ```
  curl 'https://tap.group-ib.com/api/v2/apt/threat/updated?seqUpdate=17287776262152&limit=10' \ -u 'LOGIN:API_KEY'
  ```
- Continue iterating using the top-level seqUpdate from subsequent responses

Getting All Collections' Sequence Updates

To get sequence updates for all collections at once:

```
curl 'https://tap.group-ib.com/api/v2/sequence_list?date=2024-10-14' \ -u 'LOGIN:API_KEY'
```

This is useful for: - Monitoring multiple collections - Determining which collections have updates on a specific date - Bulk synchronization across collections

Related Endpoints

- Get active collections: GET /api/v2/user/granted_collections

Search

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint provides a global search functionality across all available collections in the Group-IB Threat Intelligence platform. It allows you to search for indicators, domains, IPs, hashes, and other data types across multiple collections simultaneously, returning a summary of matches in each collection along with direct links to query those collections.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/search
Collection Name	Global Search
Type	Utility
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Global search endpoint to find indicators across all available collections with direct links to collection-specific queries.

Request

Request URL
GET /api/v2/search
Query Parameters

Parameter	Type	Required	Default	Description	Example
q					

Parameter	Type	Required	Default	Description	Example
	string	Yes	-	Search query. Can be an IP address, domain, hash, or other indicator type. The search will automatically detect the type and search across relevant collections.	8.8.8.8
df	string	No	-	Date from. Filter results to items seen from this date onwards. Format: YYYY-MM-DD	2024-01-01
dt	string	No	-	Date to. Filter results to items seen up to this date. Format: YYYY-MM-DD	2024-10-01

Query Parameter Details:

- q:
  - Required parameter
  - Can be various indicator types:
    - IP addresses (IPv4): 8.8.8.8
    - Domains: example.corp
    - File hashes (MD5, SHA1, SHA256): abc123...
    - URLs: http://example.corp/path
    - Other indicator types supported by the platform
  - The search automatically detects the indicator type and searches across relevant collections
- df (date from):
  - Optional parameter
  - Format: YYYY-MM-DD
  - Filters results to items that were first seen or detected from this date onwards
  - Useful for time-bounded searches
- dt (date to):
  -

Optional parameter

- Format: YYYY-MM-DD
- Filters results to items that were first seen or detected up to this date
- Often used together with df to define a date range

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
[{ "apiPath": string, "label": string, "link": string, "count": integer, "time": number, "detailedLinks": object | null }, ...]
The response is an array of search result objects, one for each collection that contains matches.

Search Result Object

Field	Type	Required	Description
apiPath	string	Yes	Collection API path (e.g., “suspicious_ip/scanner”, “attacks/deface”)
label	string	Yes	Human-readable label for the collection (e.g., “Suspicious IP :: Scanners”, “Attack :: Deface”)
link	string	Yes	Direct API link to query this collection with the search term. This link can be used to get detailed results from the specific collection
count	integer	Yes	Number of matches found in this collection
time	number	Yes	Query execution time in seconds (floating point number)
detailedLinks	object | null	No	Additional detailed links (usually null)

Example Request

Basic Search Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Search with Date Range
```
curl -X GET 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8&df=2024-01-01&dt=2024-10-01' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Search for Domain
```
curl -X GET 'https://tap.group-ib.com/api/v2/search?q=example.corp' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Search for Hash
```
curl -X GET 'https://tap.group-ib.com/api/v2/search?q=abc123def456...' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)
[{ "apiPath": "suspicious_ip/scanner", "label": "Suspicious IP :: Scanners", "link": "https://tap.group-ib.com/api/v2/suspicious_ip/scanner?q=ip:8.8.8.8", "count": 1, "time": 0.29085319, "detailedLinks": null }, { "apiPath": "attacks/deface", "label": "Attack :: Deface", "link": "https://tap.group-ib.com/api/v2/attacks/deface?q=ip:8.8.8.8", "count": 1, "time": 0.406312784, "detailedLinks": null }, { "apiPath": "osi/public_leak", "label": "Compromise & leaks :: Public Leaks", "link": "https://tap.group-ib.com/api/v2/osi/public_leak?q=ip:8.8.8.8", "count": 21847, "time": 0.429146568, "detailedLinks": null }, { "apiPath": "suspicious_ip/open_proxy", "label": "Suspicious IP :: Open Proxy", "link": "https://tap.group-ib.com/api/v2/suspicious_ip/open_proxy?q=ip:8.8.8.8", "count": 17, "time": 0.522133669, "detailedLinks": null }, { "apiPath": "malware/config", "label": "Malware/Source", "link": "https://tap.group-ib.com/api/v2/malware/config?q=ip:8.8.8.8", "count": 20, "time": 0.655176984, "detailedLinks": null }]

Usage Patterns

Quick Indicator Lookup

Use this endpoint for quick lookups across all collections:

```
 # Search for an IP address curl 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8' \   -u 'LOGIN:API_KEY'
```

Time-Bounded Search

Search for indicators within a specific time range:

```
 # Search for indicators seen between January and October 2024 curl
'https://tap.group-ib.com/api/v2/search?q=8.8.8.8&df=2024-01-01&dt=2024-10-01' \   -u 'LOGIN:API_KEY'
```

Following Up on Search Results

After getting search results, you can use the provided link to get detailed results from specific collections:

```
 # First, get search results SEARCH_RESULTS=$(curl 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8' \   -u 'LOGIN:API_KEY')  # Extract a link from
the results (e.g., for suspicious_ip/scanner) # Then query that collection directly curl
'https://tap.group-ib.com/api/v2/suspicious_ip/scanner?q=ip:8.8.8.8' \   -u 'LOGIN:API_KEY'
```

Filtering Results by Count

You can filter results to only show collections with matches:

```
 # Using jq to filter results with count > 0 curl 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8' \   -u 'LOGIN:API_KEY' | jq '.[] | select(.count > 0)'
```

Related Endpoints

- Collection-specific search: GET /api/v2//updated?q=

IMC API

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

The Incident Management Center (IMC) API provides programmatic access to the incidents generated by your IMC rules. It returns incidents together with their aggregated events, the rule and rule revision that produced them, and the Prevyn AI insight when AI analysis is enabled for the rule. This lets you route IMC incidents into the systems your team already works in - SIEM, SOAR, or ITSM - instead of triaging them only in the portal.

For an explanation of what IMC is, how rules and aggregation work, and how incidents are triaged in the interface, see Overview and Managing Incidents & Rules in the Manual.

The API is built around three endpoints:

- List updated incidents - retrieves incidents using a delta cursor, so each call returns only what changed since the previous one.
- Fetch an incident - retrieves a single incident by its identifier.
- List incident events - pages through the events aggregated into an incident, for one collection at a time.

Note: The IMC API is read-only. It does not create, modify, or delete incidents, rules, or event statuses. Changing an incident status, reassigning an incident, and creating or editing rules are done in the Threat Intelligence portal.

Note: The IMC API is not currently available in the ciaops Python library. Call it directly over HTTP.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/imc/incidents
Collection Name	IMC API
Module	Incident Management Center
Type	Utility
Rate Limit	See API Limitations
Short Description	Retrieve Incident Management Center incidents, their aggregated events, and Prevyn AI insights.

Request

Request URL
GET /api/v2/imc/incidents/updated GET /api/v2/imc/incidents/{id} GET /api/v2/imc/incidents/{incidentId}/matches/{collection}
List Updated Incidents

Returns a page of incidents together with a nextSyncToken. Incidents are delivered in batches of up to 100 per request.

Parameter	Type	Required	Default	Description	Example
syncToken	string	No	-	Delta cursor returned by the previous call as nextSyncToken. Omit it to start from the beginning of your incident history.	S1MAAAAA...O8AQ
filter.statuses	string	No	-	Incident status. Repeat the parameter to match any of several statuses.	INCIDENT_STATUS_TO_DO
filter.collections	string	No	-	Collection the incident's events belong to. Repeat the parameter to match any of several collections.	COLLECTION_DARK_WEB
filter.priorities	integer	No	-	Rule priority, from 1 to 10. Repeat the parameter to match any of several priorities.	2
filter.scoringFrom	integer	No	-	Lower bound of the rule score, from 0 to 100.	50
filter.scoringTo	integer	No	-	Upper bound of the rule score, from 0 to 100. Must be greater than or equal to filter.scoringFrom.	100

Parameter	Type	Required	Default	Description	Example
filter.updatedAtFrom	string	No	-	Return incidents updated at or after this moment. Format: RFC 3339.	2026-09-01T00:00:00Z
filter.updatedAtTo	string	No	-	Return incidents updated at or before this moment. Format: RFC 3339.	2026-09-30T23:59:59Z
filter.incidentRuleIds	string	No	-	Identifier of the rule that generated the incident. Must be a UUID. Repeat the parameter to match any of several rules.	019ed5d1-5517-73f8-b3c4-65c91e0fcc56
filter.assigneeUserIds	integer	No	-	Identifier of the user the incident is assigned to. Repeat the parameter to match any of several users.	12345
filter.authorUserIds	integer	No	-	Identifier of the user who created the rule. Repeat the parameter to match any of several users.	12345
filter.tags	string	No	-	Tag inherited from the incident's rule. Repeat the parameter to match any of several tags.	ransomware

Query Parameter Details:

- syncToken:
  - Opaque, fixed-length cursor. Do not construct, parse, or truncate it - pass back exactly the value you received.
  - URL-encode the value when adding it to a request. It may contain characters that are not safe in a query string.
  - An invalid value returns 400 with a decode sync token message.
- filter parameters:

- The filter. prefix is required. A parameter sent without it - for example statuses instead of filter.statuses - is ignored, and the request returns unfiltered results.
- Enumerated values must be given by name, not by number. filter.statuses=5 returns 400.
- Repeating a parameter combines its values with OR. Different parameters combine with AND. For example, repeating filter.statuses twice and adding filter.collections returns incidents that have either status and belong to that collection.

Fetch an Incident

Returns a single incident by its identifier, including its rule revision and Prevyn AI insight. The response body is the Incident object itself, not a wrapper.

Parameter	Type	Required	Description	Example
id	string	Yes	Incident identifier. Must be a UUID.	01a08c0d-413d-748c-8db6-321dc0344aba

A well-formed identifier that does not exist returns 404; a value that is not a UUID returns 400.

List Incident Events

Returns the events aggregated into an incident for a single collection. An incident that combines triggers from several collections is read one collection at a time; use the matchCounts.byCollection object of the incident to see which collections contain events and how many.

Parameter	Type	Required	Description	Example
incidentId	string	Yes	Incident identifier. Must be a UUID.	01a08b31-831d-7ae5-8b30-91c379fd47f4
collection	string	Yes	Collection path segment. See the table below.	vulnerabilities

Parameter	Type	Required	Default	Description	Example
sortOrder	string	No	-	Order in which events are returned. Use SORT_ORDER_DESC.	SORT_ORDER_DESC

Parameter	Type	Required	Default	Description	Example
pageToken	string	No	-	Cursor returned by the previous call as nextPageToken. Omit it to request the first page.	ChoyMDI2LTA5...

Important! Always page with sortOrder=SORT_ORDER_DESC. Paging with SORT_ORDER_ASC returns duplicate events on the second page and stops returning a page token, so the full set cannot be retrieved.

Collection path segments:

Collection	Path segment
Vulnerabilities	vulnerabilities
Accounts	compromised-accounts
Bank cards	compromised-cards
Masked bank cards	compromised-masked-cards
Shops	compromised-shops
Darkweb	dark-web
Breached DB	breached-db
Suspicious payment details	suspicious-payments
Public leaks	public-leaks
Last threats	threats
Git leaks	git-leaks

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

All field names are in camelCase. Numeric identifiers of users are returned as strings. Objects that are not set are returned as null.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Vary	Headers affecting the cached representation	Accept-Encoding

Response Body Schema

Root Object

The response of the List updated incidents endpoint:
{ "incidents": [Incident, ...], "nextSyncToken": string }

Field	Type	Required	Description
incidents			

Field	Type	Required	Description
	array	Yes	Incidents in this batch. Up to 100 items. An empty array means there is nothing left to read.
nextSyncToken	string	Yes	Cursor to pass as syncToken in the next call.

The response of the List incident events endpoint:
{ "matches": [{ "matchInfo": RuleMatchInfo }, ...], "nextPageToken": string }

Field	Type	Required	Description
matches	array	Yes	Events in this page. Up to 100 items.
nextPageToken	string	No	Cursor to pass as pageToken to request the next page. Absent on the last page.

Incident Object
{ "id": string, "status": string, "number": integer, "windowStart": string, "windowEnd": string, "matchCounts": RuleMatchCounts, "incidentRuleRevision": IncidentRuleRevision, "assignee": UserInfo, "aiSummary": AiSummary, "createdAt": string, "updatedAt": string }

Field	Type	Required	Description
id	string	Yes	Unique incident identifier (UUID). Use this value to fetch the incident and to read its events.
status	string	Yes	Current incident status. See Incident Status.
number	integer	Yes	Sequence number of the incident within the rule that generated it. It is not unique across rules - use id to identify an incident.
windowStart	string	Yes	Start of the aggregation window that produced the incident. Format: RFC 3339.

Field	Type	Required	Description
windowEnd	string	Yes	End of the aggregation window that produced the incident. Format: RFC 3339.
matchCounts	object	Yes	Number of aggregated events, in total and per collection.
incidentRuleRevision	object	Yes	The exact revision of the rule that generated the incident.
assignee	object | null	No	User the incident is assigned to, or null when the incident is unassigned.
aiSummary	object | null	No	Prevyn AI insight, or null when AI analysis is off for the rule or has not produced a result.
createdAt	string	Yes	When the incident was created. Format: RFC 3339.
updatedAt	string	Yes	When the incident was last updated. Format: RFC 3339.

RuleMatchCounts Object

{ "total": integer, "byCollection": { "vulnerability": integer, "compromisedAccount": integer, "compromisedCard": integer, "compromisedMaskedCard": integer, "compromisedShop": integer, "darkWeb": integer, "breachedDb": integer, "suspiciousPayment": integer, "publicLeak": integer, "threat": integer, "gitLeak": integer } }

Field	Type	Required	Description
total	integer	Yes	Total number of events aggregated into the incident.
byCollection	object	Yes	Number of events per collection. Every key is always present; collections with no events are 0.

IncidentRuleRevision Object

{ "id": string, "incidentRuleId": string, "isCurrent": boolean, "versionNumber": integer, "collectionRules": CollectionRules, "incidentRule": IncidentRule, "createdAt": string }

Field	Type	Required	Description
id	string	Yes	Identifier of this rule revision (UUID).
incidentRuleId	string	Yes	Identifier of the rule (UUID). Stable across revisions.
isCurrent	boolean	Yes	Whether this revision is the rule's current one. false means the rule has been edited since this incident was generated.
versionNumber	integer	Yes	Revision number, incremented each time the rule is saved.
collectionRules	object	Yes	Trigger queries of this revision, keyed by collection. Collections without a trigger are null.
incidentRule	object	Yes	Rule attributes as of this revision.
createdAt	string	Yes	When this revision was created. Format: RFC 3339.

Each entry of collectionRules that is not null contains the trigger query:

Field	Type	Required	Description
query	string	Yes	The Lucene query used as the trigger for this collection.

IncidentRule Object
{ "id": string, "name": string, "author": UserInfo, "assignee": UserInfo, "tags": [string, ...], "priority": integer, "scoring": integer, "createdAt": string, "updatedAt": string }

Field	Type	Required	Description
id	string	Yes	Rule identifier (UUID).

Field	Type	Required	Description
name	string	Yes	Rule name as set in the portal.
author	object	Yes	User who created the rule.
assignee	object | null	No	Default assignee for incidents this rule generates, or null.
tags	array	Yes	Tags assigned to the rule. Incidents inherit them. Empty when the rule has no tags.
priority	integer	Yes	Rule priority, from 1 (highest) to 10 (lowest). Corresponds to P1-P10 in the portal.
scoring	integer	Yes	Numeric score of the rule, from 0 to 100.
createdAt	string	Yes	When the rule was created. Format: RFC 3339.
updatedAt	string	Yes	When the rule was last updated. Format: RFC 3339.

UserInfo Object

Field	Type	Required	Description
id	string	Yes	User identifier. Returned as a string, but supplied as an integer in filter.assigneeUserIds and filter.authorUserIds.
email	string	Yes	User email address.

AiSummary Object
{ "title": string, "description": string, "level": string }

Field	Type	Required	Description
title			

Field	Type	Required	Description
	string	Yes	Generated one-line title describing the incident.
description	string	Yes	Generated narrative describing what the underlying events show and what to do next. Formatted as Markdown and may contain several sections.
level	string	Yes	Assessed severity of the underlying threat. See AI Summary Level.

Note: Prevyn AI can make mistakes. Its insights are a preliminary assessment intended to accelerate triage, not replace it - we recommend verifying them before acting.

RuleMatchInfo Object
{ "idInIncident": string, "collectionItemId": string, "status": string, "matchedAt": string }

Field	Type	Required	Description
idInIncident	string	Yes	Opaque identifier of the event within the incident.
collectionItemId	string	Yes	Identifier of the record in the corresponding Threat Intelligence collection. Use it to retrieve the full record - see Resolving Events to Threat Intelligence Records.
status	string	Yes	Current status of the event. See Rule Match Status.
matchedAt	string	Yes	When the event matched the rule. Format: RFC 3339.

Enumerations

Incident Status

Value	Portal label
INCIDENT_STATUS_TO_DO	To do
INCIDENT_STATUS_PROCESSING	In progress
INCIDENT_STATUS_ON_HOLD	On hold
INCIDENT_STATUS_RESOLVED	Resolved
INCIDENT_STATUS_FALSE_POSITIVE	False
INCIDENT_STATUS_CANCELLED	Cancelled

Rule Match Status

Event statuses are separate from incident statuses.

Value	Portal label
RULE_MATCH_STATUS_NEW	New
RULE_MATCH_STATUS_IN_PROGRESS	In progress
RULE_MATCH_STATUS_DONE	Done
RULE_MATCH_STATUS_FALSE_POSITIVE	False

Collection

Used in filter.collections.

Value	Collection
COLLECTION_VULNERABILITY	Vulnerabilities
COLLECTION_COMPROMISED_ACCOUNT	Accounts

Value	Collection
COLLECTION_COMPROMISED_CARD	Bank cards
COLLECTION_COMPROMISED_MASKED_CARD	Masked bank cards
COLLECTION_COMPROMISED_SHOP	Shops
COLLECTION_DARK_WEB	Darkweb
COLLECTION_BREACHED_DB	Breached DB
COLLECTION_SUSPICIOUS_PAYMENT	Suspicious payment details
COLLECTION_PUBLIC_LEAK	Public leaks
COLLECTION_THREAT	Last threats
COLLECTION_GIT_LEAK	Git leaks

AI Summary Level

Value	Meaning
LEVEL_LOW	Low assessed severity
LEVEL_MEDIUM	Medium assessed severity
LEVEL_HIGH	High assessed severity

Sort Order

Value	Meaning
SORT_ORDER_DESC	Newest events first. The supported order for paging.

Value	Meaning
SORT_ORDER_ASC	Oldest events first. Not supported for paging beyond the first page.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY pair before running the command.

First Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/imc/incidents/updated' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json'
```

Subsequent Requests

```
curl -X GET -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json' \  --data-urlencode 'syncToken=S1MAAAAA...O8AQ'
```

Filtered Request

```
curl -X GET -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json' \  --data-urlencode 'filter.statuses=INCIDENT_STATUS_TO_DO' \  --data-urlencode 'filter.statuses=INCIDENT_STATUS_PROCESSING' \  --data-urlencode 'filter.collections=COLLECTION_VULNERABILITY' \  --data-urlencode 'filter.scoringFrom=90' \  --data-urlencode 'filter.scoringTo=100'
```

Fetch a Single Incident

```
curl -X GET 'https://tap.group-ib.com/api/v2/imc/incidents/01a08c0d-413d-748c-8db6-321dc0344aba' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json'
```

List the Events of an Incident

```
curl -X GET -G 'https://tap.group-ib.com/api/v2/imc/incidents/01a08c0d-413d-748c-8db6-321dc0344aba/matches/threats' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json' \  --data-urlencode 'sortOrder=SORT_ORDER_DESC'
```

Example Response

Success Response (200 OK) - List Updated Incidents


```
{  "incidents": [  {  "id": "01a08c0d-413d-748c-8db6-321dc0344aba",  "status": "INCIDENT_STATUS_TO_DO",  "number": 411,  "windowStart": "2026-09-10T15:00:00Z",  "windowEnd": "2026-09-10T16:00:00Z",  "matchCounts": {  "total": 2,  "byCollection": {  "vulnerability": 0,  "compromisedAccount": 0,  "compromisedCard": 0,  "compromisedMaskedCard": 0,  "compromisedShop": 0,  "darkWeb": 0,  "breachedDb": 0,  "suspiciousPayment": 0,  "publicLeak": 0,  "threat": 2,  "gitLeak": 0  }  },  "incidentRuleRevision": {  "id": "019f0462-ef69-713e-ba17-6f5a38264710",  "incidentRuleId": "019ed5d1-5517-73f8-b3c4-65c91e0fcc56",  "isCurrent": true,  "versionNumber": 3,  "collectionRules": {  "vulnerability": null,  "compromisedAccount": null,  "compromisedCard": null,  "compromisedMaskedCard": null,  "compromisedShop": null,  "darkWeb": null,  "breachedDb": null,  "suspiciousPayment": null,  "publicLeak": null,  "threat": {  "query": "country:\"US\" AND expertise:\"Ransomware\""  },  "gitLeak": null  },  "incidentRule": {  "id": "019ed5d1-5517-73f8-b3c4-65c91e0fcc56",  "name": "Last threats US",  "author": {  "id": "12345",  "email": "analyst@example.corp"  },  "assignee": null,  "tags": ["US ransomware", "darkweb"],  "priority": 1,  "scoring": 100,  "createdAt": "2026-06-17T13:42:06.359256Z",  "updatedAt": "2026-07-17T14:11:13.225308Z"  },  "createdAt": "2026-06-26T14:43:40.521077Z"  },  "assignee": null,  "aiSummary": {  "title": "example",  "description": "example",  "level": "LEVEL_MEDIUM"  },  "createdAt": "2026-09-10T16:01:14.044968Z",  "updatedAt": "2026-09-10T16:01:20.676338Z"  } ],  "nextSyncToken": "S1MAAAAA...O8AQ" }
```


Success Response (200 OK) - List Incident Events


```
{  "matches": [  {  "matchInfo": {  "idInIncident": "eyJ0aW1lc3RhbXAiOiIyMDI2LTA5LTEwVDE1OjU5OjI1LjczMVoiLCJzZXFfbm8iOjJ9",  "collectionItemId": "da00b1cbd51ad1559a492bc55f820a2a22812698",  "status": "RULE_MATCH_STATUS_NEW",  "matchedAt": "2026-09-10T15:59:25.731Z"  } },  {  "matchInfo": {  "idInIncident": "eyJ0aW1lc3RhbXAiOiIyMDI2LTA5LTEwVDE1OjU5OjI1LjczMVoiLCJzZXFfbm8iOjF9",  "collectionItemId": "ff88e3833abb934b59d110a7acc83db71ad9e4a5",  "status": "RULE_MATCH_STATUS_NEW",  "matchedAt": "2026-09-10T15:59:25.731Z"  } } ] }
```


Error Response (400 Bad Request)


```
{  "code": 3,  "message": "invalid parameter \"filter.statuses\": unknown enum: BOGUS_STATUS",  "details": [] }
```


Error Response (404 Not Found)


```
{  "code": 5,  "message": "not found",  "details": [] }
```


Usage Patterns

Incremental Synchronization

The List updated incidents endpoint is a delta feed. Each response carries a nextSyncToken that marks your position, and each call returns up to 100 incidents.

- Make the first call without a token to begin reading your incident history: curl -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' -u "$GIB_CREDENTIALS"
- Store the nextSyncToken from the response and pass it back on the next call: curl -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' -u "$GIB_CREDENTIALS" \ --data-urlencode 'syncToken='
- Repeat until incidents comes back empty. At that point you have read everything, and the response returns the same token you sent. Persist that token.
- Poll on a schedule using the stored token. Each later call returns only the incidents created or updated since the previous one, and yields a new token to store in its place.

Note: Determine that you are up to date by checking whether incidents is empty, not by checking the token. nextSyncToken is never empty once you have incidents to read.

Resolving Events to Threat Intelligence Records

The events returned by List incident events identify the matched record but do not embed it. Each event carries a collectionItemId that you resolve against the corresponding Threat Intelligence collection to retrieve the full record.

Collection	Path segment	Resolve the record with
Vulnerabilities	vulnerabilities	GET /api/v2/osi/vulnerability/{collectionItemId}
Accounts	compromised-accounts	GET /api/v2/compromised/account_group/{collectionItemId}
Bank cards	compromised-cards	GET /api/v2/compromised/bank_card_group/{collectionItemId}
Masked bank cards	compromised-masked-cards	GET /api/v2/compromised/masked_card/{collectionItemId}
Shops	compromised-shops	GET /api/v2/compromised/access/{collectionItemId}
Darkweb	dark-web	GET /api/v2/darkweb/forums/{collectionItemId}
Breached DB	breached-db	GET /api/v2/compromised/breacheddb/updated?q=id:{collectionItemId}
Suspicious payment details	suspicious-payments	GET /api/v2/compromised/spd/{collectionItemId}
Public leaks	public-leaks	GET /api/v2/osi/public_leak/{collectionItemId}

Collection	Path segment	Resolve the record with
Last threats	threats	GET /api/v2/hi/threat/{collectionItemId}
Git leaks	git-leaks	GET /api/v2/osi/git_repository/{collectionItemId}

Note: Breached DB is the one collection that is not resolved through a path parameter. Look the record up on the Breached DB collection with the q search parameter, using the id field: q=id:. The response is a standard feed response, with the record as the single element of items. It is the record already matched to your monitored scope, and it carries the breach description, publication date, source download links, and the evaluation block (severity, reliability, credibility, TLP, and Admiralty code).

A complete drill-down for one incident:

- Read the incident and check which collections hold events: curl 'https://tap.group-ib.com/api/v2/imc/incidents/' -u "$GIB_CREDENTIALS"
- Page its events for a collection that has a non-zero count: curl -G 'https://tap.group-ib.com/api/v2/imc/incidents//matches/threats' \ -u "$GIB_CREDENTIALS" --data-urlencode 'sortOrder=SORT_ORDER_DESC'
- Retrieve each record by its collectionItemId: curl 'https://tap.group-ib.com/api/v2/hi/threat/da00b1cbd51ad1559a492bc55f820a2a22812698' \ -u "$GIB_CREDENTIALS"
- Continue paging by passing nextPageToken as pageToken until the response no longer contains one.

For the full list of collection endpoints and their properties, see Collections Overview.

Filtering Incidents

Filters apply to the List updated incidents endpoint and can be combined with syncToken.

Retrieve open, high-scoring incidents only:
curl -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' -u "$GIB_CREDENTIALS" \ --data-urlencode 'filter.statuses=INCIDENT_STATUS_TO_DO' \ --data-urlencode 'filter.scoringFrom=90'
Retrieve incidents from two specific rules:
curl -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' -u "$GIB_CREDENTIALS" \ --data-urlencode 'filter.incidentRuleIds=019ed5d1-5517-73f8-b3c4-65c91e0fcc56' \ --data-urlencode 'filter.incidentRuleIds=019d430f-f40b-7c67-9a6c-776bb0150908'
Retrieve incidents updated within a time range:
curl -G 'https://tap.group-ib.com/api/v2/imc/incidents/updated' -u "$GIB_CREDENTIALS" \ --data-urlencode 'filter.updatedAtFrom=2026-09-01T00:00:00Z' \ --data-urlencode 'filter.updatedAtTo=2026-09-30T23:59:59Z'
Warning: Omitting the filter. prefix does not produce an error. The parameter is ignored and the request returns unfiltered results, which can silently ingest far more data than intended.

Related Endpoints

- Get active collections: GET /api/v2/user/granted_collections - see User Granted Collections
- Global search across collections: GET /api/v2/search - see Search

Collections Details - Feeds Threats and Actors - APT Threat Actors

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint is part of a comprehensive threat intelligence system that provides both threat actor profiles and threat reports. The system differentiates between nation-state Advanced Persistent Threat (APT) groups and cybercrime groups. For complete threat intelligence coverage, consider integrating all four related endpoints: APT Threat Actor (profiles), APT Threat (reports), HI Threat Actor (profiles), and HI Threat (reports). This allows you to build comprehensive actor profiles with associated reports for both nation-state and cybercrime threats in your third-party security systems. In some integration scenarios, collecting only the report endpoints may be sufficient for your use case.

Specifically, the APT Threat Actor endpoint provides threat actor profiles of nation-state APT groups, including their history, capabilities, and organizational details. It works alongside the APT Threat endpoint, which provides detailed reports on nation-state APT activities, to deliver complete threat intelligence coverage. Together, these endpoints enable you to build comprehensive actor profiles with associated reports for enhanced threat detection and response capabilities.

Related Threat Intelligence Endpoints

The following table provides an overview of all four threat intelligence endpoints and their characteristics:

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
APT Threat Actor	/api/v2/apt/threat_actor/updated	Threat Actor Profiles	Nation-state APT	Highest	Comprehensive profiles of government-sponsored Advanced Persistent Threat groups, including their history, capabilities, and organizational details.
APT Threat	/api/v2/apt/threat/updated	Threat Reports	Nation-state APT	Highest	Detailed reports on nation-state APT activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
HI Threat Actor	/api/v2/hi/threat_actor/updated	Threat Actor Profiles	Cybercrime	High	Comprehensive profiles of cybercriminal groups (non-government sponsored), including financially motivated and other organized threat groups.
HI Threat	/api/v2/hi/threat/updated	Threat Reports	Cybercrime	High	Detailed reports on cybercriminal threat activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Integration Recommendations:

- Best Practice: Collect all four endpoints to build complete threat actor profiles with associated reports for both nation-state APT and cybercrime groups in your security systems. This provides the most comprehensive threat intelligence coverage.
- Alternative: For integrations that focus primarily on threat detection and IOC enrichment, collecting only the report endpoints (APT Threat and HI Threat) may be sufficient. Reports contain IOCs with severity ratings that help prioritize security responses.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/apt/threat_actor/updated
Collection	apt/threat_actor
Collection Name	APT Threat Actors
Module	Threats and Actors

Property	Value
Submodule	Actors
Type	Common + Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	None
Severity	9
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Comprehensive profiles of government-sponsored APT groups.

Request

Request URL

GET /api/v2/apt/threat_actor/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17274816349479
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:221e05fe443deec1356b0006817931ca16974f68
is_tailored	integer	No	0	Filter for tailored threat actors. Set to 1 to enable.	1
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:

- Maximum value: 100 for apt/threat_actor/updated collection
- If not specified, defaults to 100
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ThreatActorItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of threat actor items returned in this response
items	array[ThreatActorItem]	Yes	Array of threat actor objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ThreatActorItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
aliases	array[string]	Yes	Array of alternative names/aliases for the threat actor
country	string | null	No	Country code (ISO 3166-1 alpha-2)

Field	Type	Required	Description
isAPT	boolean	Yes	Whether this is an APT (Advanced Persistent Threat) group. For this collection, typically true
description	string	Yes	HTML-formatted description of the threat actor
createdAt	string	Yes	ISO 8601 timestamp when the record was created
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
seqUpdate	integer	Yes	Sequence update number for this specific item
techSeqUpdate	integer | null	No	Technical sequence update number
oldId	string | null	No	Previous identifier (if migrated)
haslocs	boolean	Yes	Whether the threat actor has associated indicators of compromise
langs	array[string]	Yes	Array of language codes
spokenOnLangs	array[string]	Yes	Array of languages spoken by the threat actor
labels	array[string]	Yes	Array of label strings (e.g., [“hacker”, “spy”, “nation-state”])
roles	array[string]	Yes	Array of role strings (e.g., [“malware-author”, “infrastructure-architect”, “infrastructure-operator”])
goals	array[string]	Yes	Array of goal strings (e.g., [“Information”, “Research”, “Financial”])

Field	Type	Required	Description
files	array	Yes	Array of file objects
addedToThreatLandscapeFor	array | null	No	Array of threat landscape options
threatLandscapeOptions	array[ThreatLandscapeOption]	Yes	Array of available threat landscape options
stat	ThreatActorStat	Yes	Statistics object containing aggregated data about the threat actor
displayOptions	DisplayOptions	Yes	Display options object

ThreatActorStat Object

Field	Type	Required	Description
allIndicatorsCount	integer	Yes	Total number of indicators associated with this threat actor
allReportsCount	integer	Yes	Total number of reports associated with this threat actor
contactsCount	integer	Yes	Number of contacts associated with this threat actor
forumsAccountsCount	integer	Yes	Number of forum accounts associated with this threat actor
relatedThreatActorsCount	integer	Yes	Number of related threat actors
countries	array[string]	Yes	Array of country codes where this threat actor is active
regions	array[string]	Yes	Array of regions where this threat actor is active

Field	Type	Required	Description
sectors	array[string]	Yes	Array of sectors targeted by this threat actor
cve	array[string]	Yes	Array of CVE identifiers used by this threat actor
malware	array[string]	Yes	Array of malware names used by this threat actor
expertise	array[string]	Yes	Array of expertise types (e.g., [“AutoReport”, “Backdoor”, “Cobalt Strike”])
dateFirstSeen	string	Yes	Date when the threat actor was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the threat actor was last seen (format: YYYY-MM-DD)
reports	array[ReportSummary]	Yes	Array of report summary objects
targetedCompany	array[string]	Yes	Array of targeted company names
targetedPartnersAndClients	array[string]	Yes	Array of targeted partners and clients

ReportSummary Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the report (SHA-1 hash)
datePublished	string	Yes	Date when the report was published (format: YYYY-MM-DD)

Field	Type	Required	Description
name	object	Yes	Object with language keys containing report names (e.g., {“en”: “APT41 - New indicators have been found”, “ru”: “APT41 - New indicators have been found”})
companyId	array	Yes	Array of company IDs (empty for common reports)

ThreatLandscapeOption Object

Field	Type	Required	Description
label	string	Yes	Label for the threat landscape option
value	string	Yes	Value for the threat landscape option

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat_actor/updated?seqUpdate=0&limit=100' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```
Request with Search Query
```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat_actor/updated?seqUpdate=0&limit=100&q=id:221e05fe443deec1356b0006817931ca16974f68' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```
Request with Hunting Rules
```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat_actor/updated?seqUpdate=0&limit=100&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)
{ "count": 19, "items": [{ "addedToThreatLandscapeFor": null, "aliases": ["CamoFei"], "country": "CN", "createdAt": "2019-02-20T17:44:21+00:00", "description": "
Experts gave the group the name ChamelGang...
", "displayOptions": { "isFavourite": false, "isHidden": false }, "files": [{ "hash": "23f780c4ad6cdc16989acdb4f218712ba1d2d038e9c057026e54249b031957a3", "mime": "image/png", "name": "23f780c4ad6cdc16989acdb4f218712ba1d2d038e9c057026e54249b031957a3", "size": 60084 }], "goals": [], "haslocs": true, "id": "de70f8194526173b885baf2999f65225927c2f31", "isAPT": true, "labels": [], "langs": ["en", "ru"], "name": "ChamelGang", "oldId": null,

"roles": [], "seqUpdate": 17274816349479, "spokenOnLangs": ["en"], "stat": { "allIndicatorsCount": 51, "allReportsCount": 6, "contactsCount": 4, "countries": ["BR", "IN", "JP", "RU", "TW", "US"], "cve": [], "dateFirstSeen": "2022-11-01", "dateLastSeen": "2024-09-28", "expertise": ["AutoReport", "Brief Report", "Ransomware"], "forumsAccountsCount": 0, "malware": ["CatB", "Cobalt Strike"], "regions": ["america:northern_america", "america:south_america", "asia", "europe"], "relatedThreatActorsCount": 0, "reports": [{ "companyId": [], "datePublished": "2024-09-28", "id": "9c8d61663f8e4b2c58d9029238ac9b2e6d65793d", "name": { "ru": "ChamelGang - New indicators have been found", "en": "ChamelGang - New indicators have been found" } }], "sectors": ["government-and-military", "health-care"], "targetedCompany": [], "targetedPartnersAndClients": [] }, "techSeqUpdate": null, "threatLandscapeOptions": [{ "label": "company", "value": "company" }, { "label": "partner", "value": "partner" }, { "label": "industry", "value": "industry" }, { "label": "other", "value": "other" }], "updatedAt": "2024-09-28T03:00:34+03:00" }], "seqUpdate": 17277408454364 }

Threats and Actors - APT Threat Reports

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint is part of a comprehensive threat intelligence system that provides both threat actor profiles and threat reports. The system differentiates between nation-state Advanced Persistent Threat (APT) groups and cybercrime groups. For complete threat intelligence coverage, consider integrating all four related endpoints: APT Threat Actor (profiles), APT Threat (reports), HI Threat Actor (profiles), and HI Threat (reports). This allows you to build comprehensive actor profiles with associated reports for both nation-state and cybercrime threats in your third-party security systems. In some integration scenarios, collecting only the report endpoints may be sufficient for your use case.

Specifically, the APT Threat endpoint provides threat reports on nation-state APT activities, including IOCs, attack techniques, and MITRE ATT&CK mappings. It works alongside the APT Threat Actor endpoint, which provides comprehensive profiles of government-sponsored APT groups, to deliver complete threat intelligence coverage. Use this endpoint to stay informed about emerging APT activities and enhance your threat detection and response capabilities.

Note: This endpoint includes IOCs, which are also part of the IOC Primary collection.

Related Threat Intelligence Endpoints

The following table provides an overview of all four threat intelligence endpoints and their characteristics:

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
APT Threat Actor	/api/v2/apt/threat_actor/updated	Threat Actor Profiles	Nation-state APT	Highest	Comprehensive profiles of government-sponsored Advanced Persistent Threat groups, including their history, capabilities, and organizational details.
APT Threat	/api/v2/apt/threat/updated	Threat Reports	Nation-state APT	Highest	Detailed reports on nation-state APT activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
HI Threat Actor	/api/v2/hi/threat_actor/updated	Threat Actor Profiles	Cybercrime	High	Comprehensive profiles of cybercriminal groups (non-government sponsored), including financially motivated and other organized threat groups.
HI Threat	/api/v2/hi/threat/updated	Threat Reports	Cybercrime	High	Detailed reports on cybercriminal threat activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Integration Recommendations:

- Best Practice: Collect all four endpoints to build complete threat actor profiles with associated reports for both nation-state APT and cybercrime groups in your security systems. This provides the most comprehensive threat intelligence coverage.
- Alternative: For integrations that focus primarily on threat detection and IOC enrichment, collecting only the report endpoints (APT Threat and HI Threat) may be sufficient. Reports contain IOCs with severity ratings that help prioritize security responses.
- Note on Severity Classification: Both threat report feeds (APT Threat and HI Threat) contain high severity IOCs; however, APT IOCs are more rare and by nature are the most important.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/apt/threat/updated
Collection	apt/threat
Collection Name	APT Threat Reports
Module	Threats and Actors

Property	Value
Submodule	Last threats
Type	Common + Individual
TTL (Days)	360 (recommended one and in most cases not provided in API)
Admiralty Code	Can differ
Severity	9
Collection Limit	10 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Reports on nation-state APT activities with IOCs, attack techniques, and MITRE ATT&CK mappings.

Request

Request URL

GET /api/v2/apt/threat/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	16172928022293
limit	integer	No	10	Limit the amount of returned data for this collection. Maximum allowed: 10 for this collection.	10
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:e8bee5b0e6e286ca753feed3476649438e4e4488
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 10 for apt/threat/updated collection
  -

If not specified, defaults to 10

- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ThreatItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of threat items returned in this response
items	array[ThreatItem]	Yes	Array of threat objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ThreatItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat report (SHA-1 hash)
title	string	Yes	Title of the threat report
shortTitle	string | null	No	Short title of the threat report
description	string	Yes	HTML-formatted description of the threat
shortDescription	string | null	No	Short description of the threat

Field	Type	Required	Description
type	string	Yes	Type of the threat. Value: “event”
reportNumber	string	Yes	Internal report number
dateFirstSeen	string	Yes	Date when the threat was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the threat was last seen (format: YYYY-MM-DD)
datePublished	string	Yes	Date when the report was published (format: YYYY-MM-DD)
createdAt	string	Yes	ISO 8601 timestamp when the record was created
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
isPublished	boolean	Yes	Whether the threat is published
isTailored	boolean	Yes	Whether the threat is tailored for specific clients
isAutogen	boolean	Yes	Whether the report was automatically generated
hasIocs	boolean	Yes	Whether the threat has indicators of compromise
langs	array[string]	Yes	Array of language codes (at this point, only Enis up to date - no other laguages)
seqUpdate	integer	Yes	Sequence update number for this specific item
techSeqUpdate	integer | null	No	Technical sequence update number

Field	Type	Required	Description
oldId	string | null	No	Previous identifier (if migrated)
contacts	array	Yes	Array of contact objects (usually empty)
countries	array	Yes	Array of country objects
regions	array	Yes	Array of region objects
sectors	array	Yes	Array of sector objects
labels	array	Yes	Array of label objects
cveList	array	Yes	Array of CVE identifiers
expertise	array[string]	Yes	Array of expertise types (e.g., [“AutoReport”])
sourceList	array	Yes	Array of source objects
sources	array	Yes	Array of source identifiers
files	array	Yes	Array of file objects
forumsAccounts	array	Yes	Array of forum account objects
malwareList	array	Yes	Array of malware objects
toolList	array	Yes	Array of tool objects
relatedThreatActors	array	Yes	Array of related threat actor objects
targetedCompany	array	Yes	Array of targeted company objects
targetedPartnersAndClients	array	Yes	Array of targeted partners and clients
companyId	array	Yes	Array of company IDs

Field	Type	Required	Description
author	string | null	No	Author of the report
indicators	array[Indicator]	Yes	Array of indicator objects
indicatorsIds	array[string]	Yes	Array of indicator IDs
indicatorRelationships	array	Yes	Array of indicator relationship objects
indicatorMalwareRelationships	array	Yes	Array of indicator-malware relationship objects
indicatorToolRelationships	array	Yes	Array of indicator-tool relationship objects
unreliableIndicators	array	Yes	Array of unreliable indicator objects
unreliableIndicatorsRelations	array	Yes	Array of unreliable indicator relationship objects
threatActor	ThreatActor | null	No	Associated threat actor object
mitreMatrix	array	Yes	Array of MITRE ATT&CK matrix objects
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	DisplayOptions	Yes	Display options object

Indicator Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the indicator (SHA-1 hash)

Field	Type	Required	Description
type	string	Yes	Type of indicator. Possible values: “network”, “file”, “email”, etc.
title	string | null	No	Title of the indicator
description	string | null	No	Description of the indicator
dateFirstSeen	string	Yes	Date when the indicator was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the indicator was last seen (format: YYYY-MM-DD)
deleted	boolean	Yes	Whether the indicator is deleted
seqUpdate	integer	Yes	Sequence update number for this indicator
techSeqUpdate	integer | null	No	Technical sequence update number
langs	array[string]	Yes	Array of language codes
sources	array[string]	Yes	Array of source identifiers
malwareIdList	array[string] | null	No	Array of related malware IDs
malwareList	array	Yes	Array of malware objects
attributes	object | null	No	Additional attributes
params	IndicatorParams	Yes	Indicator parameters object (contains actual indicator data)

IndicatorParams Object

Field	Type	Required	Description
domain			

Field	Type	Required	Description
	string | null	No	Domain name
ipv4	array[string]	Yes	Array of IPv4 addresses
ipv6	array[string]	Yes	Array of IPv6 addresses
url	string	Yes	URL (can be empty string)
ssl	array	Yes	Array of SSL certificate objects

ThreatActor Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
country	string	Yes	Country code (ISO 3166-1 alpha-2)
isAPT	boolean	Yes	Whether this is an APT (Advanced Persistent Threat) group

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “C3”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “red”, “amber”, “green”)

Field	Type	Required	Description
tlp	string	Yes	Traffic Light Protocol level (e.g., “red”, “amber”, “green”, “white”)
ttl	integer | null	No	Time to live in days (usually null for this collection)

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat/updated?seqUpdate=0&limit=10' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat/updated?seqUpdate=0&limit=10&q=id:e8bee5b0e6e286ca753feed3476649438e4e4488' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/apt/threat/updated?seqUpdate=0&limit=10&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 57, "items": [{ "contacts": [], "countries": [], "createdAt": "2024-09-23T23:20:09+03:00", "cveList": [], "dateFirstSeen": "2024-09-23", "dateLastSeen": "2024-09-23", "datePublished": "2024-09-24", "description": "", "displayOptions": { "isFavourite": false, "isHidden": false }, "evaluation": { "admiraltyCode": "C3", "credibility": 60, "reliability": 60, "severity": "red", "tlp": "red", "ttl": null }, "expertise": ["AutoReport"], "files": [], "forumsAccounts": [], "hasIocs": true, "id": "d1da0a53543a18e5240ece12d031b6ad711a8202", "indicatorMalwareRelationships": [], "indicatorRelationships": [], "indicatorToolRelationships": [], "indicators": [{ "attributes": null, "dateFirstSeen": "2024-09-23", "dateLastSeen": "2024-09-23", "description": null, "id": "6ecb34d68b26c7bc369dd209f0db9cc3a9c6a8c7", "langs": ["ru"], "malwareIdList": null, "malwareList": [], "params": { "domain": null, "ipv4": ["95.179.134.240"], "ipv6": [], "ssl": [], "url": "" }, "seqUpdate": 17271228138607, "sources": ["panda_playbook"], "techSeqUpdate": null, "title": null, "type": "network" }], "indicatorsIds": ["6ecb34d68b26c7bc369dd209f0db9cc3a9c6a8c7"], "isAutogen": true, "isPublished": true, "isTailored": false, "labels": [], "langs": ["en", "ru"], "malwareList": [], "mitreMatrix": [], "oldId": null, "regions": [], "relatedThreatActors": [], "reportNumber": "CP-2809-2320", "sectors": [], "seqUpdate": 17271360303706, "shortDescription": null, "shortTitle": null, "sourceList": [], "sources": [], "targetedCompany": [], "targetedPartnersAndClients": [], "techSeqUpdate": null, "threatActor": { "country": "CN", "id": "59a1326f2bed234dcb864a69e7ab28b2fa4b14e9", "isAPT": true, "name": "APT41" }, "title": "APT41 - New indicators have been found", "toolList": [], "type": "event", "unreliableIndicators": [], "unreliableIndicatorsRelations": [], "updatedAt": "2024-09-24T03:00:30+03:00" }], "seqUpdate": 17272224279604 }

Threats and Actors - HI Threat Actors

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint is part of a comprehensive threat intelligence system that provides both threat actor profiles and threat reports. The system differentiates between nation-state Advanced Persistent Threat (APT) groups and cybercrime groups. For complete threat intelligence coverage, consider integrating all four related endpoints: APT Threat Actor (profiles), APT Threat (reports), HI Threat Actor (profiles), and HI Threat (reports). This allows you to build comprehensive actor profiles with associated reports for both nation-state and cybercrime threats in your third-party security systems. In some integration scenarios, collecting only the report endpoints may be sufficient for your use case.

Specifically, the HI Threat Actor endpoint provides threat actor profiles of cybercriminal groups (non-government sponsored), including financially motivated and organized threat groups. It works alongside the HI Threat endpoint, which provides detailed reports on cybercriminal activities, to deliver complete threat intelligence coverage. Together, these endpoints enable you to build comprehensive actor profiles with associated reports for enhanced threat detection and response capabilities.

Related Threat Intelligence Endpoints

The following table provides an overview of all four threat intelligence endpoints and their characteristics:

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
APT Threat Actor	/api/v2/apt/threat_actor/updated	Threat Actor Profiles	Nation-state APT	Highest	Comprehensive profiles of government-sponsored Advanced Persistent Threat groups, including their history, capabilities, and organizational details.
APT Threat	/api/v2/apt/threat/updated	Threat Reports	Nation-state APT	Highest	Detailed reports on nation-state APT activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
HI Threat Actor	/api/v2/hi/threat_actor/updated	Threat Actor Profiles	Cybercrime	High	Comprehensive profiles of cybercriminal groups (non-government sponsored), including financially motivated and other organized threat groups.
HI Threat	/api/v2/hi/threat/updated	Threat Reports	Cybercrime	High	Detailed reports on cybercriminal threat activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Integration Recommendations:

- Best Practice: Collect all four endpoints to build complete threat actor profiles with associated reports for both nation-state APT and cybercrime groups in your security systems. This provides the most comprehensive threat intelligence coverage.
- Alternative: For integrations that focus primarily on threat detection and IOC enrichment, collecting only the report endpoints (APT Threat and HI Threat) may be sufficient. Reports contain IOCs with severity ratings that help prioritize security responses.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/hi/threat_actor/updated
Collection	hi/threat_actor
Collection Name	HI Threat Actors
Module	Threats

Property	Value
Submodule	Actors
Type	Common + Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	None
Severity	9
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Comprehensive profiles of cybercriminal groups.

Request

Request URL

GET /api/v2/hi/threat_actor/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17597831696284
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:221e05fe443deec1356b0006817931ca16974f68
is_tailored	integer	No	0	Filter for tailored threat actors. Set to 1 to enable.	1
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:

- Maximum value: 100 for hi/threat_actor/updated collection
- If not specified, defaults to 100
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ThreatActorItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of threat actor items returned in this response
items	array[ThreatActorItem]	Yes	Array of threat actor objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ThreatActorItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
aliases	array[string]	Yes	Array of alternative names/aliases for the threat actor
country	string | null	No	Country code (ISO 3166-1 alpha-2)

Field	Type	Required	Description
isAPT	boolean	Yes	Whether this is an APT (Advanced Persistent Threat) group. For HI threats, this is typically false
description	string	Yes	HTML-formatted description of the threat actor
createdAt	string	Yes	ISO 8601 timestamp when the record was created
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
seqUpdate	integer	Yes	Sequence update number for this specific item
techSeqUpdate	integer | null	No	Technical sequence update number
oldId	string | null	No	Previous identifier (if migrated)
haslocs	boolean	Yes	Whether the threat actor has associated indicators of compromise
langs	array[string]	Yes	Array of language codes
spokenOnLangs	array[string]	Yes	Array of languages spoken by the threat actor
labels	array[string]	Yes	Array of label strings
roles	array[string]	Yes	Array of role strings
goals	array[string]	Yes	Array of goal strings
files	array	Yes	Array of file objects
addedToThreatLandscapeFor	array | null	No	Array of threat landscape options

Field	Type	Required	Description
threatLandscapeOptions	array[ThreatLandscapeOption]	Yes	Array of available threat landscape options
stat	ThreatActorStat	Yes	Statistics object containing aggregated data about the threat actor
displayOptions	DisplayOptions	Yes	Display options object

ThreatActorStat Object

Field	Type	Required	Description
allIndicatorsCount	integer	Yes	Total number of indicators associated with this threat actor
allReportsCount	integer	Yes	Total number of reports associated with this threat actor
contactsCount	integer	Yes	Number of contacts associated with this threat actor
forumsAccountsCount	integer	Yes	Number of forum accounts associated with this threat actor
relatedThreatActorsCount	integer	Yes	Number of related threat actors
countries	array[string]	Yes	Array of country codes where this threat actor is active
regions	array[string]	Yes	Array of regions where this threat actor is active
sectors	array[string]	Yes	Array of sectors targeted by this threat actor

Field	Type	Required	Description
cve	array[string]	Yes	Array of CVE identifiers used by this threat actor
malware	array[string]	Yes	Array of malware names used by this threat actor
expertise	array[string]	Yes	Array of expertise types
dateFirstSeen	string	Yes	Date when the threat actor was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the threat actor was last seen (format: YYYY-MM-DD)
reports	array[ReportSummary]	Yes	Array of report summary objects
targetedCompany	array[string]	Yes	Array of targeted company names
targetedPartnersAndClients	array[string]	Yes	Array of targeted partners and clients

ReportSummary Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the report (SHA-1 hash)
datePublished	string	Yes	Date when the report was published (format: YYYY-MM-DD)
name	object	Yes	Object with language keys containing report names
companyId	array	Yes	Array of company IDs (empty for common reports)

ThreatLandscapeOption Object

Field	Type	Required	Description
label	string	Yes	Label for the threat landscape option
value	string	Yes	Value for the threat landscape option

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/threat_actor/updated?seqUpdate=0&limit=100' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET
'https://tap.group-ib.com/api/v2/hi/threat_actor/updated?seqUpdate=0&limit=100&q=id:221e05fe443deec1356b0006817931ca16974f68' \   -u
'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/threat_actor/updated?seqUpdate=0&limit=100&apply_hunting_rules=1' \   -u 'LOGIN:API_KEY' \   -H
'Accept: application/json'
```

Example Response

Success Response (200 OK)

The response structure is similar to apt/threat_actor/updated, with the main difference being that isAPT is typically false for HI threat actors.

{ "count": 150, "items": [{ "addedToThreatLandscapeFor": null, "aliases": [], "country": null, "createdAt": "2019-02-20T17:44:21+00:00", "description": "
Threat actor description...
", "displayOptions": { "isFavourite": false, "isHidden": false }, "files": [], "goals": [], "hasIocs": true, "id": "example_id_hash", "isAPT": false, "labels": [], "langs": ["en", "ru"], "name": "Example Threat Actor", "oldId": null, "roles": [], "seqUpdate": 17597831696284, "spokenOnLangs": [], "stat": { "allIndicatorsCount": 100, "allReportsCount": 5, "contactsCount": 0, "countries": ["US", "GB"], "cve": [], "dateFirstSeen": "2020-01-01", "dateLastSeen": "2024-09-30", "expertise": ["AutoReport"], "forumsAccountsCount": 0, "malware": [], "regions": ["america:northern_america", "europe"], "relatedThreatActorsCount": 0, "reports": [], "sectors": [], "targetedCompany": [], "targetedPartnersAndClients": [] }, "techSeqUpdate": null, "threatLandscapeOptions": [{ "label": "company", "value": "company" }, { "label": "partner", "value": "partner" }, { "label": "industry", "value": "industry" }, { "label": "other", "value": "other" }], "updatedAt": "2024-09-30T03:00:45+03:00" }], "seqUpdate": 17597831696284 }

Threats and Actors - HI Threat Reports

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint is part of a comprehensive threat intelligence system that provides both threat actor profiles and threat reports. The system differentiates between nation-state Advanced Persistent Threat (APT) groups and cybercrime groups. For complete threat intelligence coverage, consider integrating all four related endpoints: APT Threat Actor (profiles), APT Threat (reports), HI Threat Actor (profiles), and HI Threat (reports). This allows you to build comprehensive actor profiles with associated reports for both nation-state and cybercrime threats in your third-party security systems. In some integration scenarios, collecting only the report endpoints may be sufficient for your use case.

Specifically, the HI Threat endpoint provides threat reports on cybercriminal activities, including IOCs, attack techniques, and MITRE ATT&CK mappings. It works alongside the HI Threat Actor endpoint, which provides comprehensive profiles of cybercriminal groups, to deliver complete threat intelligence coverage. Use this endpoint to stay informed about emerging cybercriminal threats and enhance your threat detection and response capabilities.

Note: This endpoint includes IOCs, which are also part of the IOC Primary collection.

Related Threat Intelligence Endpoints

The following table provides an overview of all four threat intelligence endpoints and their characteristics:

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
APT Threat Actor	/api/v2/apt/threat_actor/updated	Threat Actor Profiles	Nation-state APT	Highest	Comprehensive profiles of government-sponsored Advanced Persistent Threat groups, including their history, capabilities, and organizational details.
APT Threat	/api/v2/apt/threat/updated	Threat Reports	Nation-state APT	Highest	Detailed reports on nation-state APT activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Endpoint	API Path	Data Type	Actor Type	IOC Severity	Description
HI Threat Actor	/api/v2/hi/threat_actor/updated	Threat Actor Profiles	Cybercrime	High	Comprehensive profiles of cybercriminal groups (non-government sponsored), including financially motivated and other organized threat groups.
HI Threat	/api/v2/hi/threat/updated	Threat Reports	Cybercrime	High	Detailed reports on cybercriminal threat activities, including IOCs, attack techniques, MITRE ATT&CK mappings, and tactical intelligence.

Integration Recommendations:

- Best Practice: Collect all four endpoints to build complete threat actor profiles with associated reports for both nation-state APT and cybercrime groups in your security systems. This provides the most comprehensive threat intelligence coverage.
- Alternative: For integrations that focus primarily on threat detection and IOC enrichment, collecting only the report endpoints (APT Threat and HI Threat) may be sufficient. Reports contain IOCs with severity ratings that help prioritize security responses.
- Note on Severity Classification: Both threat report feeds (APT Threat and HI Threat) contain high severity IOCs; however, APT IOCs are more rare and by nature are the most important.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/hi/threat/updated
Collection	hi/threat
Collection Name	HI Threat Reports
Module	Threats

Property	Value
Submodule	Last threats
Type	Common + Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	Can differ
Severity	9
Collection Limit	10 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Reports on cybercriminal threat activities with IOCs, attack techniques, and MITRE ATT&CK mappings.

Request

Request URL
GET /api/v2/hi/threat/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	16738668845708
limit	integer	No	10	Limit the amount of returned data for this collection. Maximum allowed: 10 for this collection.	10
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:e3fa2b5e0c1e7f5916db3480cd43faf400a5eee8
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 10 for hi/threat/updated collection
  -

If not specified, defaults to 10

- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ThreatItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of threat items returned in this response
items	array[ThreatItem]	Yes	Array of threat objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ThreatItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat report (SHA-1 hash)
title	string	Yes	Title of the threat report
shortTitle	string | null	No	Short title of the threat report
description	string	Yes	HTML-formatted description of the threat
shortDescription	string | null	No	Short description of the threat

Field	Type	Required	Description
type	string	Yes	Type of the threat. Possible values: “event”, “threat”
reportNumber	string	Yes	Internal report number
dateFirstSeen	string	Yes	Date when the threat was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the threat was last seen (format: YYYY-MM-DD)
datePublished	string	Yes	Date when the report was published (format: YYYY-MM-DD)
createdAt	string	Yes	ISO 8601 timestamp when the record was created
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
isPublished	boolean	Yes	Whether the threat is published
isTailored	boolean	Yes	Whether the threat is tailored for specific clients
isAutogen	boolean	Yes	Whether the report was automatically generated
hasIocs	boolean	Yes	Whether the threat has indicators of compromise
langs	array[string]	Yes	Array of language codes (at this point, only En is up to date - no other languages)
seqUpdate	integer	Yes	Sequence update number for this specific item
techSeqUpdate	integer | null	No	Technical sequence update number

Field	Type	Required	Description
oldId	string | null	No	Previous identifier (if migrated)
contacts	array	Yes	Array of contact objects
countries	array	Yes	Array of country objects
regions	array	Yes	Array of region objects
sectors	array	Yes	Array of sector objects
labels	array	Yes	Array of label objects
cveList	array	Yes	Array of CVE identifiers
expertise	array[string]	Yes	Array of expertise types (e.g., [“AutoReport”], [“Leak”], [“Ransomware”])
sourceList	array	Yes	Array of source objects
sources	array	Yes	Array of source identifiers
files	array	Yes	Array of file objects
forumsAccounts	array	Yes	Array of forum account objects
malwareList	array	Yes	Array of malware objects
toolList	array	Yes	Array of tool objects
relatedThreatActors	array	Yes	Array of related threat actor objects
targetedCompany	array	Yes	Array of targeted company objects
targetedPartnersAndClients	array	Yes	Array of targeted partners and clients
companyId	array	Yes	Array of company IDs

Field	Type	Required	Description
author	string | null	No	Author of the report
indicators	array[Indicator]	Yes	Array of indicator objects
indicatorsIds	array[string]	Yes	Array of indicator IDs
indicatorRelationships	array	Yes	Array of indicator relationship objects
indicatorMalwareRelationships	array	Yes	Array of indicator-malware relationship objects
indicatorToolRelationships	array	Yes	Array of indicator-tool relationship objects
unreliableIndicators	array	Yes	Array of unreliable indicator objects
unreliableIndicatorsRelations	array	Yes	Array of unreliable indicator relationship objects
threatActor	ThreatActor | null	No	Associated threat actor object
mitreMatrix	array	Yes	Array of MITRE ATT&CK matrix objects
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	DisplayOptions	Yes	Display options object

Indicator Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the indicator (SHA-1 hash)

Field	Type	Required	Description
type	string	Yes	Type of indicator. Possible values: “network”, “file”, etc.
title	string | null	No	Title of the indicator
description	string | null	No	Description of the indicator
dateFirstSeen	string	Yes	Date when the indicator was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the indicator was last seen (format: YYYY-MM-DD)
deleted	boolean	Yes	Whether the indicator is deleted
seqUpdate	integer	Yes	Sequence update number for this indicator
techSeqUpdate	integer | null	No	Technical sequence update number
langs	array[string]	Yes	Array of language codes
sources	array[string]	Yes	Array of source identifiers
malwareIdList	array[string] | null	No	Array of related malware IDs
malwareList	array	Yes	Array of malware objects
attributes	object | null	No	Additional attributes
params	IndicatorParams	Yes	Indicator parameters object (contains actual indicator data)

IndicatorParams Object

Field	Type	Required	Description
domain			

Field	Type	Required	Description
	string | null	No	Domain name
ipv4	array[string]	Yes	Array of IPv4 addresses
ipv6	array[string]	Yes	Array of IPv6 addresses
url	string	Yes	URL (can be empty string)
ssl	array	Yes	Array of SSL certificate objects

ThreatActor Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
country	string | null	No	Country code (ISO 3166-1 alpha-2)
isAPT	boolean	Yes	Whether this is an APT (Advanced Persistent Threat) group. For HI threats, this is typically false

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “A1”, “C3”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)

Field	Type	Required	Description
severity	string	Yes	Severity level (e.g., “red”, “amber”, “orange”, “green”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “red”, “amber”, “green”, “white”)
ttl	integer | null	No	Time to live in days (usually null for this collection)

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/threat/updated?seqUpdate=0&limit=10' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/threat/updated?seqUpdate=0&limit=10&q=id:e3fa2b5e0c1e7f5916db3480cd43faf400a5eee8' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/threat/updated?seqUpdate=0&limit=10&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 1355, "items": [{ "contacts": [], "countries": ["CA"], "createdAt": "2024-09-23T06:16:41+03:00", "cveList": [], "dateFirstSeen": "2024-09-23", "dateLastSeen": "2024-09-23", "datePublished": "2024-09-23", "description": "
2024-09-23 Qilin ransomware attacked **Canstar Restorations** canstarrestorations[.]com.
...", "displayOptions": { "isFavourite": false, "isHidden": false }, "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "severity": "orange", "tlp": "amber", "ttl": null }, "expertise": ["Leak", "Ransomware", "AutoReport"], "files": [], "forumsAccounts": [], "hasIocs": false, "id": "d4a164b9caecc0d28041bb042bfad1acfb91f77a", "indicatorMalwareRelationships": [], "indicatorRelationships": [], "indicatorToolRelationships": [], "indicators": [], "indicatorsIds": [], "isAutogen": false, "isPublished": true, "isTailored": false, "labels": [], "langs": ["en", "ru"], "malwareList": [], "mitreMatrix": [{ "attackPatternId": "attack-pattern--b80d107d-fa0d-4b60-9684-b0433e8bdba0", "attackTactic": "impact", "attackType": "enterprise_tactics", "id": null, "mitreId": "T1486", "params": null }], "oldId": null, "regions": ["america:northern_america"], "relatedThreatActors": [], "reportNumber": "CP-2809-0616", "sectors": ["real-estate:construction"], "seqUpdate": 17270614084038, "shortDescription": null, "shortTitle": null, "sourceList": [], "sources": ["http://kbsqoivihgdmwczmxkbovk7ss2dcynitwhhfu5yw725dboqo5kthfaad.onion/site/view?uuid=f73f99c9-0a5d-36ff-8fab-36e936caab39"], "targetedCompany": ["Canstar Restorations"], "targetedPartnersAndClients": [], "techSeqUpdate": null, "threatActor": { "country": null, "id": "18c14c0707e5cdaeb7975576fa54a4346d154619", "isAPT": false, "name": "Qilin" }, "title": "Qilin Ransomware attack on Canstar Restorations", "toolList": [], "type": "threat", "unreliableIndicators": [], "unreliableIndicatorsRelations": [], "updatedAt": "2024-09-23T06:16:48+03:00" }], "seqUpdate": 17270858675384 }

Threats and Actors - Open Threats

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information from the Open Threats collection, which consolidates real-time public reports on cybersecurity threats from global sources. The data is categorized by criteria such as threat actor, malware or country and tagged with common identifiers and maybe be tagged by threat actor, malware, CVE, or country, facilitating easy filtering and integration with your security measures. This makes it easier to understand the content at a glance and apply intelligent filtering based on specific tags.

Important Note: Indicators from this feed can be automatically parsed for integration with your current security measures, but you should consider this feed as low severity. Threat Intelligence team doesn't review these indicators, and we assume it can produce some false positive alerts in your environment.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/hi/open_threats/updated
Collection	hi/open_threats
Collection Name	Open Threats
Module	Threats and Actors
Submodule	Open Threats
Type	Common
TTL (Days)	None (usually specified as 0)
Admiralty Code	Mostly B3
Severity	5 (recommended)
Collection Limit	100 records per request

Property	Value
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Consolidated public reports from various cybersecurity vendors and researchers globally.

Request

Request URL

GET /api/v2/hi/open_threats/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1664217109400513
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100

Parameter	Type	Required	Default	Description	Example
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:4b5f9b40d0207d32412338000bbb24b4a7eb4397
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 100 for hi/open_threats/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)

Header	Type	Required	Description	Example
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [OpenThreatItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of open threat items returned in this response
items	array[OpenThreatItem]	Yes	Array of open threat objects

Field	Type	Required	Description
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

OpenThreatItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the open threat report (SHA-1 hash)
title	string	Yes	Title of the open threat report
text	string	Yes	Full text content of the threat report
link	string	Yes	URL link to the original source article
original	string	Yes	Original source URL (can be empty string)
source	string	Yes	Source website or publication name
sourceType	string	Yes	Type of source (e.g., "Blog", "News", "Forum")
author	Author | null	No	Author information object
createdAt	string	Yes	ISO 8601 timestamp when the record was created
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
dateDetected	string	Yes	ISO 8601 timestamp when the threat was detected

Field	Type	Required	Description
detected	string	Yes	ISO 8601 timestamp when the threat was detected (same as dateDetected)
seqUpdate	integer	Yes	Sequence update number for this specific item
threatActors	array[ThreatActor] | null	No	Array of associated threat actor objects
data	ThreatData	Yes	Threat data object containing categorized information
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	DisplayOptions	Yes	Display options object

Author Object

Field	Type	Required	Description
name	string	Yes	Author's name (can be empty string)
profileUrl	string	Yes	Author's profile URL (can be empty string)
screenName	string	Yes	Author's screen name (can be empty string)
userId	string	Yes	Author's user ID (can be empty string)

ThreatData Object

Field	Type	Required	Description
countries	array[Country] | null	No	Array of country objects mentioned in the threat

Field	Type	Required	Description
companyTags	array	Yes	Array of company tags
cryptoWallets	array | null	No	Array of cryptocurrency wallet addresses
cve	array | null	No	Array of CVE identifiers
domains	array | null	No	Array of domain names
emails	array | null	No	Array of email addresses - not recommeded to use for detection
files	array | null	No	Array of file information
hashes	array | null	No	Array of file hashes
ip	array | null	No	Array of IP addresses
malware	array[Malware] | null	No	Array of malware objects
pdbPaths	array | null	No	Array of PDB (Program Database) paths
rules	array | null	No	Array of security rules
tags	array[string]	Yes	Array of tag strings (e.g., [“Access”, “Bank”, “COVID-19”, “Cashout”, “Leak”, “Rent”])
telegramApiKeys	array | null	No	Array of Telegram API keys

Country Object

Field	Type	Required	Description
country	string	Yes	Country name
countryCode	string	Yes	Country code (ISO 3166-1 alpha-2)

Malware Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the malware (SHA-1 hash)
name	string	Yes	Name of the malware
threatLevel	string	Yes	Threat level (can be empty string)
platform	string | null	No	Platform information
category	string | null	No	Malware category
class	string | null	No	Malware class

ThreatActor Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “B3”, “C3”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “red”, “orange”, “green”)

Field	Type	Required	Description
tlp	string	Yes	Traffic Light Protocol level (e.g., “red”, “amber”, “green”, “white”)
ttl	integer	Yes	Time to live in days (usually 0 for this collection)

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/open_threats/updated?seqUpdate=0&limit=100' \
  -u 'LOGIN:API_KEY' \
  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/open_threats/updated?seqUpdate=0&limit=100&q=id:4b5f9b40d0207d32412338000bbb24b4a7eb4397' \
  -u 'LOGIN:API_KEY' \
  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/open_threats/updated?seqUpdate=0&limit=100&apply_hunting_rules=1' \
  -u 'LOGIN:API_KEY' \
  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)


```
{
  "count": 294234,
  "items": [
    {
      "author": {
        "name": "",
        "profileUrl": "",
        "screenName": "",
        "userId": ""
      },
      "createdAt": "2022-05-25T09:30:41+00:00",
      "data": {
        "countries": [
          {
            "country": "Brazil",
            "countryCode": "BR"
          },
          {
            "country": "New Zealand",
            "countryCode": "NZ"
          },
          {
            "country": "Argentina",
            "countryCode": "AR"
          },
          {
            "country": "France",
            "countryCode": "FR"
          },
          {
            "country": "Ireland",
            "countryCode": "IE"
          },
          {
            "country": "Japan",
            "countryCode": "JP"
          },
          {
            "country": "Uruguay",
            "countryCode": "UY"
          }
        ],
        "companyTags": [],
        "cryptoWallets": null,
        "cve": null,
        "domains": null,
        "emails": null,
        "files": null,
        "hashes": null,
        "ip": null,
        "malware": null,
        "pdbPaths": null,
        "rules": null,
        "tags": [
          "Access",
          "Bank",
          "COVID-19",
          "Cashout",
          "Leak",
          "Rent"
        ],
        "telegramApiKeys": null
      },
      "dateDetected": "2022-09-26T18:31:49+00:00",
      "detected": "2022-09-26T18:31:49+00:00",
      "displayOptions": {
        "isFavourite": false,
        "isHidden": false
      },
      "evaluation": {
        "admiraltyCode": "B3",
        "credibility": 50,
        "reliability": 50,
        "severity": "green",
        "tlp": "white",
        "ttl": 0
      },
      "id": "4b5f9b40d0207d32412338000bbb24b4a7eb4397",
      "link": "https://www.welivesecurity.com/2022/05/25/5-reasons-why-gdpr-milestone-data-protection/",
      "original": "",
      "seqUpdate": 1664217109388512,
      "source": "welivesecurity.com",
      "sourceType": "Blog",
      "text": "The landmark regulation changed everyone's mindset on how companies worldwide collect and use the personal data of EU citizens...",
      "threatActors": null,
      "title": "5 reasons why GDPR was a milestone for data protection",
      "updatedAt": "2022-09-26T18:31:49+00:00"
    }
  ],
  "seqUpdate": 1664217109400513
}
```

Threats and Actors - Analyst Reports

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint provides updated information on analytic reports. This collection provides reports on known incidents and cybercrime trends as well as tailored reports for clients. It also contains reports on specific threats and complex malware and attacks being prepared against Group-IB customers. Such reports contain detailed information on malicious activity, indicators, and artifacts as well as expert recommendations.

The strategic data contained in the reports helps companies prepare months before attacks take place and improve their existing security policies. Therefore, in such materials the research and forecasts based on analyses of actual data are key.

This endpoint does not allow direct download of report files. However, it provides portal links (portalLink in the file objects) that can be used to access and download the reports through the Group-IB Threat Intelligence portal.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/hi/analytic/updated
Collection	hi/analytic
Collection Name	Analytic Reports
Module	Threats and Actors
Submodule	Analytic Reports
Type	Common
TTL (Days)	None (not provided in API)
Admiralty Code	A1
Severity	N/A
Collection Limit	500 records per request

Property	Value
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Reports on known incidents, cybercrime trends, specific threats, and complex malware with expert recommendations.

Request

Request URL
GET /api/v2/hi/analytic/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17295160323428
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:0326ee95e173174a1ff9e4250f1f5bf026bcc08e

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 500 for hi/analytic/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [AnalyticItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of analytic items returned in this response
items	array[AnalyticItem]	Yes	Array of analytic report objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

AnalyticItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the analytic report (SHA-1 hash)
oldId	string | null	No	Previous identifier (if migrated)
title	string	Yes	Report title

Field	Type	Required	Description
description	string	Yes	Report description
datePublished	string	Yes	ISO 8601 date when the report was published (format: YYYY-MM-DD)
seqUpdate	integer	Yes	Sequence update number for this specific item
type	string	Yes	Report type (e.g., “pdf”)
langs	array[string]	Yes	Array of language codes (e.g., [“en”])
cover	FileObject	Yes	Cover image file object
file	FileObject	Yes	Report file object (PDF)
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	object | null	No	Display options object

FileObject Object

Field	Type	Required	Description
name	string	Yes	File path/name
hash	string	Yes	SHA-256 hash of the file
mime	string	Yes	MIME type (e.g., “application/pdf”, “image/png”)
size	integer	Yes	File size in bytes (usually 0 in API response)
fileData	object | null	No	File data object (usually null in API response)

Field	Type	Required	Description
coverData	object | null	No	Cover data object (usually null in API response)
portalLink	string	Yes	Portal link to download the file

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “A1”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “green”, “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer | null	No	Time to live in days (usually null for analytic reports)

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/hi/analytic/updated?seqUpdate=0&limit=500' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 2, "items": [{ "cover": { "name": "/8eee15f5471d44e819d09d4def4d31c3c2e53a91/file/2b20e97a18e1c811cbd0c63da05a99dde7f2841ed4b8972bd3602226eca979c8", "hash": "2b20e97a18e1c811cbd0c63da05a99dde7f2841ed4b8972bd3602226eca979c8", "mime": "image/png", "size": 0, "fileData": null, "coverData": null, "portalLink": "https://tap.group-ib.com/api/v2/hi/analytic/8eee15f5471d44e819d09d4def4d31c3c2e53a91/file/2b20e97a18e1c811cbd0c63da05a99dde7f2841ed4b8972bd3602226eca979c8" }, "datePublished": "2024-10-18", "description": "Each quarter, Group-IB publishes an in-depth report that highlights trends in high-tech cybercrime, forecasts future threats, and identifies significant global cyber risks. The report focuses on advanced persistent threats (APTs) and cybercriminal activities across regions including Europe, Latin America, the Middle East and Africa (MEA), and Asia-Pacific. It analyzes industry and government trends in areas such as ransomware, initial access brokers, data leaks, and compromised hosts, while also addressing notable state-sponsored targeted attacks.", "displayOptions": null, "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "severity": "green", "tlp": "amber", "ttl": null }, "file": { "name": "/8eee15f5471d44e819d09d4def4d31c3c2e53a91/file/aaa3b70927b5ea8bfc58dc961b69665d39700b0257e13208604ad9da0c24efbd", "hash": "aaa3b70927b5ea8bfc58dc961b69665d39700b0257e13208604ad9da0c24efbd", "mime": "application/pdf", "size": 0, "fileData": null, "coverData": null, "portalLink":

"https://tap.group-ib.com/api/v2/hi/analytic/8eee15f5471d44e819d09d4def4d31c3c2e53a91/file/aaa3b70927b5ea8bfc58dc961b69665d39700b0257e13208604ad9da0c24efbd" }, "id": "8eee15f5471d44e819d09d4def4d31c3c2e53a91", "langs": ["en"], "oldId": null, "seqUpdate": 17295160323428, "title": "Threat evolution in Q3 2024", "type": "pdf" }], "seqUpdate": 17295168766104 }

IOC Primary

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides indicators of compromise (IOCs) from Group-IB research: IP addresses, domains, URLs and file hashes. Each indicator comes with a risk score, attribution to malware families and threat actors, and evaluation metadata (Admiralty Code, TLP, TTL). Use it to block known-bad infrastructure, detect hosts that contacted it, and enrich alerts and investigations.

IOC Primary replaces IOC Common (ioc/common). It returns the same indicators as IOC Common, plus risk scores, evaluation metadata, tags and source information that IOC Common does not include. IOC Common is deprecated (see Deprecated Collections); move your integrations to IOC Primary.

Note: Indicators from Malware - C2 are included in IOC Primary. If you ingest IOC Primary, you do not need to ingest Malware - C2 separately for indicators.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/ioc/primary/updated
Collection	ioc/primary
Collection Name	Primary Indicators of Compromise
Module	Not presented in the interface
Submodule	Mix
Type	Common
TTL (Days)	Set per record in evaluation.TTL. Values range from 365 to 14600 depending on the indicator
Admiralty Code	Set per record in evaluation.admiraltyCode. Values vary by indicator

Property	Value
Severity	Not provided. Derive severity from riskScore (see “Risk Score and Severity” below)
Hunting Rules	Not applicable. The apply_hunting_rules parameter has no effect on this collection
Collection Limit	2500 records per request
Rate Limit	1 request per second (see API Limitations)
IOC Types	IP, Domain, URL, File (MD5, SHA1, SHA256)
Short Description	Group-IB’s main IOC feed: IPs, domains, URLs and file hashes, each with a risk score, malware and threat-actor attribution, and a TTL. Use it to block, detect and enrich.

Use Cases

Use case	How it works	Where it is used
Block adversary network infrastructure	Take IPs, domains and URLs from network records and block those above your riskScore threshold. Any later connection attempt to a blocked indicator is an incident.	NGFW/FW, SOAR, TIP, SIEM
Detect a host that contacted known-bad infrastructure	Match IPs, domains and URLs against DNS, proxy, NetFlow, firewall and EDR logs, both for new events and retrospectively. A match opens an incident with the indicator, its riskScore, the malware family from malwareList, and the dateFirstSeen–dateLastSeen window in which the indicator was active.	SIEM, NTA/NDR, EDR/XDR, SOAR

Use case	How it works	Where it is used
Detect malware execution or delivery by hash	Match file hashes (md5, sha1, sha256) against endpoint and mail gateway telemetry. A match is a malware execution or delivery incident with the malware family already identified.	EDR/XDR, SIEM, SOAR, Email protection
Identify the malware family behind an indicator in an open case	Look up an IP, domain, URL or hash from the case with q=<value>. The record returns malwareList, threatList and tags, which identify the family and help choose the response playbook.	SOAR, SIEM, TIP, EDR/XDR
Publish curated indicators with attribution and expiry	Publish each indicator with its riskScore, malwareList and threatList attribution and tags, and use evaluation.TTL as the expiry date. Respect the TLP value when sharing indicators further.	TIP, SOAR
Keep an indicator history for trend reporting	Store records in your own system keyed on id, with the indicator values, scores, dates, attribution and evaluation. Report trends from your stored history; the count field in the response is not a total for the collection.	SIEM

Request

Request URL

GET /api/v2/ioc/primary/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	Yes	-	Sequence update number that marks where to start reading. Use 1 for the first request, then the seqUpdate value from the previous response. Do not use 0 or omit the parameter: on this collection the feed does not advance and the same page is returned on every request.	1
limit	integer	No	-	Number of records to return. Maximum allowed: 2500 for this collection.	2500
q	string	No	-	Search query. Use it to look up a specific indicator value or record ID. See details below.	192.0.2.10
apply_hunting_rules	integer	No	-	Has no effect on this collection.	-

Query Parameter Details:

- seqUpdate:
  - Start with seqUpdate=1. This returns the full history of the collection from the oldest record (2020), so the first run is a full download.
  - After each response, save the top-level seqUpdate value and send it in the next request. Continue until a response returns no items.
  - On later runs, continue from the last saved seqUpdate value instead of starting from 1 again.
  - Sequence List can return 1 for this collection instead of a date-based value. If it does, there is no date-based starting point available: either retry the request, or start from seqUpdate=1 and expect a full download.
- limit:
  - Maximum value: 2500 for ioc/primary/updated collection
  - Set the value explicitly in every request
- q:

- To look up an indicator: q=, for example q=192.0.2.10 or q=malicious.example.corp. The response can also contain other records, so keep only records that contain the exact value you searched for.
- To look up a record by ID: q=id: or q=
- For incremental collection, use seqUpdate instead of q

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/user@example.corp/ciaops_3.2.1

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [Indicator], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of records remaining after this response. It decreases as you read the feed and is not the number of items in this response
items	array[Indicator]	Yes	Array of indicator records
seqUpdate	integer	Yes	Sequence update number to send in the next request

Indicator Object

Each record is either a network record (type is network) or a file record (type is file). The fields below are present on both.

Field	Type	Required	Description
id	string	Yes	Unique record identifier. Usually 40 characters; file records can use the 64-character SHA256 value as the ID. Use it to deduplicate records
seqUpdate	integer	Yes	Sequence update number of this record
type	string	Yes	Record type: network or file
dateFirstSeen	string	Yes	ISO 8601 timestamp when the indicator was first seen
dateLastSeen	string	Yes	ISO 8601 timestamp when the indicator was last seen
ip	array[IpEntry]	Yes	IP address indicators. Empty on file records

Field	Type	Required	Description
domain	array[DomainEntry]	Yes	Domain indicators. Empty on file records
url	array[UrlEntry]	Yes	URL indicators. Empty on file records
hash	object (Hash)	No	File hashes. Present on file records only
riskScore	integer	No	Risk score of the file, 0-100. Present on file records only; network records have a score per indicator instead
malwareList	array[Malware]	Yes	Malware families associated with the indicator. Can be empty
threatList	array[Threat]	Yes	Threats associated with the indicator. Can be empty
threatActorList	array	Yes	Threat actors associated with the indicator. Can be empty
tags	array[string]	Yes	Category labels, for example Phishing, RAT, Ransomware, Exploit. May be empty
source	string	Yes	Type of source the indicator came from
potentialNames	array	Yes	Possible names associated with the indicator. Can be empty
evaluation	object (Evaluation)	Yes	Evaluation metadata of the record

Network Record Entries

A network record can contain IPs, domains and URLs at the same time. Read all three arrays.

Object	Field	Type	Required	Description
IpEntry	ip	string	Yes	IPv4 address. This collection does not contain IPv6 addresses
IpEntry	riskScore	integer	No	Risk score of the IP address, 0-100
DomainEntry	domain	string	Yes	Domain name
DomainEntry	riskScore	integer	No	Risk score of the domain, 0-100. May be absent
UrlEntry	url	string	Yes	URL
UrlEntry	riskScore	integer	No	Risk score of the URL, 0-100

Hash Object

Field	Type	Required	Description
md5	string	No	MD5 hash
sha1	string	No	SHA1 hash
sha256	string	No	SHA256 hash
other	string	No	Hash calculated with another algorithm

Note: Any of the hash values can be missing, including sha256. A small number of file records have no hash object at all. Check each value before using it.

Malware Object

Field	Type	Required	Description
name	string	Yes	Malware family name
aliases	array[string] | null	No	Alternative names of the malware family. Can be null

Threat Object

Field	Type	Required	Description
name	string	Yes	Name of the threat
title	string	Yes	Title of the threat. Can be empty

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code, for example A1, B2 or C3 (see Data Classification)
credibility	integer	Yes	Credibility of the information, 0-100
reliability	integer	Yes	Reliability of the source, 0-100
TLP	string	Yes	Traffic Light Protocol value, including the TLP: prefix, for example TLP:AMBER. Remove the prefix if your system expects a value such as AMBER
TTL	integer	Yes	Time to live of the indicator in days, for example 365, 730, 1825, 2555 or 14600. Use it to set the expiry of the indicator in your system

Note: The TLP and TTL field names are uppercase. This collection does not return a severity field.

Risk Score and Severity

This collection does not return a severity value. Use riskScore to assign severity in your system. The ranges below are the same as for IP Scoring and Domain Scoring.

Score	Category	Suggested severity	Suggested action
0-39			

Score	Category	Suggested severity	Suggested action
	Low	Low	No action
40-59	Suspicious	Medium	Monitor
60-79	High	High	Investigate
80-100	Malicious	Critical	Block or alert

Where to find the score:

- Network records: each entry in ip, domain and url has its own riskScore. There is no top-level riskScore on network records.
- File records: one top-level riskScore applies to all hashes in the record.

If riskScore is not present, the indicator has not been scored. Do not treat a missing score as 0.

Data Handling

- Respect the TLP value of each record when you share indicators with other teams or organizations.
- Indicators point to malicious infrastructure. Defang values when displaying them (for example, hxxp://malicious[.]example[.]corp) so that they cannot be opened by accident.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

First Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/primary/updated?seqUpdate=1&limit=2500' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json'
```

Next Request

Replace with the top-level seqUpdate value from the previous response.

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/primary/updated?seqUpdate=&limit=2500' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json'
```

Look Up an Indicator

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/primary/updated?q=192.0.2.10' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json'
```

Look Up a Record by ID

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/primary/updated?q=id:0a1b2c3d4e5f60718293a4b5c6d7e8f901234567' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

The example contains one network record and one file record. All values are examples.

{ "count": 182340, "items": [{ "id": "0a1b2c3d4e5f60718293a4b5c6d7e8f901234567", "seqUpdate": 17762117245804, "type": "network", "dateFirstSeen": "2026-09-15T00:00:00Z", "dateLastSeen": "2026-10-02T00:00:00Z", "ip": [{ "ip": "192.0.2.10", "riskScore": 95 }], "domain": [{ "domain": "malicious.example.corp" }], "url": [{ "url": "http://malicious.example.corp/login.php", "riskScore": 100 }], "malwareList": [{ "name": "ExampleRAT", "aliases": null }], "threatList": [], "threatActorList": [], "tags": ["RAT"], "source": "example-source", "potentialNames": [], "evaluation": { "admiraltyCode": "B2", "credibility": 80, "reliability": 80, "TLP": "TLP:AMBER", "TTL": 365 } }, { "id": "e3b0c44298fc1c149afbf4c8996fb92427ae41e4649b934ca495991b7852b855", "seqUpdate": 17762117245805, "type": "file",

"dateFirstSeen": "2026-09-20T00:00:00Z", "dateLastSeen": "2026-09-20T00:00:00Z", "ip": [], "domain": [], "url": [], "hash": { "md5": "d41d8cd98f00b204e9800998ecf8427e", "sha1": "da39a3ee5e6b4b0d3255bfef95601890afd80709", "sha256": "e3b0c44298fc1c149afbf4c8996fb92427ae41e4649b934ca495991b7852b855" }, "riskScore": 100, "malwareList": [{ "name": "ExampleStealer", "aliases": ["ExampleStealer v2"] }], "threatList": [], "threatActorList": [], "tags": [], "source": "example-source", "potentialNames": [], "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "TLP": "TLP:AMBER", "TTL": 1825 } }], "seqUpdate": 17762117245805 }

IOC Common

Deprecated: IOC Common is replaced by IOC Primary, which returns the same indicators with risk scores, evaluation metadata and attribution. New integrations should use IOC Primary.

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information from the Common IoCs collection, which consolidates Indicators of Compromise (IOCs) from multiple TI modules - Threats and Malware. This collection is specially created to get only IoCs and has no extra context (in some cases - attribution to malware family of threat actor), making it ideal for firewall rules and security filtering.

Important Note: The Common IoCs collection contains indicators from the following collections: - malware/cnc (C2 servers) - hi/threat (Human Intelligence threats) - apt/threat (Advanced Persistent Threat reports)

The main idea of IOC Common collection is to use it for firewall rules and security filtering without the need for additional context or attribution.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/ioc/common/updated
Collection	ioc/common
Collection Name	Common Indicators of Compromise
Module	Not presented in the interface
Submodule	Mix
Type	Common + Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	None
Severity	9
Collection Limit	5000 records per request

Property	Value
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IP, URL, File (MD5, SHA1, SHA256)
Short Description	Consolidated Indicators of Compromise from multiple threat intelligence sources.

Request

Request URL

GET /api/v2/ioc/common/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17272224279604
limit	integer	No	5000	Limit the amount of returned data for this collection. Maximum allowed: 5000 for this collection.	5000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:6c3e5247ee68545c60d850af02c2bc210aa08e50

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 5000 for ioc/common/updated collection
  - If not specified, defaults to 5000
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp, hash:abc123...)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [Indicator], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of indicator items returned in this response
items	array[Indicator]	Yes	Array of indicator objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request’s seqUpdate parameter to get the next portion of feeds

Indicator Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the indicator (SHA-1 hash)
type	string	Yes	Type of indicator. Possible values: “network”, “file”, etc.

Field	Type	Required	Description
dateFirstSeen	string	Yes	ISO 8601 timestamp when the indicator was first seen (format: YYYY-MM-DDTHH:mm:ss+03:00)
dateLastSeen	string	Yes	ISO 8601 timestamp when the indicator was last seen (format: YYYY-MM-DDTHH:mm:ss+03:00)
seqUpdate	integer	Yes	Sequence update number for this specific item
hash	array[string]	No	Array of file hash values (MD5, SHA1, SHA256). Present for file-type indicators.
malwareList	array[Malware]	Yes	Array of malware objects associated with this indicator
threatList	array[Threat]	Yes	Array of threat objects associated with this indicator

Note: The structure varies based on indicator type: - File indicators: Include hash array with MD5, SHA1, and/or SHA256 values - Network indicators: May include IP addresses, domains, or URLs (structure may vary)

Malware Object

Field	Type	Required	Description
name	string	Yes	Name of the malware
aliases	array[string]	Yes	Array of alternative names/aliases for the malware

Threat Object

Field	Type	Required	Description
name	string	Yes	Name of the threat

Field	Type	Required	Description
title	string	Yes	Title or description of the threat

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/common/updated?seqUpdate=0&limit=5000' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/common/updated?seqUpdate=0&limit=5000&q=id:6c3e5247ee68545c60d850af02c2bc210aa08e50' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with IP Search

```
curl -X GET 'https://tap.group-ib.com/api/v2/ioc/common/updated?seqUpdate=0&limit=5000&q=ip:8.8.8.8' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response - hashes (200 OK)


```
{  "count": 15234,  "items": [  {  "id": "6337a9653cd46b5e2fc5394696201951027905b6",  "type": "file",  "dateFirstSeen": "2024-10-05T00:00:00+03:00",  "dateLastSeen": "2024-10-05T00:00:00+03:00",  "seqUpdate": 15996048022320,  "hash": [ "73fe053e733bd116d605b76e02b74fb1456326a7",  "fe16a85a3f0094134eef4ba209c188a186ed269de90a6b5a84bcc4b90470cc79", "b372fd09864d839112b79b7f0675f7df"  ],  "malwareList": [  {  "name": "CobInt",  "aliases": []  }  ],  "threatList": [  { "name": "Cobalt",  "title": "Attacks of Cobalt gang based on using CobInt"  }  ]  }  ],  "seqUpdate": 15996048022320 }
```

Malware - C2

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on Command and Control (C2) servers. The CNC collection contains information on the control center where malware related to targeted attacks use to store stolen data or download commands from.

Note: This endpoint includes IOCs, which are also part of the IOC Primary collection.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/malware/cnc/updated
Collection	malware/cnc
Collection Name	Command and Control Servers
Module	Malware
Type	Common
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	None
Severity	9
Collection Limit	1000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL

Property	Value
Short Description	Information on control centers where malware related to targeted attacks use to store stolen data or download commands from.

Request

Request URL
GET /api/v2/malware/cnc/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	13700304004
limit	integer	No	1000	Limit the amount of returned data for this collection. Maximum allowed: 1000 for this collection.	1000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:cb08296b420fcce499ef84edb7ac314970953a00

Query Parameter Details:

- seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:

  - Maximum value: 1000 for malware/cnc/updated collection
  - If not specified, defaults to 1000
  - The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [CncItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of C2 server items returned in this response
items	array[CncItem]	Yes	Array of C2 server objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

CncItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the C2 server (SHA-1 hash)
cnc	string	Yes	Command and control server identifier (domain or IP)
domain	string	Yes	Domain name (can be empty string)

Field	Type	Required	Description
url	string	Yes	URL (can be empty string)
ipv4	array[IPv4Object]	Yes	Array of IPv4 address objects
ipv6	array[IPv6Object]	Yes	Array of IPv6 address objects
dateDetected	string	Yes	ISO 8601 timestamp when the C2 server was detected
dateFirstSeen	string	Yes	ISO 8601 timestamp when the C2 server was first seen
dateLastSeen	string	Yes	ISO 8601 timestamp when the C2 server was last seen
seqUpdate	integer	Yes	Sequence update number for this specific item
platform	string	Yes	Platform string (can be empty string)
file	object | null	No	File object (usually null)
malwareList	array	Yes	Array of malware objects
threatActor	array[ThreatActorRef]	Yes	Array of threat actor references

IPv4Object Object

Field	Type	Required	Description
ip	string	Yes	IPv4 address
countryCode	string	Yes	Country code (ISO 3166-1 alpha-2, can be empty string)

Field	Type	Required	Description
countryName	string	Yes	Country name (can be empty string)
city	string	Yes	City name (can be empty string)
region	string	Yes	Region name (can be empty string)
provider	string	Yes	ISP/provider name (can be empty string)
asn	string	Yes	ASN number (can be empty string)

ThreatActorRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/cnc/updated?seqUpdate=0&limit=1000' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/cnc/updated?seqUpdate=0&limit=1000&q=id:cb08296b420fcce499ef84edb7ac314970953a00' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 148783, "items": [{ "cnc": "hint09.9966.org", "dateDetected": "2013-05-31T20:00:00Z", "dateFirstSeen": "2013-05-31T20:00:00Z", "dateLastSeen": "2013-05-31T20:00:00Z", "domain": "hint09.9966.org", "file": null, "id": "cb08296b420fcce499ef84edb7ac314970953a00", "ipv4": [], "ipv6": [], "malwareList": [], "platform": "", "seqUpdate": 13700304004, "threatActor": [{ "id": "96054da361e4092a5a509862356f9f2541b86e9e", "name": "NetTraveler" }], "url": "" }, { "cnc": "82.113.19.75", "dateDetected": "2014-08-06T20:00:00Z", "dateFirstSeen": "2014-08-06T20:00:00Z", "dateLastSeen": "2014-08-06T20:00:00Z", "domain": "", "file": null, "id": "d67606f9fb3f81dbddbea74f3231613a742dc397", "ipv4": [{ "asn": "", "city": "", "countryCode": "", "countryName": "", "ip": "82.113.19.75", "provider": "", "region": "" }], "ipv6": [], "malwareList": [], "platform": "", "seqUpdate": 14073552002, "threatActor": [{ "id": "03cf30aa129ecf2eba833773e10786b1558ac212", "name": "Turla" }], "url": "" }], "seqUpdate": 14139216000 }

Malware - Config

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated malware configuration files from the Config submodule. These configs are collected from diverse malware files and incident investigations.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/malware/config/updated
Collection	malware/config
Collection Name	Malware Configuration Files
Module	Malware
Submodule	Configs
Type	Individual
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A1
Severity	9
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	none - only data for analysis

Property	Value
Short Description	Extracted configuration files from malware samples.

Request

Request URL
GET /api/v2/malware/config/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17270645076338
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:9f61d4e05e77994724f7e29bc0fb810b26c2bb3c
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 100 for malware/config/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ConfigItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of config items returned in this response
items	array[ConfigItem]	Yes	Array of config objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ConfigItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the config (SHA-1 hash)
hash	string	Yes	Hash of the config (SHA-1)
malwareId	string	Yes	Unique identifier of the associated malware (SHA-1 hash)

Field	Type	Required	Description
malware	MalwareRef	Yes	Malware reference object
dateFirstSeen	string	Yes	Date when the config was first seen (format: YYYY-MM-DD)
dateLastSeen	string	Yes	Date when the config was last seen (format: YYYY-MM-DD)
seqUpdate	integer	Yes	Sequence update number for this specific item
content	string	Yes	Config content (can be empty string)
contentLen	integer	Yes	Length of the config content
configSummary	string | null	No	Summary of the config
file	array[FileObject]	Yes	Array of file objects
domainList	array	Yes	Array of domain objects
ipList	array	Yes	Array of IP address objects

MalwareRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the malware (SHA-1 hash)
name	string	Yes	Name of the malware

FileObject Object

Field	Type	Required	Description
name	string	Yes	File name
sha1	string	Yes	SHA-1 hash of the file
sha256	string | null	No	SHA-256 hash of the file
md5	string | null	No	MD5 hash of the file
timestamp	string	Yes	ISO 8601 timestamp when the file was seen

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/config/updated?seqUpdate=0&limit=100' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/config/updated?seqUpdate=0&limit=100&q=id:9f61d4e05e77994724f7e29bc0fb810b26c2bb3c' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/config/updated?seqUpdate=0&limit=100&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)


```
{  "count": 1411,  "items": [  {  "configSummary": null,  "content": "",  "contentLen": 0,  "dateFirstSeen": "2024-09-23",  "dateLastSeen": "2024-09-23",  "domainList": [],  "file": [  {  "md5": null,  "name": "2e432426a7a0a10a0068c035368f749c298e1ef1add61e31a8b25da74676fcaa.exe",  "sha1": "3fff365af65a3d3312c222acfe0a4d7447d0e78d",  "sha256": null,  "timestamp": "2024-09-23T00:00:00+03:00"  }  ],  "hash": "5d6ba0fd685e89e3d03e4a63de67dfaec3c5fc17",  "id": "5d6ba0fd685e89e3d03e4a63de67dfaec3c5fc17",  "ipList": [],  "malware": {  "id": "e3ad9c65499117cc68bbf3ee9e39bd93ce815547",  "name": "AsyncRAT"  },  "malwareId": "e3ad9c65499117cc68bbf3ee9e39bd93ce815547",  "seqUpdate": 17270645076338  }  ],  "seqUpdate": 17270743540724 }
```

Malware - Reports

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated malware reports from the Malware collection. The Malware collection contains detailed information about specific malware detected through analyzing Threat Actors activity. Can contain malware names, desciption, related attacker names and additionally legitimate tools used by attackers during an attack.

Note: This endpoint includes IOCs, which are also part of the IOC Primary collection.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/malware/malware/updated
Collection	malware/malware
Collection Name	Malware Reports
Module	Malware
Submodule	Reports
Type	Common
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	9
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
IOC Types	Domain, IPv4, URL, File (MD5, SHA1, SHA256)
Short Description	Detailed information about specific malware detected through analyzing Threat Actors activity.

Request

Request URL

GET /api/v2/malware/malware/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	16904733083037
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:653654fb986b47a31c73d92f4a20a273acd2f779

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 100 for malware/malware/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [MalwareItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of malware items returned in this response
items	array[MalwareItem]	Yes	Array of malware objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

MalwareItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the malware (SHA-1 hash)
name	string	Yes	Name of the malware
aliases	array[string]	Yes	Array of alternative names/aliases for the malware

Field	Type	Required	Description
description	string	Yes	Description of the malware (can be “Sorry, no description yet.”)
shortDescription	string | null	No	Short description of the malware
category	array[string]	Yes	Array of category strings (e.g., [“atm-malware”], [“Downloader”], [“Remote Access Trojan”, “Rootkit”, “Trojan”])
class	string | null	No	Malware class
platform	array[string]	Yes	Array of platform strings (e.g., [“atm”, “Windows”, “Linux”], [“Windows”])
threatLevel	string	Yes	Threat level (e.g., “High”, “Medium”)
isPublished	boolean	Yes	Whether the malware is published
langs	array[string]	Yes	Array of language codes
seqUpdate	integer	Yes	Sequence update number for this specific item
sequenceId	integer	Yes	Sequence ID
updatedAt	string	Yes	ISO 8601 timestamp when the record was last updated
geoRegion	array[string]	Yes	Array of geographic regions where the malware is active
sourceCountry	array[string]	Yes	Array of source country codes (ISO 3166-1 alpha-2)
taList	array[ThreatActorRef]	Yes	Array of threat actor references
threatActorList	array	Yes	Array of threat actor objects

Field	Type	Required	Description
linkedMalware	array[MalwareRef]	Yes	Array of linked malware references
malwareAliasList	array	Yes	Array of malware aliases
fileIocList	array	Yes	Array of file indicator objects
fileIocIdList	array	Yes	Array of file indicator IDs
networkIocList	array	Yes	Array of network indicator objects
networkIocIdList	array	Yes	Array of network indicator IDs
deletedIocList	array | null	No	Array of deleted indicators
attachedFile	array	Yes	Array of attached file objects
mitreMatrix	array	Yes	Array of MITRE ATT&CK matrix objects
signatureIdList	array	Yes	Array of signature IDs
yaraIdList	array	Yes	Array of YARA rule IDs
portalLink	string | null	No	Portal link to the malware profile

ThreatActorRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
url	string	Yes	URL to threat actor profile (can be empty string)

MalwareRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the linked malware (SHA-1 hash)
name	string	Yes	Name of the linked malware

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/malware/updated?seqUpdate=0&limit=100' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/malware/updated?seqUpdate=0&limit=100&q=id:653654fb986b47a31c73d92f4a20a273acd2f779' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 36, "items": [{ "aliases": [], "attachedFile": [], "category": ["atm-malware"], "class": null, "deletedIocList": null, "description": "Sorry, no description yet.", "fileIocIdList": [], "fileIocList": [], "geoRegion": ["asia", "europe", "america:northern_america"], "id": "d7fde57f6ed2051ffae9257ba6beefe0fc99192f", "isPublished": true, "langs": ["ru", "en"], "linkedMalware": [], "malwareAliasList": [], "mitreMatrix": [], "name": "FASTCash", "networkIocIdList": [], "networkIocList": [], "platform": ["atm", "Windows", "Linux"], "portalLink": null, "seqUpdate": 16904733083037, "sequenceId": 16269766696153, "shortDescription": "This malware in turn intercepts fraudulent Lazarus cash withdrawal requests and sends fake approval responses, allowing the attackers to steal cash from ATMs.", "signatureIdList": [], "sourceCountry": ["KP", "KR", "RU", "US"], "taList": [{ "id": "5e9f20fdcf5876b5772b3d09b432f4080711ac5f", "name": "Lazarus", "url": "" }], "threatActorList": [], "threatLevel": "High", "updatedAt": "2024-10-22T14:58:02+03:00", "yaraIdList": [] }], "seqUpdate": 17020334285354 }

Malware - Suricata

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated malware signature data used to detect and mitigate cyber threats. Each signature includes details such as the malware name, severity level, signature ID (SID), rule content, and associated metadata. The signatures are categorized by class (e.g., Trojan activity) and can be used for network and endpoint monitoring. These signatures provide crucial information for identifying malicious activity, such as observing specific SSL/TLS certificates or DNS queries linked to known malware families like QBot and MageCart.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/malware/signature/updated
Collection	malware/signature
Collection Name	Malware Signatures (Suricata)
Module	Malware
Submodule	Signatures (Suricata)
Type	Common
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	8
Collection Limit	5000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Malware signatures that can be used to enrich malware security feeds, detect potentially confidential information and identify specific malware promptly.

Request

Request URL
GET /api/v2/malware/signature/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	17285596516319
limit	integer	No	5000	Limit the amount of returned data for this collection. Maximum allowed: 5000 for this collection.	5000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:137224

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 5000 for malware/signature/updated collection
  - If not specified, defaults to 5000
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [SignatureItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of signature items returned in this response
items	array[SignatureItem]	Yes	Array of signature objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

SignatureItem Object

Field	Type	Required	Description
id	integer	Yes	Unique identifier of the signature (numeric ID)
sid	integer	Yes	Signature ID (SID) - Suricata signature identifier
name	string	Yes	Name of the signature

Field	Type	Required	Description
class	string	Yes	Signature class (e.g., “trojan-activity”)
content	string	Yes	Raw Suricata rule content
severity	integer	Yes	Severity level (numeric, typically 1-5)
seqUpdate	integer	Yes	Sequence update number for this specific item
createdAt	string	Yes	ISO 8601 timestamp when the signature was created
malware	array[MalwareRef]	Yes	Array of malware references associated with this signature
alertNum	integer	Yes	Alert number (typically 0)
sourceName	string | null	No	Source name for the signature

MalwareRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the malware (SHA-1 hash)
name	string	Yes	Name of the malware

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/signature/updated?seqUpdate=0&limit=5000' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Search Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/signature/updated?seqUpdate=0&limit=5000&q=id:137224' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "items": [{ "alertHistory": [], "alertNum": 0, "class": "trojan-activity", "content": "alert tls $EXTERNAL_NET any -> $HOME_NET any (msg:\"TROJAN Observed Malicious SSL/TLS Certificate (QakBot)\"; target:dest_ip; flow:established,to_client; tls_cert_subject; content:\"C=PT, ST=IO, L=Enbdyd Mpbuv, O=Pswouppu Vnc Inc., CN=ragouxvase.biz\"; depth:67; fast_pattern; isdataat:!1,relative; reference:url,twitter.com/Unit42_Intel/status/1585046057339207680; classtype:trojan-activity; sid:2039577; rev:2; metadata:attack_target Client_Endpoint, created_at 2022_10_26, deployment Perimeter, deprecation_reason Age, malware_family Qbot, signature_severity Major, updated_at 2024_10_08, reviewed_at 2024_10_08, severity 3, ti_malware_id e323de16fc8162e02aad6683b0f48a0e4008cbae, ti_malware_name QBot, rule_origin

etpro;)", "createdAt": "2024-10-10T06:31:01+00:00", "id": 1294223, "malware": [{ "id": "e323de16fc8162e02aad6683b0f48a0e4008cbae", "name": "QBot" }], "name": "TROJAN Observed Malicious SSL/TLS Certificate (QakBot)", "seqUpdate": 17285596516319, "severity": 3, "sid": 2039577, "sourceName": null }], "count": 347, "seqUpdate": 17285721594209 }

Malware - Yara

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated YARA rule data used for detecting and identifying specific malware threats. Each YARA rule includes information such as the rule name, description, associated malware, severity level, and detection conditions (e.g., file hashes, strings, patterns). These rules aid in identifying malware families by scanning for particular characteristics within files or processes. This information is essential for enhancing malware detection and improving threat-hunting capabilities.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/malware/yara/updated
Collection	malware/yara
Collection Name	YARA Rules
Module	Malware
Submodule	Yara rules
Type	Common
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	8
Collection Limit	5000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	YARA rules set by Group-IB and containing information about specific malware families.

Request

Request URL
GET /api/v2/malware/yara/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	16753451595662
limit	integer	No	5000	Limit the amount of returned data for this collection. Maximum allowed: 5000 for this collection.	5000

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  .

Maximum value: 5000 for malware/yara/updated collection

- If not specified, defaults to 5000
- The limit depends on the amount of data to not overload the JSON output

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	no-cache, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [YaraItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of YARA rule items returned in this response
items	array[YaraItem]	Yes	Array of YARA rule objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

YaraItem Object

Field	Type	Required	Description
id	integer	Yes	Unique identifier of the YARA rule (numeric ID)
name	string	Yes	Name of the YARA rule
class	string	Yes	Rule class (can be empty string)
content	string	Yes	Raw YARA rule content
seqUpdate	integer	Yes	Sequence update number for this specific item
createdAt	string	Yes	ISO 8601 timestamp when the rule was created
malware	array[MalwareRef]	Yes	Array of malware references associated with this rule
alertNum	integer	Yes	Alert number (typically 0)
sourceName	string | null	No	Source name for the rule (e.g., "polygon")

MalwareRef Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the malware (SHA-1 hash)
name	string	Yes	Name of the malware

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/malware/yara/updated?seqUpdate=0&limit=5000' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)


```
{   "items": [    {      "alertNum": 0,      "class": "",      "content": "import \"hash\"\n\nrule ccleaner\n{\n    meta:\n        description = \"Infected CCleaner\"\n        severity = 300\n        enabled = 1\n        ti_malware_id = \"dbbb8f0188cff98f30908263bfa8e667a2bbc026\"\n        ti_malware_name = \"404Keylogger\"\n\n    condition:\n        hash.md5 ( 0 , filesize ) == \"75735db7291a19329190757437bdb847\" or hash.md5 ( 0 , filesize ) == \"ef694b89ad7addb9a16bb6f26f1efaf7\" or hash.md5 ( 0 , filesize ) == \"a3d00b7362db6df0fcc49b6ab17b3cf0\" or hash.md5 ( 0 , filesize ) == \"d488e4b61c233293bec2ee09553d3a2f\"\n}\n",      "createdAt": "2020-09-30T11:03:52+00:00",      "id": 9,      "malware": [        {          "id": "dbbb8f0188cff98f30908263bfa8e667a2bbc026",          "name": "404Keylogger"        }      ],      "name": "ccleaner",      "seqUpdate": 16753451595662,      "sourceName": "polygon"    }  ],  "count": 10000,  "seqUpdate": 16753451601281 }
```

Malware - Vulnerability

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on software vulnerabilities, categorized by vendor and product (e.g., Microsoft Windows, Apache HTTP Server). In addition to general vulnerabilities' information, the subsection also contains data on existing exploits, with the option to view links to PoC (Proof-of-Concept), and additional information.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/osi/vulnerability/updated
Collection	osi/vulnerability
Collection Name	Vulnerabilities
Module	Malware
Submodule	Vulnerabilities
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A1
Severity	9
Collection Limit	200 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Software vulnerabilities detected by version, including exploit information and PoC links.

Request

Request URL
GET /api/v2/osi/vulnerability/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	15677944090287
limit	integer	No	200	Limit the amount of returned data for this collection. Maximum allowed: 200 for this collection.	200
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: "" to search for one specific record.	"WPVDB-ID:7181"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 200 for osi/vulnerability/updated collection
  - If not specified, defaults to 200
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific vulnerability: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [VulnerabilityItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of vulnerability items returned in this response
items	array[VulnerabilityItem]	Yes	Array of vulnerability objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

VulnerabilityItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the vulnerability (e.g., "WPVDB-ID:7181")
title	string	Yes	Vulnerability title
description	string	Yes	Vulnerability description

Field	Type	Required	Description
datePublished	string	Yes	ISO 8601 timestamp when the vulnerability was published
dateModified	string	Yes	ISO 8601 timestamp when the vulnerability was last modified
dateLastSeen	string	Yes	ISO 8601 timestamp when the vulnerability was last seen
seqUpdate	integer	Yes	Sequence update number for this specific item
bulletinFamily	string	Yes	Bulletin family (e.g., “software”)
type	string	Yes	Vulnerability type (e.g., “wpvulndb”)
reporter	string	Yes	Reporter name
provider	string	Yes	Provider name
href	string	Yes	Link to the vulnerability details
cvss	CvssObject	Yes	CVSS score object
cvssAttackVector	string	Yes	CVSS attack vector (can be empty string)
mergedCvss	integer	Yes	Merged CVSS score
cveList	array	Yes	Array of CVE identifiers
cveListEpss	array	Yes	Array of CVE EPSS data
epss	EpssObject	Yes	EPSS (Exploit Prediction Scoring System) object
affectedSoftware	array[AffectedSoftwareObject]	Yes	Array of affected software objects

Field	Type	Required	Description
cpe	array	Yes	Array of CPE identifiers
cpeTable	array	Yes	Array of CPE table entries
exploitCount	integer	Yes	Number of available exploits
hasExploit	boolean	Yes	Whether exploits are available
exploitList	array	Yes	Array of exploit references
exploitation	array	Yes	Array of exploitation data
githubLinkList	array	Yes	Array of GitHub links
references	array	Yes	Array of reference links
darkweb	array	Yes	Array of dark web references
twitter	array	Yes	Array of Twitter references
threats	array	Yes	Array of threat references
threatsList	array	Yes	Array of threat list entries
softwareMixed	array	Yes	Array of mixed software data
timeLineData	array	Yes	Array of timeline data
seenInTheWild	boolean	Yes	Whether the vulnerability has been seen in the wild
extDescription	string	Yes	Extended description (can be empty string)
portalLink	string	Yes	Portal link (can be empty string)
displayOptions	DisplayOptions	Yes	Display options object

CvssObject Object

Field	Type	Required	Description
score	integer	Yes	CVSS score
vector	string	Yes	CVSS vector string

EpssObject Object

Field	Type	Required	Description
cve	string	Yes	CVE identifier (can be empty string)
epss	number	Yes	EPSS score (0-1)
percentile	number	Yes	EPSS percentile (0-100)
date	string	Yes	ISO 8601 timestamp of EPSS data

AffectedSoftwareObject Object

Field	Type	Required	Description
name	string	Yes	Software name
version	string	Yes	Software version
operator	string	Yes	Version operator (e.g., “lt” for less than)

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Field	Type	Required	Description
favouriteForCompanies	array	Yes	Array of company IDs that marked this as favourite
hideForCompanies	array	Yes	Array of company IDs that hid this item

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/osi/vulnerability/updated?seqUpdate=0&limit=200' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/osi/vulnerability/updated?seqUpdate=0&limit=200&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 454062, "items": [{ "affectedSoftware": [{ "name": "shrimptest", "operator": "lt", "version": "1.0b3" }], "bulletinFamily": "software", "cpe": [], "cpeTable": [], "cveList": [], "cveListEpss": [], "cvss": { "score": 0, "vector": "NONE" }, "cvssAttackVector": "", "darkweb": [], "dateLastSeen": "2018-09-17T17:26:04+01:00", "dateModified": "2015-05-14T22:00:00+01:00", "datePublished": "2014-07-31T21:00:00+01:00", "description": "WordPress Vulnerability - ShrimpTest 1.0b2 - plugins/plugin-notification.php Unspecified XSS\n", "displayOptions": { "favouriteForCompanies": [], "hideForCompanies": [], "isFavourite": false, "isHidden": false }, "epss": { "cve": "", "date": "0001-01-01T00:00:00Z", "epss": 0, "percentile": 0 }, "exploitCount": 0, "exploitList": [], "exploitation": [], "extDescription": "", "githubLinkList": [], "hasExploit": false, "href": "https://wpvulndb.com/vulnerabilities/7181", "id": "WPVDB-ID:7181", "lastseen": "2018-09-17T17:26:04+01:00", "mergedCvss": 0, "modified": "2015-05-14T22:00:00+01:00", "portalLink": "", "provider": "vulners.com", "published": "2014-07-31T21:00:00+01:00", "references": [], "reporter": "wpvulndb", "seenInTheWild": false, "seqUpdate": 15677944090287, "softwareMixed": [], "threats": [], "threatsList": [], "timeLineData": [], "title": "ShrimpTest 1.0b2 - plugins/plugin-notification.php Unspecified XSS", "twitter": [], "type": "wpvulndb" }], "seqUpdate": 15677944270178 }

Malware - Phishing Kit

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on phishing kits. A Phishing kit is a collection of pages, scripts, and images that keep a phishing website up and running. In other words, it is a ready-made phishing website with a relevant settings file that specifies the parameters of how the page needs to be displayed.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/attacks/phishing_kit/updated
Collection	attacks/phishing_kit
Collection Name	Phishing Kits
Module	Malware
Submodule	Phishing Kits
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	Mostly B2
Severity	9
Collection Limit	1000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	none - only data for analysis

Property	Value
Short Description	Collection of pages, scripts, and images that keep a phishing website up and running.

Request

Request URL
GET /api/v2/attacks/phishing_kit/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1523520752839
limit	integer	No	1000	Limit the amount of returned data for this collection. Maximum allowed: 1000 for this collection.	1000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:5cf5afc22dfa08252e990c9e3fc51e287ff54dc53742767a7428dc31b25dd606
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 1000 for attacks/phishing_kit/updated collection
  - If not specified, defaults to 1000
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [PhishingKitItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of phishing kit items returned in this response
items	array[PhishingKitItem]	Yes	Array of phishing kit objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

PhishingKitItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the phishing kit (SHA-256 hash)
hash	string	Yes	Hash of the phishing kit (SHA-256)

Field	Type	Required	Description
seqUpdate	integer	Yes	Sequence update number for this specific item
dateDetected	string	Yes	ISO 8601 timestamp when the phishing kit was detected
dateFirstSeen	string	Yes	ISO 8601 timestamp when the phishing kit was first seen
dateLastSeen	string	Yes	ISO 8601 timestamp when the phishing kit was last seen
login	string	Yes	Login/user who uploaded or detected the kit
path	string	Yes	API path to download the phishing kit file
source	array[string]	Yes	Array of source identifiers
downloadedFrom	array[DownloadSource]	Yes	Array of download source objects
emails	array	Yes	Array of email addresses
targetBrand	array	Yes	Array of target brand names
telegramIds	array | null	No	Array of Telegram IDs
variables	array[Variable] | null	No	Array of variable objects (database credentials, URLs, etc.)
threatActors	array | null	No	Array of threat actor objects
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

DownloadSource Object

Field	Type	Required	Description
date	string	Yes	ISO 8601 timestamp when the kit was downloaded
url	string	Yes	URL from which the kit was downloaded
phishingUrl	string	Yes	Phishing URL (can be empty string)
domain	string	Yes	Domain name
fileName	string	Yes	File name (can be empty string)

Variable Object

Field	Type	Required	Description
type	string	Yes	Type of variable (e.g., “DB”, “LOG”, “CURL”)
filePath	string	Yes	File path where the variable is found
values	array[string]	Yes	Array of variable values (may contain masked sensitive data)

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “B2”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “orange”, “red”)

Field	Type	Required	Description
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/phishing_kit/updated?seqUpdate=0&limit=1000' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/phishing_kit/updated?seqUpdate=0&limit=1000&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 122834, "items": [{ "id": "5cf5afc22dfa08252e990c9e3fc51e287ff54dc53742767a7428dc31b25dd606", "hash": "5cf5afc22dfa08252e990c9e3fc51e287ff54dc53742767a7428dc31b25dd606", "seqUpdate": 1523520752839, "dateDetected": "2018-03-09T22:19:59+00:00", "dateFirstSeen": "2018-03-09T22:19:59+00:00", "dateLastSeen": "2018-03-27T13:18:38+00:00", "downloadedFrom": [{ "date": "2018-03-09T22:19:59+03:00", "url": "https://gt-mywyty186338.codeanyapp.com/cb.zip", "phishingUrl": "", "domain": "gt-mywyty186338.codeanyapp.com", "fileName": "" }], "emails": [], "login": "PhishingKitFetcher", "path": "https://tap.group-ib.com/api/v2/malware/phishing_kit/5cf5afc22dfa08252e990c9e3fc51e287ff54dc53742767a7428dc31b25dd606/file/5cf5afc22dfa08252e990c9e3fc51e287ff54dc53742767a7428dc31b25dd606", "source": ["ci-PhishKit"], "targetBrand": [], "telegramIds": null, "variables": [{ "type": "DB", "filePath": "./cb/pages/jsp-ns/cargando.php", "values": ["host: $mysql_host", "login: **********", "password: **********"] }], "threatActors": null, "evaluation": { "admiraltyCode": "B2", "credibility": 80, "reliability": 70, "severity": "orange", "tlp": "amber", "ttl": 30 }, "isFavourite": false, "isHidden": false }], "settings": { "search": { "fields": ["company", "domain", "has_connection_vars", "target_brand"], "tags": ["203051", "options", "target_brand"] } }, "seqUpdate": 1523520767270 }

Darkweb - Discord

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information from Discord channels and servers. Similar to Telegram, the Threat Intelligence system analyzes Discord channels and servers. Here records can contain bank/personal credentials, media, files, links, ip-addresses and domains of the companies that can be targeted in the nearest future, or were already attacked and it was discussed in the specific channel/server.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/discord/updated
Collection	compromised/discord
Collection Name	Compromised Discord Messages
Module	Darkweb
Submodule	Instant messengers (Discord)
Type	Individual
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	N/A
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Information from Discord channels and servers.

Request

Request URL

GET /api/v2/compromised/discord/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1729505868852513
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:7901bb2b1400734126168ab9bacc28bc

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  .

Maximum value: 100 for compromised/discord/updated collection

- If not specified, defaults to 100
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to compromised/messenger/updated, containing Discord messages with similar fields including message content, author information, channel statistics, and metadata.

Root Object
{ "count": integer, "items": [DiscordItem], "seqUpdate": integer, "settings": array }

Field	Type	Required	Description
count	integer	Yes	Number of Discord items returned in this response
items	array[DiscordItem]	Yes	Array of Discord message objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	array	Yes	Settings array (usually empty)

DiscordItem Object

The structure is similar to MessengerItem from compromised/messenger/updated, containing message content, author information, channel/server statistics, and metadata specific to Discord.

Example Request

Basic Request
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/discord/updated?seqUpdate=0&limit=100' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Example Response

Success Response (200 OK)

The response structure is similar to compromised/messenger/updated, with items containing Discord messages.
{ "count": 5000, "items": [{ "id": "example_id_hash", "message": "Example Discord message content", "messageId": 123456, "messageTs": "2024-10-16T05:19:02+03:00", "author": { "id": 123456789, "userName": "example_user", "type": "user" }, "seqUpdate": 1729505868852513 }], "settings": [], "seqUpdate": 1729506374088157 }

Darkweb - Telegram

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information from Telegram chats and channels. Here records can contain bank/personal credentials, media, files, links, ip-addresses and domains of the companies that can be targeted in the nearest future, or were already attacked and it was discussed in the specific chat/channel.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/messenger/updated
Collection	compromised/messenger
Collection Name	Telegram Messages
Module	Darkweb
Submodule	Instant messengers (Telegram)
Type	Individual
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	N/A
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Information from Telegram chats and channels.

Request

Request URL

GET /api/v2/compromised/messenger/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1729505868852513
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:7901bb2b1400734126168ab9bacc28bc

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  .

Maximum value: 100 for compromised/messenger/updated collection

- If not specified, defaults to 100
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [MessengerItem], "seqUpdate": integer, "settings": array }

Field	Type	Required	Description
count	integer	Yes	Number of messenger items returned in this response
items	array[MessengerItem]	Yes	Array of messenger message objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	array	Yes	Settings array (usually empty)

MessengerItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the message (SHA-1 hash)
message	string	Yes	Message content
messageId	integer	Yes	Telegram message ID
messageTs	string	Yes	ISO 8601 timestamp when the message was sent

Field	Type	Required	Description
lastEditTs	string	Yes	ISO 8601 timestamp when the message was last edited
isReply	boolean	Yes	Whether this is a reply message
repliedMessage	object | null	No	Replied message object
name	string	Yes	Chat/channel name
translatedMessage	string	Yes	Translated message (can be empty string)
seqUpdate	integer	Yes	Sequence update number for this specific item
author	AuthorObject	Yes	Author object
chatStat	ChatStatObject	Yes	Chat statistics object
highlight	object | null	No	Highlight object
selected	boolean	Yes	Whether the message is selected
edits	array[EditObject] | null	No	Array of edit objects
deleted	string	Yes	Deletion information (can be empty string)
media	MediaObject	Yes	Media object

AuthorObject Object

Field	Type	Required	Description
id	integer	Yes	Author user ID
userName	string	Yes	Author username (can be empty string)

Field	Type	Required	Description
avatar	object | null	No	Avatar object
type	string	Yes	Author type (e.g., “user”, “bot”)
firstName	string	Yes	First name (can be empty string)
lastName	string	Yes	Last name (can be empty string)

ChatStatObject Object

Field	Type	Required	Description
id	integer	Yes	Chat/channel ID
name	string	Yes	Chat/channel name
title	string	Yes	Chat/channel title
type	string	Yes	Chat type (e.g., “supergroup”, “channel”)
about	array[AboutObject]	Yes	Array of about objects
avatar	AvatarObject	Yes	Avatar object
firstMessageDate	string	Yes	ISO 8601 timestamp of the first message
lastMessageDate	string	Yes	ISO 8601 timestamp of the last message
messageNum	integer	Yes	Total number of messages
userNum	integer	Yes	Number of users

AboutObject Object

Field	Type	Required	Description
value	string	Yes	About text value
detected_date	string	Yes	Date when the about was detected

AvatarObject Object

Field	Type	Required	Description
id	integer | null	No	Avatar ID
sha256	string	Yes	SHA-256 hash of the avatar
detected_date	string	Yes	Date when the avatar was detected

EditObject Object

Field	Type	Required	Description
message	string	Yes	Edited message content
detected_date	string	Yes	Date when the edit was detected
message_translated	string	Yes	Translated edited message (can be empty string)

MediaObject Object

Field	Type	Required	Description
name	string	Yes	Media file name (can be empty string)
type	string	Yes	Media type (can be empty string)
size	integer	Yes	Media file size in bytes

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/messenger/updated?seqUpdate=0&limit=100' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)


```
{   "items": [     {       "id": "49d0aedd8eecac841b05357108d49613",       "message": "Card -> 5555555555555557|06|29|420\n\nBIN->  555555\nBrand-> MASTERCARD\nType-> DEBIT\nLevel-> PREPAID\nBank-> CIAGROUP\nPhone-> ------\nFlag-> BR\nCurrency-> BRL\nCountry-> BRAZIL (BR)",       "messageId": 2351042,       "isReply": false,       "repliedMessage": null,       "messageTs": "2024-10-16T05:19:02+03:00",       "lastEditTs": "0001-01-01T00:00:00Z",       "name": "RevyDrops",       "translatedMessage": "",       "chatStat": {         "id": -1001692680982,         "name": "RevyDrops",         "title": "Revy Drops",         "about": [           {             "value": "",             "detected_date": "2024-08-15 15:12:48"           }         ],         "type": "supergroup",         "avatar": {           "id": null,           "sha256": "1494923bf27455a3fd3f36f18b158fe1e4e67af1cfd20592fee6ad3f6cfe475f",           "detected_date": "2024-08-15 15:13:26"         },         "firstMessageDate": "2023-02-18T03:31:30+03:00",         "lastMessageDate": "2024-10-23T08:37:58+03:00",         "messageNum": 1782175,         "userNum": 0       },       "author": {         "id": 5011192745,         "userName": "AkenoBaby",         "avatar": null,         "type": "user",         "firstName": "i am just a birmd",         "lastName": ""       },       "highlight": null,       "selected": false,       "edits": null,       "deleted": "",       "media": {         "name": "",         "type": "",         "size": 0       },       "seqUpdate": 1729505868852513     }   ],   "count": 5501,   "settings": [],   "seqUpdate": 1729506374088157 }
```

Darkweb - Shops

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information from shops and marketplaces on compromised access. This collection displays the freshest information about compromised data from various darkweb marketplaces. Most often it is credentials, cookies, cards and so on. The information obtained from this collection can help detect relevant threats that compromise company employees, customers or systems on the internal network.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/access/updated
Collection	compromised/access
Collection Name	Shops
Module	Darkweb
Submodule	Shops
Type	Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	A2
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Information about compromised data from various darkweb marketplaces.

Request

Request URL

GET /api/v2/compromised/access/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  .

Maximum value: 500 for compromised/access/updated collection

- If not specified, defaults to 500
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to compromised/account_group/updated, containing compromised access credentials for shops and marketplaces. The schema includes account information, service details, events, and evaluation data.

Root Object
{ "count": integer, "items": [AccessItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of access items returned in this response
items	array[AccessItem]	Yes	Array of access objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

AccessItem Object

The structure is similar to AccountGroupItem from compromised/account_group/updated, containing login, password, service information, events, and evaluation data specific to shop/marketplace access.

Example Request

Basic Request
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/access/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Example Response

Success Response (200 OK)

The response structure is similar to compromised/account_group/updated, with items containing compromised access credentials for shops and marketplaces.

{ "count": 1000000, "items": [{ "id": "example_id_hash", "login": "examplelogin", "password": "password123", "dateFirstSeen": "2013-05-21T00:00:00+00:00", "dateLastSeen": "2013-05-21T00:00:00+00:00", "service": { "domain": "example-shop.com", "url": "http://example-shop.com/", "host": "example-shop.com" }, "events": [], "evaluation": { "admiraltyCode": "A2", "credibility": 80, "reliability": 100, "severity": "red", "tlp": "red", "ttl": 30 }, "seqUpdate": 1450014347005000 }], "seqUpdate": 1450014347019000 }

Darkweb - Forums

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides posts collected from monitored cybercrime and general underground forums. Each record represents a single forum post and includes the message text, the topic/thread it belongs to, the forum and board where it was published, the author's nickname, and a set of topic tags. Posts may reference bank/personal credentials, stolen data, access offers, tools, and mentions of companies that are being targeted or have already been attacked. This information supports monitoring, early warning, and investigation of activity discussed on underground forums.

This is an intelligence and monitoring collection. Records do not include an evaluation block, so no Admiralty Code, TLP, severity, or credibility values are returned for this collection.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/darkweb/forums/updated
Collection	darkweb/forums
Collection Name	Forums
Module	Darkweb
Submodule	Forums
Type	Individual
TTL (Days)	None (not provided in API)
Admiralty Code	None
Severity	N/A
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Posts collected from monitored cybercrime and general underground forums.

Request

Request URL
GET /api/v2/darkweb/forums/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1729505868852513
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:7901bb2b1400734126168ab9bacc28bc

Query Parameter Details:

- seqUpdate:

  .

Each row in the database has its own unique sequence update number

- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:

  - Maximum value: 100 for darkweb/forums/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Note: This is a high-volume collection. To keep results focused, narrow your requests using the search query (for example, by forum, categories, or specific keywords) rather than retrieving the full feed.

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [ForumItem], "seqUpdate": integer, "settings": array }

Field	Type	Required	Description
count	integer	Yes	Number of forum items returned in this response
items	array[ForumItem]	Yes	Array of forum post objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	array	Yes	Settings array (usually empty)

ForumItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the post
message	string	Yes	Post content. May contain sensitive data such as credentials, card data, or personal information (see Data Sensitivity below)

Field	Type	Required	Description
message_hash	string	Yes	Hash of the post content
message_len	integer	Yes	Length of the post content
message_lang	string | null	No	Detected language of the message
topic	string	Yes	Title of the thread the post belongs to
topicHash	string	Yes	Hash of the topic title
topic_info	object | null	No	Additional information about the topic
thread_id	string	Yes	Identifier of the thread
first_post	boolean	Yes	Whether this post is the opening post of the thread
forum	string	Yes	Forum host where the post was published (e.g., “breachforums.vc”)
forum_path_tree	array[string]	Yes	Board/section path within the forum
domain	string	Yes	Forum domain
url	string	Yes	URL of the post
nickname	string	Yes	Author’s handle (pseudonymous)
nicknameUrl	string	No	URL to the author’s profile (can be empty string)
categories	array[string]	Yes	Topic tags assigned to the post (e.g., “Domain”, “Bank”, “Credit card”, “Sale”, “Logs”, “Access”)
lang	array[string]	Yes	Detected language(s) of the post

Field	Type	Required	Description
datetime	string	Yes	ISO 8601 timestamp when the post was published
uploadTime	string	Yes	ISO 8601 timestamp when the post was ingested
updateDatetimeAlert	string | null	No	ISO 8601 timestamp of the latest update alert
isFavorite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden
ocr_analyser	object | null	No	Text recognized from images attached to the post
seqUpdate	integer	Yes	Sequence update number for this specific item

Note: This collection does not return an evaluation object. No Admiralty Code, TLP, severity, credibility, or reliability values are provided for forum posts.

Data Sensitivity

The message field contains raw post content and may include credentials, payment card data, or other personal information. Handle, mask, and store this data in accordance with your data-protection requirements, and do not add victim data to threat-intelligence watchlists or blocklists. Treat matches as analyst leads for investigation.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/darkweb/forums/updated?seqUpdate=0&limit=100' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 254320, "items": [{ "id": "7901bb2b1400734126168ab9bacc28bc", "message": "Selling access to example-company.com admin panel. DM for price.", "message_hash": "3d2a1f9c4b7e08d5a6c1e2f3b4a5d6c7", "message_len": 62, "message_lang": "en", "topic": "Access for sale", "topicHash": "a1b2c3d4e5f60718293a4b5c6d7e8f90", "topic_info": null, "thread_id": "1048576", "first_post": true, "forum": "example-forum.tld", "forum_path_tree": ["Marketplace", "Access"], "domain": "example-forum.tld", "url": "https://example-forum.tld/threads/1048576/post-1", "nickname": "example_seller", "nicknameUrl": "", "categories": ["Access", "Sale", "Domain"], "lang": ["en"], "datetime": "2026-05-25T14:03:21+03:00", "uploadTime": "2026-05-25T14:20:10+03:00", "updateDatetimeAlert": null, "isFavorite": false, "isHidden": false, "ocr_analyser": null, "seqUpdate": 1779670773451213 }], "settings": [], "seqUpdate": 1779670773451850 }

Compromises - Account

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on compromised accounts. Hackers use phishing websites and malware to steal logins and passwords. These can be credentials for the internal corporate systems or external services for clients. Malicious programs transfer the intercepted data to attacker-controlled remote servers. This server is the central data collection point for intercepted passwords and other information that malware gathers. All data is distributed into the following groups service, host, login and password.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/account_group/updated
Collection	compromised/account_group
Collection Name	Compromised Accounts
Module	Compromises
Submodule	Accounts
Type	Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	A2
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Credentials collected from various phishing resources, botnets, C&C servers, and drop email accounts used by hackers.

Request

Request URL

GET /api/v2/compromised/account_group/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Parameter	Type	Required	Default	Description	Example
unique	integer	No	0	Filter for unique credentials. Set to 1 to return only unique credentials. Note: 0 is interpreted as “parameter not provided” for backward compatibility.	1
combolist	integer	No	0	Filter for combo-list credentials. Set to 1 to return only combo-list credentials. Note: 0 is interpreted as “parameter not provided” for backward compatibility.	1
probable_corporate_access	integer	No	0	Filter for probable corporate access credentials. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 500 for compromised/account_group/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types
- unique and combolist:
  -

unique=1&combolist=0 -> only unique credentials

- unique=0&combolist=1 -> only combo-list credentials
- unique=1&combolist=1 (or omit both) -> all credentials
- Note: 0 is interpreted as “parameter not provided” for backward compatibility, so unique=0&combolist=0 and unique=1&combolist=1 both return all records

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [AccountGroupItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of account group items returned in this response
items	array[AccountGroupItem]	Yes	Array of account group objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

AccountGroupItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the account group (SHA-1 hash)
login	string	Yes	Login/username
password	string	Yes	Password
dateFirstSeen	string	Yes	ISO 8601 timestamp when the account was first seen
dateLastSeen	string	Yes	ISO 8601 timestamp when the account was last seen
dateFirstCompromised	string | null	No	ISO 8601 timestamp when the account was first compromised

Field	Type	Required	Description
dateLastCompromised	string | null	No	ISO 8601 timestamp when the account was last compromised
port	integer | null	No	Port number
seqUpdate	integer	Yes	Sequence update number for this specific item
parsedLogin	ParsedLogin	Yes	Parsed login object
service	ServiceObject	Yes	Service object (where the credentials were used)
events	array[EventObject]	Yes	Array of event objects
eventCount	integer	Yes	Number of events associated with this account
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	DisplayOptions	Yes	Display options object
malware	array	Yes	Array of malware references
threatActor	array	Yes	Array of threat actor references
source	array	Yes	Array of source identifiers
sourceType	array	Yes	Array of source type strings
sourceId	array	Yes	Array of source IDs
silentInsert	object | null	No	Silent insert object

ParsedLogin Object

Field	Type	Required	Description
domain	string | null	No	Domain extracted from login
ip	string | null	No	IP address extracted from login

ServiceObject Object

Field	Type	Required	Description
domain	string	Yes	Service domain name
ip	string | null	No	Service IP address
url	string	Yes	Service URL
host	string	Yes	Service host

EventObject Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the event (SHA-1 hash)
oldId	string	Yes	Previous identifier (if migrated)
stixGuid	string	Yes	STIX GUID
cnc	CncObject	Yes	Command and control server object
client	ClientObject	Yes	Client object (victim information)
source	SourceObject	Yes	Source object
person	object | null	No	Person object
malware	object | null	No	Malware object

Field	Type	Required	Description
threatActor	object | null	No	Threat actor object
dateDetected	string	Yes	ISO 8601 timestamp when the event was detected
dateCompromised	string | null	No	ISO 8601 timestamp when the account was compromised
additionalData	object | null	No	Additional data object

CncObject Object

Field	Type	Required	Description
cnc	string	Yes	Command and control server identifier (can be empty string)
domain	string | null	No	Domain name
ipv4	IPv4Object | null	No	IPv4 address object
ipv6	IPv6Object | null	No	IPv6 address object
url	string | null	No	URL

ClientObject Object

Field	Type	Required	Description
ipv4	IPv4Object | null	No	IPv4 address object of the client/victim
ipv6	IPv6Object | null	No	IPv6 address object of the client/victim

IPv4Object Object

Field	Type	Required	Description
ip	string	Yes	IPv4 address
countryCode	string | null	No	Country code (ISO 3166-1 alpha-2)
countryName	string | null	No	Country name
city	string | null	No	City name
region	string | null	No	Region name
provider	string | null	No	ISP/provider name
asn	string | null	No	ASN number

SourceObject Object

Field	Type	Required	Description
id	string	Yes	Source ID (can be empty string)
type	string	Yes	Source type (can be empty string)
idType	string	Yes	Source ID type (can be empty string)

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “A2”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)

Field	Type	Required	Description
severity	string	Yes	Severity level (e.g., “red”, “orange”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “red”, “amber”, “green”, “white”)
ttl	integer	Yes	Time to live in days

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden
favouriteForCompanies	array	Yes	Array of company IDs that marked this as favourite
hideForCompanies	array	Yes	Array of company IDs that hid this item

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/account_group/updated?seqUpdate=0&limit=500' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Unique Credentials Filter

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/account_group/updated?seqUpdate=0&limit=500&unique=1&combolist=0' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 630118817, "items": [{ "id": "96339c2618783a2ffd3fe3f0e855bc63b4890688", "dateFirstSeen": "2013-05-21T00:00:00+00:00", "dateLastSeen": "2013-05-21T00:00:00+00:00", "dateFirstCompromised": null, "dateLastCompromised": null, "port": null, "login": "examplelogin", "password": "123456789", "parsedLogin": { "domain": null, "ip": null }, "service": { "domain": "example.example.corp", "ip": null, "url": "http://example.example.corp/", "host": "example.example.corp" }, "events": [{ "id": "63b797f8b9924391d6669f55b80bbb43f1a7f285", "oldId": "6285", "stixGuid": "1db49a6a-4844-4d80-d2a6-e990a14bcba2", "cnc": { "cnc": "", "domain": null, "ipv4": null, "ipv6": null, "url": null }, "client": { "ipv4": { "asn": "AS2854", "city": "Moscow", "region": "Europe", "provider": "LLC Orange Business Services", "countryCode": "RU", "countryName": "Russian Federation", "ip": "192.168.0.1" }, "ipv6": null }, "source": { "id": "", "type": "", "idType": "" }, "person": null, "malware": null, "threatActor": null, "dateDetected": "2013-05-21T00:00:00+00:00", "dateCompromised": null, "additionalData": null }], "eventCount": 1, "silentInsert": null, "evaluation": { "admiraltyCode": "A2", "credibility": 80, "reliability": 100, "severity": "red", "tlp": "red", "ttl": 30 }, "seqUpdate": 1450014347005000, "displayOptions": { "favouriteForCompanies": [], "hideForCompanies": [], "isHidden": false, "isFavourite": false }, "malware": [], "threatActor": [], "source": [], "sourceType": [], "sourceId": [] }], "settings": { "search": { "tags": ["victim_country", "service_domain", "login", "threat_actor", "malware", "source", "id"], "fields": ["login", "service_domain", "victim_ip", "threat_actor", "malware", "source", "id"], "sorts": ["first_seen", "last_seen", "seqUpdate"] } }, "seqUpdate": 1450014347019000 }

Compromises - Git Repository

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on GIT repository leaks. This collection monitors open-source code repositories, like GitHub, for sensitive client-related information such as domain names, IP addresses, API tokens or credentials. They are often used by threat actors planning to attack a specific company. Alerts clients of any findings and provides detailed leak information, including data type and affected files.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/osi/git_repository/updated
Collection	osi/git_repository
Collection Name	GIT Repository Leaks
Module	Compromises
Submodule	GIT Leaks
Type	Individual
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A1
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Sensitive information leaked in open-source code repositories like GitHub.

Request

Request URL

GET /api/v2/osi/git_repository/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  .

Maximum value: 500 for osi/git_repository/updated collection

- If not specified, defaults to 500
- The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to osi/public_leak/updated, containing GIT repository leak information with repository details, file information, and detected sensitive data.

Root Object
{ "count": integer, "items": [GitRepositoryItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of GIT repository items returned in this response
items	array[GitRepository Item]	Yes	Array of GIT repository leak objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

GitRepositoryItem Object

The structure contains repository information including repository URL, file paths, detected sensitive data (credentials, API keys, domains, IPs), and metadata.

Example Request

Basic Request
curl -X GET 'https://tap.group-ib.com/api/v2/osi/git_repository/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Example Response

Success Response (200 OK)

The response structure is similar to osi/public_leak/updated, with items containing GIT repository leak information.
{ "count": 100000, "items": [{ "id": "example_id_hash", "repository": "https://github.com/example/repo", "file": "config/database.yml", "dateFirstSeen": "2023-05-21T00:00:00+00:00", "dateLastSeen": "2023-05-21T00:00:00+00:00", "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "severity": "red", "tlp": "amber", "ttl": 30 }, "seqUpdate": 1450014347005000 }], "seqUpdate": 1450014347019000 }

Compromises - Public Leak

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on public leaks. There are specialized websites for exchanging textual information (such as Pastebin and analogous resources). They can be used to upload texts and send anyone a link to them. Both legitimate IT specialists and hackers actively use such resources. IT professionals may underestimate the risks and load configuration files for network equipment, export tables from databases, code fragments containing access credentials, and much more. Hackers mainly post lists of usernames, passwords, bank card details, Trojan configuration files, attack outcomes, and various logs.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/osi/public_leak/updated
Collection	osi/public_leak
Collection Name	Public Leaks
Module	Compromises
Submodule	Public leaks
Type	Individual
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	C3
Severity	N/A
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Textual information leaked on public paste sites, including credentials, configuration files, and sensitive data.

Request

Request URL

GET /api/v2/osi/public_leak/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	16202106434186
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:0083e0516cac929a5f5267f8f5ebebb77063f235

Query Parameter Details:

- seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 100 for osi/public_leak/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output

- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [PublicLeakItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of public leak items returned in this response
items	array[PublicLeakItem]	Yes	Array of public leak objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

PublicLeakItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the leak (SHA-1 hash)
hash	string	Yes	Hash of the leak content (SHA-1)
data	string	Yes	Leaked data content

Field	Type	Required	Description
language	string	Yes	Programming language or file type (e.g., “xml”, “java”, “text”)
created	string	Yes	ISO 8601 timestamp when the leak was created
updated	string	Yes	ISO 8601 timestamp when the leak was last updated
seqUpdate	integer	Yes	Sequence update number for this specific item
bind	array	Yes	Array of bind objects
linkList	array[LinkObject]	Yes	Array of link objects (sources where the leak was found)
matches	MatchesObject	Yes	Matches object containing detected sensitive information
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	DisplayOptions	Yes	Display options object

LinkObject Object

Field	Type	Required	Description
link	string	Yes	URL to the leak
hash	string	Yes	Hash of the link content (SHA-1)
source	string	Yes	Source name (e.g., “pastebin.com”)
author	string	Yes	Author name (can be empty string)

Field	Type	Required	Description
title	string	Yes	Title (can be empty string)
dateDetected	string	Yes	ISO 8601 timestamp when the link was detected
datePublished	string	Yes	ISO 8601 timestamp when the link was published
itemSource	string	Yes	Item source identifier
size	integer	Yes	Size of the content in bytes
status	integer	Yes	Status code
sequenceUpdate	integer	Yes	Sequence update number for this link

MatchesObject Object

Field	Type	Required	Description
commonKeywords	object	Yes	Object containing common keywords found (e.g., password, api_key)
email	object | null	No	Object containing email addresses found

Evaluation Object

Field	Type	Required	Description
admiralty_code	string	Yes	Admiralty Code (e.g., “C3”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)

Field	Type	Required	Description
severity	string	Yes	Severity level (e.g., “green”, “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/osi/public_leak/updated?seqUpdate=0&limit=100' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 24353999, "items": [{ "bind": [], "created": "2022-05-05T20:26:25+03:00", "data": "networks:\r\n default:\r\n name: datahub_network\r\nservices:\r\n broker:\r\n container_name: broker\r\n depends_on:\r\n - zookeeper\r\n environment:\r\n - KAFKA_BROKER_ID=1\r\n - KAFKA_ZOOKEEPER_CONNECT=zookeeper:2181\r\n - KAFKA_LISTENER_SECURITY_PROTOCOL_MAP=PLAINTEXT:PLAINTEXT,PLAINTEXT_HOST:PLAINTEXT\r\n - KAFKA_ADVERTISED_LISTENERS=PLAINTEXT://broker:29092,PLAINTEXT_HOST://localhost:9092\r\n - KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR=1\r\n - KAFKA_GROUP_INITIAL_REBALANCE_DELAY_MS=0\r\n - KAFKA_HEAP_OPTS=-Xms256m -Xmx256m\r\n hostname: broker\r\n image: confluentinc/cp-kafka:5.4.0\r\n ports:\r\n - 29092:29092\r\n - 9092:9092\r\n datahub-actions:\r\n depends_on:\r\n - datahub-gms\r\n environment:\r\n - GMS_HOST=datahub-gms\r\n - GMS_PORT=8080\r\n - KAFKA_BOOTSTRAP_SERVER=broker:29092\r\n - SCHEMA_REGISTRY_URL=http://schema-registry:8081\r\n - METADATA_AUDIT_EVENT_NAME=MetadataAuditEvent_v4\r\n - METADATA_CHANGE_LOG_VERSIONED_TOPIC_NAME=MetadataChangeLog_Versioned_v1\r\n - DATAHUB_SYSTEM_CLIENT_ID=__datahub_system\r\n - DATAHUB_SYSTEM_CLIENT_SECRET=JohnSnowKnowsNothing\r\n - KAFKA_PROPERTIES_SECURITY_PROTOCOL=PLAINTEXT\r\n hostname: actions\r\n image: public.ecr.aws/datahub/acryl-datahub-actions:${ACTIONS_VERSION:-head}\r\n restart: on-failure:5\r\n datahub-frontend-react:\r\n container_name: datahub-frontend-react\r\n depends_on:\r\n - datahub-gms\r\n environment:\r\n - DATAHUB_GMS_HOST=datahub-gms\r\n - DATAHUB_GMS_PORT=8080\r\n - DATAHUB_SECRET=YouKnowNothing\r\n - DATAHUB_APP_VERSION=1.0\r\n - DATAHUB_PLAY_MEM_BUFFER_SIZE=10MB\r\n - JAVA_OPTS=-Xms512m -Xmx512m -Dhttp.port=9002 -Dconfig.file=datahub-frontend/conf/application.conf -Djava.security.auth.login.config=datahub-frontend/conf/jaas.conf -Dlogback.configurationFile=datahub-frontend/conf/logback.xml -Dlogback.debug=false -Dpidfile.path=/dev/null\r\n - KAFKA_BOOTSTRAP_SERVER=broker:29092\r\n - DATAHUB_TRACKING_TOPIC=DataHubUsageEvent_v1\r\n - ELASTIC_CLIENT_HOST=elasticsearch\r\n - ELASTIC_CLIENT_PORT=9200\r\n - AUTH_OIDC_ENABLED=true\r\n - AUTH_OIDC_CLIENT_ID=${DATAHUB_IAM_ID}\r\n - AUTH_OIDC_CLIENT_SECRET=${DATAHUB_IAM_SECRET}\r\n - AUTH_OIDC_DISCOVERY_URI=${DATAHUB_IAM_URI}\r\n - AUTH_OIDC_BASE_URL=${DATAHUB_URL}\r\n #- AUTH_OIDC_SCOPE=\\\"\\\"\r\n - METADATA_SERVICE_AUTH_ENABLED=true\r\n hostname: datahub-frontend-react\r\n image:

linkedin/datahub-frontend-react:${DATAHUB_VERSION:-head}\r\n ports:\r\n - 9002:9002\r\n volumes:\r\n - ${HOME}/.datahub/plugins:/etc/datahub/plugins\r\n - ${HOME}/.datahub/plugins/frontend/auth/user.props:/datahub-frontend/conf/user.props\r\n datahub-gms:\r\n container_name: datahub-gms\r\n depends_on:\r\n - mysql\r\n environment:\r\n - DATASET_ENABLE_SCSI=false\r\n - EBEAN_DATASOURCE_USERNAME=datahub\r\n - EBEAN_DATASOURCE_PASSWORD=datahub\r\n - EBEAN_DATASOURCE_HOST=mysql:3306\r\n - EBEAN_DATASOURCE_URL=jdbc:mysql://mysql:3306/datahub?verifyServerCertificate=false&useSSL=true&useUnicode=yes&characterEncoding=UTF-8\r\n - EBEAN_DATASOURCE_DRIVER=com.mysql.jdbc.Driver\r\n - KAFKA_BOOTSTRAP_SERVER=broker:29092\r\n - KAFKA_SCHEMAREGISTRY_URL=http://schema-registry:8081\r\n - ELASTICSEARCH_HOST=elasticsearch\r\n - ELASTICSEARCH_PORT=9200\r\n - GRAPH_SERVICE_IMPL=elasticsearch\r\n - JAVA_OPTS=-Xms1g -Xmx1g\r\n - ENTITY_REGISTRY_CONFIG_PATH=/datahub/datahub-gms/resources/entity-registry.yml\r\n - MAE_CONSUMER_ENABLED=true\r\n - MCE_CONSUMER_ENABLED=true\r\n - UI_INGESTION_ENABLED=true\r\n - UI_INGESTION_DEFAULT_CLI_VERSION=0.8.26.6\r\n - METADATA_SERVICE_AUTH_ENABLED=true\r\n hostname: datahub-gms\r\n image: linkedin/datahub-gms:${DATAHUB_VERSION:-head}\r\n ports:\r\n - 8080:8080\r\n volumes:\r\n - ${HOME}/.datahub/plugins:/etc/datahub/plugins\r\n elasticsearch:\r\n container_name: elasticsearch\r\n environment:\r\n - discovery.type=single-node\r\n - xpack.security.enabled=false\r\n - ES_JAVA_OPTS=-Xms256m -Xmx256m -Dlog4j2.formatMsgNoLookups=true\r\n healthcheck:\r\n retries: 4\r\n start_period: 2m\r\n test:\r\n - CMD-SHELL\r\n - curl -sS --fail 'http://localhost:9200/_cluster/health?wait_for_status=yellow&timeout=0s' || exit 1\r\n hostname: elasticsearch\r\n image: elasticsearch:7.9.3\r\n mem_limit: 1g\r\n ports:\r\n - 9200:9200\r\n volumes:\r\n - esdata:/usr/share/elasticsearch/data\r\n elasticsearch-setup:\r\n container_name: elasticsearch-setup\r\n depends_on:\r\n - elasticsearch\r\n environment:\r\n - ELASTICSEARCH_HOST=elasticsearch\r\n - ELASTICSEARCH_PORT=9200\r\n - ELASTICSEARCH_PROTOCOL=http\r\n hostname: elasticsearch-setup\r\n image: linkedin/datahub-elasticsearch-setup:${DATAHUB_VERSION:-head}\r\n kafka-setup:\r\n container_name: kafka-setup\r\n depends_on:\r\n - broker\r\n - schema-registry\r\n environment:\r\n - KAFKA_ZOOKEEPER_CONNECT=zookeeper:2181\r\n - KAFKA_BOOTSTRAP_SERVER=broker:29092\r\n hostname: kafka-setup\r\n image: linkedin/datahub-kafka-setup:${DATAHUB_VERSION:-head}\r\n mysql:\r\n command: --character-set-server=utf8mb4 --collation-server=utf8mb4_bin\r\n container_name: mysql\r\n environment:\r\n - MYSQL_DATABASE=datahub\r\n - MYSQL_USER=datahub\r\n - MYSQL_PASSWORD=datahub\r\n - MYSQL_ROOT_PASSWORD=datahub\r\n hostname: mysql\r\n image: mysql:5.7\r\n ports:\r\n - 3306:3306\r\n volumes:\r\n - ../mysql/init.sql:/docker-entrypoint-initdb.d/init.sql\r\n - mysqldata:/var/lib/mysql\r\n mysql-setup:\r\n container_name: mysql-setup\r\n depends_on:\r\n - mysql\r\n environment:\r\n - MYSQL_HOST=mysql\r\n - MYSQL_PORT=3306\r\n - MYSQL_USERNAME=datahub\r\n - MYSQL_PASSWORD=datahub\r\n - DATAHUB_DB_NAME=datahub\r\n hostname: mysql-setup\r\n image: acryldata/datahub-mysql-setup:head\r\n schema-registry:\r\n container_name: schema-registry\r\n depends_on:\r\n - zookeeper\r\n - broker\r\n environment:\r\n - SCHEMA_REGISTRY_HOST_NAME=schemaregistry\r\n - SCHEMA_REGISTRY_KAFKASTORE_CONNECTION_URL=zookeeper:2181\r\n hostname: schema-registry\r\n image: confluentinc/cp-schema-registry:5.4.0\r\n ports:\r\n - 8081:8081\r\n zookeeper:\r\n container_name: zookeeper\r\n environment:\r\n - ZOOKEEPER_CLIENT_PORT=2181\r\n - ZOOKEEPER_TICK_TIME=2000\r\n hostname: zookeeper\r\n image: confluentinc/cp-zookeeper:5.4.0\r\n ports:\r\n - 2181:2181\r\n volumes:\r\n - zkdata:/var/opt/zookeeper\r\nversion: '2.3'\r\nvolumes:\r\n esdata: null\r\n mysqldata: null\r\n zkdata: null\r\n",
"displayOptions": { "isFavourite": false, "isHidden": false },
"evaluation": { "admiralty_code": "C3", "credibility": 50, "reliability": 50, "severity": "green", "tlp": "amber", "ttl": 30 },
"hash": "0083e0516cac929a5f5267f8f5ebebb77063f235", "id": "0083e0516cac929a5f5267f8f5ebebb77063f235", "language": "xml",
"linkList": [{ "author": "", "hash": "024c788fdacdd8b8827de9e50c13ea0e6dde1988", "link": "https://pastebin.com/HPjD9kmj",
"title": "", "source": "pastebin.com", "dateDetected": "2022-05-05T20:26:25+03:00", "datePublished": "2022-05-05T17:16:43+00:00",
"itemSource": "api", "size": 6625, "status": 1, "sequenceUpdate": 1651771585142655 }], "matches": {
"commonKeywords": { "password": ["PASSWORD"] } }, "seqUpdate": -1651773180003874, "updated":
"2022-05-05T20:26:25+03:00" }], "seqUpdate": 16202106434186 }

Compromises - Breached DB

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides credential exposures identified in known breached databases (for example, large aggregated leaks published on hacker forums). Each record ties an exposed email address, and a password when present, to the breach it originated from, along with the breach name, description, publication date, and the source download links. By default, records are matched to your monitored scope, so you receive exposures relevant to your organization. This information supports credential-exposure monitoring, breach investigation, and exposure governance.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/breacheddb/updated
Collection	compromised/breacheddb
Collection Name	Breached DB
Module	Compromises
Submodule	Breached DB
Type	Individual
TTL (Days)	N/A
Admiralty Code	C3
Severity	N/A
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Credential exposures identified in known breached databases matched to your monitored scope.

Request

Request URL

GET /api/v2/compromised/breacheddb/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. For this collection, start iteration at 0 (see the note below). Use the top-level seqUpdate field from the previous response for subsequent requests.	0
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
has_password	integer	No	0	Filter by password presence. Set to 1 to return only records that include a password.	1
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: For this collection, start iteration at seqUpdate=0, then continue with the top-level seqUpdate value returned in each response
  - Unlike most other collections, this collection does not support bootstrapping a cursor from a specific date via /api/v2/sequence_list - a date-based cursor returns an empty result set. Always start at 0.
- limit:
  - Maximum value: 100 for compromised/breacheddb/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output
- has_password:
  - has_password=1 returns only records that include a password
  - If not specified, all matching records are returned regardless of password presence
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)

Header	Type	Required	Description	Example
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [BreachedDbItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of breached DB items returned in this response
items	array[BreachedDbItem]	Yes	Array of breached database exposure objects

Field	Type	Required	Description
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

BreachedDbItem Object

Field	Type	Required	Description
id	array[string]	Yes	Record hash(es) identifying the exposure
leakName	string	Yes	Name of the breach the exposure originated from (e.g., "Collection #2")
description	string	Yes	Description of the breach
leakPublished	string	Yes	ISO 8601 timestamp when the breach was published
authors	array[string]	Yes	Handles of those who published the leak (leak publishers, not victims)
email	string	Yes	Exposed email address (personal data)
password	string | null	No	Exposed password. Present when available; use has_password=1 to return only records that include one
addInfo	object | null	No	Additional leaked fields associated with the record (varies by breach)
downloadLinkList	array[string]	Yes	Links to the source breach data
reaperMessageId	string | null	No	Reference to the source message where the leak was observed

Field	Type	Required	Description
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
uploadTime	string	Yes	ISO 8601 timestamp when the record was ingested
updateTime	string	Yes	ISO 8601 timestamp when the record was last updated

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “C3”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “green”, “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)

Note: The evaluation block is provided per record. Read its values at runtime rather than assuming a fixed value for the whole collection.

Data Sensitivity

Records in this collection contain victim data: email (personal data), password (plaintext when present), and addInfo (additional leaked fields). The downloadLinkList field points to the source breach data. Mask, restrict, and store this data in accordance with your data-protection requirements. Do not add victim email addresses to threat-intelligence watchlists or blocklists - use this data to drive account-protection and incident-response workflows. The authors field lists leak publishers, not victims.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/breacheddb/updated?seqUpdate=0&limit=100' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json'
```

Request with Password Filter

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/breacheddb/updated?seqUpdate=0&limit=100&has_password=1' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 636, "items": [{ "id": ["96339c2618783a2ffd3fe3f0e855bc63b4890688"], "leakName": "Example Collection", "description": "Aggregated credential dump published on an underground forum.", "leakPublished": "2019-01-18T00:00:00", "authors": ["example_author"], "email": "user@example-company.com", "password": "examplePassword", "addInfo": { "registrationDate": "2016-04-02" }, "downloadLinkList": ["https://example-forum.tld/leaks/example-collection"], "reaperMessageId": "3d2a1f9c4b7e08d5a6c1e2f3b4a5d6c7", "evaluation": { "admiraltyCode": "C3", "credibility": 60, "reliability": 60, "severity": "green", "tlp": "amber" }, "uploadTime": "2025-03-14T09:12:00+00:00", "updateTime": "2025-03-14T09:12:00+00:00" }], "seqUpdate": 1780224348744247 }

Banking - Cards

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on compromised bank cards. This includes data collected from card shops, specialized forums, and public sources. All data collected is grouped by card number.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/bank_card_group/updated
Collection	compromised/bank_card_group
Collection Name	Compromised Bank Cards
Module	Banking
Submodule	Bank cards
Type	Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	A2
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Compromised bank card information collected from underground markets, forums, and messaging platforms.

Request

Request URL

GET /api/v2/compromised/bank_card_group/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:

  - Maximum value: 500 for compromised/bank_card_group/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output

- q:

  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to other compromised collections, containing bank card information grouped by card details.

Root Object
{ "count": integer, "items": [BankCardGroupItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of bank card group items returned in this response
items	array[BankCardGroupItem]	Yes	Array of bank card group objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

BankCardGroupItem Object

The structure contains bank card information including card number (masked), expiration date, CVV, BIN, bank information, and associated events/metadata.

Example Request

Basic Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/bank_card_group/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)

The response contains bank card group items with card information and associated metadata.

{ "count": 1000000, "items": [{ "id": "example_id_hash", "dateFirstSeen": "2013-05-21T00:00:00+00:00", "dateLastSeen": "2013-05-21T00:00:00+00:00", "evaluation": { "admiraltyCode": "A2", "credibility": 80, "reliability": 100, "severity": "red", "tlp": "red", "ttl": 30 }, "seqUpdate": 1450014347005000 }], "seqUpdate": 1450014347019000 }

Banking - Masked cards

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on compromised masked bank cards. Masked Card collection contains information about compromised cards. This includes data collected from card shops, specialized forums, and public sources. The main difference from the Compromised Cards collection is that, in most cases, the card details are partially masked.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/masked_card/updated
Collection	compromised/masked_card
Collection Name	Compromised Masked Cards
Module	Banking
Submodule	Bank cards
Type	Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	A2
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Compromised masked bank card information collected from underground markets, forums, and messaging platforms.

Request

Request URL

GET /api/v2/compromised/masked_card/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for compromised/masked_card/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output

- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to compromised/bank_card_group/updated, containing masked bank card information.

Root Object
{ "count": integer, "items": [MaskedCardItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of masked card items returned in this response
items	array[MaskedCardItem]	Yes	Array of masked card objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

MaskedCardItem Object

The structure contains masked bank card information where the card number is partially obscured, along with expiration date, CVV, BIN, bank information, and associated events/metadata.

Example Request

Basic Request
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/masked_card/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Example Response

Success Response (200 OK)

The response contains masked card items with partially obscured card information and associated metadata.

{ "count": 1000000, "items": [{ "id": "example_id_hash", "dateFirstSeen": "2013-05-21T00:00:00+00:00", "dateLastSeen": "2013-05-21T00:00:00+00:00", "evaluation": { "admiraltyCode": "A2", "credibility": 80, "reliability": 100, "severity": "red", "tlp": "red", "ttl": 30 }, "seqUpdate": 1450014347005000 }], "seqUpdate": 1450014347019000 }

Banking - SPD

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on Suspicious Payment Details (SPD). This collection provides a curated feed of payment identifiers that have been linked to laundering operations, ransomware transactions, illegal online casinos, and other forms of illicit financial activity. This data helps anti-fraud and risk teams proactively detect and disrupt suspicious financial flows before damage occurs. SPD replaces the deprecated Mules section, offering improved granularity, new identifier types, and enriched attribution.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/compromised/spd/updated
Collection	compromised/spd
Collection Name	Suspicious Payment Details
Module	Banking
Submodule	Suspicious Payment Details
Type	Individual
TTL (Days)	90 (recommended, not provided in API)
Admiralty Code	A2
Severity	N/A
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
Short Description	Suspicious payment details collected from underground markets, forums, and messaging platforms.

Request

Request URL

GET /api/v2/compromised/spd/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1450014347005000
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
type	string	No	-	Filter records by payment identifier type. Returns only records whose identifier matches the specified type. See the supported values below.	mobileNumber

Parameter	Type	Required	Default	Description	Example
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:96339c2618783a2ffd3fe3f0e855bc63b4890688

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 500 for compromised/spd/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- type:
  - Filters the feed to a single payment identifier type
  - Supported values:
    - bankAccountNumber
    - mobileNumber
    - cryptocurrencyWallet
    - iban
    - bankCard
    - qrPaymentString
    - unknown
  - Example: /api/v2/compromised/spd/updated?seqUpdate=0&limit=500&type=mobileNumber
  - Note: in the response, the type field is returned as a human-readable label (for example, mobileNumber is returned as Mobile Number)
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to other compromised collections, containing special personal data information.

Root Object
{ "count": integer, "items": [SpdItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of SPD items returned in this response
items	array[SpdItem]	Yes	Array of SPD objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

SpdItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the record
type	string	Yes	Payment identifier type as a human-readable label (e.g., "Mobile Number", "Cryptocurrency Wallet", "Bank Account Number", "IBAN", "Bank card", "QR payment string", "Unknown"). Use the type query parameter to filter by these values
serviceType	string | null	No	Additional classification of the identifier (e.g., a cryptocurrency family such as "BTCLike", a bank code, or an e-wallet service name)
ownerName	string | null	No	Name associated with the identifier, when available
illegalScore	integer	Yes	Numeric estimate (0-100) of how likely the identifier is being used for unlawful transactions

Field	Type	Required	Description
value	object	Yes	The payment identifier and related fields (see Value Object below)
events	array[EventObject]	Yes	Occurrences where the identifier was observed (see Event Object below)
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
displayOptions	object	Yes	Display flags (e.g., isFavourite)
malware	array	Yes	Associated malware references
threatActor	array	Yes	Associated threat actor references
tags	array	Yes	Tags associated with the record
sources	array	Yes	Source references
country	array	Yes	Associated country information
createdAt	string	Yes	ISO 8601 timestamp when the record was created in the system
firstSeenAt	string	Yes	ISO 8601 timestamp when the identifier was first seen
lastSeenAt	string	Yes	ISO 8601 timestamp when the identifier was last seen
seqUpdate	integer	Yes	Sequence update number for this specific item

Value Object

Field	Type	Required	Description
value	string	Yes	The payment identifier (e.g., wallet address, phone number, account number)
email	string | null	No	Associated email address, when available
bankCard	string | null	No	Associated bank card number, when available
iban	string | null	No	Associated IBAN, when available

Event Object

Field	Type	Required	Description
compromisedAt	string	Yes	ISO 8601 timestamp when the identifier was compromised
detectedAt	string	Yes	ISO 8601 timestamp when the identifier was detected
source	object | null	No	Source of the record (name, type)
malware	array	Yes	Malware associated with this event
threatActor	array	Yes	Threat actors associated with this event
tags	array	Yes	Tags associated with this event
illegalScore	integer	Yes	Illegal score for this event (0-100)

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “A2”)
credibility	integer	Yes	Credibility score (0-100)

Field	Type	Required	Description
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “red”, “orange”, “green”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/spd/updated?seqUpdate=0&limit=500' \  -u "$GIB_CREDENTIALS" \  -H 'Accept: application/json'
```

Request Filtered by Type

```
curl -X GET 'https://tap.group-ib.com/api/v2/compromised/spd/updated?seqUpdate=0&limit=500&type=mobileNumber' \  -u "$GIB_CREDENTIALS" \ -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)


```
{  "count": 134418,  "seqUpdate": 1751526185843,  "items": [  {  "id": "example_id_hash",  "type": "Cryptocurrency Wallet",  "serviceType": "BTCLike",  "ownerName": null,  "illegalScore": 100,  "displayOptions": {  "isFavourite": false  },  "value": {  "value": "bc1qexampleexampleexampleexampleexamplexxxxx",  "email": null,  "bankCard": null,  "iban": null  },  "events": [  {  "compromisedAt": "2025-04-29T00:00:00Z",  "detectedAt": "2025-04-29T00:00:00Z",  "source": {  "name": "Example Leak",  "type": "Example Leak"  },  "malware": [],  "threatActor": [],  "tags": [],  "illegalScore": 100  }  ],  "seqUpdate": 1751526184752,  "createdAt": "2025-07-03T07:03:04.752Z",  "firstSeenAt": "2025-04-29T00:00:00Z",  "lastSeenAt": "2025-04-29T00:00:00Z",  "evaluation": {  "admiraltyCode": "A2",  "credibility": 80,  "reliability": 100,  "severity": "red",  "tlp": "amber",  "ttl": 30  },  "malware": [],  "threatActor": [],  "tags": [],  "sources": [],  "country": []  }  ] }
```

Suspicious indicators - Deface

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on defacement attacks. Defacement attacks are often conducted by web-hooligans (a form of vandalism) or hacktivists (politically or religiously motivated actors) whose aim is to draw attention to something. After a successful attack, the threat actors publish information on special sites dedicated to defacement, social media, or their personal sites.

The section contains defaced pages along with dynamic content. In the submenu, you can also find aliases, contact details, and the names of the groups involved in the defacement attack.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/attacks/deface/updated
Collection	attacks/deface
Collection Name	Defacement Attacks
Module	Suspicious Indicators
Submodule	Deface
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	B2
Severity	3
Collection Limit	100 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)

Property	Value
IOC Types	Domain, IPv4, URL
Short Description	Information on defaced websites, typically conducted by web-hooligans or hacktivists.

Request

Request URL

GET /api/v2/attacks/deface/updated

Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1508430053029213
limit	integer	No	100	Limit the amount of returned data for this collection. Maximum allowed: 100 for this collection.	100
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:59695fabb1965600014bae7b

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 100 for attacks/deface/updated collection
  - If not specified, defaults to 100
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [DefaceItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of defacement items returned in this response
items	array[DefaceItem]	Yes	Array of defacement objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

DefaceItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the defacement (MongoDB ObjectId)
url	string	Yes	URL of the defaced website
siteUrl	string	Yes	Site URL

Field	Type	Required	Description
targetDomain	string	Yes	Target domain that was defaced
targetDomainProvider	string | null	No	Target domain provider
targetIp	IPObject	Yes	Target IP address object
providerDomain	string	Yes	Provider domain (source of the defacement information)
source	string	Yes	Source identifier
date	string	Yes	ISO 8601 timestamp when the defacement occurred
tsCreate	string	Yes	ISO 8601 timestamp when the record was created
seqUpdate	integer	Yes	Sequence update number for this specific item
threatActor	ThreatActorObject	Yes	Threat actor object
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
contacts	array	Yes	Array of contact objects
mirrorLink	string	Yes	Link to mirror of the defaced page
portalLink	string	Yes	Link to the defacement in the portal

IPObject Object

Field	Type	Required	Description
ip	string	Yes	IP address

Field	Type	Required	Description
countryCode	string	Yes	Country code (ISO 3166-1 alpha-2)
countryName	string	Yes	Country name
city	string | null	No	City name
region	string	Yes	Region name
provider	string	Yes	ISP/provider name
asn	string	Yes	ASN number

ThreatActorObject Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the threat actor (SHA-1 hash)
name	string	Yes	Name of the threat actor
country	string | null	No	Country code (ISO 3166-1 alpha-2)
isAPT	boolean	Yes	Whether this is an APT group (typically false for defacement)
stixGuid	string | null	No	STIX GUID

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “B2”)
credibility	integer	Yes	Credibility score (0-100)

Field	Type	Required	Description
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/deface/updated?seqUpdate=0&limit=100' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 17197503, "items": [{ "contacts": [], "date": "2016-04-26T05:42:48Z", "evaluation": { "admiraltyCode": "B2", "credibility": 80, "reliability": 80, "severity": "orange", "tlp": "amber", "ttl": 30 }, "id": "59695fabb1965600014bae7b", "mirrorLink": "https://deface.ti-files.com/id:-59695fabb1965600014bae7b:", "portalLink": "https://tap-stage.ci-kuber.gibdev.net/attacks/deface?searchValue=id:59695fabb1965600014bae7b", "providerDomain": "defacer.id", "seqUpdate": 1508430053029213, "siteUrl": "http://med-supplies.de/?sky008", "source": "defacer.id", "targetDomain": "med-supplies.de", "targetDomainProvider": null, "targetIp": { "asn": "AS25504", "city": null, "countryCode": "DE", "countryName": "Germany", "ip": "89.200.168.133", "provider": "Vautron Rechenzentrum AG", "region": "Europe" }, "threatActor": { "country": null, "id": "9c94863e3602876b5e0150a7cbb926dda6556e03", "isAPT": false, "name": "Sky008", "stixGuid": null }, "tsCreate": "2016-04-26T05:42:48Z", "url": "http://med-supplies.de/?sky008" }], "seqUpdate": 1508430053049467 }

Suspicious indicators - DDoS

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on DDoS (Distributed Denial of Service) attacks. An attack that creates a load on the server and is executed simultaneously from a large number of computers (often a network of infected zombie computers is used) in order to create an artificial increase in requests to a resource and thereby disable it. The data is replenished and updated in real time. IOCs are included, as well as DDoS victim IPs.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/attacks/ddos/updated
Collection	attacks/ddos
Collection Name	DDoS Attacks
Module	Suspicious Indicators
Submodule	DDoS
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A2
Severity	3
Collection Limit	5000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL

Property	Value
Short Description	Information on DDoS attacks.

Note: We do not recommend using victim IPs as IOCs because it can lead to many false positives. However, CNC data can still be used for detection and blocking depending on your use cases.

Request

Request URL
GET /api/v2/attacks/ddos/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1677065083
limit	integer	No	5000	Limit the amount of returned data for this collection. Maximum allowed: 5000 for this collection.	5000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:7927ec532db08b2e420b33cff2a9068ca8487e76
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

- seqUpdate:
  - Each row in the database has its own unique sequence update number
  - Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
  - Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date
- limit:
  - Maximum value: 5000 for attacks/ddos/updated collection
  - If not specified, defaults to 5000
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [DdosItem], "seqUpdate": integer, "settings": object }

Field	Type	Required	Description
count	integer	Yes	Number of DDoS attack items returned in this response
items	array[DdosItem]	Yes	Array of DDoS attack objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds
settings	object	Yes	Search settings object (contains search configuration)

DdosItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the DDoS attack (SHA-1 hash)

Field	Type	Required	Description
cnc	CncObject	Yes	Command and control server object
target	TargetObject	Yes	Target object (the attacked server)
dateBegin	string	Yes	ISO 8601 timestamp when the attack began
dateEnd	string	Yes	ISO 8601 timestamp when the attack ended
dateReg	string	Yes	ISO 8601 timestamp when the attack was registered
duration	integer	Yes	Duration of the attack in seconds
protocol	string	Yes	Protocol used in the attack (e.g., “udp”, “tcp”)
type	string	Yes	Type of DDoS attack (e.g., “DNS Reflection”)
seqUpdate	integer	Yes	Sequence update number for this specific item
source	string	Yes	Source of the attack data
sourceRowId	string	Yes	Source row identifier
oldId	string | null	No	Previous identifier (if migrated)
stixGuid	string | null	No	STIX GUID
malware	object | null	No	Associated malware object
threatActor	object | null	No	Associated threat actor object
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
requestData	RequestData	Yes	Request data object

Field	Type	Required	Description
messageLink	string | null	No	Link to message
displayOptions	DisplayOptions	Yes	Display options object

CncObject Object

Field	Type	Required	Description
cnc	string	Yes	Command and control server identifier
domain	string | null	No	Domain name
ipv4	IPv4Object | null	No	IPv4 address object
ipv6	IPv6Object | null	No	IPv6 address object
url	string | null	No	URL
port	integer | null	No	Port number

TargetObject Object

Field	Type	Required	Description
ipv4	IPv4Object | null	No	IPv4 address object of the target
domain	string | null	No	Domain name of the target
url	string | null	No	URL of the target
port	integer	Yes	Port number of the target
category	string | null	No	Category of the target

Field	Type	Required	Description
domainsCount	integer	Yes	Number of domains associated with the target

IPv4Object Object

Field	Type	Required	Description
ip	string	Yes	IPv4 address
countryCode	string | null	No	Country code (ISO 3166-1 alpha-2)
countryName	string | null	No	Country name
city	string | null	No	City name
region	string | null	No	Region name
provider	string | null	No	ISP/provider name
asn	string | null	No	ASN number

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “C2”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “green”, “amber”, “red”, “white”)

Field	Type	Required	Description
ttl	integer	Yes	Time to live in days

RequestData Object

Field	Type	Required	Description
link	string | null	No	Link to request data
headers	object	Yes	HTTP headers object
headersHash	string | null	No	Hash of headers
body	string | null	No	Request body
bodyHash	string | null	No	Hash of request body

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/ddos/updated?seqUpdate=0&limit=5000' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/ddos/updated?seqUpdate=0&limit=5000&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 44739317, "items": [{ "id": "7927ec532db08b2e420b33cff2a9068ca8487e76", "cnc": { "cnc": "6lxdx.s3.amazonaws.com", "port": null, "domain": "6lxdx.s3.amazonaws.com", "ipv4": null, "ipv6": null, "url": "http://6lxdx.s3.amazonaws.com" }, "dateBegin": "2019-10-23T05:34:25+00:00", "dateEnd": "2019-10-23T05:35:16+00:00", "dateReg": "2019-10-23T00:00:00+00:00", "malware": null, "evaluation": { "admiraltyCode": "C2", "credibility": 70, "reliability": 60, "severity": "orange", "tlp": "green", "ttl": 30 }, "messageLink": null, "oldId": "192868705", "duration": 51, "protocol": "udp", "seqUpdate": 1677065083, "source": "honeypot_logs:1", "sourceRowId": "11054565", "stixGuid": "9232056c-0c7d-21a7-ac4f-a7fa243adc57", "target": { "ipv4": { "asn": null, "city": "Fairfield", "region": "Connecticut", "provider": "Amazon.com", "countryCode": "US", "countryName": "United States", "ip": "3.15.14.164" }, "url": null, "category": null, "domainsCount": 0, "port": 5353, "domain": null }, "threatActor": null, "requestData": { "link": null, "headers": {}, "headersHash": null, "body": null, "bodyHash": null }, "type": "DNS Reflection", "displayOptions": { "isHidden": false, "isFavourite": false } }], "settings": { "search": { "tags": ["target_ip_country_name", "target_category",

"cnc_ip_country_name", "malware", "type", "source", "id"], "fields": ["target_ip", "ip", "target_domain", "domain", "cnc_ip", "malware", "type", "source", "id"], "sorts": ["last_seen", "date_reg", "seqUpdate"] } }, "seqUpdate": 1677065083 }

Suspicious indicators - Open Proxies IP

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on open proxy servers. The Open proxy collection shows information about lists of proxy servers that are publicly available on various Internet resources related to anonymity. In addition, proxy servers may be configured as open proxies intentionally or as a result of misconfiguration or breaches. These records can be used to identify or block connections from and to open proxy servers.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/suspicious_ip/open_proxy/updated
Collection	suspicious_ip/open_proxy
Collection Name	Open Proxy Servers
Module	Suspicious Indicators
Submodule	Open proxy
Type	Common
TTL (Days)	15 (recommended, not provided in API)
Admiralty Code	C3
Severity	3
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	IPv4

Property	Value
Short Description	Open proxy servers identified by the Group-IB TI system.

Request

Request URL
GET /api/v2/suspicious_ip/open_proxy/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1671657409977576
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by IP. Format: "" to search for one specific record.	"188.250.243.135"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for suspicious_ip/open_proxy/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific IP: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to suspicious_ip/vpn/updated, containing open proxy server information with IP addresses, dates, evaluation data, and proxy type information.

Root Object
{ "count": integer, "items": [OpenProxyItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of open proxy items returned in this response
items	array[OpenProxyItem]	Yes	Array of open proxy objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

OpenProxyItem Object

The structure is similar to VpnItem, containing IP address, dates, evaluation data, and open proxy-specific metadata.

Example Request

Basic Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/open_proxy/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Request with Hunting Rules
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/open_proxy/updated?seqUpdate=0&limit=500&apply_hunting_rules=1' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)

The response structure is similar to suspicious_ip/vpn/updated, with items containing open proxy server information.

{ "count": 500000, "items": [{ "id": "188.250.243.135", "dateFirstSeen": "2021-04-22T12:43:38+00:00", "dateLastSeen": "2021-04-22T12:43:38+00:00", "evaluation": { "admiraltyCode": "C3", "credibility": 50, "reliability": 50, "severity": "green", "tlp": "amber", "ttl": 15 }, "seqUpdate": 1671657409977576 }], "seqUpdate": 1671657410005695 }

Suspicious indicators - Phishing

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on phishing URLs. The Phishing displays information about various phishing resources (including sites masqueraded as Google, Microsoft, etc.). Group-IB collects this data with the help of Passive-DNS analysis performed by Managed XDR (ManagedExtended Detection and Response) systems, alerts received by CERT-GIB, tracked SPAM messages, malicious contextual advertising, new domain names, and other valuable data.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/attacks/phishing_group/updated
Collection	attacks/phishing_group
Collection Name	Phishing Groups
Module	Suspicious Indicators
Submodule	Phishing
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A2-A3
Severity	6
Collection Limit	1000 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	Domain, IPv4, URL

Property	Value
Short Description	Information about various phishing resources.

Request

Request URL
GET /api/v2/attacks/phishing_group/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1401373055098642
limit	integer	No	1000	Limit the amount of returned data for this collection. Maximum allowed: 1000 for this collection.	1000
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by ID. Format: id: to search for one specific record.	id:74ee810f703000d318bb144a1307abce9c05abee41465c30303922156e7ed36a
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 1000 for attacks/phishing_group/updated collection
  - If not specified, defaults to 1000
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific entry: q=id:
  - Supports various search types (e.g., ip:8.8.8.8, domain:example.corp)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [PhishingGroupItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of phishing group items returned in this response
items	array[PhishingGroupItem]	Yes	Array of phishing group objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

PhishingGroupItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the phishing group (SHA-256 hash)
brand	string	Yes	Brand name being impersonated
domain	string	Yes	Domain name of the phishing site

Field	Type	Required	Description
domainTitle	string	Yes	Title of the domain
countPhishing	integer	Yes	Number of phishing URLs in this group
seqUpdate	integer	Yes	Sequence update number for this specific item
date	DateObject	Yes	Date object containing various timestamps
domainInfo	DomainInfo	Yes	Domain information object
ip	array[IPObject]	Yes	Array of IP address objects
objective	array[string]	Yes	Array of objective strings (e.g., [“Login harvest”])
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
status	integer	Yes	Status code (1 = active)
falsePositive	boolean	Yes	Whether this is marked as a false positive
whitelist	boolean	Yes	Whether this is whitelisted
groupLifetime	integer	Yes	Group lifetime in seconds
source	array[string]	Yes	Array of source identifiers
signature	SignatureObject	Yes	Signature object
phishingKitArray	array	Yes	Array of phishing kit references
screenshot	ScreenshotObject	Yes	Screenshot object
uniqueTitles	array[TitleObject]	Yes	Array of unique title objects

Field	Type	Required	Description
threatActor	ThreatActorObject	Yes	Threat actor object
phishing	array[PhishingItem]	Yes	Array of individual phishing URL objects
urlListLink	string	Yes	Link to URL list (can be empty string)
displayOptions	DisplayOptions	Yes	Display options object

DateObject Object

Field	Type	Required	Description
added	string	Yes	ISO 8601 timestamp when the group was added
detected	string	Yes	ISO 8601 timestamp when the group was detected
blocked	string	Yes	ISO 8601 timestamp when the group was blocked
updated	string	Yes	ISO 8601 timestamp when the group was last updated
blockedIndexed	string | null	No	ISO 8601 timestamp when the group was blocked and indexed

DomainInfo Object

Field	Type	Required	Description
domain	string	Yes	Domain name
domainPuny	string	Yes	Punycode domain name

Field	Type	Required	Description
tld	string	Yes	Top-level domain
title	string	Yes	Domain title (can be empty string)
category	array	Yes	Array of category strings
registered	string | null	No	Registration date
expirationDate	string | null	No	Expiration date
registrar	string | null	No	Registrar name

IPObject Object

Field	Type	Required	Description
ip	string	Yes	IP address
countryCode	string	Yes	Country code (ISO 3166-1 alpha-2)
countryName	string	Yes	Country name
provider	string	Yes	ISP/provider name

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “C3”, “A2”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “red”, “orange”)

Field	Type	Required	Description
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days (usually 0)

SignatureObject Object

Field	Type	Required	Description
resource	array[string]	Yes	Array of resource signature strings
screen	array[string]	Yes	Array of screen signature strings
manual	array[string]	Yes	Array of manual signature strings

ScreenshotObject Object

Field	Type	Required	Description
pageHtml	FileObject	Yes	HTML page file object
pageScreen	FileObject	Yes	Screenshot file object

FileObject Object

Field	Type	Required	Description
hashSha256	string	Yes	SHA-256 hash of the file
filetype	string	Yes	File type
filename	string	Yes	File name
mime	string	Yes	MIME type

Field	Type	Required	Description
fileHashMd5	string	Yes	MD5 hash (can be empty string)

TitleObject Object

Field	Type	Required	Description
title	string	Yes	Title string
faviconHashes	FaviconHashes	Yes	Favicon hash object

FaviconHashes Object

Field	Type	Required	Description
md5	string	Yes	MD5 hash (can be empty string)
sha1	string	Yes	SHA-1 hash (can be empty string)
sha256	string	Yes	SHA-256 hash (can be empty string)

ThreatActorObject Object

Field	Type	Required	Description
id	string	Yes	Threat actor ID (can be empty string)
name	string	Yes	Threat actor name (can be empty string)
nameIndexed	string	Yes	Indexed threat actor name (can be empty string)
isAPT	boolean	Yes	Whether this is an APT group

PhishingItem Object

Field	Type	Required	Description
id	string	Yes	Unique identifier of the phishing URL (SHA-256 hash)
url	string	Yes	Phishing URL
title	string	Yes	Page title (can be empty string)
date	PhishingDateObject	Yes	Date object for this phishing URL
status	integer	Yes	Status code (1 = active)
objective	array[string]	Yes	Array of objective strings
source	array[string]	Yes	Array of source identifiers
client	object | null	No	Client object
domain	PhishingDomainObject	Yes	Domain object
ip	PhishingIPObject	Yes	IP address object
phishingKit	array	Yes	Array of phishing kit references
screen	ScreenshotObject	Yes	Screenshot object
renderedUrls	array[string]	Yes	Array of rendered URLs

PhishingDateObject Object

Field	Type	Required	Description
added	string	Yes	ISO 8601 timestamp when the URL was added

Field	Type	Required	Description
detected	string	Yes	ISO 8601 timestamp when the URL was detected
blocked	string	Yes	ISO 8601 timestamp when the URL was blocked

PhishingDomainObject Object

Field	Type	Required	Description
domain	string	Yes	Domain name
puny	string	Yes	Punycode domain name
tld	string	Yes	Top-level domain
title	string	Yes	Domain title (can be empty string)
category	array	Yes	Array of category strings
registered	string	Yes	Registration date (can be empty string)
expiration	string	Yes	Expiration date (can be empty string)
registrar	string	Yes	Registrar name (can be empty string)

PhishingIPObject Object

Field	Type	Required	Description
ip	string	Yes	IP address
countryCode	string	Yes	Country code (ISO 3166-1 alpha-2)
countryName	string	Yes	Country name
city	string	Yes	City name (can be empty string)

Field	Type	Required	Description
provider	string	Yes	ISP/provider name

DisplayOptions Object

Field	Type	Required	Description
isFavourite	boolean	Yes	Whether the item is marked as favourite
isHidden	boolean	Yes	Whether the item is hidden

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/phishing_group/updated?seqUpdate=0&limit=1000' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/attacks/phishing_group/updated?seqUpdate=0&limit=1000&apply_hunting_rules=1' \   -u 'LOGIN:API_KEY' \   -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 8439182, "items": [{ "brand": "VKontakte (vk.com)", "countPhishing": 1, "date": { "blocked": "2016-04-27T14:55:20+03:00", "added": "2014-05-29T18:17:35+04:00", "detected": "2014-05-29T18:17:35+04:00", "blockedIndexed": null, "updated": "2020-12-24T04:04:37+03:00" }, "domain": "vkontakte.0catch.com", "domainInfo": { "domain": "vkontakte.0catch.com", "domainPuny": "vkontakte.0catch.com", "expirationDate": null, "registered": null, "registrar": null, "tld": "com", "title": "", "category": [] }, "domainTitle": "Login | VKontakte", "evaluation": { "admiraltyCode": "C3", "credibility": 50, "reliability": 50, "severity": "red", "tlp": "amber", "ttl": 0 }, "falsePositive": false, "groupLifetime": 1006417, "id": "74ee810f703000d318bb144a1307abce9c05abee41465c30303922156e7ed36a", "ip": [{ "ip": "69.27.174.10", "countryCode": "US", "countryName": "United States", "provider": "U.s. Colo, LLC (uscolo)" }], "objective": ["Login harvest"], "phishingKitArray": [], "screenshot": { "pageHtml": { "hashSha256": "h:7297723b6093126c7ab2f037beac6cac256207c7492acc6b923f2cffe1fab5b4", "filetype": "pageHtml", "filename": "h:7297723b6093126c7ab2f037beac6cac256207c7492acc6b923f2cffe1fab5b4", "mime": "text/html", "fileHashMd5": "" }, "pageScreen": { "hashSha256": "s:1118760d55ebd9969f89fbc786b93276eb631cea84765d8f5d5bb908217bf632", "filetype": "pageScreen", "filename": "s:1118760d55ebd9969f89fbc786b93276eb631cea84765d8f5d5bb908217bf632", "mime": "image/jpeg", "fileHashMd5": "" } }, "seqUpdate": 1401373055098642, "signature": { "resource": [], "screen": [], "manual": ["VK_vhod"] }, "source": ["Cert", "ci-VirusTotal", "openphish"], "status": 1, "threatActor": { "id": "", "name": "", "nameIndexed": "", "isAPT": false }, "uniqueTitles": [{ "faviconHashes": { "md5": "", "sha1": "", "sha256": "" }, "title": "" }], "urlListLink": "", "whitelist": false, "phishing": [{ "id": "844923a0d22aa6141c5aa3d4e9997eea523ab0a1bb70898945e49befa57f3454", "url": "http://vkontakte.0catch.com", "date": { "blocked": "2016-04-27T14:55:20+03:00", "added": "2014-05-29T18:17:35+04:00", "detected": "2014-05-29T18:17:35+04:00" }, "status": 1, "objective": ["Login harvest"], "source": ["Cert", "openphish", "ci-VirusTotal"], "client": null, "title": "", "domain": { "registrar": "", "domain": "vkontakte.0catch.com", "registered": "", "title": "", "category": [], "expiration": "", "tld": "com", "puny": "vkontakte.0catch.com" }, "ip": { "countryCode": "US", "city": "Provo", "provider": "U.s. Colo, LLC (uscolo)", "ip": "69.27.174.10", "countryName": "United States" }, "phishingKit": [], "screen": { "pageHtml": { "hashSha256": "h:7297723b6093126c7ab2f037beac6cac256207c7492acc6b923f2cffe1fab5b4", "filetype": "pageHtml", "filename": "h:7297723b6093126c7ab2f037beac6cac256207c7492acc6b923f2cffe1fab5b4", "mime": "text/html", "fileHashMd5": "" }, "pageScreen": { "hashSha256": "s:1118760d55ebd9969f89fbc786b93276eb631cea84765d8f5d5bb908217bf632", "filetype": "pageScreen", "filename": "s:1118760d55ebd9969f89fbc786b93276eb631cea84765d8f5d5bb908217bf632", "mime": "image/jpeg", "fileHashMd5": "" } }, "renderedUrls": [""] }], "displayOptions": { "isFavourite": false, "isHidden": false } }],

"seqUpdate": 1430425612098642 }

Suspicious indicators - Scanning IP

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on scanning IP addresses. This collection contains data about public and private IP-addresses that were identified by the Group-IB TI system. These records can be used to identify or block connections between the corporate network and servers detected.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/suspicious_ip/scanner/updated
Collection	suspicious_ip/scanner
Collection Name	Scanning IP Addresses
Module	Suspicious Indicators
Submodule	Scanning IP
Type	Common
TTL (Days)	15 (recommended, not provided in API)
Admiralty Code	C3
Severity	1
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	IPv4

Property	Value
Short Description	IP addresses identified as performing scanning activities by the Group-IB TI system.

Request

Request URL
GET /api/v2/suspicious_ip/scanner/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1671657409977576
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by IP. Format: "" to search for one specific record.	"188.250.243.135"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for suspicious_ip/scanner/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific IP: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to suspicious_ip/vpn/updated, containing scanning IP information with IP addresses, dates, evaluation data, and scanning activity metadata.

Root Object
{ "count": integer, "items": [ScannerItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of scanner items returned in this response
items	array[ScannerItem]	Yes	Array of scanner IP objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

ScannerItem Object

The structure is similar to VpnItem, containing IP address, dates, evaluation data, and scanning activity-specific metadata.

Example Request

Basic Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/scanner/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Request with Hunting Rules
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/scanner/updated?seqUpdate=0&limit=500&apply_hunting_rules=1' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)

The response structure is similar to suspicious_ip/vpn/updated, with items containing scanning IP information.

{ "count": 500000, "items": [{ "id": "188.250.243.135", "dateFirstSeen": "2021-04-22T12:43:38+00:00", "dateLastSeen": "2021-04-22T12:43:38+00:00", "evaluation": { "admiraltyCode": "C3", "credibility": 50, "reliability": 50, "severity": "green", "tlp": "amber", "ttl": 15 }, "seqUpdate": 1671657409977576 }], "seqUpdate": 1671657410005695 }

Suspicious indicators - Socks Proxy IP

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on SOCKS proxy servers. The Socks proxy collection shows information about addresses where malware that turns infected computers into SOCKS proxies has been installed. Such computers (bots) are rented out and used in various attacks to ensure the attacker as much anonymity as possible. These records can be used to identify or block connections from or to SOCKS proxy servers.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/suspicious_ip/socks_proxy/updated
Collection	suspicious_ip/socks_proxy
Collection Name	SOCKS Proxy Servers
Module	Suspicious Indicators
Submodule	Socks proxy
Type	Common
TTL (Days)	2 (recommended, not provided in API)
Admiralty Code	A1
Severity	3
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	IPv4

Property	Value
Short Description	SOCKS proxy servers identified by the Group-IB TI system.

Request

Request URL
GET /api/v2/suspicious_ip/socks_proxy/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1671657409977576
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by IP. Format: "" to search for one specific record.	"188.250.243.135"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for suspicious_ip/socks_proxy/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific IP: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to suspicious_ip/vpn/updated, containing SOCKS proxy server information with IP addresses, dates, evaluation data, and proxy type information.

Root Object
{ "count": integer, "items": [SocksProxyItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of SOCKS proxy items returned in this response
items	array[SocksProxyItem]	Yes	Array of SOCKS proxy objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

SocksProxyItem Object

The structure is similar to VpnItem, containing IP address, dates, evaluation data, and SOCKS proxy-specific metadata.

Example Request

Basic Request
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/socks_proxy/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Request with Hunting Rules
```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/socks_proxy/updated?seqUpdate=0&limit=500&apply_hunting_rules=1' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
```
Example Response

Success Response (200 OK)

The response structure is similar to suspicious_ip/vpn/updated, with items containing SOCKS proxy server information.

{ "count": 500000, "items": [{ "id": "188.250.243.135", "dateFirstSeen": "2021-04-22T12:43:38+00:00", "dateLastSeen": "2021-04-22T12:43:38+00:00", "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "severity": "green", "tlp": "amber", "ttl": 2 }, "seqUpdate": 1671657409977576 }], "seqUpdate": 1671657410005695 }

Suspicious indicators - TOR IP

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on Tor nodes. The Tor collection displays data about Tor exit nodes, which are the final Tor relays in the circuit. The nodes act as an intermediary between a Tor client and public Internet. These records can be used to identify or block connections from Tor network.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/suspicious_ip/tor_node/updated
Collection	suspicious_ip/tor_node
Collection Name	Tor Nodes
Module	Suspicious Indicators
Submodule	Tor
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A1
Severity	3
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	IPv4

Property	Value
Short Description	Tor exit nodes and relay nodes identified by the Group-IB TI system.

Request

Request URL
GET /api/v2/suspicious_ip/tor_node/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1671657409977576
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by IP. Format: "" to search for one specific record.	"188.250.243.135"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for suspicious_ip/tor_node/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific IP: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

The response structure is similar to suspicious_ip/vpn/updated, containing Tor node information with IP addresses, dates, evaluation data, and node type information.

Root Object
{ "count": integer, "items": [TorNodeItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of Tor node items returned in this response
items	array[TorNodeItem]	Yes	Array of Tor node objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

TorNodeItem Object

The structure is similar to VpnItem, containing IP address, dates, evaluation data, and Tor-specific metadata (node type, exit/relay status, etc.).

Example Request

Basic Request
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/tor_node/updated?seqUpdate=0&limit=500' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Request with Hunting Rules
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/tor_node/updated?seqUpdate=0&limit=500&apply_hunting_rules=1' \ -u 'LOGIN:API_KEY' \ -H 'Accept: application/json'
Example Response

Success Response (200 OK)

The response structure is similar to suspicious_ip/vpn/updated, with items containing Tor node information.

{ "count": 500000, "items": [{ "id": "188.250.243.135", "dateFirstSeen": "2021-04-22T12:43:38+00:00", "dateLastSeen": "2021-04-22T12:43:38+00:00", "evaluation": { "admiraltyCode": "A1", "credibility": 100, "reliability": 100, "severity": "green", "tlp": "amber", "ttl": 30 }, "seqUpdate": 1671657409977576 }], "seqUpdate": 1671657410005695 }

Suspicious indicators - VPN IP

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This collection provides updated information on VPN servers. This collection contains information about public and private VPNs servers that were identified by the Group-IB TI system. These records can be used to identify or block connections between the corporate network and servers detected.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/suspicious_ip/vpn/updated
Collection	suspicious_ip/vpn
Collection Name	VPN Servers
Module	Suspicious Indicators
Submodule	VPN
Type	Common
TTL (Days)	30 (recommended, not provided in API)
Admiralty Code	A2
Severity	1
Collection Limit	500 records per request
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
IOC Types	IPv4

Property	Value
Short Description	Public and private VPN servers identified by the Group-IB TI system.

Request

Request URL
GET /api/v2/suspicious_ip/vpn/updated
Query Parameters

Parameter	Type	Required	Default	Description	Example
seqUpdate	integer	No	0	Sequence update number to get the next data chunk. Use this parameter to iterate through feeds. The value should be obtained from the previous response's top-level seqUpdate field or from /api/v2/sequence_list endpoint. Important: Always use the top-level seqUpdate field for iteration.	1671657409977576
limit	integer	No	500	Limit the amount of returned data for this collection. Maximum allowed: 500 for this collection.	500
q	string	No	-	Search query. Can be used to filter results or search for a specific entry by IP. Format: "" to search for one specific record.	"188.250.243.135"
apply_hunting_rules	integer	No	0	Apply hunting rules filter. Set to 1 to enable.	1

Query Parameter Details:

.

seqUpdate:

- Each row in the database has its own unique sequence update number
- Important: Always use the top-level seqUpdate field from the previous response to get the next portion of feeds
- Use /api/v2/sequence_list endpoint to get the required seqUpdate number for a specific date

- limit:
  - Maximum value: 500 for suspicious_ip/vpn/updated collection
  - If not specified, defaults to 500
  - The limit depends on the amount of data to not overload the JSON output
- q:
  - Can be used for general search queries
  - To search for a specific IP: q=""
  - Supports various search types

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "count": integer, "items": [VpnItem], "seqUpdate": integer }

Field	Type	Required	Description
count	integer	Yes	Number of VPN items returned in this response
items	array[VpnItem]	Yes	Array of VPN server objects
seqUpdate	integer	Yes	Sequence update number at the top level of the response. Always use this top-level value in the next request's seqUpdate parameter to get the next portion of feeds

VpnItem Object

Field	Type	Required	Description
id	string	Yes	IP address (used as unique identifier)
dateFirstSeen	string	Yes	ISO 8601 timestamp when the VPN server was first seen
dateLastSeen	string	Yes	ISO 8601 timestamp when the VPN server was last seen

Field	Type	Required	Description
seqUpdate	integer	Yes	Sequence update number for this specific item
ipv4	IPv4Object	Yes	IPv4 address object
names	array[string]	Yes	Array of VPN service names (e.g., [“SoftEther VPN”])
types	array[string]	Yes	Array of VPN types (e.g., [“self-hosted”])
rules	array[string]	Yes	Array of detection rule names
source	string	Yes	Source identifier
sources	array[string]	Yes	Array of source identifiers
evaluation	Evaluation	Yes	Evaluation object containing threat assessment
bind	object | null	No	Bind object
portalLink	string | null	No	Portal link to the VPN record

IPv4Object Object

Field	Type	Required	Description
ip	string	Yes	IPv4 address
countryCode	string | null	No	Country code (ISO 3166-1 alpha-2)
countryName	string | null	No	Country name
city	string | null	No	City name
region	string | null	No	Region name

Field	Type	Required	Description
provider	string | null	No	ISP/provider name
asn	string | null	No	ASN number

Evaluation Object

Field	Type	Required	Description
admiraltyCode	string	Yes	Admiralty Code (e.g., “A2”)
credibility	integer	Yes	Credibility score (0-100)
reliability	integer	Yes	Reliability score (0-100)
severity	string	Yes	Severity level (e.g., “green”, “orange”, “red”)
tlp	string	Yes	Traffic Light Protocol level (e.g., “amber”, “red”, “green”, “white”)
ttl	integer	Yes	Time to live in days

Example Request

Basic Request

```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/vpn/updated?seqUpdate=0&limit=500' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Request with Hunting Rules

```
curl -X GET 'https://tap.group-ib.com/api/v2/suspicious_ip/vpn/updated?seqUpdate=0&limit=500&apply_hunting_rules=1' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "count": 741499, "items": [{ "bind": null, "dateFirstSeen": "2021-04-22T12:43:38+00:00", "dateLastSeen": "2021-04-22T12:43:38+00:00", "evaluation": { "admiraltyCode": "A2", "credibility": 80, "reliability": 90, "severity": "green", "tlp": "amber", "ttl": 2 }, "id": "188.250.243.135", "ipv4": { "asn": "AS3243", "city": null, "countryCode": "PT", "countryName": null, "ip": "188.250.243.135", "provider": null, "region": null }, "names": ["SoftEther VPN"], "portalLink": null, "rules": ["vpn_soft_ether"], "seqUpdate": 1671657409977576, "source": "playbook", "sources": ["playbook"], "types": ["self-hosted"] }], "seqUpdate": 1671657410005695 }

Collections Details - Analysis Domain Whois

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint retrieves WHOIS information for second-level domain names. It provides access to domain registration and ownership data sourced from the Graph module, including current and historical WHOIS records with parsed and raw data.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/utils/graph/domain
Collection Name	Domain Whois
Module	Graph
Type	Utility for Analysis
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Domain WHOIS API collection provides access to domain registration and ownership data sourced from Graph module.

Request

Request URL
GET /api/v2/utils/graph/domain
Query Parameters

Parameter	Type	Required	Default	Description	Example
domain	string	Yes	-	Second-level domain name to query WHOIS information for	group-ib.com

Query Parameter Details:

- domain:
  - Required parameter
  - Must be a valid second-level domain name (e.g., group-ib.com)
  - The endpoint will retrieve WHOIS information for the specified domain
  - Only second-level domains are supported (e.g., group-ib.com, not subdomain.group-ib.com)

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private

Header	Description	Example
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "id": string, "name": string, "created_at": string, "updated_at": string, "is_sld": boolean, "zone": string, "whois": array, "whois_history": array, "dns": array, "dns_list": array, "netoscope": array, "createdAt": string, "updatedAt": string, "isSld": boolean }
The response is a single object containing domain metadata and WHOIS information.

Root Object Fields

Field	Type	Required	Description
id	string	Yes	Domain identifier (same as domain name)
name	string	Yes	Domain name
created_at	string	Yes	ISO 8601 timestamp when the domain record was created in the system
updated_at	string	Yes	ISO 8601 timestamp when the domain record was last updated
is_sld	boolean	Yes	Indicates if this is a second-level domain
zone	string	Yes	Top-level domain (TLD) zone (e.g., com, org, net)
whois	array	Yes	Array of current WHOIS records (see Whois Record Object below)
whois_history	array	Yes	Array of historical WHOIS records (see Whois History Record Object below)
dns	array	Yes	Array of DNS records (may be empty)
dns_list	array	Yes	Array of DNS list entries (may be empty)
netoscope	array	Yes	Array of netoscope entries (may be empty)

Field	Type	Required	Description
createdAt	string	Yes	ISO 8601 timestamp (alternative format for creation date)
updatedAt	string	Yes	ISO 8601 timestamp (alternative format for update date)
isSld	boolean	Yes	Indicates if this is a second-level domain (alternative format)

Whois Record Object

Each object in the whois array represents a current WHOIS record:

Field	Type	Required	Description
level	integer	Yes	WHOIS query level (0 = registry, 1 = registrar, 2 = registrant)
server	string	Yes	WHOIS server that provided this record
parsed	array	Yes	Array of parsed WHOIS fields (see Parsed Field Object below)
response	string	Yes	Raw WHOIS response text
checked_at	string | null	No	ISO 8601 timestamp when this record was checked
checkedAt	boolean	Yes	Indicates if the record has been checked
values	object	Yes	Additional parsed values (may be empty object)

Parsed Field Object

Each object in the parsed array represents a parsed WHOIS field:

Field	Type	Required	Description
field	string	Yes	Field name (e.g., Registrar, NameServers, CreationDate, ExpirationDate, Status, Phone, Email, Address, City, State, Country, Zipcode, Org, Name)
value	array	Yes	Array of string values for this field (may be empty array)

Whois History Record Object

Each object in the whois_history array represents a historical WHOIS record. It has the same structure as a Whois Record Object, with additional fields:

Field	Type	Required	Description
level	integer	Yes	WHOIS query level (0 = registry, 1 = registrar, 2 = registrant)
server	string	Yes	WHOIS server that provided this record
parsed	array	Yes	Array of parsed WHOIS fields (see Parsed Field Object above)
response	string	Yes	Raw WHOIS response text
checked_at	string | null	No	ISO 8601 timestamp when this record was checked
first_seen	string | null	No	ISO 8601 date when this record was first seen
last_seen	string | null	No	ISO 8601 date when this record was last seen

Example Request

Basic WHOIS Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/utils/graph/domain?domain=group-ib.com' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "id": "group-ib.com", "name": "group-ib.com", "created_at": "2015-12-11T05:32:59Z", "updated_at": "2025-12-23T14:37:59.697Z", "is_sld": true, "zone": "com", "whois": [{ "level": 1, "server": "whois.crsnic.net", "parsed": [{ "field": "Registrar", "value": ["godaddy.com, llc"] }, { "field": "NameServers", "value": ["dora.ns.cloudflare.com", "tom.ns.cloudflare.com"

] }, { "field": "Status", "value": ["clientdeleteprohibited https://icann.org/epp#clientdeleteprohibited", "clientrenewprohibited https://icann.org/epp#clientrenewprohibited", "clienttransferprohibited https://icann.org/epp#clienttransferprohibited", "clientupdateprohibited https://icann.org/epp#clientupdateprohibited"] }], "response": "[Raw WHOIS response text - truncated for brevity]", "checked_at": "2025-12-23 13:49:50", "checkedAt": true, "values": {} }], "whois_history": [{ "level": 2, "server": "whois.reg.com", "parsed": [{ "field": "name", "value": ["Domain Administrator", "Ilya Sachkov"] }, { "field": "org", "value": ["\"Group IB Service\" Ltd.", "Group IB Service Ltd."] }, { "field": "country", "value": ["RU"] }], "response": "[Raw WHOIS response text - truncated for brevity]", "checked_at": null, "first_seen": "2018-12-19", "last_seen": "2019-01-17" }], "dns": [], "dns_list": [], "netoscope": [], "createdAt": "2015-12-11T05:32:59Z", "updatedAt": "2025-12-23T14:37:59.697Z", "isSld": true }

IP Whois

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint retrieves WHOIS information for IP addresses. It provides access to IP registration and ownership data sourced from the Graph module, including ASN (Autonomous System Number), organization details, allocation range, registry data, and historical WHOIS records with parsed information.

Collection-Specific Information

Property	Value
Method	GET
Path	/api/v2/utils/graph/ip
Collection Name	IP Whois
Module	Graph
Type	Utility for Analysis
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	The IP WHOIS API provides access to registration and ownership information for IP addresses sourced from the Graph module, including details such as ASN, organization, allocation range, and registry data.

Request

Request URL
GET /api/v2/utils/graph/ip
Query Parameters

Parameter	Type	Required	Default	Description	Example
ip					

Parameter	Type	Required	Default	Description	Example
	string	Yes	-	IP address to query WHOIS information for	3.72.181.255, 2a01:4f8:10b:90f::2

Query Parameter Details:

- ip:
  - Required parameter
  - Must be a valid IP address (IPv4 or IPv6)
  - The endpoint will retrieve WHOIS information for the specified IP address
  - Returns allocation range, ASN, organization, and registry information

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type		

Header	Description	Example
	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	GET

Response Body Schema

Root Object
{ "id": string, "start": string, "end": string, "provider": string, "created_at": string | null, "updated_at": string | null, "whois_history": array, "whois_summary": object, "createdAt": string | null, "updatedAt": string | null, "whoisHistory": array, "whoisSummary": object }
The response is a single object containing IP metadata and WHOIS information.

Root Object Fields

Field	Type	Required	Description
id	string	Yes	IP address identifier (same as queried IP)
start	string	Yes	Start of the IP allocation range (CIDR block start)
end	string	Yes	End of the IP allocation range (CIDR block end)
provider	string	Yes	Regional Internet Registry (RIR) provider (e.g., ripe, arin, apnic, lacnic, afrinic)
created_at	string | null	No	ISO 8601 timestamp when the IP record was created in the system
updated_at	string | null	No	ISO 8601 timestamp when the IP record was last updated
whois_history	array	Yes	Array of historical IP WHOIS records (see Whois History Entry Object below)

Field	Type	Required	Description
whois_summary	object	Yes	Summary of current IP WHOIS information (see Whois Summary Object below)
createdAt	string | null	No	ISO 8601 timestamp (alternative format for creation date)
updatedAt	string | null	No	ISO 8601 timestamp (alternative format for update date)
whoisHistory	array	Yes	Array of historical IP WHOIS records (alternative naming, same as whois_history)
whoisSummary	object	Yes	Summary of current IP WHOIS information (alternative naming, same as whois_summary)

Whois History Entry Object

Each object in the whois_history array represents a historical WHOIS record entry:

Field	Type	Required	Description
first_seen	string	Yes	Date when this record was first seen (format: YYYY-MM-DD)
last_seen	string	Yes	Date when this record was last seen (format: YYYY-MM-DD)
data	array	Yes	Array of WHOIS data objects (see Whois Data Object below)

Whois Data Object

Each object in the data array within a history entry contains parsed WHOIS information:

Field	Type	Required	Description
first_seen			

Field	Type	Required	Description
	string	Yes	ISO 8601 timestamp when this data was first seen
last_seen	string	Yes	ISO 8601 timestamp when this data was last seen
md5	string	Yes	MD5 hash of the WHOIS data for deduplication
parsed	array	Yes	Array of parsed WHOIS fields (see Parsed Field Object below)
type	string	Yes	Type of WHOIS record (e.g., route, inetnum)
values	object	Yes	Additional parsed values (may be empty object)
values_raw	object	Yes	Raw parsed values (may be empty object)
first_appeared	boolean	Yes	Indicates if this is the first appearance of this data
last_appeared	boolean	Yes	Indicates if this is the last appearance of this data
firstSeen	string	Yes	ISO 8601 timestamp (alternative format for first seen)
lastSeen	string	Yes	ISO 8601 timestamp (alternative format for last seen)

Parsed Field Object

Each object in the parsed array represents a parsed WHOIS field:

Field	Type	Required	Description
field	string	Yes	Field name (e.g., route, descr, origin, mnt-by, parsed_domains, parsed_emails, rpki-ov-state, changed, last-modified, source, type)
value	array	Yes	Array of string values for this field (may be empty array)

Whois Summary Object

The whois_summary object provides a summary of current IP WHOIS information:

Field	Type	Required	Description
asn	string	Yes	Autonomous System Number (ASN) associated with the IP range
country	string	Yes	Country code (may be empty string)
descr	string	Yes	Description of the IP allocation (organization or network name)
isp	string	Yes	Internet Service Provider or organization name
netname	string	Yes	Network name (may be empty string)
phone	string	Yes	Contact phone number (may be empty string)

Example Request

Basic IP WHOIS Query

```
curl -X GET 'https://tap.group-ib.com/api/v2/utils/graph/ip?ip=3.72.181.255' \  -u 'LOGIN:API_KEY' \  -H 'Accept: application/json'
```

Example Response

Success Response (200 OK)

{ "id": "3.72.181.255", "start": "3.64.0.0", "end": "3.79.255.255", "provider": "ripe", "created_at": null, "updated_at": null, "whois_history": [{ "first_seen": "2025-10-29", "last_seen": "2025-10-29", "data": [{ "first_seen": "2025-10-29T16:34:39Z", "last_seen": "2025-10-29T16:34:39Z", "md5": "101ca07ce44a51a58afb79be13279032", "parsed": [{ "field": "route", "value": [] }, { "field": "descr", "value": ["Amazon EC2 FRA Prefix"] }, { "field": "origin", "value": ["AS16509"] }, { "field": "mnt-by", "value": ["MAINT-AS16509"] }, { "field": "parsed_domains", "value": ["amazon.com"] }, { "field": "parsed_emails", "value": ["noc@amazon.com"] }, { "field": "rpki-ov-state", "value": ["valid"] }, { "field": "changed", "value": ["noc@amazon.com 20201022 #18:22:02Z"] }, { "field": "last-modified", "value": [] }, { "field": "source", "value": [] }, { "field": "type", "value": [] }], "type":

"route", "values": {}, "values_raw": {}, "first_appeared": false, "last_appeared": false, "firstSeen": "2025-10-29T16:34:39Z", "lastSeen": "2025-10-29T16:34:39Z" }] }], "whois_summary": { "asn": "AS16509", "country": "", "descr": "Amazon EC2 FRA Prefix", "isp": "Amazon EC2 FRA Prefix", "netname": "", "phone": "" }, "createdAt": null, "updatedAt": null, "whoisHistory": [{ "first_seen": "2025-10-29", "last_seen": "2025-10-29", "data": [{ "first_seen": "2025-10-29T16:34:39Z", "last_seen": "2025-10-29T16:34:39Z", "md5": "101ca07ce44a51a58afb79be13279032", "parsed": [{ "field": "route", "value": [] }, { "field": "descr", "value": ["Amazon EC2 FRA Prefix"] }, { "field": "origin", "value": ["AS16509"] }, { "field": "mnt-by", "value": ["MAINT-AS16509"] }, { "field": "parsed_domains", "value": ["amazon.com"] }, { "field": "parsed_emails", "value": ["noc@amazon.com"] }, { "field": "rpki-ov-state", "value": ["valid"] }, { "field": "changed", "value": ["noc@amazon.com 20201022 #18:22:02Z"] }, { "field": "last-modified", "value": [] }, { "field": "source", "value": [] }, { "field": "type", "value": [] }], "type": "route", "values": {}, "values_raw": {}, "first_appeared": false, "last_appeared": false, "firstSeen": "2025-10-29T16:34:39Z", "lastSeen": "2025-10-29T16:34:39Z" }] }], "whoisSummary": { "asn": "AS16509", "country": "", "descr": "Amazon EC2 FRA Prefix", "isp": "Amazon EC2 FRA Prefix", "netname": "", "phone": "" } }

IP Scoring

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint returns a risk score for one or more IP addresses. Each score is a number from 0 to 100 that reflects the likelihood that the IP is associated with malicious activity, based on Group-IB Threat Intelligence data. Use it to enrich and prioritize IP addresses on demand - for example, to triage indicators, score traffic, or gate automated response.

Collection-Specific Information

Property	Value
Method	POST
Path	/api/v2/scoring/ip
Collection Name	IP Scoring
Module	Scoring
Type	Utility for Analysis
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Returns a 0-100 risk score for one or more IPv4 addresses based on Group-IB Threat Intelligence data.

Request

Request URL
POST /api/v2/scoring/ip
Request Body

The request body is a JSON object with a single ips field containing one or more IPv4 addresses.
{ "ips": ["8.8.8.8", "1.1.1.1"] }

Field	Type	Required	Description
ips	array[string]	Yes	One or more IPv4 addresses to score. IPv4 only (IPv6, hostnames, and CIDR ranges are not supported).

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Content-Type	string	Yes	Must be application/json	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip

Header	Description	Example
Cache-Control	Cache control directives	max-age=0, must-revalidate, private
Allow	Allowed HTTP methods	POST

Response Body Schema

Root Object
{ "items": { "": { "ip": string, "riskScore": integer } } }

Field	Type	Required	Description
items	object	Yes	Map keyed by the queried IP address. Each value is an IP score object. An IP with no intelligence data returns a score of 0; an empty items object is returned when there are no results.

IP Score Object

Field	Type	Required	Description
ip	string	Yes	The scored IP address
riskScore	integer	Yes	Risk score from 0 to 100 (see interpretation below)

Risk Score Interpretation

Score	Level	Description
0-39	Low	Minor or no indicators; likely benign. Well-known public infrastructure commonly falls in the 20-35 range.
40-59	Suspicious	Multiple weak indicators; worth monitoring.
60-79	High	Highly likely suspicious; investigate.

Score	Level	Description
80-100	Malicious	Confirmed malicious; immediate action recommended.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

Basic Request

```
curl -X POST 'https://tap.group-ib.com/api/v2/scoring/ip' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json' \   -H 'Content-Type: application/json' \   -d '{"ips": ["8.8.8.8", "1.1.1.1"]}'
```

Example Response

Success Response (200 OK)

```
{   "items": {     "1.1.1.1": {       "ip": "1.1.1.1",       "riskScore": 25     },     "8.8.8.8": {       "ip": "8.8.8.8",       "riskScore": 25     }   } }
```

Domain Scoring

Summary

Disclaimer: This is an endpoint-specific documentation. For common information including Authentication, Response Status Codes, Rate Limits, Additional Notes, and Troubleshooting, please refer to related articles in Integrations.

This endpoint returns a risk score for one or more domains. Each score is a number from 0 to 100 that reflects the likelihood that the domain is associated with malicious activity, based on Group-IB Threat Intelligence data. Use it to enrich and prioritize domains on demand - for example, to triage indicators, score observed domains, or gate automated response. It is the domain counterpart of the IP Scoring endpoint and uses the same 0-100 scale.

Collection-Specific Information

Property	Value
Method	POST
Path	/api/v2/scoring/domain
Collection Name	Domain Scoring
Module	Scoring
Type	Utility for Analysis
Rate Limit	1 request per 10 seconds per company per feed (see API Limitations)
Short Description	Returns a 0-100 risk score for one or more domains based on Group-IB Threat Intelligence data.

Request

Request URL
POST /api/v2/scoring/domain
Request Body

The request body is a JSON object with a single domains field containing one or more domains.
{ "domains": ["group-ib.com", "example.corp"] }

Field	Type	Required	Description
domains			

Field	Type	Required	Description
	array[string]	Yes	One or more domains to score.

Request Headers

Header	Type	Required	Description	Example
Accept	string	No	Content type accepted by the client	application/json
Content-Type	string	Yes	Must be application/json	application/json
Authorization	string	Yes	Basic authentication credentials (see Initial Steps)	Basic base64(LOGIN:API_KEY)
User-Agent	string	No	User-Agent string with product metadata (optional but recommended - especially useful in troubleshooting on our end). Format: PlatformType/PlatformName_PlatformVersion/AppName_AppVersion/Username/LibName_LibVersion	SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/ciaops_3.0.0

Response

Note: For response status codes and error handling, see Troubleshooting and Error Codes.

Response Headers

Header	Description	Example
Content-Type	Response content type	application/json
Content-Encoding	Content encoding	gzip
Cache-Control	Cache control directives	max-age=0, must-revalidate, private

Header	Description	Example
Allow	Allowed HTTP methods	POST

Response Body Schema

Root Object
{ "items": { "": { "domain": string, "riskScore": integer } } }

Field	Type	Required	Description
items	object	Yes	Map keyed by the queried domain. Each value is a domain score object. A domain with no intelligence data returns a score of 0; an empty items object is returned when there are no results.

Domain Score Object

Field	Type	Required	Description
domain	string	Yes	The scored domain
riskScore	integer	Yes	Risk score from 0 to 100 (see interpretation below)

Risk Score Interpretation

Score	Level	Description
0-39	Low	Minor or no indicators; likely benign.
40-59	Suspicious	Multiple weak indicators; worth monitoring.
60-79	High	Highly likely suspicious; investigate.
80-100	Malicious	Confirmed malicious; immediate action recommended.

Example Request

Note: In the examples below, set the GIB_CREDENTIALS environment variable to your LOGIN:API_KEY (your email and API key) before running the command.

Basic Request

```
curl -X POST 'https://tap.group-ib.com/api/v2/scoring/domain' \   -u "$GIB_CREDENTIALS" \   -H 'Accept: application/json' \   -H 'Content-Type: application/json' \   -d '{"domains": ["group-ib.com", "example.corp"]}'
```

Example Response

Success Response (200 OK)

```
{   "items": {     "example.corp": {       "domain": "example.corp",       "riskScore": 0     },     "group-ib.com": {       "domain": "group-ib.com",       "riskScore": 0   } } }
```

Deprecated Collections

Overview

This document provides a list of deprecated APIs from our system and suggests alternative APIs to use. The deprecations are part of ongoing improvements to enhance system performance and maintainability. Please update your code to use the new APIs to ensure compatibility with future versions.

Collections:

Collection	Deprecated API endpoint	New API endpoint
Malware	malware/targeted_malware	malware/config/updated
Compromised Data::Cards Compromised Data::Bank Cards	compromised/masked_cards compromised/bank_card	compromised/masked_card/updated compromised/bank_card_group/updated
Compromised Data::Accounts	compromised/account	compromised/account_group/updated
Phishing	attacks/phishing	attacks/phishing_group/updated
IOC	ioc/common	ioc/primary/updated

IOC Primary returns the same indicators as IOC Common, plus risk scores, evaluation metadata and attribution. See IOC Primary.

Reference:

For a comprehensive list of all currently supported API endpoints and their detailed descriptions, please refer to the Collections Overview article.

Custom and native integrations
List of integrations

In addition to offering various API versions, such as API 2.0 and STIX/TAXII 2.1, we provide a range of integration solutions for third-party vendors.

Current integrations are available for download through the following channels:

- Third-party marketplaces
- Public repositories
- The TI Help Center, where you can find details for installation

The following list outlines the available integrations, along with links for downloading and accessing documentation:

Vendor	Integration source	Status	Product type	Author	Documentation access
Anomali	Internal marketplace	Under update	TIP	Anomali	Built-in
ArcSight SIEM Connector	TI Help Center	Beta test	SIEM	Group-IB	Help Center
Brinqa	Internal marketplace	Ready to use	ASMP	Brinqa	Built-in
Cisco ASA	TI Help Center	Ready to use	NGFW	Group-IB	On request
Cortex SOAR	App Store	Ready to use	SOAR	Group-IB	Built-in
Cyware CTIX	Internal marketplace	Ready to use	TIP	Cyware	Built-in
EclecticIQ	Internal marketplace	Ready to use	TIP	EclecticIQ	Built-in
Google SecOps	Internal Marketplace	Ready to use	SOAR	Group-IB	Help Center

Vendor	Integration source	Status	Product type	Author	Documentation access
IBM Security QRadar SIEM ver. 7.4.3 + LogRhythm Custom	App Store	Ready to use	SIEM	Group-IB	Built-in
LogRhythm Native	TI Help Center	Ready to use	SIEM	Group-IB	Help Center
MISP	TI Help Center	Scheduled	SIEM	Group-IB	Help Center
OpenCTI	Public Repository	Ready to use	TIP	Group-IB	Help Center
Palo Alto FireWall	TI Help Center	Ready to use	TIP	Group-IB	Built-in
Splunk ES	App Store	Deprecated	NGFW	Group-IB	-
Splunk SOAR	App Store	Ready to use	SIEM	Group-IB	Built-in
Splunk TruSTAR	Internal marketplace	Ready to use	SOAR	Group-IB	Built-in
StrikeReady	Internal marketplace	Ready to use	TruSTAR	Splunk	Built-in
Swimlane	App Store	Ready to use	SOAR	StrikeReady	Built-in
ThreatConnect	App store	Ready to use	SOAR	Swimlane	Built-in
			TIP	Group-IB	Help Center

Vendor	Integration source	Status	Product type	Author	Documentation access
ThreatQ	App Store	Ready to use	TIP	ThreatQ	Built-in
Vertex Synapse	App store	Ready to use	CIS	Vertex	Built-in

Explanatory notes

Integration statuses:

- Ready to use: The integration has been published and is available for installation and implementation.
- Under update: A current version is available, but a major update is scheduled for release within approximately three months.
- Initial development: Development has commenced, with an expected timeline of up to six months for the initial application release. A pre-release version may be requested manually through the Service Desk if the team already possesses the version.
- Scheduled: application development is planned for the upcoming quarter, but has not been started yet.

Integration source:

- Internal Marketplace: Available in the private app store.
- TI Help Center: Available in the Group-IB Threat Intelligence Help Center.
- App Store: Available in the public app store.
- Public Repository: Available in the public GitHub repository.

Documentation access:

- Group-IB Help Center: Integration instructions can be found in the Help Center of the Group-IB TI portal.
- Built-in: Available in the private app store, public app store, or included within the archive of integration installation files.

Google SecOps Overview

The integration allows receiving feeds from the Group-IB Threat Intelligence, and transforming them into the Google SecOps Alerts with Entities objects. The application can be installed in two ways: using the installation file ZIP archive at Response -> IDE -> Import package and using Google SecOps Market at Marketplace -> Integrations -> and click Install at the application frame.


Current application contains active (Actions, Connectors) and passive files (Managers). You can add Actions in the Playbooks section to trigger them on Alerts creation or apply Playbooks to Entities to get extra enrichment or even run Actions separately for each Entity. You can add a scheduled Connector at Settings -> Ingestion -> Connectors to run it as a job at configured intervals. Managers contain common variables, utilities for app needs, configs, collection description and mapping filter, which can be applied to change the JSON output in some cases.

Before installing and configuring the integration, check out the start-up instructions in Group-IB TI Integration Starting Guide.


Installation

The installation process assumes that you have access to the Google SecOps Market. There you need to search the application Group-IB TI at Marketplace -> Integrations -> and click Install at the application frame. The installation icon will change to gear icon when the process is finished.

Check the application code at Response -> IDE -> Group-IB TI.



The alternative way to install the application Group-IB TI is to use the ZIP archive with the installation file at Response -> IDE -> + -> Import package. Choose Group-IB_TI_SecOps_vx.x.x.zip archive, which can be downloaded here.



Configuration

The configuration process includes several steps.

- The first step is to insert your API credentials, which are applied on the app level and let you avoid configuring it for each Action.
- The second step concerns configuring Connectors, which generate Alerts for you.
- The third step describes Alerts configuration and their connection to other subsections.

Before you begin

To ensure that Group-IB TI application is installed without errors, verify that you use only the supported versions of any Google SecOps software.


General information

The GroupIB TI application is based on requests to the Group-IB TI Portal API, gathering data and uploading it to the Google SecOps Platform. Requests gather information from different collections, which are listed in Action / Connector configuration steps. Each collection has Start date and Sequence update number parameters. A Sequence update number parameter will be stored at Google SecOps side using siemplify.save_timestamp() and extracted by siemplify.fetch_timestamp() functions.


NOTE: A more detailed description of the API operation logic can be found on the API Logic Explanation page.

Step 1. App configuration

- Go to Marketplace -> Integrations -> click Gear at the found application frame.




- Insert your Group-IB TI Portal credentials (API login - your email address used to enter the Group-IB TI Portal, API key - API key, generated at your Group-IB TI Profile).
- Click Test to test the connectivity and to validate your credentials (Ping Action runs at this time. To check the code go to Response -> IDE -> Group-IB TI -> Ping).
- Click Save.



Step 2. Connectors configuration


- Go to Settings -> Connectors -> click Plus to add a new Connector.




- In the opened Connector configuration insert your Group-IB TI Portal credentials (API login - your email address used to enter the Group-IB TI Portal, API key - API key, generated at your Group-IB TI Profile).
- Change Case name, Case severity, Case type if applicable or leave default values.
- Change Start date if applicable or leave it blank. By default it is set to one day back from today. Start date format is YYYY-MM-DD.
- Choose the Environment you use. And set a schedule parameter Run Every day (1 0 0 0) or Run Every 12 hours (0 12 0 0). You can decrease it to minutes for testing purposes but usually you get fresh collections data daily.
- Click Save.

For a better visualization of all steps, explore the screenshot on the next page.

NOTE: Please note that the steps on the screenshot do not always coincide with the steps in the text instructions. Double-check the order of the steps and all details described in the text instructions before saving.




- Before running Connector in production it is strongly recommended to open Testing tab -> Run connector once and check the output. New Sample Alert will appear. Mark it with a checkbox and click Load to system.



Warning: Please go to Step 3 Alerts configuration (you'll find the instruction below) on this stage to set Mapping for the Events before proceeding to the next step.

- At the last stage enable the app by the Slider and click Save.
- Example screenshot for the Testing tab.




- Check the Logs tab if applicable.


Step 3. Alerts configuration

The result of Connectors run generates Alerts in Google SecOps Cases.

NOTE: [These Alerts can be applied. You can add Actions in the Playbooks section to trigger them on Alerts creation or apply Playbooks to Entities to get extra enrichment or even run Actions separately for each Entity]



- Go to Cases -> choose Alert -> Events tab -> click Gear icon (Configure Event). If you run tests for Connector then an Alert with “T” marker will be created (T = Test).




- You should see new Alerts in the Cases list.



Warning: If you don't see any test Alerts then there is no data for the 1 day back period. Please go to Step 2 Connectors configuration on that stage and extend the Start date for a one week back (or more) before proceeding to the next step.

- Open a new browser tab and click on the application name (Group-IB TI) -> Mapping -> Entity Fields. You will get to app top level mapping configuration, so it will affect all new incoming Alerts to extract JSON fields in the proper way. Set Extracted Fields in the following way:
  - DestinationAddress -> ioc_ip
  - FileHash -> ioc_hash



Go to Step 2 Connectors configuration, point 8 and finnish app configuration.

Usage

The application Group-IB TI provides information about 100% IoC such as IPs and Hashes. You will receive the following IoC using existing Connectors daily:

- TI IoC IP Connector - provides you the opportunity to download all IoC IPs and add them to Alerts as Entities. Created Alert name is IoC by default. Contain IoC IP tab in the Alert itself.
- TI IoC Hash Connector - provides you the opportunity to download all IoC Hashes and add them to Alerts as Entities. Created Alert name is IoC by default. Contain IoC Hash tab in the Alert itself.

Group-IB TI application contains the following Actions:

-

Get-Collection-Info-Async - help to extract data from Group-IB TI database by chosen collection. Can be used to run daily to get fresh updates only. This Action ignores any Entities. Use the input entity as the start trigger.


- Get-Graph-Info - used to get WHOIS information based on Domain or IP Address.
- Get-TI-Search-Info - search Domain, IP Address, File Hash, Bank Card, Email in Group-IB TI database.
- Get-TI-Search-Info-By-Collection - search Domain, IP Address, URL, File Hash, Bank Card, Email in Group-IB TI database. Specify tag to get targeted field results.
- Ping - used to test connectivity.

All actions can be divided into two groups:


- Updates - gather collections information data as is from Group-IB TI API. Receive only fresh updates every day for existing events or receive new events. Include Get-Collection-Info-Async Action.
- Search - gather collections information data and enrich User input (IPs, URLs, Hashes, Bank Cards, etc.) with extra attributed information. Include Get-Graph-Info, Get-TI-Search-Info, Get-TI-Search-Info-By-Collection Actions.

The Updates group contains asynchronous types of Actions. The Search group contains synchronous types of Actions.


- Go to Response -> Playbooks -> create a new Playbook -> add any Action in Search group hover over it and click to configure.



- Fill in Parameters and click Save.




- If extra parameters are available - here is the explanation:
  - Enable mapping parser - Enable or Disable mapping parser before return JSON output
  - Collection - choose required collection to download
  - Search tag - by default Tag is empty: q=(q=8.8.8.8). If Tag is set to “domain”: q=: (q=domain:google.com).




Each Group-IB TI application Action includes a JSON result and to help the User navigate over it in the Output of Playbooks section by its own JSON Sample.


- Go to Response -> Playbooks -> create a new Playbook -> navigate the Output block and click it to configure.



- In the opened frame, find the expanded menu, called Playbook -> click the icon next to _.JsonResult.



- In the oppended frame choose the required field to extract. It will add Expression, using dot-notation. Click Save. Also you can use Add Functions to create combinations of Expressions.




Data filtering

The entire data filtering process for Google SecOps is exactly the same as in the Group-IB Threat Intelligence system.

To explore the filtering features for each collection - follow the steps below:

- Go to the REST API 2.0 page on the Group-IB Threat Intelligence portal.
- Find the required collection in the list on the left side of the window.
- Explore the information that describes the collection features.



Troubleshooting

First of all, as you begin the troubleshooting process, we kindly ask you to familiarize yourself with the common errors that occur when using our application. If errors occur outside of common cases, we will need more details for this purpose. To get to know what happened with the application on your side we need to gather information about your system, time when the error occurred and application logs. If you encounter any problems, please, follow the instructions below.

Common errors

To find detailed information about each of the common errors, please check the section Common errors solution.

- Google SecOps cloud can’t reach Group-IB Threat Intelligence portal.
- Group-IB token expired or wasn’t created.
- Group-IB account settings are not properly configured (IP addresses are not added to access list).
- Group-IB account collections access do not match to collections, chosen in the application.
- Client blocks incoming data from Group-IB portal (Client didn’t add necessary Threat Intelligence IP addresses to his access list).

Download logs

Downloading logs is the most important thing in troubleshooting. There is no direct option in Google SecOps to download log files but you can attach any error displayed in Google SecOps GUI as a plain text through the Email or Service Desk ticket.

Common errors solution

All necessary instructions can be found at the Integration manual page.

Google SecOps cloud can’t reach Group-IB Threat Intelligence portal

Execute the command below in the terminal, using your Group-IB username and Group-IB token credentials instead of LOGIN and API_KEY words.
curl 'https://tap.group-ib.com/api/v2/sequence_list' -u 'LOGIN:API_KEY' -H 'Accept: */*' -v
If your Group-IB and proxy credentials are correct, please attach output to Email or Service Desk ticket, we will check your Group-IB profile.


NOTE: If you have a proxy with authentication, add flag –proxy with relevant proxy configurations:
--proxy '<*protocol*>://<*user*>:<*password*>@<*IP address*>:<*port*>'.
If you have a proxy without authentication, add flag –proxy with relevant proxy configurations:
--proxy '<*protocol*>://<*IP address*>:<*port*>'For example, command can look as:
curl --proxy https://127.0.0.1:3128 'https://tap.group-ib.com/api/v2/sequence_list' -u 'mr.demo@group-ib.com:wYM2gZ4Tc' -H 'Accept: */*' -v.

Group-IB token expired or wasn’t created

Please make sure that your Group-IB token is active and ready to use. For that purpose check your account settings at Group-IB portal.

- Click the username in the upper-right corner and then go to the Profile tab.
- Go to the Security and Access tab -> Personal token.
- Click Generate token if you don’t have one or Generate new token if it is required.
- Click Save to submit changes.

Open your application API profile and insert a new Group-IB token in the form. API profile update form requires both of them.




Group-IB account settings are not properly configured

Please make sure that your Group-IB account settings are properly configured. For that purpose check your account settings at Group-IB portal.

- Click the username in the upper-right corner and then go to the Profile tab.
- Go to the Security and Access tab -> IP white list.

Please make sure that all your public IPs are listed in the box below. If something is missing - please, inform us via Email or Service Desk ticket. We will try to solve this issue promptly.



Group-IB account collections access does not match to collections, chosen in the application

Please make sure that your Group-IB collection settings match and you didn't overselect them. For that purpose please compare the application collections settings and collections listed at your account settings at Group-IB portal.

- Click the username in the upper-right corner and then go to the Profile tab.
- Go to the Security and Access tab.

Compare collections.

Client blocks incoming data from Group-IB portal

Please make sure that URLs and IPs listed in Starting Guide are added to the access list on your side.

LogRhythm

Python 3.10
Pytia

Before installing and configuring the integration, check out the start-up instructions in Group-IB TI Integration Starting Guide.

Installation

You can download application here

The application required Python 3.6.8+ installed on you system. Next python packages are required: pyaml, schedule, requests, urllib3, dataclasses.

Unpack archive and enter the application directory
cd group_ib_ti_logrhythm_siem
Install requirements

- Windows
  pip install -r requirements_windows.txt
- Linux
  pip install -r requirements_linux.txt

Configuration

Open configuration.yaml file and fill in missing fields.

Group-IB Threat Intelligence configuration
client: api_key: username: api_url: https://tap.group-ib.com/api/v2/ data_dir: C:\Program Files\LogRhythm\LogRhythm Job Manager\config\list_import
Proxy configuration
proxy: ip_addr: port: protocol: username: password:
Enable required collections items in the collection section

Enable required collection with enable: true or disable collection with enable: false. Set start date for each collection. Script will update seqUpdate section by its own. If you need fresh download, then set to null seqUpdate: null. You can use terminal dialog to configure collections. Use run_configuration.py script for that purpose.
collections: attacks/phishing_group: default_date: '2023-04-19' enable: true seqUpdate: null ioc/common: default_date: '2023-04-19' enable: true seqUpdate: null malware/cnc: default_date: '2023-04-19' enable: true seqUpdate: null ...
Date format

YYYY-MM-DD

Note: attacks/deface, attacks/ddos, attacks/phishing, compromised/bank_card_group, compromised/masked_card, compromised/account_group, suspicious_ip/open_proxy, suspicious_ip/socks_proxy, suspicious_ip/tor_node - are very large collections, and it is recommended to specify in the default_date field: 1-3 days ago.

Run the script

To start daemon process in the background (cron or task scheduler), use next command:
pythonw run_daemon.pyw
To run configuration dialog menu which helps you to configure collections, use next command:
python run_configuration.py
To run poller script in the terminal, use next command:
python run_single_poller.py

Automation

Tip: Use operating system (cron or task scheduler); opportunities to automate daily.

run_single_poller.py script execution. Or use run_configuration.py, run_daemon.pyw to do it automatically.

Configuration script steps

If you run run_configuration.py, please follow next steps.

- Configure API-key and Username in “Client info”.
- Select data root, by default it should be “LogRhythm\LogRhythm Job Manager\config\list_import”.
- Set the collection which you want to download “Collection info”.
- Set date from you want to get data “Collection info”.
- Run the script, it will automatically run background process, and you can close Command Prompt.
- Configure uploading file in LogRhythm following this name:

    - attacks_phishing_group_domain.txt,
    - suspicious_ip_tor_node_ip.txt,
    - suspicious_ip_open_proxy_ip.txt,
    - suspicious_ip_socks_proxy_ip.txt,
    - suspicious_ip_scanner_ip.txt,
    - suspicious_ip_vpn_ip.txt,
    - malware_cnc_ip.txt,
    - malware_cnc_domain.txt,
    - malware_cnc_url.txt,
    - ioc_common_ip.txt,
    - ioc_common_url.txt,
    - ioc_common_domain.txt,
    - ioc_common_hash.txt

Troubleshooting

- If you encounter problems, please retrieve logs from the log folder and attach them to Email or Service Desk ticket.

MISP

For the Group-IB - MISP integration, we have developed a Python script that downloads data from the Group-IB TI server and uses it to create MISP events.

Before installing and configuring the integration, check out the start-up instructions in Group-IB TI Integration Starting Guide.

Installation

You can download the integration here.

The application required Python 3.6.8+ installed on you system. App dependencies: pyaml, requests, urllib3, dataclasses, pymisp.

Extract the application

Extract and unpack archive whenever you want. Just make sure that you can reach vendor platform via HTTP/HTTPS requests.

Unpack archive and enter the application directory using the following command:

cd GroupIB_TI_MISP

Install requirements

Install local package **cyberintegrations**. Replace X.X.X with current lib version:

Windows:
pip install .\libs\cyberintegrations-X.X.X-py3-none-any.whl
Linux:
pip install ./libs/cyberintegrations-X.X.X-py3-none-any.whl
Install python packages from the PyPi.
pip install pymisp
Copy custom MISP-objects to the MISP server

Execute next commands to copy MISP-objects and make the files readable by the web user:
``` cp -r /MISP-objects/* /var/www/MISP/app/files/misp-objects/objects/ sudo chown -R www-data:www-data
/var/www/MISP/app/files/misp-objects/objects/gib-* ```
**Copy custom MISP-objects to the MISP server (docker)**

If you are using docker instance of MISP server then you can set up docker-compose.yml like,
misp: volumes: "/MISP-objects:/var/www/MISP-objects"
and then run the following commands:
docker exec -ti bash -c 'cp -r /var/www/MISP-objects/* /var/www/MISP/app/files/misp-objects/objects' docker exec -ti bash -c 'sudo chown -R
www-data:www-data /var/www/MISP/app/files/misp-objects/objects/gib-*'
**Update custom MISP-objects**

In the MISP interface go to the Global Actions -> List Object Templates and click the Update Objects button on the left side.

**Create MISP server API key**

Create MISP server API key using GUI. Go to MISP interface -> top panel -> Global Actions -> My Profile -> Auth keys -> Add authentication key.

## Configuration

Open docs/configs/endpoints_config.yaml with some text editor and fill in missing fields. Before proceed, please check again the Starting Guide at our TI portal.
```

Group-IB Threat Intelligence API configuration

The parameter username is a login to Group-IB TI. The parameter api_key can be generated on the TI portal at your profile.

ti_client: api_key: username:

Platform vendor API configuration

Fill in platform vendor Server configuration params.

misp: misp_key: misp_url: misp_verifycert: false

Proxy configuration

Fill in proxy configuration params, if required.

proxy: proxy_ip: proxy_port: proxy_protocol: proxy_username: proxy_password:

Enable required collections

The parameter default_date is used for initial start only. After the download process begins it will not be used anymore. Instead of default_date we will use seqUpdate parameter to iterate over the next portion. It is technical field. If you need fresh initial start based on the default_date, please set seqUpdate parameter to null.

To start download process for any collection, you need to enable it first. Set enable parameter to true. Set default_date parameter in single quotes, if needed or leave it as null. By default, it is set to 3 days back to the present time.

collections: attacks/ddos: default_date: '2021-08-01' enable: true seqUpdate: null attacks/phishing: default_date: '2021-08-01' enable: true seqUpdate: null ioc/common: default_date: '2021-08-01' enable:true seqUpdate: 16747401659568 ...

Date format

Default date format.

'YYYY-MM-DD'

Notes

Note: To use Firewall rules mode only, enable next collections: ioc/common, attacks/ddos.

Note: The ioc/common collection contains IoC only and based on malware/cnc, hi/threat, apt/threat, hi/threat_actor, apt/threat_actor collections.

Note: attacks/deface, attacks/ddos, attacks/phishing_group, compromised/bank_card_group, compromised/masked_card, compromised/account_group, suspicious_ip/open_proxy, suspicious_ip/socks_proxy, suspicious_ip/tor_node - are very large collections, and it is recommended to specify in the default_date field: 1-3 days ago.

Extra MISP server settings

Tags and options

You can find all available tags in the MISP interface go to the Event Actions -> List Tags.

Each collection can be marked with its own tag. Set local_custom_tag parameter in single quotes, if needed or leave it as null.

collections: attacks/ddos: local_custom_tag: null attacks/phishing: local_custom_tag: 'My Phishing Tag' ioc/common: local_custom_tag: 'Just 100% IoC' ...

The extra_settings section contains configuration related to MISP side.

- misp_distribution - can be set on the next levels:

.

0: Your organization only.

- 1: Your community only.
- 2: Connected communities.
- 3: All communities.
- 4: Shared group.

- misp_global_custom_tag - all data that is coming from the app can be marked with its own tag. Set misp_global_custom_tag parameter in single quotes, if needed or leave it as null.
- misp_published - could be set to true to publish events by default or false to leave them unpublished.
- misp_sharing_group_id - you can find in your interface go to Global Actions -> List Sharing Groups tab -> ID column. This option will work only with misp_distribution set to 4.

extra_settings : misp_distribution: 0 misp_global_custom_tag: null misp_published: false misp_sharing_group_id: 0 ...

Intrusion Detection System (IDS) and correlations

You can customize the IDS to suit your needs if you don't like how it's set up. In the app itself you can find MISP-objects folder and the custom objects in it. Modify them and follow the instructions in Installation section at Copy custom MISP-objects to the MISP server subsection.

As an example, open GroupIB_TI_MISP/MISP-objects/gib-malware/definition.json file. Set "to_ids" parameter to true or false (where the "name" nested to "attributes").

The same way you can reconfigure correlations. Set "disable_correlation" parameter to true or false.

{ "description": "Malware information", "meta-category": "misc", "name": "gib-malware", "required": ["name"], "uuid": "242cbc72-793e-4294-86a7-558ce041ecdd", "version": 2, "attributes": { "object-id": { "description": "Object ID in the Group-IB TI", "disable_correlation": true, "to_ids": false, "misp-attribute": "text", "ui-priority": 1 }, "name": { "description": "Malware name", "disable_correlation": false, "to_ids": true, "misp-attribute": "text", "ui-priority": 0, "multiple": true } } }

Extra collections settings

Ignore data upload

To prevent DDOS attacks without malware or Threats without indicators from being uploaded to the MISP server, set next params to true:

extra_settings: ignore_non_malware_ddos: true ignore_non_indicator_threats: true

Task scheduling automation

Use operating system (cron or task scheduler) opportunities to automate daily poller.py script execution. You can use Cron (for Unix-based systems) or Task Scheduler (for Windows).The User must have appropriate rights.

Cron:

- Open file /etc/crontab
- Set the following job:

0 0 * * * cd %% && %%/python %%/poller.py

This job will start polling daily at midnight.

Task Scheduler:

- Create a new file GIB_poller.bat with the following content:

"%%" "%%\poller.py" pause

- Go to Control Panel -> Administrative Tools -> Task Scheduler.
- Choose the Create Task option.
- Fill in the task name and description.
- In the Triggers tab create a new daily trigger and set it to be repeated each 12 hours for an infinite amount of days.
-

In the Actions tab add a new action and select the .bat file created on the first step.

- Click the Ok button.

The script scheduler opportunity

To run script via Task Scheduler install local package schedule for Windows.

Windows:

pip install .\libs\schedule-1.1.0-py2.py3-none-any.whl

And run the script via **PythonW**:
`pythonw run_daemon.pyw`
Also, you can set upload start time via configuration file. Task Scheduler start time can be configured in docs/configs/endpoints_config.yaml file. Set schedule_time parameter to required value (16:00, 00:00, etc.) in extra_settings section.
extra_settings: schedule_time: 00:00 ...

Troubleshooting

- If you encounter problems, please retrieve logs from the log folder and attach them to Email or Service Desk ticket.
- If you have problems with proxy configuration, attach the proxy environment by executing this command:
  printenv | grep proxy

FAQ

- How to add Group-IB as a creator/owner org?

  Create a company that represents us, and a user inside this company with appropriate rights and use his API key in the integration.
- Where I can find reports from last threats?

  They are separated similarly to TI interface. hi/threat stands for Cybercriminals and apt/threat stands for Nation-State.
- What tags we are using for our events?

  Besides tags, that you can set in the configuration, we are using:
  - collection name (but with spaces instead of "_" or "/") - admiralty codes and TLP, where applicable - for **osi/vulnerability** we add affected products as tags - for **hi/threat** and **apt/threat** we add "Tailored" tag, similar to the TI portal
- Why app raise an access deny error in logs?

  Please check that MISP user has correct rights and access. Also, please check if you install integration app separate from the MISP server virtual machine. MISP server is a separate app which control its folders rights.

ThreatConnect

The integration allows receiving feeds from Group-IB Threat Intelligence and transforming them into ThreatConnect Groups and Indicators objects. These objects use extra Attribute Types, which should be uploaded via the attributes.json file manually at Gear Icon -> System Settings -> Attribute Types, or will be uploaded automatically if your system allows you to see listed ThreatConnect Marketplace apps.

Current application type - Job App. The ThreatConnect Platform provides the ability for customers to schedule applications as jobs, specifically known as Job Apps, that can be run at configured intervals.

Before installing and configuring the integration, check out the start-up instructions in Group-IB TI Integration Starting Guide.


Installation

Before you begin, ensure you have access to the Group-IB TI Portal -> Integrations section, where you can find the ThreatConnect tab and download link, or access to the public ThreatConnect GitHub repository. There you need to download the application .tcx archive and install it in your ThreatConnect system.

Step 1: Download the appropriate version of the integration here.

Step 2: Create a ThreatConnect API User

- Login to the ThreatConnect web interface as an administrator.
- Click the Gear icon (top right) -> Organization Settings.
- In the Membership tab, click Create API User.




Step 3: Install the Application

- Go to Gear Icon -> Organization Settings -> Apps.
- Click Install App.
- Upload the .tcx file.
- Click Install.

Step 4: Verify Installation

- Ensure you have the correct Group-IB TI username and API token. Check the Group-IB Starting Guide for more info.
- Once installation is complete, you should see the “Group-IB Threat Intelligence (vx.x.x)” app at Gear Icon -> Organization Settings -> Apps tab -> Add Job menu -> Run Program dropdown.



Step 5: Create a Job: follow the instructions in the next Configuration section to create a new job for the app.

Configuration

The configuration process includes several steps. The first step is to create a Job App based on the integration app. The second step concerns configuring collections. Each collection is a set of data that contains different information for each type of attack. You can find a more detailed description at our Group-IB TI Portal.

Before you begin


- Ensure you are running a supported version of the ThreatConnect Platform.
- Verify that the TC Group-IB TI application has been installed without errors.
- Make sure you have valid Group-IB and ThreatConnect API credentials.

General information


The TC GroupIB TI application is based on requests to the Group-IB TI Portal API, gathering data and uploading it to the ThreatConnect Platform. Requests gather information from different collections, which are listed in Job App configuration steps. Each collection has Initial date and Sequence update number parameters.

Step 1. Add new Job

- Go to Gear Icon -> Organization Settings -> Apps tab -> Add Job menu -> Run Program dropdown. Enter the Job name and select the app Group-IB Threat Intelligence (vx.x.x). Click Next.




- Fill in ThreatConnect API User, ThreatConnect Owner and Group-IB credentials (Group-IB Login, Group-IB API Key) in the Parameters tab.
- Enable Attach Group-IB portal links per your preference (enabled by default).
- Enable required collections and set the Initial date of data collection. Click Next.



- Configure the Schedule tab with the daily option and click Next.
- Configure the Output tab and click Save.
- Activate created Job to set scheduled run in the background or run it once to check.

Step 2. Collections configuration

All listed collections can be enabled and run as one separate Job or can be configured as one Job for each collection. This option is available as API requests 1-second limit applies only to one collection, but can run in a separate thread.



Here in the example on the screenshot how you can mark collections you need, to get data from Threat Intelligence. Gathered data will be transferred to the ThreatConnect Groups and Indicators objects and uploaded to the system. Mark the required collection using the checkbox. After finishing the configuration process, click “Next” and finish a Job creation.

Collection Parameters

- Initial date - the “starting point” of the collection data download process. When the download process starts this date will be ignored and iteration over collection data will be based on “Sequence update number”. So if you need to change this date and get a fresh download process you need to set “Sequence update number” to “None”.
- Sequence update number - Each row in our database has its own unique sequence update number. So, we can get all the events one by one, using the iteration. This number helps to fix the “end point” of data for the last day and continue iteration on the next day with new data. The “Sequence update number” accepts values “None”, “0” or a random number (e.g.17083410361167). One of these values is required. An empty “Sequence update number” field will raise an error.
- Optional fields (for selected collection only):
  - Apply Hunting Rules (Optional) - collections data will be filtered according to the hunting rules you’ve set up in Group-IB Threat Intelligence.
  - Is in combolist or a unique record (Optional, **compromised/account_group collection**) - Combolist entries come from collections of usernames and passwords that have been compiled from various sources, do not have compromise date and usually assign low Admiralty. Unique entries come from singular detections and therefore have compromise date and higher Admiralty. N.B: selecting both filters is equal to selecting none. One will see a full set of data without filtering.
  - Probable corporate access (Optional, **compromised/account_group collection**) - special filtering option for compromised/account_group collection. Data will be filtered in according to your corporate settings Group-IB Threat Intelligence.
  -

Has password (Optional, **compromised/breacheddb collection**) - Boolean (default off). On -> has_password=1: only breach records that include a password.

- IOC type (Optional, **ioc/primary collection**) - Choice all / network / file (default all). Restricts the IoC Primary feed to network indicators or file indicators; all sends no filter.
- Suspicious payment type (Optional, **compromised/spd collection**) - Choice: all / Cryptocurrency Wallet / Bank Account Number / Mobile number / IBAN / Bank card / Unknown / QR payment string (default all). Filters Suspicious Payment Details to a single payment-detail type; all sends no filter.
- Malware with description (Optional, **malware/malware collection**) - 3-state Choice: API default / true / false. Include or exclude the malware long-description field; API default sends nothing.

How Data Pull Works

- When a job starts, it retrieves the latest Sequence update number based on the chosen Initial date.
- Data is downloaded in small portions.
- After each portion, the application stores a new Sequence update number for use in the next run.
- On the next scheduled execution, the job resumes from the last stored Sequence update number-the Initial date is no longer used.

Resetting the Collection

To restart collection from a new Initial date:

- Set the new Initial date.
- Change Sequence update number to None.
- Save changes.
- Run the job manually or wait for the next scheduled run.

Storage Considerations


Some collections can grow rapidly (e.g., Attacks -> DDoS, Compromised -> Bank Cards / Masked Cards, Suspicious IPs, IoC). Plan your ThreatConnect TIP storage capacity accordingly.

Usage

All downloaded feeds from Group-IB Threat Intelligence are stored in Groups and Indicators within ThreatConnect.


To access this data:

- Click the Search & Create tab in the top panel.
- Select Indicators or Groups.
- A data table with additional details will open.




Viewing Indicators / Groups Details

- Select any row in the data table to expand the overview tab.
- The Overview tab displays:
  - Security label
  - First seen
  - Date added
  - Last modified
  - Description
  - Attributes
  - and other relevant fields.




Associations Tab The Associations tab lists all related data for the selected indicator or group, including:

- TQL Queries
- Groups
- Indicators
- and other linked objects



Dashboard View The Dashboard tab (top panel) provides widgets with plots and diagrams summarizing events and activity. The following widgets are available:

- My Recent History
- Intelligence Breakdown
- Source Composition
- Intelligence Lookup
- Intelligence ROI
- Indicators Observed (Past 24 Hours)
- My Open Tasks
- Intelligence Creation



Dashboards and widgets can be fully customized to match your needs.

Data filtering

Once the configuration is complete, the following sourcetypes become available in TC. All data received from a particular collection is marked with special tags. The table below displays the mapping of Group-IB collections into Groups and Indicators presented in ThreatConnect Platform. Note: If you're using a POC or partner license, access to data is limited to 30 days. The recommended date ranges below are guidelines and can be adjusted according to your needs.

Collection	Description	TC data type	Tag
APT :: Report	Reports on nation-state APTs activities, including associated indicators (IOCs), attack techniques, and MITRE ATT&CK mappings.	Campaign	APT/Threat
		Intrusion Set	APT/Threat Actor

Collection	Description	TC data type	Tag
		File	APT/Threat
		URL	APT/Threat
		Address	APT/Threat
		Host	APT/Threat
APT :: Actors	Profiles of nation-state groups detailing their characteristics, targets, motivations, and techniques.	Intrusion Set	APT/Threat Actor
Attacks :: DDoS	Data on Distributed Denial of Service (DDoS) attacks, including targeted resources and attack durations.	Incident	Attacks/DDOS
		Address	Attacks/DDOS, CNC, DDOS
Attacks :: Deface	Records of defacement attacks, highlighting compromised websites and related actors.	Report	Attacks/Deface
		URL(defaced site)	
Attacks :: Phishing	Information on phishing attacks, including URLs of phishing websites. Note: do not use IPs for detection - it may cause many false positives. Focus only on URLs.	Incident	Attacks/Phishing
		URL	

Collection	Description	TC data type	Tag
Attacks :: Phishing Kit	Collections of phishing website templates, scripts, and configurations used by attackers.	Incident	Attacks/Phishing Kit
		URL	
		E-mail	
Compromised Data :: Shops	Sales proposals on compromised data on darkweb marketplaces	Report	Compromised Data/Shop
		URL	
		Address	
Compromised Data :: Accounts	Data on compromised access (credentials, malware infections) sold in darkweb marketplaces	Report	Compromised Data/Account
		URL	Compromised Data/Account, CNC
		Address	Compromised Data/Account, CNC
		Host	Compromised Data/Account, CNC

Collection	Description	TC data type	Tag
Compromised Data :: Bank Cards	Information about compromised bank cards, sourced from card shops, forums, and public leaks.	Report	Compromised Data/Bank Card
Compromised Data :: Masked Cards	Information on compromised masked bank cards gathered from illicit marketplaces and forums.	Report	Compromised Data/Masked Card
IM :: Discord	Extracted intelligence from Discord channels and servers, mostly discussions.	Report	Compromised Data/Discord
IM :: Telegram	Intelligence collected from Telegram channels, including credentials, targeted companies and attack discussions.	Report	Compromised Data/Telegram
Compromised Data :: SPD	Data on suspicious payment details (SPD) - bank accounts, crypto wallets, phone numbers and other data used for laundering/illicit/stolen funds	Report	Compromised Data/Suspicious payment details
Darkweb::Forums	Darkweb forum posts.	Report	Darkweb/Forums
Open Threats	This feed aggregates real-time public reports on cybersecurity threats from diverse sources, including vendor blogs and social networks.The data is enriched with our private threat intelligence and categorized by threat actors, malware families, and other key identifiers, providing comprehensive global threat coverage.	Campaign	HI/Open Threats

Collection	Description	TC data type	Tag
		File	
		Address	
		Host	
		E-mail	
Cybercriminals :: Report	Financially motivated cybercriminals reports, including associated indicators (IOCs), attack techniques, and MITRE ATT&CK mappings.	Campaign	HI/Threat /Threat
		Intrusion Set	HI/Threat /Threat Actor
		File	HI/Threat /Threat
		URL	HI/Threat /Threat
		Address	HI/Threat /Threat
		Host	HI/Threat /Threat
Cybercriminals :: Actors	Profiles of financially motivated cybercriminals detailing their characteristics, targets, motivations, and techniques.	Intrusion Set	HI/Threat Actor

Collection	Description	TC data type	Tag
IOC :: Common	General indicators of Compromise (IoCs) from threat reports (cybercriminals and APT) and Malware sections. Consists of Hashes (MD5, SHA1, SHA256), IPs, domains and URLs. Major source of IOCs	Campaign	IoC/Common
		File	
		URL	
		Address	
IOC::Primary	Same as IOC::Common; Enriched with evaluation block and risk score for each IOC	Campaign	IoC/Primary
		File	
		URL	
		Host	
		Address	
Malware :: C2	Information on malware Command-and-Control (C&C) servers used for data exfiltration and command distribution. This feed is also part of IOC Common	URL	Malware/CNC, CNC
		Address	
		Host	
Malware :: Configs	Extracted malware configuration data.	Report	Malware Config

Collection	Description	TC data type	Tag
		File	Malware, Malware Config
		Host	
		Address	
Malware :: Report	Detailed malware descriptions.	Report	Malware Report
Malware :: Signature	Suricata signatures for malware detection.	Signature	Suricata, Signature
Malware :: Yara rule	YARA rules for identifying specific malware families.	Signature	YARA, Signature
Compromised Data :: Git Leaks	Publicly available code from repositories like GitHub, filtered by your hunting rules. Note: hunting rules are on by default here	Incident	OSI/Git Leak
Compromised Data :: Public Leak	Public data leaks from sources like Pastebin, ghostbin, and others., including credentials, database dumps, configuration files, and logs. Note: hunting rules are on by default here	Incident	OSI/Public Leak
OSI :: Vulnerability	Information on software vulnerabilities, associated exploits, and available proof-of-concept details.	Vulnerability	OSI/Vulnerability
Suspicious IP :: Open Proxy	Information on publicly available proxy servers, including potentially misconfigured proxies.	Address	Open Proxy

Collection	Description	TC data type	Tag
Suspicious IP :: Scanners	IP addresses identified as scanning or probing corporate networks.	Address	Scanner
Suspicious IP :: Socks Proxy	IP addresses of infected hosts configured as SOCKS proxies used for anonymized attacks.	Address	Socks Proxy
Suspicious IP :: Tor Node	Data about known Tor exit nodes used as anonymity relays.	Address	Tor Node
Suspicious IP :: VPN	Information about public and private VPN servers identified as potentially malicious or suspicious.	Address	VPN

Note: Collection IOC :: Primary - is specially created to get only IoC and has different attribution parameters in place. Contains information from the following collections: [APT:: Report, APT :: Actors, Cybercriminals :: Reports, Cybercriminals :: Actors, Malware :: C2]. It is possible to find correlations between collections but this is not the case. The main idea of IOC :: Primary collection is to use it for detection rules. It is a replacement for IOC :: Common, so you don't need to use both in parallel.

Troubleshooting

First of all, as you begin the troubleshooting process, we kindly ask you to familiarize yourself with the common errors that occur when using our application. If errors occur outside of common cases, we will need more details for this purpose. Before starting, please review the Common Errors and Solutions listed below - if your issue is not listed, gather the following details for support:

- Your system information
- The exact time the error occurred
- Application logs (see “Log Collection” section)

Enable Debug Logging

Before collecting logs, enable debug mode for the failed job:

- In ThreatConnect, go to Organization Settings -> Apps tab -> Jobs.
- Locate the job related to the Group-IB TI integration.
- Edit the job configuration and change log level to debug.
- Save the changes and allow the job to run again so debug entries are written to the logs.


Log Collection

When contacting support, always include application logs:

- Go to Organization Settings -> Apps tab -> Jobs.
- Expand the settings for the failed job.
-

Select View Log.

- Click Download to save the log file.
- Attach the log to your support request via Email or Service Desk.



Testing API Connectivity via cURL

To verify that your Group-IB TI credentials are valid and the API is accessible, run the following curl command from your terminal: curl 'https://tap.group-ib.com/api/v2/sequence_list' -u 'LOGIN:API_KEY' -H 'Accept: */*' -v

- Replace with the email address used for your Group-IB Threat Intelligence account.
- Replace with your personal API key (not your password).

If authentication succeeds, you'll receive a list of available collections. If it fails, refer to the HTTP status code and the "Common Errors & Solutions" section below.

If your Group-IB and proxy credentials are correct, attach the command output to your support request via Email or Service Desk so we can verify your Group-IB profile. Using a proxy:

- With authentication:
  - --proxy '://:@:'
- Without authentication:
  - --proxy '://:'

Example: curl --proxy https://127.0.0.1:3128 'https://tap.group-ib.com/api/v2/sequence_list' -u 'LOGIN:API_KEY' -H 'Accept: */*' -v

Common Errors and Solutions

Issue	Resolution
ThreatConnect token expired or missing	Go to Gear -> Org Settings -> Membership tab and ensure the API token exists and is active. Renew if expired.

Issue	Resolution
Group-IB API key expired or missing	In the Group-IB TI Portal, go to Profile -> Security and Access -> Personal Token, generate a new token, and update it in the job configuration.
Server cannot reach Group-IB TI Portal	Run the cURL test from the ThreatConnect server. If using a proxy, verify configuration. If needed, test from another machine and whitelist its IP.
Group-IB account settings misconfigured	In Profile -> Security and Access -> IP Whitelist, ensure all ThreatConnect server IPs are listed.
Mismatched collection access	Verify that the collections enabled in ThreatConnect match those granted in your Group-IB account.
License expired or Partner/POC limitation	Check your license status. Partner/POC licenses typically expire in 30 days.
Client blocking incoming data	Add all URLs and IPs listed in the Group-IB TI Integration Starting Guide to your firewall or proxy allowlist.
API key errors	Regenerate the API key and copy it without extra spaces or hidden characters.

Data Input Error Code (HTTP) in TC

When configuring or running the Group-IB Threat Intelligence Data Input in TC, the app communicates with the Group-IB API. If something goes wrong, HTTP status code will appear in your logs. Below are common error code and how to resolve this:

Code	Cause	Solution
403: Forbidden	Authenticated, but denied access	Ensure the TC server IP is in your access list in the Group-IB profile. Confirm the API key is valid and has permissions for the selected collections. Use curl to test other endpoints.
429: Too Many Requests	API rate limit exceeded.	Reduce request frequency. The allowed rate depends on your license. Wait a few minutes and retry.

ArcSight SIEM Connector

ArcSight SIEM Connector

The integration connects Group-IB Threat Intelligence to ArcSight, giving security teams a continuous stream of external threat data across multiple feed types - each suited to different SOC workflows:

- Indicators of compromise feed directly into correlation rules and alert enrichment.
- Compromised credential and card data can drive automated responses when employee or customer accounts appear in breaches.
- APT and cybercriminals reports with full MITRE ATT&CK mapping support threat hunting and actor attribution.
- Attack campaign feeds provide early warning for brand and infrastructure threats.
- Suspicious IP feeds populate active lists for real-time blocking, while malware and C2 data enable correlation against known adversary infrastructure.

Technically, a Python poller fetches data from the Group-IB TI portal and writes JSON files to a local folder, which the ArcSight FlexConnector monitors and forwards as structured CEF events to the Logger.

Note: Initial Steps must also be completed before proceeding.

Requirements

- ArcSight FlexConnector 7.7.0.8044.0 or newer (JSON Folder Follower)
- Docker >= 24 with the Compose plugin (recommended), or Python 3.10+ installed with the following modules: black==24.10.0 certifi==2024.12.14 charset-normalizer==2.0.12 ciaops==1.0.1 click==8.1.8 dataclasses==0.6 idna==3.10 isort==5.13.2 mypy-extensions==1.0.0 packaging==24.2 pathspec==0.12.1 platformdirs==4.3.6 pyaml==21.10.1 python-dotenv==1.0.1 PyYAML==6.0.2 requests==2.32.3 tomli==2.2.1 typing_extensions==4.12.2 urllib3==1.26.9
- Threat Intelligence credentials (username + API key) with access to the collections you intend to enable

Configuration

Copy the example config and open it for editing.

Docker
cp .env.example .env $EDITOR .env
Set your credentials:
GIB_USERNAME= GIB_API_KEY=
Enable the collections you want:
GIB_COLLECTIONS_IOC__COMMON_ENABLE=true GIB_COLLECTIONS_IOC__COMMON_DEFAULT_DATE=2026-01-01
Encoding rule: collection names use __ (double underscore) in place of /, uppercased. For example: apt/threat -> GIB_COLLECTIONS_APT__THREAT_ENABLE

PII redaction: by default, sensitive fields (passwords, emails, card numbers) are redacted before data reaches ArcSight. This is controlled by two settings:
GIB_REDACT_PII=true # true (default) = redact. Recommended for production. # false = send plaintext. Only for trusted environments # or IR workflows that need raw values. GIB_REDACT_KEY= # HMAC secret for reproducible hashing across runs. # Generate once: openssl rand -hex 32 # Leave blank to auto-generate per process start # (hashes then change on restart; cross-run joins break).
Note: GIB_REDACT_KEY is ignored if GIB_REDACT_PII=false.

All collections default to false - an unconfigured deploy fetches nothing. Enable only collections your API key has been granted access to.

Bare-metal/VM

cp configuration.sample.yaml configuration.yaml $EDITOR configuration.yaml

Fill in your credentials and enable collections:

client: username: api_key: redact_pii: true redact_key: collections: ioc/common: enable: true default_date: 2026-01-01

Note: If default_date is not set, the initial poll starts from 3 days ago. Avoid a very early start date for high-volume collections such as suspicious_ip/*.

Deploy

Download the Group-IB Threat Intelligence SIEM Connector for ArcSight from here and unpack it.

Docker

- Build and start the container:
  docker compose up -d --build
- Check it is running:
  docker compose logs -f gib-poller

JSON files will appear in ./data on the host. The FlexConnector should be pointed at this directory.

Note: The container runs as non-root UID 10001. Create the required directories first:

mkdir -p data logs state sudo chown -R 10001:10001 data logs state

The container includes a healthcheck that verifies the data/ directory is accessible. You can monitor container health with:

docker compose ps

Bare-metal/VM

- Install dependencies:
  pip install -r requirements.txt
- Run the poller from the working directory:
  cd /opt/current/arcsight/connectors/gib python3.10 GIB_poller.py
- Schedule it to run hourly via cron:
  5 * * * * cd /opt/current/arcsight/connectors/gib && \ flock -n .gib_poller.lock python3.10 GIB_poller.py >> logs/cron.log 2>&1

ArcSight FlexConnector Setup

Create a Receiver

- Log in to the ArcSight web interface.
- Go to Configuration -> Receivers -> Add.
- Set Type to SmartMessage Receiver, encoding UTF-8, source type CEF.
- Enable, save, and note the Receiver Name.

Configure the FlexConnector

- Before running runagentsetup.sh, copy all configs/*.jsonparser.properties into /current/user/agent/flexagent/gib_root_parser/
- Run the setup wizard:
  ./runagentsetup.sh -i console
- In the wizard, select Add a connector -> ArcSight FlexConnector JSON Folder Follower and set:
  - JSON Log Folder Location: the path to the data/ directory (host path of the ./data bind mount for Docker, or the working directory for Bare-metal/VM)
  - JSON Configuration File Name Prefix: configs/gib_root_parser

  Note: The “Folder does not exist” warning is harmless if the poller has not run yet.
-

Set destination to ArcSight Logger SmartMessage (encrypted), enter host:port, Receiver name from above, Compression Disabled, CEF Version 0.1.

- Fill in metadata (Name, Location, DeviceLocation, Comment) - avoid empty or digits-only values.
- Install as a service and start it:

service arc_ start

Verify Data Flow

In ArcSight web UI go to Analyze -> Search and run:

receiver=""

If events appear, the integration is working correctly.

Working with the Integration

Enabling and Configuring Collections

Each collection is toggled independently. Open your .env (Docker) or configuration.yaml (Bare-metal/VM) and enable the collections you need.

Docker

GIB_COLLECTIONS_APT__THREAT_ENABLE=true GIB_COLLECTIONS_APT__THREAT_DEFAULT_DATE=2026-01-01 GIB_COLLECTIONS_IOC__COMMON_ENABLE=true

Bare-metal/VM

collections: apt/threat: enable: true default_date: 2026-01-01 ioc/common: enable: true

The default_date field sets how far back the first poll reaches. If omitted, it defaults to 3 days ago. After the first run the poller tracks its own position - changing default_date later has no effect unless you delete the .state checkpoint file.

Note: For high-volume collections such as suspicious_ip/*, set a recent default_date (e.g. last 2 days) to avoid ingesting an overwhelming backlog on the first run.

After editing .env, apply the changes:

docker compose up -d

Checking the Poller is Running

Docker

docker compose ps docker compose logs --tail 50 gib-poller

Bare-metal/VM

pgrep -af GIB_poller tail -50 logs/current_session_poll.log

Result

A healthy run produces lines like:

[INFO] apt/threat - 12 portions fetched, seqUpdate 1735200000 [INFO] ioc/common - 3 portions fetched, seqUpdate 1735200100

If a collection is skipped with a not granted warning, your API key does not have access to it.

To confirm JSON files are being written:

ls -lh data/

Files follow the naming pattern:

___.json



Adjusting Poll Frequency

By default the poller runs hourly (Bare-metal/VM via cron) or every 900 seconds (Docker loop mode). To change the Docker interval:

```
GIB_POLL_INTERVAL=1800   # 30 minutes
```

To switch to one-shot mode (useful if you prefer to drive execution from an external scheduler):

```
GIB_RUN_MODE=once
```

Querying Data in ArcSight

Log in to the ArcSight web interface and go to Analyze -> Search.

See all events from this integration:

```
receiver=""
```

Filter to a specific collection:

```
receiver="" AND name CONTAINS "apt/threat"
```

Search within a time range:

```
receiver="" AND deviceReceiptTime >= 2026-01-01T00:00:00
```

Find events for a specific indicator:

```
receiver="" AND destinationAddress = "192.0.2.1"
```

Filter by threat category:

```
receiver="" AND deviceEventCategory CONTAINS "Malware"
```

Resetting a Collection

To re-fetch a collection from scratch, delete the .state checkpoint file and restart the poller. The next run will treat default_date as the starting point again.

Docker

```
docker compose stop rm state/.state docker compose up -d
```

Bare-metal/VM

```
rm .state python3.10 GIB_poller.py
```

Available Collections

The table below lists all collections available for ingestion. Enable only those your API key has been granted access to.

Collection	Contents	Notes
apt/threat		

Collection	Contents	Notes
	APT threat reports with MITRE ATT&CK mapping	
apt/threat_actor	APT actor profiles - TTPs, targets, infrastructure	
hi/threat	Cybercriminals threat reports with MITRE mapping	
hi/threat_actor	Cybercriminals actor profiles - TTPs, targets, infrastructure	
attacks/ddos	DDoS campaign records - target, dates, method	
attacks/deface	Web defacement campaigns - target domain, actor	
attacks/phishing_kit	Phishing kit fingerprints and hosting infrastructure	
compromised/account_group	Compromised credentials from stealer logs. Emails and passwords are redacted before writing to disk.	High volume - set a recent default_date
compromised/bank_card_group	Compromised payment cards. PAN is masked (first6-last4).	
compromised/breacheddb	Breached database records - email domain, location, phone, IP. Supersedes the legacy breached collection.	High volume - set a recent default_date
compromised/mule	Money mule records (legacy collection)	Auto-skipped if not granted
compromised/spd	Stolen personal data - type, service type, IBAN, bank card, linked threat actor and malware	

Collection	Contents	Notes
ioc/primary	Primary curated IOCs with per-indicator risk scores (domain, URL, IP, hash) plus linked threat actor and malware family	
ioc/common	Aggregated indicators of compromise - IPs, domains, URLs, hashes	
malware/malware	Malware sample reports - family, behaviour, targeted sectors	
malware/cnc	C2 infrastructure - IPs, domains, protocols	
osi/git_repository	Leaked credentials and secrets found in public Git repositories	High volume - set a recent default_date
osi/public_leak	Sensitive data found in public paste sites and forums	High volume - set a recent default_date
suspicious_ip/tor_node	Tor exit node IP list	Very high volume - use a recent default_date
suspicious_ip/open_proxy	Open HTTP/HTTPS proxy IPs	Very high volume - use a recent default_date
suspicious_ip/socks_proxy	SOCKS proxy IPs	Very high volume - use a recent default_date

Troubleshooting

No Events Appearing in ArcSight Search

Issue	Likely cause	Fix
Query returns no results	FlexConnector service not running	Run: service arc_<name> status - start it if stopped
Service is running but no data	Wrong JSON Log Folder Location in FlexConnector config	Re-run runagentsetup.sh and verify the path matches the actual data/ directory
Service running, path correct, still no data	Poller has not run yet or is not producing files	Check data/ for .json files. If empty, run the poller manually and check logs/current_session_poll.log
Events arrive but CEF fields are empty	.jsonparser.properties files not in place before setup	Stop the service, copy all configs/*.jsonparser.properties to flexagent/gib_root_parser/, restart

Authentication & API Errors

Issue	Likely cause	Fix
401 Unauthorized in logs	Wrong or expired API key	Regenerate the token in the TI portal and update .env or configuration.yaml

Issue	Likely cause	Fix
Collection skipped with “not granted” warning	API key does not have access to that collection	Disable the collection or contact Group-IB to extend access
Connection timeout or SSL error	Proxy or firewall blocking outbound HTTPS to tap.group-ib.com	Configure proxy settings via GIB_PROXY_* in .env or the proxy section in configuration.yaml

Docker-Specific Issues

Issue	Likely cause	Fix
Container exits immediately on start	Missing or malformed .env file	Verify .env exists and GIB_USERNAME / GIB_API_KEY are set. Run: docker compose logs gib-poller
Permission denied writing to data/ or logs/	Host directories not owned by UID 10001	Run: sudo chown -R 10001:10001 data logs state
ciaops not found during image build	No internet access and vendor/ wheel is missing	Place ciaops-1.0.1-py3-none-any.whl in vendor/ and rebuild

Issue	Likely cause	Fix
FlexConnector cannot see new JSON files	data/ bind mount path mismatch between container and connector host	Ensure the FlexConnector JSON Log Folder Location points to the same host path as the ./data bind mount
docker compose ps shows container as unhealthy	data/ directory missing or not accessible inside the container	Check that the ./data bind mount was created before starting: mkdir -p data && sudo chown -R 10001:10001 data

Collections Returning No Data

Issue	Likely cause	Fix
Collection enabled but no events appear	default_date set too far in the past for a high-volume collection	Set a more recent default_date, delete .state to reset the checkpoint, and restart the poller
Some collections work, others do not	Mixed access rights on the API key	Check logs/current_session_poll.log for per-collection skip or error messages


Issue	Likely cause	Fix
Data stops arriving after running fine	Poller process crashed or cron job stopped	Docker: docker compose ps. Bare-metal/VM: pgrep -af GIB_poller and check cron logs

PII Redaction Issues

Issue	Likely cause	Fix
Emails and passwords arriving in ArcSight as plaintext	GIB_REDACT_PII set to false, or not set in an older config	Set GIB_REDACT_PII=true in .env (Docker) or redact_pii: true in configuration.yaml. Restart the poller.
Hashes differ between runs for the same email	GIB_REDACT_KEY is blank - a new random key is generated each process start	Set GIB_REDACT_KEY to a stable secret (openssl rand -hex 32). Store it as a secret and reuse across restarts.
Need plaintext values for an IR investigation	Production redaction settings active	Set GIB_REDACT_PII=false temporarily in a controlled environment. Ensure Logger access controls are in place. Revert after the investigation.

Custom API tools
TI Data Export Utility

This guide provides step-by-step instructions on how to install, configure and use the Group-IB TI Data Export Utility for exporting attributed and non-attributed threat intelligence data in various formats.



Glossary

EU (Export Utility) Refers to the Group-IB TI Data Export Utility used for retrieving and exporting threat intelligence data.

AD (Attributed Data) Exported threat intelligence data that includes attribution details such as threat actor names, malware families, or source references.

IoC (Indicator of Compromise) Non-attributed technical indicators such as IP addresses, domains, file hashes, or filenames used for threat detection.

seqUpdate A mechanism that supports incremental export, ensuring the tool continues from the last exported record and avoids reprocessing already exported data.

TI (Threat Intelligence) Group-IB's platform for collecting, analyzing, and distributing cyber threat intelligence.

Collection A defined data stream or dataset within the Threat Intelligence platform (e.g., hi/threat, attacks/deface) from which data can be exported.

Keyword Filtering An optional setting that allows filtering of export results based on the presence of specific keywords in certain fields (e.g., expertise, tags).

BI Tools (Business Intelligence Tools) Software platforms used to analyze and visualize data to support decision-making. Common examples include Microsoft Power BI, Tableau, and Looker. In cybersecurity, BI tools are often used for trend analysis, historical threat tracking, and reporting.

Format The output file type selected for exported data. Supported formats include CSV, XLSX, JSON, and TXT.

Introduction

The Group-IB TI Data Export Utility is a command-line tool designed to export threat intelligence data in structured formats for internal analysis, automation, or integration with other systems. It supports both attributed (AD Export) and non-attributed (IoC Export) data.

Before using the Group-IB TI Data Export Utility, please review the startup instructions in the Group-IB TI Integration Starting Guide.

Once you have completed the initial setup, follow the steps below.

Use Cases

The TI Data Export Utility is a command-line tool designed to export structured threat intelligence data from the Group-IB TI platform. Below are practical, realistic use cases where this tool helps streamline cybersecurity workflows across security operations, threat hunting, and compliance teams.

1. IOC Export for Local Storage and Integration Purpose: Export threat indicators (IPs, hashes, domains, URLs) into a local directory for further use. Use case: The utility can place exported IOCs into a designated folder where other systems (such as SIEM or SOAR) can pick them up for integration. Value: Offers a flexible method to stage IOCs locally, enabling controlled ingestion into security platforms without requiring direct API integration.

2. Customized Threat Monitoring via Hunting Rules Correlation Purpose: Export threat data based on applied Hunting Rules configured in the TI Platform Use case: Users can extract threat reports and indicators that align with their configured hunting rules, focusing only on intelligence matching their environment. Value: Enables tailored threat visibility and reduces the volume of irrelevant data.

3. Populate Internal Dashboards or Threat Repositories Purpose: Save exported TI data into your own internal systems such as threat portals, spreadsheets, or data lakes. Use case: The exported data can be manually uploaded to internal BI tools for pivoting, searching, or cross-referencing with internal telemetry. Value: Enables centralized access to threat intelligence across multiple teams.

Installation

Important! The application requires Python 3.10.X-3.12.X installed on your system.

Steps:

- Download the archive package from here and unpack it.
- Navigate to the utility directory
  cd group_ib_ti_data_export_utility
- Install dependencies
  pip install -r requirements.txt

Warning! It is recommended to use python and pip aliases instead of python3 and pip3.

Offline Installation

If you are not connected to the Internet, use the following commands:

- For Windows:
  pip install -r requirements_windows.txt
- For Linux and Linux-based systems:
  pip install -r requirements_linux.txt

Running the Utility

To start the utility, run the following command:

python run_configuration.py

The Main Menu will appear, from which all configuration and export actions are accessible.




CLI Menu Structure Overview

Below is a simplified visual representation of the tool's menu structure. It helps users understand how the different configuration sections are organized and interact with each other.




Use this visual as a reference while working through each section described below.

Data Export Utility Options



1. Client Configuration Menu

This menu allows you to configure your client profile settings. Use the arrow keys to navigate between options. To modify a setting, select it and press Enter.




Option	Description
Credentials	Add and manage credentials (API key, URL, username).
Proxy Configuration	Add proxy connection settings if needed.
Destination Directory	Specify the export output path, where retrieved data will be saved.

Option	Description
Frequency Configuration	Set how often the tool should run (e.g., once a day, twice a day, four times a day, or hourly).

1.1 Credentials

This menu allows you to configure multiple credentials.




Option	Description
Show Credentials	Display all currently configured credentials.
Update a Credential	Modify an existing credential without affecting others.
Update All Credentials	Configure all credentials sequentially.

Required Fields


Option	Description
API Key	The client API key, generated in the TI portal profile settings.
API URL	The API network address. By default, it is set to https://tap.group-ib.com/api/v2/.
Username	The client username, used to log into the TI portal.

1.2 Proxy Configuration (Optional)




Option	Description
IP Address	Enter the IP address of your proxy server.
Password	Enter the password for your proxy server.
Port	Enter the required port.
Protocol	Enter the required protocol.
Username	Enter the username for your proxy.
Enable proxy	Enable / Disable the proxy.

2. Export Configuration



2.1 Attributed Data (AD Export)


This option allows you to configure the export of data with attribution from the TI system. Menu options:



Option	Description
Change Status	Enable / Disable export. Options: False and True.
Change File Configuration	Select one or more export formats from the available options: CSV, XLSX, JSON and TXT. Multiple formats can be selected simultaneously for download. Note: This option applies only to Attributed Data (AD Export). Non-Attributed Data (IoC Export) is always downloaded in TXT format.
Collection Settings	Configure collection settings (see below).
Keyword-based filtering	Enable / Disable keyword filtering with specifying filter field and keyword.

Collection Settings include

To modify collection settings, select the Change Configuration option and start typing the name of the desired collection from the suggested list. Once selected, configure the collection options:




.

Change Start Date: Enter a new start date in the specified format.

- Change End Date: Enter a new end date (optional, for “Run: data for period”).
- Change Status: Enable or disable the collection export. True enables, False disables.
- Clear seqUpdate: Resets the export progress. If the seqUpdate is cleared, data export will start from the specified start date. If left unchanged, the export will resume from where it last stopped.
- Set Filtering Flags: Change the status of filtering flags like apply_hunting_rules, is_tailored, or apply_has_exploit if applicable for the selected collection. Use True to enable filtering and False to disable.

Keyword-based filtering

To modify keyword-based filtering settings, press enter and start typing the name of the desired collection from the suggested list. Once selected, proceed with the following options:



- Enable/Disable Filtering: Turn filtering by the keywords on or off.
- Set Filtering Field: Specify the field to filter by. This must be entered manually.
- Set Filtering Keyword: Define the keyword to use for filtering. This must be entered manually.
- Set Both Field & Keyword: Configure both the filtering field and the keyword in a single operation.


Note: To filter by the expertise field using the keyword Ransomware in the hi/threat collection, set expertise as the filtering field and Ransomware as the keyword.

Important! Filtering is available only for the fields listed in the List_of_filter_fields_for_collections.txt file. If a required field does not appear on the list, please contact support through the Service Desk. Our team will review the proposal and provide further assistance if the enhancement is applicable.

2.2 Non-Attributed Data (IoC Export)

Follows the same process as Attribution Data Export, but it exports data without attribution. For configuration follow the same process as described in the AD Export.

3. Running Export Operations



3.1 Run Test Connection

This option checks whether the Data Export Tool works properly with the current configuration and can reach the TI API. If errors are encountered, the utility will notify you.

3.2 Run: Data for Period (AD Export)

This option starts the data export for the period set in the Attribution Data for Period settings. Upon completion, the file will be saved in the directory specified under Client Configuration -> Data Directory. If the directory was not specified, that file will be stored under data -> result directory.

3.3 Run: TI_Data_Export_Utility (AD/IoC Export)

This option starts the Data Export Tool in the background. Ensure that the AD Export and IoC Export settings are configured before running the script.

The file formats used will match those selected in the Attribution Data Export and Non-Attribution Data Export configuration sections. Upon completion, the file will be saved in the directory specified under Client Configuration -> Data Directory. If the directory was not specified, that file will be stored under data -> updated directory for AD Export and data -> ioc for IoC Export.

Tips and Best Practices

- Clear seqUpdate when starting a new export run. Even if a new start date is specified, the utility will continue from the last saved seqUpdate unless it is manually cleared. This ensures the export uses the defined date range instead of resuming from the previous state.
- Run a test connection before launching an export. Always use the “Run Test Connection” option to verify that your configuration is correct and connectivity with the TI API is functional.
- Review filtering flags for each collection. Ensure filters such as apply_hunting_rules, is_tailored, or apply_has_exploit are configured as needed, as they significantly affect the resulting data set.
- Use keyword filtering to narrow results. If supported for the collection, enabling keyword-based filtering helps reduce noise and retrieve more relevant, actionable threat intelligence.
- Use separate credentials for multi-tenant environments. If you manage exports for multiple organizations, it is recommended to configure distinct credentials for each to maintain clarity and separation of data.

TI Python library

The ciaops Python library is available on PyPI: ciaops. It simplifies work with the Group-IB TI, DRP, and ASM APIs and gives you flexibility to customize search and retrieval of data.

ciaops

ciaops - Python library to communicate with Group-IB Products (TI, DRP, ASM) via API.

License

This project is licensed under the MIT License - see the LICENSE file in the project repository for details.

Installation

Lib deps: requests, urllib3.

ciaops lib is available on PyPI:
pip install ciaops
Or use a Portal WHL archive. Replace X.X.X with current lib version:
pip install ./ciaops-X.X.X-py3-none-any.whl

Usage

Initialization

Initialize a poller with your credentials. TLS certificate verification is enabled by default.

Call set_verify() only when you need to override the default: pass False to disable verification (for example, local testing behind a corporate proxy), or pass a path to a custom CA bundle.
from ciaops import TIPoller, DRPPoller, ASMPoller # Threat Intelligence ti = TIPoller(username='example@gmail.com', api_key='API_KEY', api_url='TI_API_URL') # Digital Risk Protection drp = DRPPoller(username='example@gmail.com', api_key='API_KEY', api_url='DRP_API_URL') # Attack Surface Management asm = ASMPoller(username='example@gmail.com', api_key='API_KEY', api_url='ASM_API_URL') # Override only when needed: ti.set_verify(False) # disable TLS check (local testing only) ti.set_verify('/path/to/ca-bundle') # custom CA bundle
Proxy setup (all pollers share the same interface):
ti.set_proxies(proxy_protocol='https', proxy_ip='10.0.0.1', proxy_port='3128', proxy_username='user', # optional proxy_password='secret', # optional)
Use pollers as context managers to ensure the session is always closed:
with TIPoller(username='...', api_key='...', api_url='...') as ti: generator = ti.create_update_generator('apt/threat', sequpdate=16172928022293) for portion in generator: print(portion.parse_portion())
Tag your integration in the User-Agent header with set_product() - required by some on-premise deployments:
ti.set_product(product_type='SIEM', product_name='MySIEM', product_version='2.1', integration_name='ciaops-siem', integration_version='1.0',)
Collection constants

Use typed constants instead of bare strings to avoid typos and get IDE autocomplete:
from ciaops.collection_meta import TICollections, DRPCollections, ASMCollections # TI examples TICollections.APT_THREAT # "apt/threat" TICollections.COMPROMISED_ACCOUNT_GROUP # "compromised/account_group" TICollections.MALWARE_CNC # "malware/cnc" # DRP DRPCollections.VIOLATION # "violation" # ASM ASMCollections.ASSETS_UPDATED # "assets/updated" ASMCollections.ISSUES_UPDATED # "issues/updated"

Look up the recommended TTL for any TI collection:
TICollections.get_ttl(TICollections.MALWARE_CNC) # 90 (days) TICollections.get_ttl(TICollections.COMPROMISED_MESSENGER) # None (no expiry)
Use constants anywhere a collection name string is expected:
poller.set_keys(TICollections.APT_THREAT, keys) generator = poller.create_update_generator(TICollections.MALWARE_CNC, sequpdate=...)

Collections mapping

Method set_keys() sets keys to search in the selected collection. It should be a python dict mapping_keys = {key: value} where
key - result name
value - dot-notation string with searchable keys
mapping_keys = {"result_name": "searchable_key_1.searchable_key_2"}
Parser finds keys recursively in the API response, using dot-notation in value. If you want to add your own data to the results start the value with a star *.
mapping_keys = { "network": "indicators.params.ip", "result_name": "*My_Value" }
For set_keys() or set_iocs_keys() methods you can make a full template to get nested data in the way you want.
mapping_keys = { 'network': { 'ips': 'indicators.params.ip' }, 'url': 'indicators.params.url', 'type': '*network' }
poller.set_keys(collection_name="apt/threat", keys=mapping_keys) poller.set_iocs_keys(collection_name="apt/threat", keys={"ips": "indicators.params.ip"})

Portions generator

Use the methods create_update_generator() and create_search_generator() to create a generator, which returns portions of limited feeds.
Update generator - goes through the feeds in ascending order. Feed iteration is based on the seqUpdate field.
Search generator - goes through the feeds in descending order. Feed iteration is based on the resultId field.
generator = poller.create_update_generator(collection_name='compromised/account_group', date_from='2021-01-30', date_to='2021-02-03', query='8.8.8.8', sequpdate=20000000, limit=200)
Each portion (iterable object) is presented as a Parser class object. You can get raw data (in JSON format) or a parsed portion (python dictionary format), using its methods and attributes.
for portion in generator: parsed_json = portion.parse_portion(as_json=False) iocs = portion.get_iocs(as_json=False) sequpdate = portion.sequpdate count = portion.count raw_json = portion.raw_json raw_dict = portion.raw_dict
Attribute sequpdate of the generator iterable object gives you the last sequence update number (seqUpdate) of the feed, which you can save locally.

Attribute count of the generator iterable object shows you the number of feeds left in the queue. For the search generator, count returns the total number of feeds in the queue.

Methods parse_portion() and get_iocs() of generator iterable objects use your mapping keys (IoCs keys) to return parsed data. You can override mapping keys using the keys parameter in these functions.
parsed_json = portion.parse_portion(as_json=False) iocs = portion.get_iocs(as_json=False, keys=mapping_override_keys)
You can also use the bulk_parse_portion() method to get multiple parsed dicts from every feed.
new_parsed_json = portion.bulk_parse_portion(keys_list=[{"ips": "indicators.params.ip"}, {"url": "indicators.params.url"}], as_json=False,)

TIPoller extra methods

Available collections

Call get_available_collections() to discover which collections your API key can access before iterating.
collection_list = ti.get_available_collections() seq_update_dict = ti.get_seq_update_dict(date='2020-12-12') compromised_account_sequpdate = seq_update_dict.get('compromised/account_group') # Check which collections have active hunting rules applied hunting_collections = ti.get_hunting_rules_collections()

Find feed by ID

Returns a Parser object for a single feed by its ID.
feed = ti.search_feed_by_id(collection_name='apt/threat', feed_id='abc123') parsed = feed.parse_portion()

Download file

Download a binary file embedded inside a threat report.

```
binary = ti.search_file_in_threats(    collection_name='hi/threat',    feed_id='feed_id',    file_id='file_id_inside_feed', )
```

Download PDF reports

```
# Download a PDF for an HI or APT threat pdf_bytes = ti.download_threat_pdf(threat_id='abc123')  # Download an HI analytic report PDF (use the file.name field from an hi/analytic record) pdf_bytes = ti.download_analytic_report_pdf(file_name='/23ae4ab7.../file/450ffbd4...')  with open('report.pdf', 'wb') as f:    f.write(pdf_bytes)
```

Risk scoring

Score one or more IPs or domains against the TI database. Scores range from 0 to 100. For endpoint details and score interpretation, see the IP Scoring and Domain Scoring articles.

```
# IP scoring - single or multiple ti.get_ip_scoring('8.8.8.8') ti.get_ip_scoring(['8.8.8.8', '1.1.1.1'])  # Domain scoring - single or multiple ti.get_domain_scoring('group-ib.com') ti.get_domain_scoring(['group-ib.com', 'example.corp']) # -> {"items": {"group-ib.com": {"domain": "group-ib.com", "riskScore": 0}}}
```

MITRE ATT&CK

Fetch the full MITRE ATT&CK technique vocabulary or a ready-to-use ID->name map.

```
# Raw vocabulary (includes all AttackPattern details) vocab = ti.get_mitre_techniques()  # Convenient ID -> name dict mitre_map = ti.get_mitre_attack_pattern_map() # -> {"T1059": "Command and Scripting Interpreter", "T1078": "Valid Accounts", ...}  technique_name = mitre_map.get("T1059")
```

Global search

Search across all TI collections by query string.

```
results = ti.global_search('8.8.8.8') # -> [{"apiPath": "suspicious_ip/scanner", "count": 14, ...}, ...]
```

DRPPoller methods

```
from ciaops import DRPPoller  drp = DRPPoller(username='...', api_key='...', api_url='DRP_URL')
```

Update generator - iterate violation feeds:

```
generator = drp.create_update_generator(    collection_name='violation',    sequpdate=1700000000000000,    subtypes=[6],         # 1=counterfeit 2=piracy 3=partner_policy 4=trademark 5=malware 6=phishing 7=fraud    section=[1, 2],       # 1=Web 2=Mobile 3=Marketplace 4=Social 5=Advertising 6=Messengers    brands=['brand_id'],    approve_states=['under_review'], ) for portion in generator:    data = portion.parse_portion()
```

Change violation status (only when status=detected and approveState=under_review):

```
drp.change_status(feed_id='violation_id', status='approve')  # or 'reject'
```

Brands and subscriptions:

```
brands = drp.get_brands() subscriptions = drp.get_subscriptions()
```

ASMPoller methods

```
from ciaops import ASMPoller  asm = ASMPoller(username='...', api_key='...', api_url='ASM_URL')
```

List companies:

```
companies = asm.get_companies()         # all companies active = asm.get_companies(status='active')
```

Update generator - uses POST requests with automatic rate limiting:

```
generator = asm.create_update_generator(    collection_name='assets/updated',   # or 'leaks/updated', 'issues/updated' company_id='company-uuid',         # or list of UUIDs    date_from='2024-01-01',    date_to='2024-06-01',             # optional    count=500,  # max 5000    status=['new', 'confirmed'],       # optional filter    type=['domain', 'ip'],            # optional filter (assets only) ) for portion in generator:  data = portion.parse_portion()
```

Dashboard scores and issue/asset management are also available (get_dashboard_scores(), get_issue_evidence(), add_issue_comment(), change_issue_status(), add_assets(), remove_assets(), change_asset_status()).

Close session

Always close the session in a try...finally block, or use the context manager:

```
from ciaops import TIPoller from ciaops.exception import InputException, ConnectionException  try:    poller = TIPoller(username='example@gmail.com', api_key='API_KEY', api_url='API_URL')    # ... do work ... except InputException as e:    logger.error("Wrong input: %s", e) except ConnectionException as e:    logger.error("Connection error: %s", e) finally:    poller.close_session()
```

Parsing

Common example of an API response from a collection (received feeds):

```
api_response = [    {        'iocs': {            'network': [                {'ip': [1, 2], 'url': 'url.com'},                {'ip': [3], 'url': ''}            ]        }    },    {        'iocs': {
'network': [                {'ip': [4, 5], 'url': 'new_url.com'}            ]        }    } ]
```

Parse portion method

Your mapping dict for the parse_portion() or bulk_parse_portion() methods:

```
mapping_keys = {    'network': {'ips': 'iocs.network.ip'},    'url': 'iocs.network.url',    'type': '*custom_network' }
```

Result of parse_portion() output:

```
parsing_result = [    {'network': {'ips': [[1, 2], [3]]}, 'url': ['url.com', ''], 'type': 'custom_network'},    {'network': {'ips': [[4, 5]]}, 'url': ['new_url.com'], 'type':
'custom_network'} ]
```

Get IoCs method

Your mapping dict for the get_iocs() method:

```
mapping_keys = {    'ips': 'iocs.network.ip',    'url': 'iocs.network.url' }
```

Result of get_iocs() output:

```
parsing_result = {    'ips': [1, 2, 3, 4, 5],    'url': ['url.com', 'new_url.com'] }
```

Records limits

The default limit is 100 records per request. Due to the different sizes of feeds, there are different limits for getting data. To change the record limit in the response, add the limit parameter to the request (for example, limit=500). Per-collection limits are listed in the API Limitations article.

```
curl -X 'GET' 'https:///api/v2/apt/threat/updated?limit=500&seqUpdate=16172928022293'
```

Troubleshooting

401 response code

Returned if no credentials were sent. Make sure you send the Authorization header and use Basic authentication.

403 response code

Possible reasons:

- IP limitation. Make sure you send the request from an allowed IP address (see Initial Steps).
- API key issue. Make sure your API key is active and valid.
- No access to the feed. Make sure you have access to the requested feed (Profile page -> Security and Access).

504 response code or timeout

Try setting a smaller limit when requesting the API.

For additional questions, contact Group-IB via the Service Desk.

TI Postman configuration

Prerequisites

Before configuring Group-IB TI Postman, ensure you have reviewed the Group-IB TI Integration Starting Guide for initial setup instructions.


Warning: Never make this configuration publicly available in Postman, especially with your credentials. Always use the native desktop application instead of the cloud version.

Installation

- Download the Configuration File: You can download the current configuration file here.
- Import into Postman:
  - Open the Postman application.
  - Click Import and select the previously downloaded configuration file.


Configuration

- Navigate to the Group-IB Threat Intelligence API (v2.x.x) section in Postman.
- Click the Variables button.
- Locate the username and api_key variables and set them in the active Postman environment.



Usage


- Select an API collection from the available list.
- Choose an endpoint (e.g., GET /api/v2/hi/threat/updated).
- Configure the request parameters as needed.
- Click Send to execute the request and view the response.




Example Requests

The following examples demonstrate how to send API requests and interpret responses in Group-IB TI Postman. These examples cover common use cases such as retrieving threat data. Each request type includes sample usage scenarios and response examples:

GET Example: Retrieving Threat Data



GET Example: Retrieving Malware Data



Additional Notes


- Ensure your API key has the required permissions for the selected endpoints.
- Refer to the API Documentation for a full list of supported queries and parameters.
- If you encounter issues, check the Troubleshooting section or contact support.

Developer Guide
Common Dev Info

Authentication

Basic authentication is necessary to access API methods. You should provide credentials with each request in username and API-key format.

Curl example:
curl 'https://tap.group-ib.com/api/v2/sequence_list' -u 'LOGIN:API_KEY'
Note: LOGIN is your username to log in to the Group-IB portal. API_KEY key you have generated on the previous step.



Rest API Scope

There are several ways to get feeds:

- Global search
- Receive data
- Retrieve feed by ID

Global search

It is possible to perform a global search across all collections.

Request format:
curl 'https://tap.group-ib.com/api/v2/search?q=8.8.8.8' -u 'LOGIN:API_KEY'
Params:

Name	Type	Required	Description
q	string	true	Search query

Response example:
[{ "apiPath": "attacks/ddos", "count": 389, "detailedLinks": [], "label": "Attack :: DDoS", "link": "https://tap.group-ib.com/attacks/ddos?q=ip:8.8.8.8" }, { "apiPath": "attacks/deface", "count": 1, "detailedLinks": [], "label": "Attack :: Deface", "link": "https://tap.group-ib.com/attacks/deface?q=ip:8.8.8.8" }, ...]
Global search simplifies the process of searching through all collections and indicates which collections generally have matching entries. However, to get the found items, you need to perform the same search query in the collection specified in the apiPath parameter using one of the methods described below.

Receive data

Using this method, you can read feeds sorted by their seqUpdate value in ascending order. Every time a feed changes, its seqUpdate increases, and this feed appears at the top of the queue. This value is stored on the integration side and used to request only new data.

Group-IB TI uses continuous seqUpdate numbering across feeds. For example, seqUpdate 1999998 can be in compromised/account_group, and seqUpdate 1999999 can be in attacks/ddos. This example explains sequence semantics only.

Warning: Using df/dt together with seqUpdate in /updated endpoints is a legacy pattern and may produce inconsistent results. Use sequence_list + seqUpdate for update polling. Note: df/dt parameters are valid for /api/v2/search.

Request format:
GET /api/v2//updated
Params:

Name	Type	Required	Description
q	string	false	Search query
seqUpdate	integer	false	seqUpdate to get the next data chunk
limit	integer	false	Feed portion size. Default: 100. Maximum depends on collection (see API Limitations).

Rate limit reminder: 1 request per 10 seconds per company per feed per route (see API Limitations).

Procedure:

- Use a sequence_list request to get an update for a specific date to start the session. Date format: YYYY-MM-DD Request format:
  GET /api/v2/sequence_list?date=
  Note: Date must be in this format: YYYY-MM-DD (for example, 2021-11-11).
- Received seqUpdate can be used as a parameter for further requests. When you submit this argument as a parameter, you will get a portion of feeds starting with the next seqUpdate for this collection. Request format:

GET /api/v2//updated?seqUpdate=

- To get the next portion of feeds, use the top-level seqUpdate value from the response (not the seqUpdate of individual items).
- Repeat step 3 while the response contains data (the returned array is not empty).
- Save the last top-level seqUpdate value for future reference after each iteration.

Retrieve Feed by ID

Each item in the system is uniquely identifiable by its id field. You can retrieve a specific feed by using the following request.

Request format:
GET /api/v2//
If the above request does not return the expected result, use the following alternative request format:
GET /api/v2/?q=id:

Additional Resources

Status codes:

For detailed information on status codes, error explanations, and troubleshooting steps, please refer to Troubleshooting and Error Codes. This guide includes:

- Steps to verify access if you encounter authorization issues
- Explanations of common error codes, such as 400(Bad request), 401(Unauthorized), and 404(Not Found).
- Recommendations for handling rate limits and server errors.

Specific features in some collections:

- Collection limits are route-specific and can differ significantly. Use the current limits from API Limitations.

Misc:

- For complete sequence/search iteration details, see API Logic Explanation.
- For endpoint-level global search behavior and schema, see Search.
- You can find additional JSON schema details and constraints in related endpoint articles.

User-Agent mask with product metadata information

The User-Agent request header contains a string with attributes that servers and network nodes can use to determine the application category, operating system, vendor, and/or version of the user agent.

The view of the User-Agent string is:
/_/_//_

Field	Description
Platform type	Platform type. Must be one of the following: SIEM, SOAR, TIP, XDR, IRP, NGFW, SGRC, SCRIPT, CIS, IDR, EDR.
Platform name	Official platform name. Examples: QRadar, ThreatQuotinet.
Platform version	Vendor platform version.
App name	Integration application name, e.g. Threat Intelligence, Attack Surface Management, Digital Risk Protection
App version	Integration application version.
Username	Username used for authorization in the TI portal.
Lib name	Library token if used (for example, ciaops).
Lib version	Library version if used (for example, 0.14.1).

Note: Using a client library is optional. If no library is used in the integration, specify unknown instead of **Lib name** and **Lib version**.

Examples:

- SIEM/QRadar_2020.10.6/GroupIB_TI_1.0.0/gibuser@group-ib.com/gibunipy_0.5.12
- TIP/ThreatQuotient_2.5.0/Group_IB_Threat_Intelligence_1.2.0/gibuser@group-ib.com/unknown
- SCRIPT/unknown/GIB_TI-A_PanOS_unknown/gibuser@group-ib.com/pytia_0.5.13

App name

Detailed view of the application name
Group-IB___

Abbreviation

Product:

- TI - Threat Intelligence
- DRP - Digital Risk Protection
- ASM - Attack Surface Management
-

MXDR - Managed Extended Detection and Response

Platform:

- TIP - Threat Intelligence Platform
- SIEM - Security Information and Event Management
- SOAR - Security Orchestration, Automation and Response
- IRP - Incident Response Platform
- NGFW - Next Generation Firewall
- IDR - Identity Detection and Response
- EDR - Endpoint Detection and Response
- XDR - Extended Detection and Response
- SGRC - Security Government, Risk management and Compliance

Collections:

- APT - Advanced Persistent Threat - Nation-state reports (pro-government)
- HI - Human Intelligence - Cyber-criminals reports (non-government, all others)
- IoC - Indicator of Compromise
- OSI - Open Systems Interconnection Model

API Logic Explanation

API logic

To iterate over received portions from API response, you should follow one of the next iteration logic:

- Sequence update iteration - based on seqUpdate parameter, which was retrieved from previous response. Uses updated endpoint (/updated) after collection name (/apt/threat) >>> /api/v2/apt/threat/updated.

To search IPs, domains, hashes, emails, etc., you should follow the next logic:

Search logic - First you should reach /api/v2/search endpoint with any q parameter >>> /api/v2/search?q=8.8.8.8. In the output response you will receive collections, which contains the search result (8.8.8.8). Use Sequence update iteration as a next step to retrieve all events.

To get the latest updates on each collection events you should follow the next logic:

- Sequence update logic - first you should reach /api/v2/sequence_list endpoint with date and collection parameters (optional) >>> /api/v2/search?date=2022-01-01&collection=apt/threat. In the output response you will receive seqUpdate number, which you should use in the next request to collection /updated endpoint. Use Sequence update iteration as a next step to retrieve all events.

Sequence Update logic

Most collections at the Threat Intelligence portal has /updated endpoint. And this endpoint uses updated logic based on seqUpdate key field which comes from JSON response.

The seqUpdate key - is a time from Epoch converted to a big number (microseconds), using the next formula:

UTC timestamp * 1000 * 1000

Note: Don't rely on this formula. Because of the rising amount of data it could be changed. For that purpose /api/v2/sequence_list endpoint was created. Use this endpoint to get the required seqUpdate number.

API response

Each row in our database has its own unique sequence update number. So, we can get all the events one by one. To check it you can explore JSON output and then explore each item in the "items" field. So, each item contains a seqUpdate field. And the last element's seqUpdate is put to the top level of JSON output. You can use it to get the next portion of feeds. Each collection has its own updated route like /api/v2/apt/threat/updated, so we can use the next output as an example.

{ "count": 1761, "items": [{"id": "fake286ca753feed3476649438e4e4488"...}, {"id": "fake51d29357b22b80564a1d2f9fc8751"...}, { "author": null, "companyId": [], "id": "fake4f16300296d20ef9b909dc0d354fb", ..., "indicators": [{ "dateFirstSeen": null, "dateLastSeen": null, "deleted": false, "description": null, "domain": "fake-fakesop.net", "id": "fakebe483bb82759fbee7038235e0f52d0", ... }], "indicatorsIds": ["fakebe483bb82759fbee7038235e0f52d0"], "isPublished": true, "isTailored": false, "labels": [], "langs": ["en"], "malwareList": [], ..., "seqUpdate": 16172928022293 },], "seqUpdate": 16172928022293 }

Iteration steps

To iterate over /api/v2/apt/threat/updated endpoint data, you need to collect this field number ("seqUpdate": 16172928022293) right at the top level of the JSON response, received from previous request or from /sequence_list endpoint.

```
curl -X 'GET' 'https:///api/v2/sequence_list'
```

Add gathered seqUpdate in the next request, using endpoint params.

```
curl -X 'GET' 'https:///api/v2/apt/threat/updated?seqUpdate=16172928022293'
```

In the received JSON output check the "count": 1751. -> Gather seqUpdate from last feed or at top level -> Put it in next request ->

```
curl -X 'GET' 'https:///api/v2/apt/threat/updated?seqUpdate=16172928536227'
```

In the received JSON output, check the "count": 1741 -> Gather seqUpdate from last feed or at top level -> Repeat till the end.

Stop the iteration

The "stop word" in that logic is items "count" or "items" list length. For the collection apt/threat in above example, the limit is set to 10 by default, the other collections usually have 100 limit. The limit depends on the amount of data to not overload the JSON output. For example, usually you receive a portion of 100 feeds (not 10) for the first iteration. -> Then could be a portion of 23 feeds -> Then a portion of 0 feeds -> The end.

Search logic

Search logic is used to find attribution to the search value in the Threat Intelligence database.

Global search

To find events related to IP, domain, hash, email, etc., you should send a request to the /api/v2/search endpoint with any q parameter (/api/v2/search?q=8.8.8.8). It will return a list of collections, which contains this searchable parameter. As a next step we need to use Sequence update iteration over all items in each collection. You can specify the searchable type keyword to avoid side results by setting q parameter like /api/v2/search?q=ip:8.8.8.8. The same can be done for domain, email, hash, etc. (/api/v2/search?q=domain:google.com, /api/v2/search?q=email:example@gmail.com).

[{ "apiPath": "suspicious_ip/open_proxy", "label": "Suspicious IP :: Open Proxy", "link": "https://tap.group-ib.com/api/v2/suspicious_ip/open_proxy?q=ip:8.8.8.8", "count": 14, "time": 0.304644684, "detailedLinks": null }, { "apiPath": "attacks/ddos", "label": "Attack :: DDoS", "link": "https://tap.group-ib.com/api/v2/attacks/ddos?q=ip:8.8.8.8", "count": 1490, "time": 0.389418291, "detailedLinks": null }, {"apiPath": "attacks/deface"...}, {"apiPath": "malware/config"...}, {"apiPath": "suspicious_ip/scanner"...}]

Iteration steps

On the first search step we receive information that collection attacks/ddos contain 1490 items ("count": 1490). Let’s extract all of them. First we need to send a request to this collection with the q parameter (?q=ip:8.8.8.8). Then we retrieve the "seqUpdate" field right at the top level of the JSON response and use it in the next request ("seqUpdate": 1673373011294).

{ "count": 1490, "items": [{ "body": null, "cnc": {"cnc": "http://ex-ex.net/drv/"...}, "company": null, "companyId": null, "dateBegin": null, "dateEnd": null, "dateReg": "2017-08-16T00:00:00+00:00", "evaluation": {}, "favouriteForCompanies": [], "headers": [], "hideForCompanies": [], "id": "examplec58903baddc84b8c51eaef1f904374025d", "isFavourite": false, ... }], ..., "seqUpdate": 1673373011294 }

So the next request should look like this /api/v2/attacks/ddos/updated?q=ip:8.8.8.8&seqUpdate=1673373011294. We can also set the limit parameter in the requests, like limit=500. Explore the example below.

curl -X 'GET' 'https:///api/v2/search?q=ip:8.8.8.8'

Add gathered seqUpdate in the next request, using endpoint params.

curl -X 'GET' 'https:///api/v2/attacks/ddos/updated?seqUpdate=1673373011294'

In the received JSON output check the “count”: 1390. -> Gather seqUpdate from last feed or at top level -> Put it in next request ->

curl -X 'GET' 'https:///api/v2/attacks/ddos/updated?seqUpdate=1673375930599'

In the received JSON output, check the "count": 1290 -> Gather seqUpdate from last feed or at top level -> Repeat till the end.

Stop the iteration

The “stop word” in that logic is items "count" or "items" list length. For the collection attacks/ddos in the above example, the limit is set to 100 by default, the other collections may differ. The limit depends on the amount of data to not overload the JSON output. For example, usually you receive a portion of 100 feeds for the first iteration. -> Then could be a portion of 23 feeds -> Then a portion of 0 feeds -> The end.

GROUP-IB

Threat intelligence



Preventing and investigating cybercrime since 2003

intelligence@group-ib.com
+65 3159-3798

www.group-ib.com
blog.group-ib.com