

1. When performing logistic regression on sentiment analysis, you represented each tweet as a vector of ones and zeros. However your model did not work well. Your training cost was reasonable, but your testing cost was just not acceptable. What could be a possible reason?

1 / 1 point

- ☒ The vector representations are sparse and therefore it is much harder for your model to learn anything that could generalize well to the test set.
- ☐ You probably need to increase your vocabulary size because it seems like you have very little features.
- ☐ Logistic regression does not work for sentiment analysis, and therefore you should be looking at other models.
- ☐ Sparse representations require a good amount of training time so you should train your model for longer

✓ **Correct**
This is correct.

2. Which of the following are examples of text preprocessing?

1 / 1 point

- ☒ Stemming, or the process of reducing a word to its word stem.

✓ **Correct**

2. Which of the following are examples of text preprocessing?

1 / 1 point

- ☒ Stemming, or the process of reducing a word to its word stem.

✓ **Correct**
This is correct.

- ☒ Lowercasing, which is the process of removing changing all capital letter to lower case.

✓ **Correct**
This is correct.

- ☒ Removing stopwords, punctuation, handles and URLs

✓ **Correct**
This is correct.

- ☐ Adding new words to make sure all the sentences make sense

3. The sigmoid function is defined as $h(x^{(i)}; \theta) = \frac{1}{1 + e^{-x}}$. Which of the following is true.

1 / 1 point

☐ Adding new words to make sure all the sentences make sense

3. The sigmoid function is defined as $h(x^{(i)}, \theta) = \frac{1}{1 + e^{-\theta^T x^{(i)}}}$. Which of the following is true.

1 / 1 point

- ☐ Large positive values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ closer to 1 and large negative values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ close to -1.
- ☒ Large positive values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ closer to 1 and large negative values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ close to 0.
- ☐ Small positive values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ closer to 1 and large positive values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ close to 0.
- ☐ Small positive values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ closer to 0 and large negative values of $\theta^T x^{(i)}$ will make $h(x^{(i)}, \theta)$ close to -1.

✓ **Correct**
This is correct.

4. The cost function for logistic regression is defined as $J(\theta) = -\frac{1}{m} \sum_{i=1}^m [y^{(i)} \log h(x^{(i)}, \theta) + (1 - y^{(i)}) \log (1 - h(x^{(i)}, \theta))]$. Which of the following is true about the cost function above. Mark all the correct ones.

1 / 1 point

☒ When $y^{(i)} = 1$, as $h(x^{(i)}, \theta)$ goes close to 0, the cost function approaches ∞ .

✓ **Correct**
This is correct.

☐ When $y^{(i)} = 1$, as $h(x^{(i)}, \theta)$ goes close to 0, the cost function approaches 0.

☒ When $y^{(i)} = 0$, as $h(x^{(i)}, \theta)$ goes close to 0, the cost function approaches 0.

✓ **Correct**
This is correct.

☐ When $y^{(i)} = 0$, as $h(x^{(i)}, \theta)$ goes close to 0, the cost function approaches ∞ .



Logistic Regression

Practice Quiz • 30 min • 10 total points

5. For what value of $\theta^T x$ in the sigmoid function does $h(x^{(i)}, \theta) = 0.5$.

1 / 1 point

0

✓ Correct



Logistic Regression

Practice Quiz • 30 min • 10 total points

6. Select all that apply. When performing logistic regression for sentiment analysis using the method taught in this week's lecture, you have to:

1 / 1 point

- ☒ Perform data processing.

✓ Correct

This is correct.

- ☒ Create a dictionary that maps the word and the class that word is found in to the number of times that word is found in the class.

✓ Correct

This is correct.

- ☐ Create a dictionary that maps the word and the class that word is found in to see if that word shows up in the class.

- ☒ For each tweet, you have to create a **positive feature** with the sum of positive counts of each word in that tweet. You also have to create a **negative feature** with the sum of negative counts of each word in that tweet.

✓ Correct

This is correct.



Logistic Regression

Practice Quiz • 30 min • 10 total points

7. When training logistic regression, you have to perform the following operations in the desired order.

1 / 1 point

- ☐ Initialize parameters, get gradient, classify/predict, update, get loss, repeat
- ☒ Initialize parameters, classify/predict, get gradient, update, get loss, repeat
- ☐ Initialize parameters, get gradient, update, classify/predict, get loss, repeat
- ☐ Initialize parameters, get gradient, update, get loss, classify/predict, repeat

✓ Correct

This is correct.

8. Assuming we got the classification correct, where $y^{(i)} = 1$ for some specific example i . This means that $h(x^{(i)}, \theta) > 0.5$. Which of the following has to hold:

1 / 1 point

- ☐ Our prediction, $h(x^{(i)}, \theta)$ for this specific training example is exactly equal to its corresponding label $y^{(i)}$.
- ☐ Our prediction, $h(x^{(i)}, \theta)$ for this specific training example is less than $(1 - y^{(i)})$.
- ☐ Our prediction, $h(x^{(i)}, \theta)$ for this specific training example is less than $(1 - h(x^{(i)}, \theta))$.
- ☒ Our prediction, $h(x^{(i)}, \theta)$ for this specific training example is greater than $(1 - h(x^{(i)}, \theta))$.

To exit full screen, move mouse to top of screen or press **F11**

9. What is the purpose of gradient descent? Select all that apply.

1 / 1 point

- ☒ Gradient descent allows us to learn the parameters θ in logistic regression as to minimize the loss function J.



Correct

This is correct.

- ☐ Gradient descent allows us to learn the parameters θ in logistic regression as to maximize the loss function J.

- ☒ Gradient descent, $grad_theta$ allows us to update the parameters θ by computing $\theta = \theta - \alpha * grad_theta$



Correct

This is correct.

- ☐ Gradient descent, $grad_theta$ allows us to update the parameters θ by computing $\theta = \theta + \alpha * grad_theta$

10. What is a good metric that allows you to decide when to stop training/trying to get a good model? Select all that apply.

1 / 1 point



- ☐ Gradient descent, $grad_theta$ allows us to update the parameters θ by computing $\theta = \theta + \alpha * grad_theta$

10. What is a good metric that allows you to decide when to stop training/trying to get a good model? Select all that apply.

1 / 1 point

- ☒ When your accuracy is good enough on the test set.



Correct

This is correct.

- ☐ When your accuracy is good enough on the train set.

- ☒ When you plot the cost versus (# of iterations) and you see that your the loss is converging (i.e. no longer changes as much).



Correct

This is correct.

- ☐ When α , your step size is neither too small nor too large.

