

# Programming Languages and Paradigms

## COMP 302

Instructor: Jacob Thomas Errington  
School of Computer Science  
McGill University

Application of higher-order functions: continuations

# Let's talk performance

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

Discuss with the person beside you the performance characteristics of this function.

- What is its time complexity?
- Its space complexity?

# Let's talk performance

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

# Let's talk performance

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

Running time: linear in  $l1 - O(n)$

# Let's talk performance

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

Running time: linear in  $l1 - O(n)$

Memory usage: **linear** in  $l1 - O(n)$

# Why linear memory usage?

We could rewrite

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

# Why linear memory usage?

We could rewrite

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

into

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs ->  
  let ys = append xs l2 in  
  x :: ys
```

# Why linear memory usage?

We could rewrite

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

into

```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs ->  
    let ys = append xs l2 in  
    x :: ys
```

It's clear that the `::` (cons) is happening **after the recursive call returns**.



```
let rec append l1 l2 = match l1 with  
| [] -> l2  
| x :: xs -> x :: append xs l2
```

How would we even rewrite this using an accumulator???

All functions can be written tail recursively.

## Idea: use a *higher-order* accumulator

- This accumulator, instead of storing list items, stores **pending operations**.
- That's normally what the call stack does for us!

# Rewriting append tail-recursively

demo

# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Consider this example; it's the base case.

```
append_tr [] [1;2] (fun x -> x)
```

# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Consider this example; it's the base case.

```
append_tr [] [1;2] (fun x -> x)  
(fun x -> x) [1;2]
```

# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Consider this example; it's the base case.

```
append_tr [] [1;2] (fun x -> x)  
(fun x -> x) [1;2]  
[1;2]
```

Nothing too strange.

## Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Now let's try with a nonempty list. This is trickier!



# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Now let's try with a nonempty list. This is trickier!

```
append_tr [1;2] ls id
```

# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Now let's try with a nonempty list. This is trickier!

```
append_tr [1;2] ls id  
append_tr [2] ls (fun r -> id (1 :: r))
```

# Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Now let's try with a nonempty list. This is trickier!

```
append_tr [1;2] ls id  
append_tr [2] ls (fun r -> id (1 :: r))  
append_tr [] ls (fun r' -> (fun r -> id (1 :: r)) (2 :: r'))
```

## Step-by-step, how does this work?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Now let's try with a nonempty list. This is trickier!

```
append_tr [1;2] ls id
```

```
append_tr [2] ls (fun r -> id (1 :: r))
```

```
append_tr [] ls (fun r' -> (fun r -> id (1 :: r)) (2 :: r'))
```

A “stack” of pending operations has been built up explicitly in the return function!

# What's next?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Discuss with the person beside you what the next step should be after this!

```
append_tr [] ls (fun r' -> (fun r -> id (1 :: r)) (2 :: r'))
```

# What's next?

```
let rec append_tr l1 l2 return =  
  match l1 with  
  | [] -> return l2  
  | x :: xs ->  
    append_tr xs l2  
    (fun ys -> return (x :: ys))
```

Discuss with the person beside you what the next step should be after this!

```
append_tr [] ls (fun r' -> (fun r -> id (1 :: r)) (2 :: r'))
```

- ① `append_tr [] ls (fun r' -> id (1 :: (2 :: r')))` `ls`
- ② `(fun r' -> (fun r -> id (1 :: r)) (2 :: r'))` `ls`
- ③ `id (1 :: 2 :: ls)`
- ④ `(fun r' -> id (1 :: (2 :: r')))` `ls`

# Just a few more steps...

```
(fun r' -> (fun r -> id (1 :: r)) (2 :: r')) ls
```

## Just a few more steps...

```
(fun r' -> (fun r -> id (1 :: r)) (2 :: r')) ls  
      (fun r -> id (1 :: r)) (2 :: ls)
```



## Just a few more steps...

```
(fun r' -> (fun r -> id (1 :: r)) (2 :: r')) ls  
  (fun r -> id (1 :: r)) (2 :: ls)  
    id (1 :: (2 :: ls))
```

## Just a few more steps...

```
(fun r' -> (fun r -> id (1 :: r)) (2 :: r')) ls
      (fun r -> id (1 :: r)) (2 :: ls)
            id (1 :: (2 :: ls))
1 :: 2 :: ls
```

# More generally

The “return function” we introduced is an example of a **continuation**.

# More generally

The “return function” we introduced is an example of a **continuation**.

## Continuations

In general, a **continuation** is a representation of the *execution state* of a program at a certain point in time.

# More generally

The “return function” we introduced is an example of a **continuation**.

## Continuations

In general, a **continuation** is a representation of the *execution state* of a program at a certain point in time.

Usually, the execution state we want to represent and manipulate ourselves is the *call stack*.

# More generally

The “return function” we introduced is an example of a **continuation**.

## Continuations

In general, a **continuation** is a representation of the *execution state* of a program at a certain point in time.

Usually, the execution state we want to represent and manipulate ourselves is the *call stack*.

Specifically: what work is left to do? In other words; “what happens when we return?” Continuations let us manipulate *what happens next* directly.

# In other languages

Some languages provide *second-class* continuations at least in some form: they provide constructs specifically for saving, manipulating, and restoring execution states.

- Async programming using `async/await` (C#, JavaScript)
- Coroutines and generators (JavaScript, Lua, Python)

# In other languages

Some languages provide *second-class* continuations at least in some form: they provide constructs specifically for saving, manipulating, and restoring execution states.

- Async programming using `async/await` (C#, JavaScript)
- Coroutines and generators (JavaScript, Lua, Python)

Some languages provide *first-class* continuations: you can save execution states, and manipulate them just like you would any other function. Calling the function re-instates the saved execution state.

- Scheme and some other Lisps
- sml/NJ (similar to OCaml)



## Remark: performance

`append` will outperform `append_tr` on small lists. On (very) large lists, `append` will crash whereas `append_tr` will run.

## Remark: performance

`append` will outperform `append_tr` on small lists. On (very) large lists, `append` will crash whereas `append_tr` will run. Both `append` and `append_tr` use  $O(n)$  memory, but it's the *type* of memory used that is different.

`append` uses the *stack* which is not very big (8 MiB)

`append_tr` uses the *heap* which is plentiful (several GiB)

## Remark: performance

`append` will outperform `append_tr` on small lists. On (very) large lists, `append` will crash whereas `append_tr` will run. Both `append` and `append_tr` use  $O(n)$  memory, but it's the *type* of memory used that is different.

`append` uses the *stack* which is not very big (8 MiB)

`append_tr` uses the *heap* which is plentiful (several GiB)

However, our continuations in the form of *closures* (functions capturing an environment) incurs an extra time and space penalty.

# Recap: how to convert to continuation-passing style

- 1 Change the type signature: add the continuation.

e.g. `append : 'a list -> 'a list -> 'a list.`

becomes

`append_tr : 'a list -> 'a list -> ('a list -> 'r) -> 'r.`

# Recap: how to convert to continuation-passing style

- 1 Change the type signature: add the continuation.

e.g. `append : 'a list -> 'a list -> 'a list.`

becomes

`append_tr : 'a list -> 'a list -> ('a list -> 'r) -> 'r.`

- 2 Move all the work that should happen after the recursive call into the continuation.

e.g.

```
| x :: xs ->  
  let ys = append xs l2 in  
  x :: ys
```

becomes

```
| x :: xs ->  
  append_tr xs l2  
    (fun ys -> return (x :: ys))
```

and returning becomes an explicit call to the continuation.

# Conclusion

Higher-order functions allow us to:

- express **concise generic algorithms**;
- directly **manipulate control flow**.

Next time: creatively using this control flow manipulation.