

```
1  #include<stdio.h>
2  int main()
3  {
4  int n,i,j,temp;
5  float package[100];
6  float highest,lowest,sum=0,average;
7  float searchpackage;
8  int found=0;
9  printf("Enter the no of students placed: ");
10 scanf("%d",&n);
11 printf("\nEnter the salary packages (inLPA):\n");
12 for(i=0;i<n;i++)
13 {
14 printf ("\nPackage of students %d:",i+1);
15 scanf("%f", &package[i]);
16 sum+=package[i];
17 }
18 highest=lowest=package[0];
19 for(i=1;i<n; i++)
20 {
21 if (package[i]>highest)
22 highest=package[i];
23 if (package[i]<lowest)
24 lowest=package[i];
25 }
26 average=sum/n;
27 printf("\n----Pacement Package analysis----\n");
28 printf("\nHighest package:%.2fLPA\n", highest);
29 printf ("\nLowest package:%.2fLPA\n", lowest);
30 printf ("\nAverage package:%.2fLPA\n", average);
31 printf("\n Enter package to search:");
32 scanf("%f",&searchpackage);
33 for(i=0;i<n;i++)
34 {
35 if (package[i]==searchpackage)
```

```

32 scanf("%f",&searchpackage);
33 for(i=0;i<n;i++)
34 {
35     if (package[i]==searchpackage)
36     {
37         printf("\npackage found at position %d \n",i+1);
38         found=1;
39         break;
40     }
41 }
42 if (found==0)
43 {
44     printf("\npackage not found\n");
45 }
46 /*sorting in descending order*/
47 for(i=0;i<n-1;i++)
48 {
49     for(j=0;j<n-i-1;j++)
50     {
51         if(package[j]<package[j+1])
52         {
53             temp=package[j];
54             package[j]=package[j+1];
55             package[j+1]=temp;
56         }
57     }
58 }
59 printf("\n packages in descending order: \n");
60 for(i=0;i<n; i++)
61 {
62     printf("%.2f", package[i]);
63 }
64 return 0;
65 }

```

Enter the no of students placed:
Enter the salary packages (inLPA):

Package of students 1:1000000

Package of students 2:1000000

----Pacement Package analysis----

Highest package:1000000.00LPA

Lowest package:1000000.00LPA

Average package:1000000.00LPA

Enter package to search:
package not found

packages in descending order:
1000000.001000000.00