

```
1 #include<stdio.h>
2 int main()
3 {
4     int sales[3][4];
5     int producttotal[3];
6     int grandtotal=0;
7     int i,j,bestproduct=0;
8     printf("Enter sales data for 3 products and 4 months:\n");
9     for(i=0;i<3;i++)
10    {
11        producttotal[i]=0;
12        printf("\nProduct%d\n", i+1);
13        for(j=0;j<4;j++)
14        {
15            scanf("%d", &sales[i][j]);
16            printf("\nMonth%dSales:%d",j+1,sales[i][j]);
17            producttotal[i]+=sales[i][j];
18        }
19        grandtotal+=producttotal[i];
20    }
21    for(i=1;i<3;i++)
22    {
23        if(producttotal[i]>producttotal [bestproduct])
24        {
25            bestproduct=i;
26        }
27    }
28    printf("\n----- ");
29    printf("\nProduct\tTotal Sales");
30    printf("\n-----");
31    for(i=0;i<3;i++)
32    {
33        printf("\nP%d\t%d",i+1,producttotal[i]);
34    }
35    printf("\n-----");
36    printf("\nGrand Total Sales=%d", grandtotal);
37    printf("\nBest Selling Product Product%d", bestproduct+1);
38    return 0;
39 }
```

Enter sales data for 3 products and 4 months:

Product1

Month1Sales:20000

Month2Sales:30000

Month3Sales:50000

Month4Sales:70000

Product2

Month1Sales:40000

Month2Sales:60000

Month3Sales:20000

Month4Sales:70000

Product3

Month1Sales:50000

Month2Sales:10000

Month3Sales:80000

Month4Sales:90000

Product Total Sales

P1 170000

P2 190000

P3 230000

Grand Total Sales=590000

Best Selling Product Product3