AI Executive Advisory System

UI wireframes, backend workflows and production plan

Technical assessment: Personal AI and Digital Operations Executive

Author: Niaz Mahmud

October 2026

Contents

- Live demo, source code and test accounts (page 2).
- Part 1. UI wireframes: the screens drawn first and used to generate the React user interface.
- Part 2. Backend workflows and data flows: sequence diagrams of every workflow, with an explanation and production improvements.
- Part 3. Data storage today and in production: from JSON files to Amazon S3, Amazon RDS and AWS Secrets Manager.

Live demo, source code and test accounts

The application runs on Render (free plan). The source code is in two public GitHub repositories.

Item	Link	Use
Web app (frontend)	https://ai-executive-advisory-frontend.onrender.com	Start testing here
API server (backend)	https://ai-executive-advisory-backend-1.onrender.com	Wake it first (step 1)
Frontend source code	https://github.com/NiazMahmud2001/AI_Executive_Advisory--FrontEnd	React + Vite
Backend source code	https://github.com/NiazMahmud2001/AI_Executive_Advisory--Backend	FastAPI + LangGraph

Before testing

1. Open https://ai-executive-advisory-backend-1.onrender.com/api/health and wait until it shows {"status":"ok", ...}. The free server sleeps when idle, so this can take about a minute.
2. Then open https://ai-executive-advisory-frontend.onrender.com and sign in with an account below.

Test accounts

Role	Name	Email	Password	Access
Administrator	Layla Mansour	admin@oasispeak.example	AdminDemo2026!	All documents (incl. confidential) and all pages
Standard user	Omar Siddiqui	employee@oasispeak.example	UserDemo2026!	General documents only; no Administration pages

Good to know

- Demo accounts for testing only; every document is synthetic (a fictional company).
- Administration pages (Automations, Users & roles, Audit log) are for the administrator only.
- A server restart deletes uploads and new users; demo accounts and sample files come back.
- Five wrong passwords lock that email for 15 minutes; a session ends after 30 idle minutes.
- AI answers take about 5 to 15 seconds. If 'The AI service is temporarily unavailable' appears, the free AI model is busy or out of its daily quota; try again later.

Quick checks

Sign in as	Ask or open	Expected result
Standard user	What is the CEO's total salary package?	No evidence (the file is confidential)
Administrator	The same question	Answer cites Executive Compensation 2026
Any account	How many days of annual leave do employees get?	A note that two HR documents disagree
Any account	How much did revenue grow in Q3 2026?	Figures computed in code, with sources
Any account	What is the company's parking policy?	No evidence: no document covers it
Administrator	Audit log page	Sign-ins, AI questions and security events

Part 1. UI wireframes

Before any code was written, every screen was drawn as a low-fidelity wireframe. These wireframes were then used to generate and build the React user interface in frontend/, so each page of the application follows the layouts below.

All signed-in pages share one shell. The sidebar shows Overview, Ask Advisor and Documents to every user, and an Administrator section (Automations, Users and roles, Audit log) only to administrators. A user card at the bottom holds the Logout button, and the top bar shows the page title, the user's role and the light and dark theme toggle.

1.1 Sign-in page

Brand and theme toggle at the top. The left panel introduces the system (document encryption, the AI advisors and confidential access); the right panel holds the email and password fields and the Sign in button.



Figure 1. Wireframe: Sign-in page

1.2 Overview dashboard

A greeting with the date and the user's name, shortcuts to upload a document and to ask the advisors, and four role-aware cards. Administrators see questions from all users, security events, automation runs and recent uploads; standard users see their own questions and the general documents.




Figure 2. Wireframe: Overview dashboard

1.3 Ask advisor (chat)

The conversation area with example questions, three buttons to choose the advisor (Finance, HR and Management, Knowledge) or let the system route automatically, the question input, and a side panel that introduces the advisors.



Figure 3. Wireframe: Ask advisor (chat)

1.4 Documents

The document library with a search field, filters for category and access level, and the Upload document button.




Figure 4. Wireframe: Documents

1.5 Users and roles (administrator)

Every account with its name, a role dropdown (administrator or user), its status and last sign-in, a Disable button, and Add new user.




Figure 5. Wireframe: Users and roles (administrator)

1.6 Automations (administrator)

Each uploaded document with its five pipeline steps: file checked, encrypted and stored; text extracted; summary generated; result recorded in the database; administrators notified. A Refresh button reloads the list.




Figure 6. Wireframe: Automations (administrator)

1.7 Audit log (administrator)

The time, event, actor email, IP address and details of every audited action. The implemented page adds a filter by event group (security, sign-in, documents, AI and users).




Figure 7. Wireframe: Audit log (administrator)

Part 2. Backend workflows and data flows

The backend is a FastAPI application. The diagrams in this part document each workflow as a sequence diagram, drawn from the code. Each vertical bar is a participant (lifeline): the user, the browser or React UI, the FastAPI middleware, the session guard (require_user and require_admin), the router (the endpoint), service modules (security.py, automation.py and the agents), the JSON store (backend/data), the encrypted file store (backend/storage) and the OpenRouter LLM.

How to read the diagrams

- Arrows are numbered in order. A solid arrow is a request or a call, a dashed arrow is a response, and a red dashed arrow is an error.
- A dashed line across the diagram starts a conditional branch (alt) or a loop.
- Each label shows the call in bold and the data it carries below it, with types: str, int, bool, bytes, uuid and datetime (an ISO 8601 string in UTC, for example 2026-10-31T12:25:12+00:00).
- Under each diagram, 'For a production-grade system' lists what would be added beyond this prototype.

A. Foundation

Flow 1. Data dictionary

All records, where they are stored today and the type of every field. Passwords and session tokens are never stored in plain text: users.json keeps a bcrypt hash and sessions.json keeps the SHA-256 of the cookie token. The API never returns password_hash or storage_key.

1. Data dictionary

User users.json	id: uuid, email: str, name: str, role: admin|user, password_hash: str (bcrypt), active: bool, created_at: datetime, last_login_at: datetime|null
Session sessions.json	id: str (sha256 of cookie token), user_id: uuid, csrf_token: str, created_at, last_seen_at, expires_at: datetime, ip: str, user_agent: str
Document documents.json + storage/{id}.bin	id: uuid, title, filename, extension, size_bytes: int, sha256: str, category, classification: general|confidential, storage_key, uploaded_by, created_at, status: processing|processed, summary
AutomationRun automations.json	id, document_id, triggered_by, status: running|completed|failed, started_at, finished_at, summary, steps[{key, label, status, at, note}]
Question questions.json (last 500)	id, user_id, at: datetime, question: str, advisor: str, status: str
AuditEvent audit.json (last 2000)	id, at, event: str, user_id, user_email, ip: str, detail: dict
Answer POST /api/agent/ask response	id, question, advisor, routing{mode, reason, matched}, status, answer, citations[], calculations[], conflicts[], missing_information[], suggestions[], security_notice, engine, created_at, latency_ms: int
Transport cookie and headers	aea_session: str (HttpOnly, SameSite=Strict, Secure in prod, Max-Age 28800); X-CSRF-Token: str; X-Request-ID: str (12 hex)

Figure 8. Flow 1: Data dictionary

For a production-grade system

- Postgres tables with UUID primary keys, timestamptz columns, constraints and indexes, managed with migrations (Alembic).
- A retention policy for personal data in sessions, questions and the audit log.

Flow 2. First-time setup (seed.py)

seed.py prepares a new installation. It creates backend/.env with a fresh Fernet key, so every installation has its own key and no key reaches git, creates the demo accounts with bcrypt hashes, and imports the sample documents encrypted at rest. It is idempotent: existing users and documents are skipped, and --reset wipes data/ and storage/ first.




Figure 9. Flow 2: First-time setup (seed.py)

For a production-grade system

- Keys in AWS KMS or Secrets Manager instead of a file.
- No demo accounts: the first administrator comes from SSO or an invitation.
- Key rotation (MultiFernet or envelope encryption).

Flow 3. API startup (lifespan)

On start the lifespan hook fails fast on configuration errors: a missing or invalid encryption key, or the LangGraph engine without an OpenRouter key, stops the server with a clear message. It also creates the data folders and purges expired sessions.




Figure 10. Flow 3: API startup (lifespan)

For a production-grade system

- Liveness and readiness probes for the hosting platform.
- Typed configuration validation (pydantic-settings).
- Database migrations in the deploy pipeline and graceful shutdown.

Flow 4. Request pipeline (every request)

Every request passes the same middleware. It receives a request ID, the session guard runs before body validation, unhandled errors become a generic 500 with the request ID (no stack trace leaks), and every response gets security headers (CSP, nosniff, frame denial, no-store on the API, HSTS in production) and one JSON log line.




Figure 11. Flow 4: Request pipeline (every request)

For a production-grade system

- A TLS-terminating load balancer with a WAF, request size limits and rate limits.
- Distributed tracing (OpenTelemetry) and central logs (CloudWatch).
- Static files served from a CDN (CloudFront).

Flow 5. Session and CSRF guard

require_user resolves the HttpOnly cookie to a server-side session through its SHA-256 hash, enforces the 8-hour lifetime and the 30-minute idle timeout, rejects disabled users and checks the CSRF token with a constant-time comparison on every request that changes data. require_admin adds the role check and audits denials. The role always comes from the server, never from the client.




Figure 12. Flow 5: Session and CSRF guard

For a production-grade system

- Sessions in Redis (Amazon ElastiCache) with a TTL.
- SSO (OIDC, for example Microsoft Entra ID) with MFA.
- A page to list and revoke active sessions, and alerts on new devices.

B. Authentication

Flow 6. App load or refresh

After a refresh the React state is empty but the HttpOnly cookie is still in the browser. AuthProvider calls GET /api/auth/me to restore the user and the CSRF token, so nothing sensitive is kept in localStorage. Without a valid session the user goes to the sign-in page and returns to the original page after signing in.




Figure 13. Flow 6: App load or refresh

For a production-grade system

- Sign out in every tab at once (BroadcastChannel).
- Route-level code splitting for faster loading.

Flow 7. Login (success)

The login endpoint checks the lockout, looks the user up and verifies the bcrypt hash; for an unknown email a dummy hash is checked, so the timing reveals nothing. Every sign-in issues a new random token and only its SHA-256 is stored. The browser receives the token in an HttpOnly, SameSite=Strict cookie and the CSRF token in the response body.




Figure 14. Flow 7: Login (success)

For a production-grade system

- SSO with MFA.
- Argon2id and a breached-password check.
- Email notification for sign-ins from a new device.

Flow 8. Login failures and lockout

Unknown emails and wrong passwords get the same 401 message and take the same time. Five failures for one email and IP address lock that pair for 15 minutes (429). A disabled account is only reported after the correct password. Every case is written to the audit log.




Figure 15. Flow 8: Login failures and lockout

For a production-grade system

- Lockout state in Redis, so it survives restarts and works across instances.
- CAPTCHA and exponential backoff after repeated failures.
- Brute-force alerts in a SIEM.

Flow 9. Logout

Logout deletes the session on the server and expires the cookie, so an old cookie cannot be replayed. The request carries the CSRF token, so other websites cannot sign the user out.




Figure 16. Flow 9: Logout

For a production-grade system

- Sign out of all devices.
- Single logout with the SSO provider.

Flow 10. Session expiry and idle timeout

Timeouts are enforced on the server. The first request after 30 idle minutes (or 8 hours in total) receives 401, and api.js turns any 401 into a sign-out with a notice, so the UI never shows stale data.




Figure 17. Flow 10: Session expiry and idle timeout

For a production-grade system

- A warning before the session ends ('Stay signed in?').
- Scheduled cleanup of expired sessions.
- Timeouts per role, following company policy.

C. Overview and UI shell

Flow 11. Overview dashboard

One endpoint returns role-aware numbers. Standard users receive only figures about what they can access; the administrator figures (users, confidential documents, security events of the last 24 hours) are computed only for administrators, so they never reach a standard user's browser.




Figure 18. Flow 11: Overview dashboard

For a production-grade system

- Count 'today' in Gulf time (Asia/Dubai, UTC+4) instead of UTC.
- Pre-computed metrics and caching.
- Live updates with server-sent events.

Flow 12. Navigation, roles and theme

The sidebar shows administrator pages only to administrators, and RequireAdmin blocks them in the browser. This is a convenience only: every administrator endpoint returns 403 to standard users. The theme preference is stored in localStorage and never reaches the server.




Figure 19. Flow 12: Navigation, roles and theme

For a production-grade system

- Menus built from a permission list sent by the server.
- Arabic and right-to-left support.
- An accessibility audit (WCAG 2.2 AA).

D. Documents

Flow 13. Document library list

The clearance filter is applied inside the store query, so confidential documents never leave the server for a standard user. Internal fields (storage_key, seed_key) are removed before the response.




Figure 20. Flow 13: Document library list

For a production-grade system

- Server-side search, filters and pagination.
- Row Level Security in Postgres.
- Full-text search across document content.

Flow 14. File upload

Uploads are checked from the cheapest test to the most expensive: category and classification, administrator-only confidential uploads, the file type allow-list, the 10 MB limit, an empty-file check and the file signature (magic bytes). A SHA-256 fingerprint rejects duplicates within the caller's clearance. The file is encrypted before it is written, under a server-generated name, and the automation run starts in the background.




Figure 21. Flow 14: File upload

For a production-grade system

- Malware scanning (for example ClamAV) before storage.
- Direct uploads to Amazon S3 with pre-signed URLs and a size limit at the load balancer.
- Per-user quotas and classification suggestions from a DLP service.

Flow 15. Encryption at rest

Files are encrypted with Fernet (AES-128-CBC with HMAC-SHA256) using DOC_ENCRYPTION_KEY. The HMAC detects any change to a stored file. Plain text exists only in memory while a file is downloaded or read by the agent. Without the key the stored files are unreadable, and losing the key means losing the files.




Figure 22. Flow 15: Encryption at rest

For a production-grade system

- Envelope encryption with AWS KMS: a data key per file, wrapped by a KMS key.
- Key rotation and an audit trail of key use (CloudTrail).
- S3 server-side encryption (SSE-KMS) as an additional layer.

Flow 16. Upload automation pipeline

The upload returns 201 at once and a background task runs the pipeline: stored, extracted, summarized, recorded, notified. Each step's status is saved, so the UI can poll and show progress, and a failure is recorded with its reason instead of being lost. In phase 1 the later steps are simulated.




Figure 23. Flow 16: Upload automation pipeline

For a production-grade system

- A job queue (Amazon SQS with worker services) with retries and a dead-letter queue; in-process background tasks are lost if the server restarts.
- Real text extraction, an LLM summary and email notification (Amazon SES).
- Progress pushed with server-sent events instead of polling.

Flow 17. File download

A download goes through the same visibility check as every other read. The file is decrypted in memory and sent as an attachment with the correct MIME type and a UTF-8 file name, so it is never rendered inside the application. Every download is audited.




Figure 24. Flow 17: File download

For a production-grade system

- Short-lived S3 pre-signed URLs.
- Streaming decryption for large files.
- Watermarks on confidential documents.

Flow 18. Reclassify or rename (administrator)

Only administrators can change a document. Because every query takes the caller's clearance and nothing is cached, a reclassification applies to the next request everywhere: the library, downloads and the AI advisors.




Figure 25. Flow 18: Reclassify or rename (administrator)

For a production-grade system

- Four-eyes approval before a document is declassified.
- Classification history.
- More access levels and department-based access (ABAC).

Flow 19. Delete a document (administrator)

The administrator deletes the encrypted file and its record. The audit entry keeps the title, because an ID alone means nothing after deletion. Past automation runs stay as history but are hidden from standard users.




Figure 26. Flow 19: Delete a document (administrator)

For a production-grade system

- Soft delete with a retention period and restore.
- Legal hold.
- Crypto-shredding by deleting the file's data key.

Flow 20. Blocked confidential access

A standard user who requests a confidential document by its ID receives the same 404 as for a document that does not exist, so its existence is not revealed. The attempt is written to the audit log and appears on the administrator's dashboard.




Figure 27. Flow 20: Blocked confidential access

For a production-grade system

- SIEM alerts on repeated denials.
- Rate limits against ID enumeration.

E. Users and roles

Flow 21. User list

Administrators see every account with its role, status and last sign-in; the password hash is never returned. The wireframe also asks for 'signed in now', which needs a signed_in flag derived from active sessions; the API does not return it yet.




Figure 28. Flow 21: User list

For a production-grade system

- Provisioning from the company directory (SCIM from Microsoft Entra ID).
- Search, pagination and departments.

Flow 22. Add user

The administrator creates an account with a validated email and a password that meets the policy (at least 10 characters, letters and digits, at most 72 bytes). The password is stored only as a bcrypt hash and the creation is audited.




Figure 29. Flow 22: Add user

For a production-grade system

- Invitation links with one-time tokens instead of passwords chosen by an administrator.
- MFA enrolment and a forced password change at the first sign-in.

Flow 23. Change role (promote or downgrade)

Changing a user's role deletes all of that user's sessions, so the new permissions apply immediately: a downgraded administrator cannot keep a session with confidential access open. Administrators cannot downgrade themselves, so at least one administrator always remains.




Figure 30. Flow 23: Change role (promote or downgrade)

For a production-grade system

- Approval before administrator rights are granted.
- Time-bound (just-in-time) elevation.
- Role change history.

Flow 24. Disable or enable a user

Disabling signs the user out everywhere and blocks future sign-ins (403 after the correct password). Disabling instead of deleting keeps the history linked to the account: audit entries, uploads and questions.




Figure 31. Flow 24: Disable or enable a user

For a production-grade system

- Automatic deprovisioning when HR records a leaver.
- Scheduled disabling at the end of a contract.
- Handling of data deletion requests under the UAE PDPL.

Flow 25. Reset a password

The new password is checked against the policy and stored only as a bcrypt hash, and all of the user's sessions end. The audit entry records that the password changed, never the hash.




Figure 32. Flow 25: Reset a password

For a production-grade system

- Self-service reset by email with an expiring link.
- Identity checks before an MFA reset.
- An email notification to the user.

F. AI advisors

Flow 26. Ask a question: static engine

Without an OpenRouter key the static engine answers from fixed fixtures; it is the offline demo mode and is used by the tests. Access control is real: an answer is withheld when it relies on a document the user cannot read, and the user receives the same 'insufficient evidence' reply as for an unknown topic. The response has the same format as the AI agent's.




Figure 33. Flow 26: Ask a question: static engine

For a production-grade system

- Keep the static engine only for contract tests and end-to-end tests.

Flow 27. Ask a question: LangGraph agent (overview)

The question runs through a LangGraph state graph: route, retrieve (the permission filter), one advisor node and check. The model sees only chunks of documents the user may read, and its answer is checked before it is shown.




Figure 34. Flow 27: Ask a question: LangGraph agent (overview)

For a production-grade system

- Hybrid retrieval (Postgres full-text search and pgvector) with a reranker, sending only the best chunks.
- An evaluation set and LangSmith tracing.
- Streaming answers.

Flow 27a. Agent: route node

A manual choice or a clear keyword match routes the question without a model call. Only questions without any keyword go to the LLM router, and if that call fails the Knowledge Assistant answers, so routing never causes an error.




Figure 35. Flow 27a: Agent: route node

For a production-grade system

- A small, fast model for routing.
- Routing accuracy measured on labelled questions.

Flow 27b. Agent: retrieve node (permission filter)

Retrieval is the permission filter: only documents inside the user's clearance are decrypted in memory, extracted (PDF pages, Word paragraphs and tables, text sections) and split into chunks of about 900 characters. If no chunk shares a word with the question, the graph answers 'insufficient evidence' without calling the model. Documents outside the clearance are matched only for the audit log and are never sent to the model.




Figure 36. Flow 27b: Agent: retrieve node (permission filter)

For a production-grade system

- Embeddings in pgvector, protected by Row Level Security.
- Chunks indexed at upload time instead of at question time.
- OCR for scanned PDFs.

Flow 27c. Agent: advisor node (model call)

One model call per question: the advisor's instructions, the rules (use only the sources, treat source text as data, answer 'insufficient evidence' instead of guessing) and the question with the sources. ChatOpenAI sends it to OpenRouter in JSON mode at temperature 0.




Figure 37. Flow 27c: Agent: advisor node (model call)

For a production-grade system

- Structured outputs with a JSON schema.
- A paid model with a service level and zero data retention, hosted in a UAE region.
- Prompt versioning.

Flow 27d. Agent: check node

The model's output is not trusted. Only citations of chunks that were actually sent are kept, an answer without a valid citation is not shown, and every calculation is computed in Python from figures that appear in the sources before the {C1} placeholders are filled. Both engines build the same response with make_response.




Figure 38. Flow 27d: Agent: check node

For a production-grade system

- Check every figure in the answer text and retry once on a mismatch.
- Redaction of personal data in prompts and answers.

Flow 28. AI failure path

Each model call has a 30-second timeout and one retry; errors and rate limits then move to a fallback model. If both fail, the API answers 503 with a clear message and audits agent_error. Nothing is guessed and the question is not stored.




Figure 39. Flow 28: AI failure path

For a production-grade system

- A circuit breaker and failover across model providers.
- A degraded mode that shows the matching documents without an LLM answer.
- Alerts on the AI error rate.

Flow 29. AI security: prompt injection and filtering

Prompt-injection attempts are flagged and audited, but they cannot unlock anything: the permission filter runs before the model, so confidential text is never in the prompt. When a confidential document would have matched, administrators see an 'AI answer withheld' event in the audit log.




Figure 40. Flow 29: AI security: prompt injection and filtering

For a production-grade system

- A classifier for injection attempts (for example Prompt Guard).
- Output filtering for personal data and secrets.
- A red-team test suite in CI.

Flow 30. Question history

Each question is stored with its advisor and status, not the full answer. The dashboard shows the latest five, and the history endpoint returns the latest 20 for the current user.




Figure 41. Flow 30: Question history

For a production-grade system

- Store full answers with citations, model, latency and tokens for audit and evaluation.
- Conversation threads and a retention policy.

G. Administrator monitoring

Flow 31. Audit log viewer

Every security-relevant action calls log_event, which appends the time, event, user, IP address and details to the audit log; the latest 2,000 events are kept. Administrators filter the log by group: security, sign-in, documents, AI and users.




Figure 42. Flow 31: Audit log viewer

For a production-grade system

- Append-only (WORM) storage with a hash chain.
- Export to a SIEM (Amazon Security Lake, Splunk or Microsoft Sentinel) with alert rules.
- Retention according to company policy.

Flow 32. Automations page

Administrators see every automation run; standard users see only the runs of their own uploads that they can still read. The page refreshes every 1.5 seconds while a run is in progress.




Figure 43. Flow 32: Automations page

For a production-grade system

- Updates pushed with server-sent events.
- A retry button for failed runs.
- A queue monitoring dashboard.

Flow 33. Health check

An unauthenticated endpoint for uptime monitors and the hosting platform. It reports the version, the project phase and which AI engine is active.




Figure 44. Flow 33: Health check

For a production-grade system

- Separate liveness and readiness checks (database, storage, LLM).
- No version details on a public endpoint.
- A metrics endpoint for CloudWatch or Prometheus.

H. Cross-cutting

Flow 34. Error and status code map

Every error reaches the UI as a status code with a readable message. A 401 always signs the user out; 403, 404, 409, 413, 415 and 422 appear next to the action that caused them; a 503 offers 'Try again'; a 500 carries the request ID that links it to the server log.




Figure 45. Flow 34: Error and status code map

For a production-grade system

- Machine-readable error codes.
- Error tracking (Sentry) for the frontend and the backend.
- Downloads through fetch, so errors appear as messages instead of raw JSON.

Flow 35. Production deployment flow

In production one service serves the built UI and the API on the same HTTPS origin, so the cookie stays SameSite=Strict and no CORS is needed. Secrets come from the environment, cookies are Secure and HSTS is on. The JSON files of phase 1 would be lost on an ephemeral disk; Part 3 describes the target storage.




Figure 46. Flow 35: Production deployment flow

For a production-grade system

- Several instances behind a load balancer.
- CI/CD with tests and security scans, a staging environment and infrastructure as code.
- Backups and disaster recovery with defined RPO and RTO.

Part 3. Data storage today and in production

3.1 Phase 1: JSON files

In this prototype all data is stored in JSON format. The records live in backend/data as users.json, sessions.json, documents.json, automations.json, questions.json and audit.json. Each write goes through a lock and a temporary file that replaces the original in one step, so a crash never leaves a half-written file. Uploaded documents are Fernet-encrypted .bin files in backend/storage, and the secrets (the document encryption key and the OpenRouter API key) are environment variables in backend/.env, which is excluded from git.

This keeps the prototype easy to run, inspect and demonstrate, but it is not suitable for production: it supports a single server process, offers no transactions or concurrent writers, has no backups, and the files disappear on an ephemeral disk such as a free hosting tier.

3.2 Production on AWS

For production the data moves to managed AWS services. The application is ready for this change: every data access goes through small named functions in store.py, so moving to a database changes only that module, while the routers, the response format and the UI stay the same.

Today (phase 1)	Production on AWS	Why
data/*.json: users, sessions, documents, automation runs, questions, audit	Amazon RDS for PostgreSQL (Multi-AZ, encrypted, automated backups); pgvector for document search; an append-only audit table	Transactions, concurrent access, backups, point-in-time recovery and Row Level Security
storage/*.bin: encrypted documents	Amazon S3 (object or blob storage): a private bucket with SSE-KMS encryption, versioning and pre-signed URLs	Durable and scalable file storage that is never public
DOC_ENCRYPTION_KEY in .env	AWS KMS with envelope encryption (a data key per file)	The master key never leaves KMS; rotation and an audit trail of every use
OPENROUTER_API_KEY and other secrets in .env	AWS Secrets Manager (or Systems Manager Parameter Store)	No secrets in files, IAM-controlled access and automatic rotation
Sessions and the sign-in lockout in a file and in memory	Amazon ElastiCache for Redis with TTLs	Shared by every instance and kept across restarts
In-process background tasks	Amazon SQS with worker services	Retries and a dead-letter queue, so no upload is lost
Logs on standard output	Amazon CloudWatch Logs, metrics and alarms	Central search, dashboards and alerts

Hosting in the AWS Middle East (UAE) region keeps company data in the country, in line with the UAE Personal Data Protection Law (PDPL). The application runs on Amazon ECS behind an Application Load Balancer with HTTPS.

3.3 Summary

Phase 1 proves the complete workflow with real security controls, and phase 2 adds the LangGraph agent. For production the same design moves its data from JSON files to Amazon RDS, its documents to Amazon S3, and its keys and API secrets to AWS KMS and AWS Secrets Manager.