TMS320 DSP

DESIGNER'S NOTEBOOK

Detecting the reset source on the TMS320x240 DSP Controller

Contributed by Jeff Crankshaw

Design Problem

The TMS320x240 ('x240) DSP Controller allows three internal and two external methods to generate device resets. How do I configure the 'x240 to detect which source initiated the reset?

Solution

The 'x240 DSP Controller provides the capability to detect the source of a reset through the use of the System Status Register (SYSSR@701Ah). This register contains a status bit for four of the five possible reset sources. The fifth source, the external $\overline{RS}$ pin, does not have a status bit, and is identifiable when the other four bits are cleared. These bits are summarized below:

Bit 15	PORST	external Power-on Reset ($\overline{PORESET}$) pin
Bit 12	ILLADR	Illegal Address Access
Bit 10	SWRST	Software Reset
Bit 9	WDRST	Watchdog Timer
None of these set -		External Reset ($\overline{RS}$) pin

The reset service routine should be written to check the status of each bit and take the appropriate action. When the status bit equals 1, the indicated event triggered the reset. In the case when none of the reset status bits are set, the external $\overline{RS}$ pin triggered the reset.

On detection of power-on-reset, the programmer should initialize the PLL, if necessary, configure the CLKOUT pin for the desired function, and clear the PORST status bit. In addition, the programmer may wish to implement a wait loop while the PLL locks. Once the PLL locks, the internal clock will run at the programmed frequency. This ensures that software-timed events will work as expected.

An assembly language code example is included below for reference.

Example 1. Code Listing

```
; .set definitions for useful constants

DP_PF1    .set   224       ;page 1 of periph. file (7000h/80h)
SYSCR     .set   07018h    ;System Module Control Register
SYSSR     .set   0701Ah    ;System Module Status Register
RTICR     .set   07027h    ;RTI Control register
WDTCR     .set   07029h    ;WD Control register
CKCR0     .set   0702ah    ;PLL Clock Control Register 0
CKCR1     .set 0702ch      ;PLL Clock Control Register 1
;Bit codes for Test bit instruction (BIT)
BIT15     .set   0000h     ;Bit Code for 15
BIT12     .set   0003h     ;Bit Code for 12
BIT10     .set   0005h     ;Bit Code for 10
BIT9      .set   0006h     ;Bit Code for 9
BIT5      .set   000Ah     ;Bit Code for 5
    .text
RESET: B   START
       B   INT1_ISR    ;User's interrupt vector table inserted
                       ;here
    :
   (etc …)
;================================================================
; This first segment of code is executed after every reset.
; The CPU modes, such as sign extension, overflow, XF output
; state, and global interrupt mask are initialized for clarity
; In addition, the data page pointer is set to access the first
; page in the peripheral register file, address 0x7000. Finally,
; the watchdog timer is configured to be disabled if Vccp = 5V,
; and run with the maximum period for both the watchdog timer and
; the real time interrupt timer.
;================================================================
START:
   SETC   CNF
   CLRC   OVM   ; Reset overflow mode
   CLRC   SXM   ; Reset sign extension mode
   CLRC   XF
   SETC   INTM      ; Set global interrupt mask
; Set DP to first peripheral file page, 0x7000-7f.
   LDP #DP_PF1
; initialize WDT registers
   SPLK   #06Fh, WDTCR ; clear WDFLAG, Disable WDT, set WDT for 1
                       ; second overflow (max)
   SPLK   #07h, RTICR  ; clear RTI Flag, set RTI for 1 second
                       ; overflow (max)
;configure SYSCLK=CPUCLK/2 after reset
   LACC   CKCR0        ; ACC=CKCR0
   OR     #01h         ; set PLLPS=1
   SACL   CKCR0        ; and write back to CKCR0
;================================================================
; The following section of code executes only once, on power-up.
;================================================================
; Detect Power On Reset
PORCHK:   BIT SYSSR,BIT15
   BCND   ILLCHK,NTC   ;if power on reset continue,
                       ; else branch to next reset source
; set up PLL clockin=10Mhz,CPUCLK=20Mhz,SYSCLK=10Mhz
   SPLK   #00b1h,CKCR1
   SPLK   #0081h,CKCR0
; Clear all reset status bits: POR, ILLADR, WDTRST, SWRST
   LACC   SYSSR
   AND #0FFh
   SACL   SYSSR
; Set up CLKOUT to be SYSCLK
   SPLK   #4080h,SYSCR
```

```
           ; Wait until PLL is locked before executing main section of code
PLLCHK:    BIT CKCR0,BIT5
    BCND   PLLCHK,NTC
                 ;Any additional initialization code may be
                 ;inserted here.
    B  MAIN
;===============================================================
; This ends the power-up code section and begins the reset source
; identification section. The following code checks for Illegal
; Address, Software, and Watchdog resets. If found, the
; corresponding bit in the system status register, SYSSR, is
; cleared. In addition to clearing the status bits, the user may
; execute code specific to each reset type before executing the
; main code.
;===============================================================
ILLCHK:    BIT SYSSR,BIT12
    BCND   SWCHK,NTC
    LACL   SYSSR
    AND #0EFFFh       ;Clear ILLADR bit
    SACL   SYSSR
                 ;User specific code may be inserted here.
    B  MAIN
SWCHK: BIT SYSSR,BIT10
    BCND   WDCHK,NTC
    LACL   SYSSR
    AND #0FBFFh       ;Clear SWRST bit
    SACL   SYSSR
                 ;User specific code may be inserted here.
    B  MAIN
WDCHK: BIT SYSSR,BIT9
    BCND   EXTRST,NTC
    LACL   SYSSR
    AND #0FDFFh       ;Clear WDRST bit
    SACL   SYSSR
                 ;User specific code may be inserted here.
    B  MAIN
EXTRST:    NOP       ;User specific code may be inserted here.
MAIN:
```

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgment, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Customers are responsible for their applications using TI components.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, license, warranty or endorsement thereof.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations and notices. Representation or reproduction of this information with alteration voids all warranties provided for an associated TI product or service, is an unfair and deceptive business practice, and TI is not responsible nor liable for any such use.

Resale of TI's products or services with _statements different from or beyond the parameters_ stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service, is an unfair and deceptive business practice, and TI is not responsible nor liable for any such use.

Also see: Standard Terms and Conditions of Sale for Semiconductor Products. www.ti.com/sc/docs/stdterms.htm

Mailing Address:

Texas Instruments
Post Office Box 655303
Dallas, Texas 75265