
data_tools Documentation

Release 0.0.1

Nicolas Palacio

May 18, 2018

CONTENTS:

1	data_tools.sets	1
2	data_tools.strings	3
3	Indices and tables	5
	Python Module Index	7
	Index	9

DATA_TOOLS.SETS

Set operations module

`data_tools.sets.in_all(x, N)`

Checks if a vector `x` is present in all sets contained in a list `N`.

- **Arguments:**

- `x` [tuple]: Or any hashable type as long as is the same contained in the sets of `N`.
- `N` [list]: Or any iterable type containing [set] objects.

- **Returns:**

- [bool]: True if `x` is found in all sets of `N`, False otherwise.

- **Examples:**

```
>>> N = [{(0, 0), (0, 1)}, # <- set A
...      {(0, 0), (1, 1), (1, 0)}] # <- set B
>>> x = (0, 0)
>>> in_all(x, N)
True
>>> y = (0, 1)
>>> in_all(y, N)
False
```

`data_tools.sets.bit_or(a, b)`

Returns the bit operation OR between two bit-strings `a` and `b`. NOTE: `a` and `b` must have the same size.

- **Arguments:**

- `a` [tuple]: Or any iterable type.
- `b` [tuple]: Or any iterable type.

- **Returns:**

- [tuple]: OR operation between `a` and `b` element-wise.

- **Examples:**

```
>>> a, b = (0, 0, 1), (1, 0, 1)
>>> bit_or(a, b)
(1, 0, 1)
```

`data_tools.sets.multi_union(N)`

Returns the union set of all sets contained in a list `N`.

- **Arguments:**

- N [list]: Or any iterable type containing [set] objects.

- **Returns:**

- [set]: The union of all sets contained in N.

- **Examples:**

```
>>> A = {1, 3, 5}
>>> B = {0, 1, 2}
>>> C = {0, 2, 5}
>>> multi_union([A, B, C])
set([0, 1, 2, 3, 5])
```

data_tools.sets.**find_min**(A)

Finds and returns the subset of vectors whose sum is minimum from a given set A.

- **Arguments:**

- A [set]: Set of vectors ([tuple] or any iterable).

- **Returns:**

- [set]: Subset of vectors in A whose sum is minimum.

- **Examples:**

```
>>> A = {(0, 1, 1), (0, 1, 0), (1, 0, 0), (1, 1, 1)}
>>> find_min(A)
set([(0, 1, 0), (1, 0, 0)])
```

DATA_TOOLS.STRINGS

String operations module

`data_tools.strings.is_numeric(s)`

Determines if a string can be considered a numeric value. NaN is also considered, since it is float type.

- **Arguments:**

- `s [str]`: String to be evaluated.

- **Returns:**

- `[bool]`: True/False depending if the condition is satisfied.

- **Examples:**

```
>>> is_numeric('4')
True
>>> is_numeric('-3.2')
True
>>> is_numeric('number')
False
>>> is_numeric('NaN')
True
```

`data_tools.strings.join_str_lists(a, b, sep="")`

Joins element-wise two lists (or any 1D iterable) of strings with a given separator (if provided). Length of the input lists must be equal.

- **Arguments:**

- `a [list]`: Contains the first elements `[str]` of the joint strings.
- `b [list]`: Contains the second elements `[str]` of the joint strings.
- `sep [str]`: Optional “ (non separated) by default. Determines the separator between the joint strings.

- **Returns:**

- `[list]`: List of the joint strings.

- **Example:**

```
>>> a = ['a', 'b']
>>> b = ['1', '2']
>>> join_str_lists(a, b, sep='_')
['a_1', 'b_2']
```


INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

d

`data_tools.sets`, [1](#)

`data_tools.strings`, [2](#)

INDEX

B

`bit_or()` (in module `data_tools.sets`), 1

D

`data_tools.sets` (module), 1

`data_tools.strings` (module), 2

F

`find_min()` (in module `data_tools.sets`), 2

I

`in_all()` (in module `data_tools.sets`), 1

`is_numeric()` (in module `data_tools.strings`), 3

J

`join_str_lists()` (in module `data_tools.strings`), 3

M

`multi_union()` (in module `data_tools.sets`), 1