



Settings

Configure a GRASP-FS pipeline run using the files available in the shared datasets folder.

3 datasets

4 algorithms

3 local searches

Execution Setup

Datasets & Summary

Operations

Execution budget

Core parameters that control the size and cost of the initial construction.

Max. Number of Generations

10

RCL Cutoff

20

Sample Size

5

Neighborhood Max Iterations

10

Distributed local search

Choose which local search services the DLS can use and set their per run iteration budgets.

☒ BiFFip

Swaps attributes between the current solution and the RCL.

BiFFip Neighborhood Max Iterations

100

☒ IWSS

Adds features sequentially based on the observed gain.

IWSS Neighborhood Max Iterations

20

☒ IWSSR

Refines the addition step with removal and replacement.

IWSSR Neighborhood Max Iterations

20

Classifier and orchestration

Choose the classifier and how the distributed local-search stage should be orchestrated.

Classifier Algorithm

J48

Neighborhood Strategy

VND

☐ Reuse cached training dataset

Keeps a copy of the selected training file in memory inside the services to reduce repeated load time on later executions.

RCL algorithms

Select the initial solution generators that should be dispatched by the gateway.

☒ Information Gain

Selects features by information gain.

☒ Gain Ratio

Reduces Information Gain bias on broader attributes.

☒ ReliefF

Evaluates relevance through instance neighborhoods.

☒ Symmetrical Uncertainty

Normalizes dependency between feature and class.

QUEUE EXECUTION

RESET