Example Slide Set
LATEX beamer theme "FrankfurtUniversity"

Prof. Dr. Eicke Godehardt
Frankfurt University of Applied Sciences
Faculty of Computer Science and Engineering
godehardt@fb2.fra-uas.de

Wissen durch Praxis stärkt

"If you are not prepared to be wrong,
you never come up with anything
original.

Sir Ken Robinson

Agenda

Normal Slide

Floats
  Figures
  Tables

Emphasize
  Block
  Text Emphasize
 Code Blocks

Example of Normal Slide
Subtitle

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam sit amet vulputate ante, vel laoreet erat. Cras pulvinar, sem nec lobortis vehicula, leo dolor commodo.

- Item 1
- Item 2:
    - Subitem 2.1
    - …

Figure on slide

Image and Bullet Points Side by Side

- **Lorem ipsum**
  1. Lorem ipsum dolor sit amet, consectetur adipiscing elit.
  2. Donec ut est laoreet, sagittis tortor ac, rhoncus metus.
- **Etiam eget**
  - Etiam eget lectus ac nisl blandit pretium in id velit.
- **Ut in lorem sollicitudin**
  - Ut in lorem sollicitudin, condimentum magna ac, condimentum urna.
  - Ut malesuada eros id odio rutrum auctor varius a mi.
  - Nulla nec sapien condimentum, faucibus libero at, tristique ante.

Example of a Table

2015 (2014)	Language	Ratings	Change
1 (1)	C	16.703%	-1.24%
2 (2)	Java	15.528%	-1.00%
3 (3)	Objective-C	6.953%	-4.14%
4 (4)	C++	6.705%	-0.86%
5 (5)	C#	5.045%	-0.80%
6 (6)	PHP	3.784%	-0.82%
7 (9)	JavaScript	3.274%	**+1.70%**
8 (8)	Python	2.613%	+0.24%
9 (13)	Perl	2.256%	+1.33%
10 (17)	PL/SQL	2.014%	+1.38%

Table: TIOBE Index as of January 2015

Source: http://www.tiobe.com

Using the `block` environment

Title of Bock
Content of block goes here.

Example No. 42
This is an example.

Watch out!!!
You must not do that!

Using the \emph command

You can **emphasize** words by using \emph{emphasize}.
It will automatically use the color of your faculty.

BTW you can access all the different colors as FB1Color,
FB2Color etc.

Displaying chunks of code

```
1 part = new Part()
2 part.name = "Sample part"
3 part.price = 123.45
4 part.save()
```

Another example with a:

```
1 INSERT INTO parts (name, price) VALUES ('Sample part', 123.45);
```

You must not forget

... to mark your frame as `[fragile]`