

ClickBlocks\Net\Request

General information

Inheritance	no
Child classes	no
Interfaces	no
Source	Framework/net/request.php

Class provides access to HTTP-headers of the current HTTP-request.

Public static methods

getInstance()

```
public static ClickBlocks\Net\Request getInstance()
```

Returns an instance of the class.

Public non-static properties

method

```
public string $method
```

Method of the current HTTP-request.

headers

```
public ClickBlocks\Net\Headers $headers
```

Object of class `ClickBlocks\Net\Headers` that provides access to headers of the current HTTP-request.

data

```
public array $data = []
```

By default, contains content from `$_GET`, `$_POST` and `$_COOKIE`.

files

```
public array $files = []
```

By default, contains content from `$_FILES`.

server

```
public array $server = []
```

By default, contains content from `$_SERVER`.

isAjax

```
public boolean $isAjax
```

Contains TRUE for all AJAX requests and FALSE otherwise.

isMobileBrowser

```
public boolean $isMobileBrowser
```

Contains TRUE for all requests that come from mobile browsers and FALSE otherwise.

ip

```
public string $ip
```

IP address of the client.

url

```
public ClickBlocks\Net\URL $url
```

Object of class `ClickBlocks\Net\URL` provides access to URL components of the current HTTP-request.

body

```
public string $body
```

The raw body of the current request. This property is overloaded by using the magic methods `__get()`, `__set()`, `__isset()` and `__unset()`.

Public non-static methods

reset()

```
public void reset()
```

Initializes all properties of the class with values from PHP's super globals.

__toString()

```
public string __toString()
```

Returns the request as a string. This method allows to use the class object as a string.

Protected non-static properties

body

```
protected string $body = null
```

The raw body of the current request.