ClickBlocks\Cache\PHPRedis

General information

Inheritance	ClickBlocks\Cache\Cache
Child classes	no
Interfaces	Countable
Source	Framework/cache/phpredis.php

This class is intended for caching any data using by Redis PHP extension. See more information here

Public static methods

isAvailable()

public static boolean isAvailable()

Returns TRUE if the Redis extension is enabled on your system and FALSE otherwise.

Public non-static methods

_construct()

public void __construct(string \$host = '127.0.0.1', integer \$port = 6379, integer \$timeout = 0, string \$password = null, integer \$

\$host	string	host or path to a unix domain socket for a redis connection.	
\$port	integer	port for a connection, optional.	
\$time out	integer	the connection timeout, in seconds.	
\$password	string	password for server authentication, optional.	
\$database	integer	number of the redis database to use.	

Constructor. Establishes connection with the redis server.

getRedis()

public Redis getRedis()

Returns an instance of the Redis class for performing low-level operations.

set()

public void set(string \$key, mixed \$content, integer \$expire, string \$group = null)

\$key	string	unique identifier of caching data.
\$content	mixed	any data to cache.
\$content	mixed	any data to cache.

\$expire	integer	cache lifetime in seconds.
\$group	string	cache group name.

Stores data in cache by their identifier.

get()

public mixed get(string \$key)

\$key string unique identifier of caching data.

Returns previously stored data from cache by their identifier.

remove()

public void remove(string \$key)

\$key string unique identifier of caching data.

Removes data from cache by their identifier.

isExpired()

public boolean isExpired(string \$key)

\$key string unique identifier of caching data.

Returns TRUE, if the lifetime of the cache has expired, and FALSE otherwise. If the lifetime of the cache expires, the cache file will be deleted.

clean()

public void clean()

Removes all data from cache.