


Series 33AO
Price List

Division RAE Corporation

Air Cooled Chillers



STANDARD FEATURES

UNIT CONFIGURATION

Removeable Access Panels

Hinged Control Panel Access

Closed Cell Polyvinyl Evaporator Insulation

Liquid Line Shut Off Valve with Charging Port

Liquid Line Drier, Sightglass and Moisture Indicator (loose)

"Maximum Operating Pressure" TXV (loose)

Oil Failure Switch/Each Compressor

High Pressure Safety Control

Freeze/Low Charge Control with Time Delay

COMPRESSORS

Energy Efficient Copeland Compressors

Compressor Service Valves

Internal Compressor Overload Protection

Compressor Contactors

Compressor Fusing (CD, and CM units)

Time Delay Compressor Start (CD & CM Units)

Oil Equalizatoion system for each circuite (CM Units)

CONDENSER

Direct Drive Condenser Fans

Polyvinyl Covered Fan Guards

Three Phase Motors with Permanently Lubricated Ball Bearings

Fan Staging Head Pressure Control to +20°F.

Sub-Circuit Fan Motor Fusing with Internal Overload Motor Protector

Fan Motor Contactor

Plate Fin / Full Tube Collar Condenser Coils

Baffled Condenser Plenum

True Sub cooling

Personnel Grilles (CM Units)

ELECTRICAL COMPONENTS

Return Water Temperature Control

Prewired Controls

Flow Switch for Field Installation

Auto/Demand Pumpdown Switch (loose)