


Accelerating Joins with Filters

Nicholas Corrado Xiating Ouyang



University of Wisconsin-Madison

Star Schema




- If the query optimizer chooses a poor join order, intermediate join results may be unnecessarily large.
- Solution: try to filter out extraneous tuples before performing joins

Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)





Lookahead Information Passing (LIP)




6/8




Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)




Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)




6/8


5/6





Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)



Lookahead Information Passing (LIP)





6/8



5/6

Lookahead Information Passing (LIP)





6/8

5/6



Lookahead Information Passing (LIP)





6/8

5/6

1/5

Lookahead Information Passing (LIP)




1/5

6/8

5/6

Lookahead Information Passing (LIP)



1/5



6/8




5/6



- LIP uses statistics from all previous batches to compute σ
 - Slow response to local changes in key distributions in fact table
 - e.g. (11/28/2019, Turkey)
- **LIP- k** : Only use the previous k batches to compute σ

Implementation and benchmarking



An Example Experiment

- Select where Credit Score ≥ 700



Credit Score

720	}	50 batches
750		
720		
...		
400	}	50 batches
400		
400		
...		
770	}	50 batches
810		
800		
...		

An Example Experiment

- Select where Credit Score ≥ 700

Credit Score



An Example Experiment

- Select where Credit Score ≥ 700

Credit Score

720

750

720

...

400

400

400

...

770

810


800

...

} 50 batches

} 50 batches



} 50 batches



An Example Experiment

- Select where Credit Score ≥ 700

Credit Score





- LIP- k performs better than LIP on some queries...

An Example Experiment

- Select where Credit Score ≥ 700

Credit Score



- LIP- k performs better than LIP on some queries...
- ...but LIP performs better on others

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary
 - if not, at least one filter rejects it: 1 probe best / n probes worst

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary
 - if not, at least one filter rejects it: 1 probe best / n probes worst

$$\frac{\text{\#probes by } \mathcal{M}}{\text{\#probes by OPT}} \leq n.$$

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary
 - if not, at least one filter rejects it: 1 probe best / n probes worst

$$\text{Competitive ratio of } \mathcal{M} = \frac{\# \text{probes by } \mathcal{M}}{\# \text{probes by OPT}} \leq n.$$

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary
 - if not, at least one filter rejects it: 1 probe best / n probes worst

$$\text{Competitive ratio of } \mathcal{M} = \frac{\# \text{probes by } \mathcal{M}}{\# \text{probes by OPT}} \leq n.$$

Theorem

*There is no **deterministic** mechanism \mathcal{M} for LIP achieving a competitive ratio less than N , where N is the number of filters used in LIP.*

LIP is solving an online problem

- Given any tuple t , a mechanism \mathcal{M} decides a sequence of applying the filters to *minimize* the number of probes.
 - if t passes **all** filters: n probes necessary
 - if not, at least one filter rejects it: 1 probe best / n probes worst

$$\text{Competitive ratio of } \mathcal{M} = \frac{\# \text{probes by } \mathcal{M}}{\# \text{probes by OPT}} \leq n.$$

Theorem

*There is no **deterministic** mechanism \mathcal{M} for LIP achieving a competitive ratio less than N , where N is the number of filters used in LIP.*


- Randomness?

Conclusion

- Implemented LIP and its variant LIP- k
- Relative performance of LIP and LIP- k depends on the query
- Can we use randomness to achieve a better robustness guarantee?

Thank you!

Competitive Ratio vs. k on Uniform Data



Competitive Ratio vs. k on Adversarial Data

- Adversarial data set constructed such that LIP- k has worst case performance for odd k
- Run on query with $N = 2$ joins

