

# Module 2 - Data collection, validation and privacy

## Assignment overview

In this assignment, you will be exploring various aspects related to collecting data and identifying bias in datasets. You will also be asked to consider issues of data privacy and governance.

For this assignment, it is possible to work in **groups of up to 2 students**.

## Group members

Leave blanks if group has less than 2 members:

- Student 1: Jingyuan Liu (S.N. 69763183)
- Student 2: Nicholas Tam (S.N. 45695970)

## Learning Goals:

After completing this week's lecture and tutorial work, you will be able to:

1. Discuss the implications of data governance and data ownership in data science
2. Argue the advantages and disadvantages of collecting individuals' data online
3. Distinguish between a sample and a population, what attributes make a representative sample and the possible ethical implications of a non-representative sample
4. Explain the elements of experimental design
5. Identify possible sources of bias in datasets (such as historical, measurement, and representation bias)
6. Describe the ethical implications of variable choice in data science (e.g., use of proxies, use of gender and race as variables)
7. Apply good practices for minimizing errors in data cleaning
8. Apply methods for improving privacy and anonymity in stored data and data analysis, such as k-anonymity and randomized response
9. Explain the notion of differential privacy

## Part 1: Data collection, sampling and bias

In class, we discussed different sources of bias that can affect the data we want to use for our Data Science applications. Here is a summary:

## 1. Historical bias

**Historical bias:** bias that exists in society and is reflected in the data. It is the most insidious because it arises even if we are able to perfectly sample from the existing population. Most often, it affects groups that are historically disadvantaged.

E.g. In 2018, 5% of Fortune 500 CEOs were women. Historically, women have less frequently made it to a CEO position. A classifier trained to predict the best choice for a new CEO may learn this pattern and determine that being a woman makes one less qualified to be a CEO.

## 2. Representation bias

**Representation bias:** the sample underrepresents part(s) of the population and fails to generalize well. This may happen for different reasons:

1. The sampling methods only reached a portion of the population. E.g. Data collected via smartphone apps can under-represent lower incomes or older groups, who may be less likely to own smartphones.
2. The population of interest has changed or is distinct from the sample used during model training. E.g. Data that is representative of Vancouver may not be representative if used to analyze the population in Toronto. Similarly, data representative of Vancouver 100 years ago may not reflect today's population.

## 3. Measurement bias

**Measurement bias:** it occurs when choosing features that fail to correctly represent the problem, or when there are issues with the data collection. For example:

1. The measurement processes varies across groups. E.g. one group of workers is monitored more closely and thus more errors are observed in that group.
2. The quality of data varies across groups. E.g. women often self-report less pain than men and are therefore less likely to receive certain diagnoses
3. The defined classification task or one of the features used is an oversimplification. E.g. We are designing a model to predict whether a student will be successful in college. We choose to predict the final GPA as metric of success. This, however, ignores other indicators of success.

### Question 1

Consider a crowd-sourcing project called [Street Bump](#) aimed at helping improve neighbourhood streets in Boston from 2011 to 2014. Volunteers used a smartphone app, which captured GPS location and reported back to the city everytime the driver hit a pothole. The data was provided to governments so they could use the data to fix any road issues.

Can you think of any sources of bias in the scenario above? Explain them.

There is a risk of representation bias, as the data will likely under-represent lower-income or older groups that are less likely to have smartphones, on top of the population of people that

would be interested in volunteering potentially not being representative of the overall population. There is also a risk of measurement bias, as road quality is determined by more attributes than potholes alone, such as effective drainage and traffic management. The frequency of drivers hitting potholes is also determined by other factors, such as the proficiency of the drivers themselves, or the location of the potholes. In other words, the feature used to determine the road quality is an oversimplification.

## Observational and experimental studies

- **Observational study:** study where there is no deliberate human intervention regarding the variable under investigation. Observational studies are ones where researchers observe the effect of a treatment/intervention without trying to change who is or isn't exposed to it. In an observational study, the subjects are assigned or assign themselves to the exposure group they belong to.
- **Experimental study:** : study that involves planned intervention on the exposure to a condition. In an experiment, subjects are assigned to a condition by the researcher and thus one can establish a cause-and-effect relationship when we see a difference in the outcome between the experimental groups. Randomizing study subjects balances any differences between treatment groups with respect to all variables except the condition of exposure.

## A/B testing

A/B testing can be considered the most basic kind of randomized controlled experiment.

Complete the following reading, then answer the comprehension questions below:

<https://hbr.org/2017/06/a-refresher-on-ab-testing>

### Question 2

In the following table, select which statements are true or false:

Statement	True	False
A/B testing is an example of experimental study.	✓	
Observational studies require subjects to not be informed that they are being studied.		✓
Ethical experimental studies require genuine uncertainty about the benefits/harms of treatment or exposure (equipoise)	✓	
A researcher is interested in studying the effects of certain dietary habits. They recruit people and, through a survey, they ask them to disclose their current dietary habits,		✓

Statement	True	False
on which bases they will be assigned to treatment or control group. This is an example of experimental study.		
The control group and the exposed group must include different individuals.		✓
One of the main advantages of experimental studies is that they allow for better randomization.	✓	

### Question 3

Explain the role of blocking in A/B testing.

Blocking is defined as splitting the data by similarity in a factor that is of less interest, but will still heavily influence the success metric of our interest. For example, from the article, whether or not someone views a website on mobile or desktop will influence the click rates on both versions of a website, but the groups of interest in the study are the two versions of our website, not the devices of users. In this case, we should first divide the users into blocks for each type of device used, then randomly assign users to each version within each block. Blocking in A/B testing allows for a more accurate reflection of the distinctions between the methods of interest.

### Question 4

The authors warn about observing too many metrics when running an A/B test. Why is that the case? What could happen if I ignore this warning?

Observing too many metrics runs the risk of observing "spurious correlations", where multiple variables are only seemingly correlated without being causally related. The more metrics we observe, the more likely we will see some statistically significant results that only happen by chance, which is as what Fund described as "random fluctuation". Ignoring the warning will lead to some incorrect or misleading conclusions, making the interpretation of results difficult due to too many metrics influencing changes in data all at once. For example, you may want to switch to the new version of the product because you found some metrics significant from the A/B testing. But if you have too many metrics, it is more likely that some significant metrics occur only by chance. In this case, if you make a decision to switch the product to the new version based on this result, the new version may at best not be any more effective than the original one.

### Question 5

You want to determine the size of the subscribe button on your website. You plan to evaluate the performance by the number of visitors who click on the button. To run the test, you show one set of users one version and collect information about the number of visitors who click on the button. One month later you show users another version where the only thing different is

the size of the button. Based on this test, you determine that the second version had a higher number of visitors who clicked on the button. Can you conclude that this version of the website leads to a higher number of visitors clicking on the button? Briefly explain.

I would argue that we cannot conclude that this version of the website leads to a higher number of visitors clicking on the button. There is no statistic provided to indicate that the difference in button clicks is statistically significant enough to reject the null hypothesis that the number of clicks for both websites is the same. More importantly, as the test was conducted in two different periods, there might be some other variables that could potentially influence the results also changing over time (i.e. users' mood, seasonal effect, etc). The data we collected for each version of the website may also be representative of different populations due to the difference in time frames, leading to representation bias. Therefore, we should conduct this test simultaneously by randomly assigning users to one of the versions, minimizing the effect of other variables on the result.

## Ethical A/B testing

Ethical A/B testing still requires all the ethical considerations of any experimental study, such as informed consent or possibility to opt out. A notorious case of a company failing to meet ethics requirement in A/B testing is the infamous Facebook "social contagion experiment", in which almost 700,000 users were showed, for a week, only positive or only negative content, to see how this variation impacted their online behaviour. The selected users were not informed and could not opt out. Furthermore, their emotional state was affected. Facebook defended itself by saying that Facebook's Data Use Policy warns users that Facebook "may use the information we receive about you...for internal operations, including troubleshooting, data analysis, testing, research and service improvement". This defense was largely rejected by the scientific community, which still considered the study as unethical. You can read more about this incident in this [article](#).

## Case Study: National Institute of Justice's (NIJ) Recidivism Dataset

We will now look at the NIJ's Recidivism data set, which contains data on 26,000 individuals from the State of Georgia released from prison on parole (early release from prison where the person agrees to abide by certain conditions) between January 1, 2013 and December 31, 2015. **Recidivism** is the act of committing another crime.

This dataset is split into two sets, training and test, 70% of the data is in the training dataset and 30% in the test dataset. The training set contains four variables that measure recidivism: whether an individual recidivated within three years of the supervision start date and whether they recidivated in year 1, year 2, or year 3. In this data set, recidivism is defined as being arrested for a new crime during this three-year period. The test set does not include these four variables.

The data was provided by the Georgia Department of Community Supervision (GDCS) and the Georgia Bureau of Investigation.

*Source: <https://data.ojp.usdoj.gov/stories/s/daxx-hznc>*

Let's start by familiarizing with the [dataset source](#). The website includes a lot of information on the dataset and a detailed description of each of its columns (look for Appendix 2: Codebook).

**Question 6** Think about how the data set was collected and what we are trying to predict. Are there any potential sources of bias (historical, representation, measurement)? Explain your answer.

- Historical: The historical bias against some certain racial groups (i.e. Black people) can affect the performance of the model nowadays, reflecting past inequalities and unfairness.
- Representation: The population of individuals used for model training would have changed over time, such as the proportions of people at certain ages on release, and thus may not be reflective of the current population of people on parole. In addition, as the data only collects individuals from the State of Georgia, people released from prison on parole from other states or countries may be underrepresented. The data was also collected between 2013 and 2015, which may not be representative of the population of interests nowadays, due to social and political events and changes over time, such as COVID-19.
- Measurement: In this study, recidivism is defined as being arrested for a new crime during this three-year period. By contrast, recidivism is generally defined as the act of relapsing into criminal behaviour, often after intervention for a previous crime. As such, the study's definition excludes criminals that have reoffended but have not been arrested for such. Factors such as race and age may also lead to unfairness in measurements and quality of data between groups of individuals, such as stricter monitoring between those in the same supervision level due to racism or prioritization of criminal acts. In other words, the feature used to determine recidivism is an oversimplification.

## Question 7: Exploratory Data Analysis (EDA)

We are now going to perform some Exploratory Data Analysis on the NIJ's Recidivism Training set. This will serve 2 purposes:

- it will help us familiarize with the dataset
- it will help us spot possible imbalances or sources of bias in the dataset

You are free to use tools and functions of your choice to complete the EDA. Your goal is to answer the following questions:

1. Does the dataset include protected characteristics? We recommend using the [BC Human Rights Code](#) for reference.
2. If the dataset includes protected characteristic, do you think they are necessary to perform the predictive task? Why or why not?
3. If we were to remove the columns including protected characteristics, do you think it would still be possible to retrieve that information through other features (proxies)? Explain how.
4. Is the target variable balanced? If not, what could happen?
5. Is the target variable balanced *across protected segments of the population*? What could happen if this is not the case?
6. Are there features with missing values? Do you suspect that they may be Missing Not At Random (MNAR), and if so, how would it be best to fill this information?

**Notes:**

- Bar charts and other plots are helpful to visually spot imbalances
- You are encouraged to talk to the instructor and TA to discuss your EDA strategy and if you need suggestions with the code

*# Your solution here. You may add more code/markdown cells as needed.*  
import pandas as pd

```
train_df =
pd.read_csv("NIJ_s_Recidivism_Challenge_Training_Dataset.csv")
train_df.head()
```

	ID	Gender	Race	Age_at_Release	Residence_PUMA	Gang_Affiliated	\
0	1	M	BLACK	43-47	16	False	
1	2	M	BLACK	33-37	16	False	
2	3	M	BLACK	48 or older	24	False	
3	4	M	WHITE	38-42	16	False	
4	5	M	WHITE	33-37	16	False	

	Supervision_Risk_Score_First	Supervision_Level_First	\
0	3.0	Standard	
1	6.0	Specialized	
2	7.0	High	
3	7.0	High	
4	4.0	Specialized	

	Education_Level	Dependents	...	DrugTests_Cocaine_Positive	\
0	At least some college	3 or more	...	0.0	
1	Less than HS diploma	1	...	0.0	
2	At least some college	3 or more	...	0.0	
3	Less than HS diploma	1	...	0.0	
4	Less than HS diploma	3 or more	...	0.0	

	DrugTests_Meth_Positive	DrugTests_Other_Positive
Percent_Days_Employed		
0	0.000000	0.0
0.488562		
1	0.000000	0.0
0.425234		
2	0.166667	0.0
0.000000		
3	0.000000	0.0
1.000000		
4	0.058824	0.0
0.203562		

	Jobs_Per_Year	Employment_Exempt	Recidivism_Within_3years	\
0	0.447610	False	False	
1	2.000000	False	True	
2	0.000000	False	True	
3	0.718996	False	False	
4	0.929389	False	True	

	Recidivism_Arrest_Year1	Recidivism_Arrest_Year2
0	False	False
1	False	False
2	False	True
3	False	False
4	True	False

[5 rows x 53 columns]

display(train\_df.describe())

	ID	Residence_PUMA	Supervision_Risk_Score_First	\
count	18028.000000	18028.000000	17698.000000	
mean	13386.065343	12.307577	6.064753	
std	7721.451992	7.143255	2.382811	
min	1.000000	1.000000	1.000000	
25%	6702.750000	6.000000	4.000000	
50%	13405.500000	12.000000	6.000000	
75%	20081.250000	18.000000	8.000000	
max	26761.000000	25.000000	10.000000	

	Avg_Days_per_DrugTest	DrugTests_THC_Positive	\
count	13768.000000	14396.000000	
mean	93.585860	0.063120	
std	117.561341	0.138357	
min	0.500000	0.000000	
25%	28.666667	0.000000	
50%	55.000000	0.000000	
75%	110.000000	0.068242	
max	1087.000000	1.000000	

	DrugTests_Cocaine_Positive	DrugTests_Meth_Positive	\
count	14396.000000	14396.000000	
mean	0.014173	0.012768	
std	0.063473	0.059572	
min	0.000000	0.000000	
25%	0.000000	0.000000	
50%	0.000000	0.000000	
75%	0.000000	0.000000	
max	1.000000	1.000000	

DrugTests_Other_Positive	Percent_Days_Employed	Jobs_Per_Year
--------------------------	-----------------------	---------------



count	14396.000000	17721.000000	17494.000000
mean	0.007681	0.480035	0.766423
std	0.042224	0.424396	0.813474
min	0.000000	0.000000	0.000000
25%	0.000000	0.000000	0.000000
50%	0.000000	0.466543	0.636324
75%	0.000000	0.966184	1.000000
max	1.000000	1.000000	8.000000

*# 1, 2: Protected characteristics*

display(train\_df.info())

<class 'pandas.core.frame.DataFrame'>

RangeIndex: 18028 entries, 0 to 18027

Data columns (total 53 columns):

#	Column	Non-Null Count
Dtype		
---	-----	-----
0	ID	18028 non-null
int64		
1	Gender	18028 non-null
object		
2	Race	18028 non-null
object		
3	Age_at_Release	18028 non-null
object		
4	Residence_PUMA	18028 non-null
int64		
5	Gang_Affiliated	15811 non-null
object		
6	Supervision_Risk_Score_First	17698 non-null
float64		
7	Supervision_Level_First	16816 non-null
object		
8	Education_Level	18028 non-null
object		
9	Dependents	18028 non-null
object		
10	Prison_Offense	15707 non-null
object		
11	Prison_Years	18028 non-null

object		
12	Prior_Arrest_Episodes_Felony	18028 non-null
object		
13	Prior_Arrest_Episodes_Misd	18028 non-null
object		
14	Prior_Arrest_Episodes_Violent	18028 non-null
object		
15	Prior_Arrest_Episodes_Property	18028 non-null
object		
16	Prior_Arrest_Episodes_Drug	18028 non-null
object		
17	Prior_Arrest_Episodes_PPViolationCharges	18028 non-null
object		
18	Prior_Arrest_Episodes_DVCharges	18028 non-null
bool		
19	Prior_Arrest_Episodes_GunCharges	18028 non-null
bool		
20	Prior_Conviction_Episodes_Felony	18028 non-null
object		
21	Prior_Conviction_Episodes_Misd	18028 non-null
object		
22	Prior_Conviction_Episodes_Viol	18028 non-null
bool		
23	Prior_Conviction_Episodes_Prop	18028 non-null
object		
24	Prior_Conviction_Episodes_Drug	18028 non-null
object		
25	Prior_Conviction_Episodes_PPViolationCharges	18028 non-null
bool		
26	Prior_Conviction_Episodes_DomesticViolenceCharges	18028 non-null
bool		
27	Prior_Conviction_Episodes_GunCharges	18028 non-null
bool		
28	Prior_Revocations_Parole	18028 non-null
bool		
29	Prior_Revocations_Probation	18028 non-null
bool		
30	Condition_MH_SA	18028 non-null
bool		
31	Condition_Cog_Ed	18028 non-null
bool		
32	Condition_Other	18028 non-null
bool		
33	Violations_ElectronicMonitoring	18028 non-null
bool		
34	Violations_Instruction	18028 non-null
bool		
35	Violations_FailToReport	18028 non-null
bool		

36	Violations_MoveWithoutPermission	18028	non-null
bool			
37	Delinquency_Reports	18028	non-null
object			
38	Program_Attendances	18028	non-null
object			
39	Program_UnexcusedAbsences	18028	non-null
object			
40	Residence_Changes	18028	non-null
object			
41	Avg_Days_per_DrugTest	13768	non-null
float64			
42	DrugTests_THC_Positive	14396	non-null
float64			
43	DrugTests_Cocaine_Positive	14396	non-null
float64			
44	DrugTests_Meth_Positive	14396	non-null
float64			
45	DrugTests_Other_Positive	14396	non-null
float64			
46	Percent_Days_Employed	17721	non-null
float64			
47	Jobs_Per_Year	17494	non-null
float64			
48	Employment_Exempt	18028	non-null
bool			
49	Recidivism_Within_3years	18028	non-null
bool			
50	Recidivism_Arrest_Year1	18028	non-null
bool			
51	Recidivism_Arrest_Year2	18028	non-null
bool			
52	Recidivism_Arrest_Year3	18028	non-null
bool			

dtypes: bool(20), float64(8), int64(2), object(23)  
memory usage: 4.9+ MB

None

Q7.1: From the list of columns provided by `train_df.info()`, the columns that likely include protected characteristics are `Gender`, `Race`, `Age_at_Release`, `Dependents`, and the characteristics involving prior arrests, convictions and revocations (`Prior_Arrest_Episodes_Felony`, `Prior_Arrest_Episodes_Misdemeanor`, `Prior_Arrest_Episodes_Violent`, `Prior_Arrest_Episodes_Property`, `Prior_Arrest_Episodes_Drug`, `Prior_Arrest_Episodes_PPViolationCharges`, `Prior_Arrest_Episodes_DomesticViolenceCharges`, `Prior_Arrest_Episodes_GunCharges`, `Prior_Conviction_Episodes_Felony`, `Prior_Conviction_Episodes_Misdemeanor`, `Prior_Conviction_Episodes_Violent`, `Prior_Conviction_Episodes_Property`,

Prior\_Conviction\_Episodes\_Drug, Prior\_Conviction\_Episodes\_PPViolationCharges, Prior\_Conviction\_Episodes\_DomesticViolenceCharges, Prior\_Conviction\_Episodes\_GunCharges, Prior\_Revocations\_Parole, and Prior\_Revocations\_Probation). Q7.2: The Gender, Race, Age\_at\_Release, and Dependents characteristics are unnecessary as they appear to only be indirectly correlated to their probability of a person undergoing recidivism. The characteristics relating to prior arrests, convictions, and revocations appear to be more directly related to a person recommitting crimes and thus may be necessary for the predictive task. Q7.3: It could be possible to retrieve an individual's Age\_at\_Release, Prior\_Arrest\_Episodes\_Drug, and Prior\_Conviction\_Episodes\_Drug. The former characteristic could be inferred from characteristics that would likely tie to someone's work such as Percent\_Days\_Employed and Jobs\_Per\_Year, under the assumption that a younger individual would likely have lower values for both of those characteristics. The latter two characteristics are potentially associated with other characteristics involving drug testing, as individuals with a history of drug abuse would likely be closely monitored for potential relapses.

```
# 4: Check if the class distribution is balanced
display(train_df["Recidivism_Within_3years"].value_counts(normalize=True),

train_df["Recidivism_Arrest_Year1"].value_counts(normalize=True),

train_df["Recidivism_Arrest_Year2"].value_counts(normalize=True),

train_df["Recidivism_Arrest_Year3"].value_counts(normalize=True))

Recidivism_Within_3years
True      0.578045
False     0.421955
Name: proportion, dtype: float64

Recidivism_Arrest_Year1
False     0.701742
True      0.298258
Name: proportion, dtype: float64

Recidivism_Arrest_Year2
False     0.819558
True      0.180442
Name: proportion, dtype: float64

Recidivism_Arrest_Year3
False     0.900655
True      0.099345
Name: proportion, dtype: float64
```

Q7.4: The target variable Recidivism\_Within\_3years is not balanced, with 57.8% of samples having Recidivism\_Within\_3years == True, and 42.2% of samples having Recidivism\_Within\_3years == False. The proportions of recidivism in each of the trees

are not balanced either. As a result, the model may have biased predictive results in favor of the more frequent class of the target variable.

```
# 5: Check if class distribution is balanced within protected segments
for gender in train_df["Gender"].unique():
    print("Recidivism_Within_3years for gender:" + gender)
    display(train_df[train_df["Gender"] == gender]
["Recidivism_Within_3years"].value_counts(normalize=True))

for race in train_df["Race"].unique():
    print("Recidivism_Within_3years for race:" + race)
    display(train_df[train_df["Race"] == race]
["Recidivism_Within_3years"].value_counts(normalize=True))

for age in train_df["Age_at_Release"].unique():
    print("Recidivism_Within_3years for age group:" + age)
    display(train_df[train_df["Age_at_Release"] == age]
["Recidivism_Within_3years"].value_counts(normalize=True))

for dep in train_df["Dependents"].unique():
    print("Recidivism_Within_3years for dependent groups:" + dep)
    display(train_df[train_df["Dependents"] == dep]
["Recidivism_Within_3years"].value_counts(normalize=True))

Recidivism_Within_3years for gender:M
Recidivism_Within_3years
True      0.595155
False     0.404845
Name: proportion, dtype: float64

Recidivism_Within_3years for gender:F
Recidivism_Within_3years
False     0.543978
True      0.456022
Name: proportion, dtype: float64

Recidivism_Within_3years for race:BLACK
Recidivism_Within_3years
True      0.589159
False     0.410841
Name: proportion, dtype: float64

Recidivism_Within_3years for race:WHITE
Recidivism_Within_3years
True      0.563189
False     0.436811
Name: proportion, dtype: float64
```

Recidivism\_Within\_3years for age group:43-47

Recidivism\_Within\_3years

True 0.503229

False 0.496771

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:33-37

Recidivism\_Within\_3years

True 0.57479

False 0.42521

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:48 or older

Recidivism\_Within\_3years

False 0.587656

True 0.412344

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:38-42

Recidivism\_Within\_3years

True 0.537745

False 0.462255

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:18-22

Recidivism\_Within\_3years

True 0.719395

False 0.280605

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:23-27

Recidivism\_Within\_3years

True 0.666574

False 0.333426

Name: proportion, dtype: float64

Recidivism\_Within\_3years for age group:28-32

Recidivism\_Within\_3years

True 0.6196

False 0.3804

Name: proportion, dtype: float64

Recidivism\_Within\_3years for dependent groups:3 or more

Recidivism\_Within\_3years

True 0.54828

```

False      0.45172
Name: proportion, dtype: float64

Recidivism_Within_3years for dependent groups:1

Recidivism_Within_3years
True        0.605972
False       0.394028
Name: proportion, dtype: float64

Recidivism_Within_3years for dependent groups:2

Recidivism_Within_3years
True        0.582845
False       0.417155
Name: proportion, dtype: float64

Recidivism_Within_3years for dependent groups:0

Recidivism_Within_3years
True        0.585462
False       0.414538
Name: proportion, dtype: float64

```

Q7.5: The target variable `Recidivism_Within_3years` is not balanced across most protected segments, nor are the distributions of each `Recidivism_Within_3years` category equal across each level of protected segments. For instance, the proportion of `Recidivism_Within_3years` being true is 59.5% among male individuals and 54.4% among female individuals; the proportion of `Recidivism_Within_3years` being true is 72% among age group:18-22 individuals and 50% among age group:43-47 individuals. This runs the risk of differential treatment and measurement of recidivism between categories of protected characteristics and increases the predictive bias against certain groups under protected characteristics

```

# 6: Presence of NaN
# https://stackoverflow.com/questions/36226083/how-to-find-which-columns-contain-any-nan-value-in-pandas-dataframe
display(train_df.isna().any())

```

ID	False
Gender	False
Race	False
Age_at_Release	False
Residence_PUMA	False
Gang_Affiliated	True
Supervision_Risk_Score_First	True
Supervision_Level_First	True
Education_Level	False
Dependents	False
Prison_Offense	True

Prison_Years	False
Prior_Arrest_Episodes_Felony	False
Prior_Arrest_Episodes_Misd	False
Prior_Arrest_Episodes_Violent	False
Prior_Arrest_Episodes_Property	False
Prior_Arrest_Episodes_Drug	False
Prior_Arrest_Episodes_PPViolationCharges	False
Prior_Arrest_Episodes_DVCharges	False
Prior_Arrest_Episodes_GunCharges	False
Prior_Conviction_Episodes_Felony	False
Prior_Conviction_Episodes_Misd	False
Prior_Conviction_Episodes_Viol	False
Prior_Conviction_Episodes_Prop	False
Prior_Conviction_Episodes_Drug	False
Prior_Conviction_Episodes_PPViolationCharges	False
Prior_Conviction_Episodes_DomesticViolenceCharges	False
Prior_Conviction_Episodes_GunCharges	False
Prior_Revocations_Parole	False
Prior_Revocations_Probation	False
Condition_MH_SA	False
Condition_Cog_Ed	False
Condition_Other	False
Violations_ElectronicMonitoring	False
Violations_Instruction	False
Violations_FailToReport	False
Violations_MoveWithoutPermission	False
Delinquency_Reports	False
Program_Attendances	False
Program_UnexcusedAbsences	False
Residence_Changes	False
Avg_Days_per_DrugTest	True
DrugTests_THC_Positive	True
DrugTests_Cocaine_Positive	True
DrugTests_Meth_Positive	True
DrugTests_Other_Positive	True
Percent_Days_Employed	True
Jobs_Per_Year	True
Employment_Exempt	False
Recidivism_Within_3years	False
Recidivism_Arrest_Year1	False
Recidivism_Arrest_Year2	False
Recidivism_Arrest_Year3	False
dtype: bool	

Q7.6: The columns `Gang_Affiliated`, `Supervision_Risk_Score_First`, `Supervision_Level_First`, `Prison_Offense`, `Avg_Days_per_DrugTest`, `DrugTests_THC_Positive`, `DrugTests_Cocaine_Positive`, `DrugTests_Meth_Positive`, `DrugTests_Other_Positive`, `Percent_Days_Employed`, and `Jobs_Per_Year` contain missing values. Of these characteristics, `Gang_Affiliated`,



Supervision\_Risk\_Score\_First, Supervision\_Level\_First, and Prison\_Offense are categorical, while the rest are numerical. The variables Gang\_Affiliated, Avg\_Days\_per\_DrugTest, and Jobs\_Per\_Year may be MNAR, as they may not be applicable to the individual (e.g. Avg\_Days\_per\_DrugTest for someone that never got tested for drugs in the first place), or actively refused to disclose such information (e.g. Gang\_Affiliated). Gang\_Affiliated and Prison\_Offense can have their information filled by creating/using a separate "Other" category, while Avg\_Days\_per\_DrugTest can be filled with a default value of 0 to indicate a lack of drug testing in the first place.

## Part 2: Privacy

When collecting data for a study, privacy is almost always a primary concern. Our data set may include information that makes it possible to identify an individual, including:

- **Direct identifiers**, which are the ones that can be used to uniquely identify an individual or a household in a dataset, such as a record ID number, patient number, social insurance number, full address, etc. Usually, name is also considered a direct identifier (although several people can have the same name). Other features such as age, date of birth, or postal code are not sufficient on their own to uniquely identify an individual and would not be considered direct identifiers.
- **Indirect (or quasi) identifiers**, which are the columns that do not themselves identify any individual or household, but can do so when combined with other indirect-identifiers. For example, postal code and date of birth are often indirect identifiers, because it is very likely that within a zip code only one individual has this particular birth date. The more indirect identifiers that you have, the more likely it is that individuals become identifiable because there are more possible unique combinations of identifying features.

### Question 8

1. Which columns in the NIJ dataset are direct identifiers? Briefly motivate your answer.
2. Which of the remaining columns make good candidates for indirect identifiers? Which ones do not?

Hint: It can be useful to use the `nunique()` and `value_counts()` dataframe methods to get an idea of how many distinct values a feature has.

```
# Your answer here (code portion)
```

```
display(train_df.nunique())
display(train_df.shape)
```

ID	18028
Gender	2
Race	2
Age_at_Release	7
Residence_PUMA	25
Gang_Affiliated	2
Supervision_Risk_Score_First	10
Supervision_Level_First	3

Education_Level	3
Dependents	4
Prison_Offense	5
Prison_Years	4
Prior_Arrest_Episodes_Felony	11
Prior_Arrest_Episodes_Misd	7
Prior_Arrest_Episodes_Violent	4
Prior_Arrest_Episodes_Property	6
Prior_Arrest_Episodes_Drug	6
Prior_Arrest_Episodes_PPViolationCharges	6
Prior_Arrest_Episodes_DVCharges	2
Prior_Arrest_Episodes_GunCharges	2
Prior_Conviction_Episodes_Felony	4
Prior_Conviction_Episodes_Misd	5
Prior_Conviction_Episodes_Viol	2
Prior_Conviction_Episodes_Prop	4
Prior_Conviction_Episodes_Drug	3
Prior_Conviction_Episodes_PPViolationCharges	2
Prior_Conviction_Episodes_DomesticViolenceCharges	2
Prior_Conviction_Episodes_GunCharges	2
Prior_Revocations_Parole	2
Prior_Revocations_Probation	2
Condition_MH_SA	2
Condition_Cog_Ed	2
Condition_Other	2
Violations_ElectronicMonitoring	2
Violations_Instruction	2
Violations_FailToReport	2
Violations_MoveWithoutPermission	2
Delinquency_Reports	5
Program_Attendances	11
Program_UnexcusedAbsences	4
Residence_Changes	4
Avg_Days_per_DrugTest	7654
DrugTests_THC_Positive	311
DrugTests_Cocaine_Positive	203
DrugTests_Meth_Positive	201
DrugTests_Other_Positive	197
Percent_Days_Employed	7915
Jobs_Per_Year	3044
Employment_Exempt	2
Recidivism_Within_3years	2
Recidivism_Arrest_Year1	2
Recidivism_Arrest_Year2	2
Recidivism_Arrest_Year3	2

dtype: int64

(18028, 53)

- Q8.1: ID is the only column in the NIJ dataset that is a direct identifier, as the number of unique values in the training dataset is equal to the number of individuals in the dataset, which is 18028.
- Q8.2: Gender, Race, Age\_at\_Release, Residence\_PUMA, Education\_Level, and Dependents are effective as indirect identifiers, as they are unlikely to change drastically over extended periods of time and can be used to narrow down the individuals of interest; we can use a combination of these features to identify individuals of interest. The characteristics relating to supervision activities, from Violations\_ElectronicMonitoring to Employment\_Exempt, would make for poor candidates for indirect identifiers, as they are directly measured during parole and thus are unlikely to be matched with other anonymous data.

## De-identification of structured data

To safeguard the privacy of the individuals in our dataset, we need to make sure that they are not identifiable, either directly or indirectly. There are three main strategies to achieve this: suppression, pseudonymization, and generalization.

### Suppression

Suppression is an effective way to get rid of a direct identifier by simply removing the entire column.

**Question 9:** using the appropriate dataframe methods, suppress all direct identifier in the NIJ training set. Save the result in a new dataframe called `suppressed_df`

*# Your answer here*

```
direct_id = ["ID"]
suppressed_df = train_df.drop(columns=direct_id)
suppressed_df.head()
```

	Gender	Race	Age_at_Release	Residence_PUMA	Gang_Affiliated	\
0	M	BLACK	43-47	16	False	
1	M	BLACK	33-37	16	False	
2	M	BLACK	48 or older	24	False	
3	M	WHITE	38-42	16	False	
4	M	WHITE	33-37	16	False	

	Supervision_Risk_Score_First	Supervision_Level_First	\
0	3.0	Standard	
1	6.0	Specialized	
2	7.0	High	
3	7.0	High	
4	4.0	Specialized	

	Education_Level	Dependents	Prison_Offense	...	\
0	At least some college	3 or more	Drug	...	
1	Less than HS diploma	1	Violent/Non-Sex	...	

```

2 At least some college 3 or more Drug ...
3 Less than HS diploma 1 Property ...
4 Less than HS diploma 3 or more Violent/Non-Sex ...

DrugTests_Cocaine_Positive DrugTests_Meth_Positive
DrugTests_Other_Positive \
0 0.0 0.000000
0.0
1 0.0 0.000000
0.0
2 0.0 0.166667
0.0
3 0.0 0.000000
0.0
4 0.0 0.058824
0.0

Percent_Days_Employed Jobs_Per_Year Employment_Exempt \
0 0.488562 0.447610 False
1 0.425234 2.000000 False
2 0.000000 0.000000 False
3 1.000000 0.718996 False
4 0.203562 0.929389 False

Recidivism_Within_3years Recidivism_Arrest_Year1
Recidivism_Arrest_Year2 \
0 False False
False
1 True False
False
2 True False
True
3 False False
False
4 True True
False

Recidivism_Arrest_Year3
0 False
1 True
2 False
3 False
4 False

[5 rows x 52 columns]

```

## Pseudonymization

A big issue with suppression of direct identifier is that it is not reversible. If at some point we need to identify an individual in our dataset, we would be out of luck. If you have reasons to

believe that re-identification may be required, pseudonymization would be a better option to handle direct identifiers. Pseudonymization replaces one or more direct identifiers with a unique but less meaningful value. Usually when we pseudonymize an identifier, there is a possibility of re-identification if required (but it would not be available to the general public).

**Question 10:** pseudomyze the ID column of the NIJ training set and save the result in a new dataframe called `pseudo_df`. In a different code cell, show that it is possible to re-identify the samples by converting them back to the original ID number.

There are different ways to achieve this you may want to explore:

- Write your own pseudonymization function. You should write at least 2 functions: one to pseudomyze, and another to re-identify. The function does not have to be exceedingly complex but it should not be obvious either (e.g. only basic arithmetic involved).
- Use an existing library, such as `cryptography`.

Q10 with `cryptography`

```
# Your answer here (you may add more cells as needed)
from cryptography.fernet import Fernet

# define the pseudomyze function:
def psuedo_encry(col):
    key = Fernet.generate_key()
    f = Fernet(key)
    result1 = col.apply(lambda x: x.to_bytes(2, byteorder='big'))
    result2 = result1.apply(lambda x: f.encrypt(x))
    print("Data encrypted")
    return result2, f

# define the re-identify function:
def psuedo_decry(col, f):
    result1 = col.apply(lambda x: f.decrypt(x))
    result2 = result1.apply(lambda x: int.from_bytes(x,
byteorder='big'))
    print("Data decrypted")
    return result2

# Pseudomyzation
pseudo_df = train_df.copy()
pseudo_df["ID"], f = psuedo_encry(train_df["ID"])
pseudo_df.head()
```

Data encrypted

	ID	Gender	Race	\
0	b'gAAAAABm-5MXA9hGJCvBCeDUzlsYUWMdNs-dxLIcx10G...	M	BLACK	
1	b'gAAAAABm-5MXmhhN8FFgyl7G9MR0dBZqFs0NiN2krkIG...	M	BLACK	
2	b'gAAAAABm-5MXFP3MYwFK8QvUEUn2RB8f9_GoYEuMqiH4...	M	BLACK	
3	b'gAAAAABm-5MXU8pJWIlAVggD8Fg-6m0HAI7CDwTUdu7W...	M	WHITE	
4	b'gAAAAABm-5MX_sBJbLLIU4dMYEKKd3MKIWPzFd6aP2oo...	M	WHITE	

	Age_at_Release	Residence_PUMA	Gang_Affiliated	\
0	43-47	16	False	
1	33-37	16	False	
2	48 or older	24	False	
3	38-42	16	False	
4	33-37	16	False	

	Supervision_Risk_Score_First	Supervision_Level_First	\
0	3.0	Standard	
1	6.0	Specialized	
2	7.0	High	
3	7.0	High	
4	4.0	Specialized	

	Education_Level	Dependents	...	DrugTests_Cocaine_Positive	\
0	At least some college	3 or more	...	0.0	
1	Less than HS diploma	1	...	0.0	
2	At least some college	3 or more	...	0.0	
3	Less than HS diploma	1	...	0.0	
4	Less than HS diploma	3 or more	...	0.0	

	DrugTests_Meth_Positive	DrugTests_Other_Positive
Percent_Days_Employed	\	
0	0.000000	0.0
0.488562		
1	0.000000	0.0
0.425234		
2	0.166667	0.0
0.000000		
3	0.000000	0.0
1.000000		
4	0.058824	0.0
0.203562		

	Jobs_Per_Year	Employment_Exempt	Recidivism_Within_3years	\
0	0.447610	False	False	
1	2.000000	False	True	
2	0.000000	False	True	
3	0.718996	False	False	
4	0.929389	False	True	

	Recidivism_Arrest_Year1	Recidivism_Arrest_Year2
Recidivism_Arrest_Year3		
0	False	False
False		
1	False	False
True		
2	False	True
False		

```

3           False           False
False
4           True           False
False

```

```
[5 rows x 53 columns]
```

```
# Reidentification
```

```
pseudo_df["ID"] = psuedo_decry(pseudo_df["ID"], f)
pseudo_df.head()
```

```
Data decrypted
```

	ID	Gender	Race	Age_at_Release	Residence_PUMA	Gang_Affiliated	\
0	1	M	BLACK	43-47	16	False	
1	2	M	BLACK	33-37	16	False	
2	3	M	BLACK	48 or older	24	False	
3	4	M	WHITE	38-42	16	False	
4	5	M	WHITE	33-37	16	False	

	Supervision_Risk_Score_First	Supervision_Level_First	\
0	3.0	Standard	
1	6.0	Specialized	
2	7.0	High	
3	7.0	High	
4	4.0	Specialized	

	Education_Level	Dependents	... DrugTests_Cocaine_Positive	\
0	At least some college	3 or more	...	0.0
1	Less than HS diploma	1	...	0.0
2	At least some college	3 or more	...	0.0
3	Less than HS diploma	1	...	0.0
4	Less than HS diploma	3 or more	...	0.0

	DrugTests_Meth_Positive	DrugTests_Other_Positive
Percent_Days_Employed		
0	0.000000	0.0
0.488562		
1	0.000000	0.0
0.425234		
2	0.166667	0.0
0.000000		
3	0.000000	0.0
1.000000		
4	0.058824	0.0
0.203562		

	Jobs_Per_Year	Employment_Exempt	Recidivism_Within_3years	\
0	0.447610	False	False	
1	2.000000	False	True	

2	0.000000	False	True
3	0.718996	False	False
4	0.929389	False	True

	Recidivism_Arrest_Year1	Recidivism_Arrest_Year2
Recidivism_Arrest_Year3		
0	False	False
False		
1	False	False
True		
2	False	True
False		
3	False	False
False		
4	True	False
False		

[5 rows x 53 columns]

## Generalization

Generalization is a commonly used technique in anonymization, which involves reducing the precision of a column. For example, the date of birth or the date of a doctor's visit can be generalized to a month and year, to a year, or to a five-year interval. Generalization can help achieving  $k$ -anonymity.

To check for  $k$ -anonymity, we will use the [pycanon library](#). You can install this library in your virtual environment by running the command:

```
pip install pycanon
```

**Question 11:** `pycanon` includes several functions (feel free to explore them in the related documentation), but we will only be using `k-anonymity`. Look at the documentation, then use `k-anonymity` to determine the  $k$ -anonymity of the following groups of variables:

- $k$ -anonymity of Gender and Race features: 743
- $k$ -anonymity of Gender, Race, and Age\_at\_Release features: 44
- $k$ -anonymity of Gender, Race, Age\_at\_Release and Residence\_PUMA features: 1

```
from pycanon import anonymity

# Your answer here
k1 = anonymity.alpha_k_anonymity(train_df, quasi_ident = ["Gender",
"Race"], sens_att = ["Gender", "Race"])[1]
k2 = anonymity.alpha_k_anonymity(train_df, quasi_ident = ["Gender",
"Race", "Age_at_Release"], sens_att = ["Gender", "Race",
"Age_at_Release"])[1]
k3 = anonymity.alpha_k_anonymity(train_df, quasi_ident = ["Gender",
"Race", "Age_at_Release", "Residence_PUMA"], sens_att = ["Gender",
```



```

"Race", "Age_at_Release"])[1]
print("k-anonymity of Gender and Race features: " + str(k1))
print("k-anonymity of Gender, Race, and Age_at_Release features: " +
str(k2))
print("k-anonymity of Gender, Race, Age_at_Release and Residence_PUMA
features: " + str(k3))

```

```

k-anonymity of Gender and Race features: 743
k-anonymity of Gender, Race, and Age_at_Release features: 44
k-anonymity of Gender, Race, Age_at_Release and Residence_PUMA
features: 1

```

The  $k$ -anonymity of the combination of Gender, Race, Age\_at\_Release and Residence\_PUMA is clearly problematic! It would be very easy to identify someone if we knew these 4 pieces of information about them.

**Question 12:** can you bin the Residence\_PUMA feature to achieve 4-anonymity for this set of features? Add the new column to the existing dataframe, using the name `Binned_PUMA`.

For this task, you may want to look into the `cut()` and `qcut()` functions of the pandas library.

Remember that now, when checking for  $k$ -anonymity, you should be looking at the new column `Binned_PUMA`, not at `Residence_PUMA`.

```

# Your answer here
import warnings
warnings.filterwarnings("ignore", category=FutureWarning)

for bin in range(20):
    train_df["Binned_PUMA"] = pd.qcut(train_df["Residence_PUMA"], bin)
    k = anonymity.alpha_k_anonymity(train_df, quasi_ident = ["Gender",
"Race", "Age_at_Release", "Binned_PUMA"], sens_att = ["Gender",
"Race", "Age_at_Release"])[1]
    if k==4:
        print("Minimum optimal number of bins: " + str(bin))
        print("k-anonymity of Gender, Race, Age_at_Release and
Binned_PUMA features: " + str(k))
        display(train_df.head())
        break

```

```

Minimum optimal number of bins: 5
k-anonymity of Gender, Race, Age_at_Release and Binned_PUMA features:
4

```

	ID	Gender	Race	Age_at_Release	Residence_PUMA	Gang_Affiliated	\
0	1	M	BLACK	43-47	16	False	
1	2	M	BLACK	33-37	16	False	
2	3	M	BLACK	48 or older	24	False	
3	4	M	WHITE	38-42	16	False	
4	5	M	WHITE	33-37	16	False	

	Supervision_Risk_Score_First	Supervision_Level_First	\
0	3.0	Standard	
1	6.0	Specialized	
2	7.0	High	
3	7.0	High	
4	4.0	Specialized	

  

	Education_Level	Dependents	...	DrugTests_Meth_Positive	\
0	At least some college	3 or more	...	0.000000	
1	Less than HS diploma	1	...	0.000000	
2	At least some college	3 or more	...	0.166667	
3	Less than HS diploma	1	...	0.000000	
4	Less than HS diploma	3 or more	...	0.058824	

  

	DrugTests_Other_Positive	Percent_Days_Employed	Jobs_Per_Year	\
0	0.0	0.488562	0.447610	
1	0.0	0.425234	2.000000	
2	0.0	0.000000	0.000000	
3	0.0	1.000000	0.718996	
4	0.0	0.203562	0.929389	

  

	Employment_Exempt	Recidivism_Within_3years	
Recidivism_Arrest_Year1	\		
0	False	False	False
1	False	True	False
2	False	True	False
3	False	False	False
4	False	True	True

  

	Recidivism_Arrest_Year2	Recidivism_Arrest_Year3	Binned_PUMA
0	False	False	(15.0, 20.0]
1	False	True	(15.0, 20.0]
2	True	False	(20.0, 25.0]
3	False	False	(15.0, 20.0]
4	False	False	(15.0, 20.0]

[5 rows x 54 columns]

With 4-anonymity for these set of features, we can rest assured that there are at least 4 individuals sharing the same combination, making it more difficult to identify someone by knowing only these 4 pieces of information. However, let's not ignore the following issues:

- We did not test  $k$ -anonymity for other combinations of features, so it is very likely that our dataset is still not anonymized.

- 4-anonymity is not very strong; if I can narrow down my search to 4 people, I can still learn a lot about a person (at least approximatively).
- We may lose  $k$ -anonymity by adding more information.

## Differential Privacy

As discussed in class, differential privacy is a stronger, mathematically robust definition of privacy for an algorithm. You can learn more about it by watching this video from Minute Physics: [Protecting Privacy with MATH](#)

After watching this video, try answering the following questions:

1. If you have two differentially private datasets, one with and one without your data, what does differential privacy guarantee regarding your privacy?
  2. An algorithm has differential privacy  $\epsilon = 2$ , another one  $\epsilon = 4$ . Which one provides a higher level of privacy? Explain your answer.
  3. The video highlights at least two of the main challenges with differential privacy. Summarize them.
- Q12.1: Differential privacy guarantees that the change in output of the algorithm between the two datasets will be minimal, and thus it would be difficult to deduce which dataset your data is present in. In other words, whether your data is in a dataset or not, the change in the output will be limited, so if the data is published, other people cannot easily detect your presence in the data.
  - Q12.2:  $\epsilon$  is a measure of the privacy loss as a result from differential changes in data, such as the addition or removal of new entries. As such, the algorithm with  $\epsilon = 2$  indicates that the change in the output will be small with and without the presence of your data, and thus has a higher level of privacy.
  - Q12.3: There is a tradeoff between differential privacy and informational accuracy, so people will need to figure out the minimum amount of noise required to maximise both privacy and accuracy. The publication of multiple jittered statistics also runs the risk of being combined to reconstruct the data that was meant to be hidden, so their publication need to be future-proofed to prevent such.

## Randomized response

In class, we described randomized polling as a way to conduct interviews including sensitive questions, while protecting individuals' privacy.

**Question 13:** imagine that UBC has been surveying students to understand how many of them have been cheating in a final exam. Because the information is very sensitive and students will most likely not want to share this information, they use the randomized polling protocol described in class. If 1000 students have been surveyed, and 300 of them responded "yes", what is the actual percentage of students who cheated in a final?

Let  $x$  be the actual percentage of students who cheated in the final.

$$\frac{x \cdot 3}{4} + \frac{(1 - x) \cdot 1}{4} = \frac{300}{1000}$$

$$\frac{1}{4} + \frac{x}{2} = \frac{3}{10}$$

$$x = \frac{1}{10} = 10\%$$

Therefore, we conclude that  $x = 10\%$  is the actual percentage of students who cheated in the final.

## Part 3: Data Governance

Data governance refers to the set of policies, procedures and standards that companies and organization must adopt to ensure quality, security and usability of the data in their possession.

To gain a better understanding of what data governance is, why it is important and what common mistakes affect it, please read the following articles:

- <https://www.egnyte.com/guides/governance/data-ownership>
- <https://atlan.com/data-governance-mistakes/#what-is-data-governance>

As you can see, the issue of data governance is complex and multifaceted. A group of experts with a variety of expertise is necessary to design and implement a robust data governance plan. Still, we can train ourselves to spot the most common mistakes when we see them. Take, for example, the following fictional scenario (co-authored in collaboration with [ChatGPT](#))

"SleekTech Solutions" is a cutting-edge technology company specializes in technologies related to artificial intelligence and data analytics. Their services include data analytics, big data processing, cloud computing, and Internet of Things (IoT). They offer their services to various industries, such as healthcare, finance, retail, manufacturing.

The company is young, only founded in 2021, and has rapidly expanded. At their inception, they used to accumulate data in a vast digital repository known as the "Data Lake." Initially, this seemed like a cost-effective solution to store all types of data, and they have not changed this strategy to this date.

To increase agility, SleekTech's different divisions have significant autonomy over their data. This means that the same data may be recorded by different department using different standards and metrics. SleekTech also encourages a culture of openness. Employees have access to vast amounts of data, including sensitive customer information, to complete the tasks they are assigned to.

SleekTech has been expanding rapidly. Founded in Canada, is now looking to expand into new markets including US and Europe.

**Question 14:** using the readings as reference, outline at least 4 distinct mistakes that SleekTech Solutions is likely to commit because of their data governance strategy.

- **Unrestricted access privileges:** In the question description, it says that "SleekTech also encourages a culture of openness. Employees have access to vast amounts of data, including sensitive customer information, to complete the tasks they are

assigned to". All employees having little to no restriction on access privileges, including access to sensitive customer information, leads to a severe risk of security breaches and thus damage to the company's reputation.

- Inadequate communication: In the question description, it says that "The company is young, only founded in 2021, and has rapidly expanded". The rapid growth and significant autonomy would require significant amounts of communication between departments, otherwise "data governance initiatives may be misunderstood or improperly implemented" (atlan, 2023). The significant autonomy over the data within each department provides greater risks of potential misunderstandings and redundancies, improper implementation, and unnecessary confusion over the same data.
- Neglected data quality: SleekTech Solutions' data lake contains data on various industries with no indication that they are segregated for more efficient organization, which can lead to unnecessary difficulties in relevant operations involving seeking relevant data. Different departments are also likely to use differing standards and metrics on the same data, which if not communicated well can lead to misunderstandings that eventually cause degraded data quality and consistency, unnecessary maintenance costs and failures to comply with data regulations.
- Failure to evolve and adapt: The lack of adaptation to more effective data storage options since they were founded in 2021 may lead to their data management tools becoming redundant and irrelevant compared to their competition. By using the same strategy for more than three years without accommodating for changes in new technology, the tools for their system may not be compatible with said technology, driving away potential and existing customers, as well as more effort and costs required to update their system to remain competitive with similar companies.

## Final thoughts

1) If you have completed this assignment in a group, please write a detailed description of how you divided the work and how you helped each other completing it:

- Jingyuan's response: We worked on the assignment separately, then collaborated to form our final assignment submission.
- Nicholas' response: We worked on the assignment separately, each taking turns answering all parts and modifying the responses down the line.

2) Have you used ChatGPT or a similar Large Language Model (LLM) to complete this homework? Please describe how you used the tool. **We will never deduct points for using LLMs for completing homework assignments**, but this helps us understand how you are using the tool and advise you in case we believe you are using it incorrectly.

- Jingyuan's response: I used ChatGPT to help debug the codes for pseudonymization and re-identification from pycanon.

- Nicholas' response: I have used Poe to assist in accessing the `pycanon` module, as well as the encoding in Q10 with both the pseudonymization function idea and using cryptography.

3) Have you struggled with some parts (or all) of this homework? Do you have pending questions you would like to ask? Write them down here!

- Jingyuan's response: Pending questions: what is the mathematical definition of  $\epsilon$ -differential privacy? How do we interpret  $\epsilon$ ?
- Nicholas' response: Encoding ideas for Q10, computing  $\epsilon$  for differential privacy.