

RUBY `AWS::SDK` EXAMPLES (AWS-SDK GEM ~>2)

SETTINGS

You can setup the connection on global way:

```
Aws.config.update(  
  endpoint: 'https://objects.dreamhost.com.',  
  access_key_id: 'my-access-key',  
  secret_access_key: 'my-secret-key',  
  force_path_style: true,  
  region: 'us-east-1'  
)
```

and instantiate a client object:

```
s3_client = Aws::S3::Client.new
```

LISTING OWNED BUCKETS

This gets a list of buckets that you own. This also prints out the bucket name and creation date of each bucket.

```
s3_client.list_buckets.buckets.each do |bucket|  
  puts "#{bucket.name}\t#{bucket.creation_date}"  
end
```

The output will look something like this:

```
mahbuckat1    2011-04-21T18:05:39.000Z  
mahbuckat2    2011-04-21T18:05:48.000Z  
mahbuckat3    2011-04-21T18:07:18.000Z
```

CREATING A BUCKET

This creates a new bucket called my-new-bucket

```
s3_client.create_bucket(bucket: 'my-new-bucket')
```

If you want a private bucket:

`acl` option accepts: # private, public-read, public-read-write, authenticated-read

```
s3_client.create_bucket(bucket: 'my-new-bucket', acl: 'private')
```

LISTING A BUCKET'S CONTENT

This gets a list of hashes with the contents of each object This also prints out each object's name, the file size, and last modified date.

```
s3_client.get_objects(bucket: 'my-new-bucket').contents.each do |object|  
  puts "#{object.key}\t#{object.size}\t#{object.last-modified}"  
end
```

The output will look something like this if the bucket has some files:

```
myphoto1.jpg 251262 2011-08-08T21:35:48.000Z
myphoto2.jpg 262518 2011-08-08T21:38:01.000Z
```

DELETING A BUCKET

Note: The Bucket must be empty! Otherwise it won't work!

```
s3_client.delete_bucket(bucket: 'my-new-bucket')
```

FORCED DELETE FOR NON-EMPTY BUCKETS

First, you need to clear the bucket:

```
Aws::S3::Bucket.new('my-new-bucket', client: s3_client).clear!
```

after, you can destroy the bucket

```
s3_client.delete_bucket(bucket: 'my-new-bucket')
```

CREATING AN OBJECT

This creates a file `hello.txt` with the string "Hello World!"

```
s3_client.put_object(
  key: 'hello.txt',
  body: 'Hello World!',
  bucket: 'my-new-bucket',
  content_type: 'text/plain'
)
```

CHANGE AN OBJECT'S ACL

This makes the object `hello.txt` to be publicly readable, and `secret_plans.txt` to be private.

```
s3_client.put_object_acl(bucket: 'my-new-bucket', key: 'hello.txt', acl: 'public-read')
s3_client.put_object_acl(bucket: 'my-new-bucket', key: 'private.txt', acl: 'private')
```

DOWNLOAD AN OBJECT (TO A FILE)

This downloads the object `poetry.pdf` and saves it in `/home/larry/documents/`

```
s3_client.get_object(bucket: 'my-new-bucket', key: 'poetry.pdf', response_target: '/home/larr
```

DELETE AN OBJECT

This deletes the object `goodbye.txt`

```
s3_client.delete_object(key: 'goodbye.txt', bucket: 'my-new-bucket')
```

GENERATE OBJECT DOWNLOAD URLs (SIGNED AND UNSIGNED)

This generates an unsigned download URL for `hello.txt`. This works because we made `hello.txt` public by setting the ACL above. This then generates a signed download URL for `secret_plans.txt` that will work for 1 hour. Signed download URLs will work for the time period even if the object is private (when the time period is up, the URL will stop working).

```
puts Aws::S3::Object.new(  
  key: 'hello.txt',  
  bucket_name: 'my-new-bucket',  
  client: s3_client  
) .public_url  
  
puts Aws::S3::Object.new(  
  key: 'secret_plans.txt',  
  bucket_name: 'hermes_ceph_gem',  
  client: s3_client  
) .presigned_url(:get, expires_in: 60 * 60)
```

The output of this will look something like:

```
http://objects.dreamhost.com/my-bucket-name/hello.txt  
http://objects.dreamhost.com/my-bucket-name/secret_plans.txt?Signature=XXXXXXXXXXXXXXXXXXXXX
```

RUBY `AWS::S3` EXAMPLES (AWS-S3 GEM)

CREATING A CONNECTION

This creates a connection so that you can interact with the server.

```
Aws::S3::Base.establish_connection!(  
  :server      => 'objects.dreamhost.com',  
  :use_ssl     => true,  
  :access_key_id => 'my-access-key',  
  :secret_access_key => 'my-secret-key'  
)
```

LISTING OWNED BUCKETS

This gets a list of `AWS::S3::Bucket` objects that you own. This also prints out the bucket name and creation date of each bucket.

```
Aws::S3::Service.buckets.each do |bucket|  
  puts "#{bucket.name}\t#{bucket.creation_date}"  
end
```

The output will look something like this:

```
mahbuckat1  2011-04-21T18:05:39.000Z  
mahbuckat2  2011-04-21T18:05:48.000Z  
mahbuckat3  2011-04-21T18:07:18.000Z
```

CREATING A BUCKET

This creates a new bucket called my-new-bucket

```
AWS::S3::Bucket.create('my-new-bucket')
```

LISTING A BUCKET'S CONTENT

This gets a list of hashes with the contents of each object This also prints out each object's name, the file size, and last modified date.

```
new_bucket = AWS::S3::Bucket.find('my-new-bucket')
new_bucket.each do |object|
  puts "#{object.key}\t#{object.about['content-length']}\t#{object.about['last-modified']}
end
```

The output will look something like this if the bucket has some files:

```
myphoto1.jpg 251262 2011-08-08T21:35:48.000Z
myphoto2.jpg 262518 2011-08-08T21:38:01.000Z
```

DELETING A BUCKET

Note: The Bucket must be empty! Otherwise it won't work!

```
AWS::S3::Bucket.delete('my-new-bucket')
```

FORCED DELETE FOR NON-EMPTY BUCKETS

```
AWS::S3::Bucket.delete('my-new-bucket', :force => true)
```

CREATING AN OBJECT

This creates a file hello.txt with the string "Hello World!"

```
AWS::S3::S3Object.store(
  'hello.txt',
  'Hello World!',
  'my-new-bucket',
  :content_type => 'text/plain'
)
```

CHANGE AN OBJECT'S ACL

This makes the object hello.txt to be publicly readable, and secret_plans.txt to be private.

```
policy = AWS::S3::S3Object.acl('hello.txt', 'my-new-bucket')
policy.grants = [ AWS::S3::ACL::Grant.grant(:public_read) ]
AWS::S3::S3Object.acl('hello.txt', 'my-new-bucket', policy)

policy = AWS::S3::S3Object.acl('secret_plans.txt', 'my-new-bucket')
policy.grants = []
AWS::S3::S3Object.acl('secret_plans.txt', 'my-new-bucket', policy)
```

DOWNLOAD AN OBJECT (TO A FILE)

This downloads the object `poetry.pdf` and saves it in `/home/larry/documents/`

```
open('/home/larry/documents/poetry.pdf', 'w') do |file|
  AWS::S3::S3Object.stream('poetry.pdf', 'my-new-bucket') do |chunk|
    file.write(chunk)
  end
end
```

DELETE AN OBJECT

This deletes the object `goodbye.txt`

```
AWS::S3::S3Object.delete('goodbye.txt', 'my-new-bucket')
```

GENERATE OBJECT DOWNLOAD URLS (SIGNED AND UNSIGNED)

This generates an unsigned download URL for `hello.txt`. This works because we made `hello.txt` public by setting the ACL above. This then generates a signed download URL for `secret_plans.txt` that will work for 1 hour. Signed download URLs will work for the time period even if the object is private (when the time period is up, the URL will stop working).

```
puts AWS::S3::S3Object.url_for(
  'hello.txt',
  'my-new-bucket',
  :authenticated => false
)

puts AWS::S3::S3Object.url_for(
  'secret_plans.txt',
  'my-new-bucket',
  :expires_in => 60 * 60
)
```

The output of this will look something like:

```
http://objects.dreamhost.com/my-bucket-name/hello.txt
http://objects.dreamhost.com/my-bucket-name/secret_plans.txt?Signature=XXXXXXXXXXXXXXXXXXXXX
```