

CEPH-POST-FILE - POST FILES FOR CEPH DEVELOPERS

SYNOPSIS

ceph-post-file [-d *description*] [-u **user*] *file or dir ...*

DESCRIPTION

ceph-post-file will upload files or directories to ceph.com for later analysis by Ceph developers.

Each invocation uploads files or directories to a separate directory with a unique tag. That tag can be passed to a developer or referenced in a bug report (<http://tracker.ceph.com/>). Once the upload completes, the directory is marked non-readable and non-writeable to prevent access or modification by other users.

WARNING

Basic measures are taken to make posted data be visible only to developers with access to ceph.com infrastructure. However, users should think twice and/or take appropriate precautions before posting potentially sensitive data (for example, logs or data directories that contain Ceph secrets).

OPTIONS

-d **description**, **--description** **description**

Add a short description for the upload. This is a good opportunity to reference a bug number. There is no default value.

-u **user**

Set the user metadata for the upload. This defaults to *whoami`@`hostname -f*.

EXAMPLES

To upload a single log:

```
ceph-post-file /var/log/ceph/ceph-mon.`hostname`.log
```

To upload several directories:

```
ceph-post-file -d 'mon data directories' /var/log/ceph/mon/*
```

AVAILABILITY

ceph-post-file is part of the Ceph distributed file system. Please refer to the Ceph documentation at <http://ceph.com/docs> for more information.

SEE ALSO

[ceph\(8\)](#), [ceph-debugpack\(8\)](#),