EE 044252: Digital Systems and Computer Structure

Spring 2018

Lecture 9a: RISC-V instruction formats



31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
rd = rs1 OP rs2									
imm[11:0]				rs1	funct3	rd		opcode	I-type
rd = rs1 OP Immediate; Load rd from Memory(rs1 + Immediate); *JALR (rd = PC + 4, PC = rs1 + Immediate)*									
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
Store rs2 to Memory(rs1 + Immediate)									
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type
Branch if (rs1 condition rs2) is true to Memory(PC + Immediate*2), i.e., PC = PC + Immediate*2									
imm[31:12]						rd		opcode	U-type
Upper "Long" Immediate (AUIPC, LUI): PC or rd = {imm, 12b'0}									
imm[20]	imm[10:1]		imm[11]	imm[19:12]		rd		opcode	J-type
JAL to Memory (PC + Immediate*2), i.e., rd = PC + 4; PC = PC + immediate*2									

EE 044252: Digital Systems and Computer Structure

Topic	wk	Lectures	Tutorials	Workshop	Simulation
Arch	1	Intro. RISC-V architecture	Numbers. Codes		
Comb	2	Switching algebra & functions	Assembly programming		
	3	Combinational logic	Logic minimization	Combinational	
	4	Arithmetic. Memory	Gates		Combinational
Seq	5	Finite state machines	Logic		
	6	Sync FSM	Flip flops, FSM timing	Sequential	Sequential
	7	FSM equiv, scan, pipeline	FSM synthesis		
	8	Serial comm, RISC-V functions	Serial comm, pipeline		
µArch	9	RISC-V instruction formats, single cycle	Function call		
	10	Multi-cycle RISC-V	Single cycle RISC-V		Multi-cycle
	11	Interrupts, pipeline RISC-V	Multi-cycle RISC-V		
	12	Dependencies in pipeline RISC-V	Microcode, interrupts		
	13		Depend. in pipeline RISC-V		

Outline

- RISC-V instruction formats

Big Idea: Stored-Program Computer

First Draft of a Report on the EDVAC
by
John von Neumann
Contract No. W–670–ORD–4926
Between the
United States Army Ordnance Department and the
University of Pennsylvania
Moore School of Electrical Engineering
University of Pennsylvania

June 30, 1945

- Instructions are bit patterns, like numbers
- Therefore, programs can be stored in read/write memory like data
- Can reprogram quickly (seconds), don’t have to rewire computer (days)
- Known as the “von Neumann” computers

EDSAC (Cambridge, 1949)
First General Stored-Program Computer

- Programs held as numbers in memory
- 35-bit binary 2's complement words

Consequence #1: Everything Has a Memory Address

- Instructions and data stored in memory → everything has a memory address
  - Branches and jumps use these
- Pointers are memory addresses
  - can lead to nasty bugs
- One register keeps address of instruction being executed: **"Program Counter" (PC)**
  - Pointer to memory

Instructions as Numbers (1/2)

- Most data we work with is in words (32-bit chunks):
  - Each register is a word
  - **`lw`** and **`sw`** both access memory one word at a time
- So how do we represent instructions?
  - "**`add x10,x11,x0`**" is meaningless to hardware
    - Use 1's, 0's instead
  - RISC-V seeks simplicity: since data is in words, make instructions be fixed-size 32-bit words also
    - Same 32-bit instructions used for RV32, RV64, RV128

Instructions as Numbers (2/2)

- One word is 32 bits. Divide instruction word into "fields"
- For simplicity, define six instruction formats:
  - **R**-format: register-register arithmetic operations
  - **I**-format: register-immediate arithmetic, loads
  - **S**-format: stores
  - **B**-format: branches
  - **U**-format: 20-bit upper immediate
  - **J**-format: jumps

RISC-V Instruction Formats



31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type
imm[31:12]						rd		opcode	U-type
imm[20]	imm[10:1]		imm[11]	imm[19:12]		rd		opcode	J-type

R-Format Instruction Layout



- 32-bit instruction word divided into six fields of varying numbers of bits each: 7+5+5+3+5+7 = 32
- Examples
  - opcode is a 7-bit field that lives in bits 6-0 of the instruction
  - rs2 is a 5-bit field that lives in bits 24-20 of the instruction

R-Format Instructions opcode/funct fields

31 25	24 20	19 15	14 12	11 7	6 0
funct7	rs2	rs1	funct3	rd	opcode
7	5	5	3	5	7

- **opcode**: partially specifies what instruction it is
  - 0110011_{two} for all R-Format register-register arithmetic instructions
- **funct7+funct3**: combined with **opcode**, these two fields describe what operation to perform

- Question: Why aren't **opcode** and **funct7** and **funct3** a single 17-bit field?
  - We'll answer this later

R-Format Instructions register specifiers

31 25	24 20	19 15	14 12	11 7	6 0
funct7	rs2	rs1	funct3	rd	opcode
7	5	5	3	5	7

- **`rs1`** (Source Register #1): specifies register containing first operand
- **`rs2`** : specifies second register operand
- **`rd`** (Destination Register): specifies register which will receive result of computation
- Each register field holds a 5-bit unsigned integer (0-31) corresponding to a register number (**`x0`**-**`x31`**)

R-Format Example

- RISC-V Assembly Instruction:

```
add  x18,x19,x10
```



31 25	24 20	19 15	14 12	11 7	6 0
funct7	rs2	rs1	funct3	rd	opcode
7	5	5	3	5	7

0000000	01010	10011	000	10010	0110011
ADD	rs2=10	rs1=19	ADD	rd=18	Reg-Reg OP

All RV32 R-format instructions

0000000	rs2	rs1	000	rd	0110011	ADD
0100000	rs2	rs1	000	rd	0110011	SUB
0000000	rs2	rs1	001	rd	0110011	SLL
0000000	rs2	rs1	010	rd	0110011	SLT
0000000	rs2	rs1	011	rd	0110011	SLTU
0000000	rs2	rs1	100	rd	0110011	XOR
0000000	rs2	rs1	101	rd	0110011	SRL
0100000	rs2	rs1	101	rd	0110011	SRA
0000000	rs2	rs1	110	rd	0110011	OR
0000000	rs2	rs1	111	rd	0110011	AND

Different encoding in funct7 + funct3 selects different operations

I-Format Instructions

- What about instructions with immediates?
  - 5-bit field only represents numbers up to the value 31: immediates may be much larger than this
  - Ideally, RISC-V would have only one instruction format (for simplicity): unfortunately, we need to compromise
- Define new instruction format that is mostly consistent with R-format
  - Notice if instruction has immediate, then uses at most 2 registers (one source, one destination)

I-Format Instruction Layout

31 20	19 15	14 12	11 7	6 0
imm[11:0]	rs1	funct3	rd	opcode
12	5	3	5	7

- Only one field is different from R-format, rs2 and funct7 replaced by 12-bit signed immediate, **`imm[11:0]`**
- Remaining fields (rs1, funct3, rd, opcode) same as in R-format
- imm[11:0] can hold values in range [-2048$_{\text{ten}}$, +2047$_{\text{ten}}$]
- Immediate is always sign-extended to 32-bits before use in an arithmetic operation
- We'll later see how to handle immediates > 12 bits

I-Format Example

- RISC-V Assembly Instruction:

  addi   x15,x1,-50



31 – 20	19 – 15	14 – 12	11 – 7	6 – 0
imm[11:0]	rs1	funct3	rd	opcode
12	5	3	5	7

111111001110	00001	000	01111	0010011
imm=-50	rs1=1	ADD	rd=15	OP-Imm

All RV32 I-format Arithmetic Instructions



imm[11:0]		rs1	000	rd	0010011	ADDI
imm[11:0]		rs1	010	rd	0010011	SLTI
imm[11:0]		rs1	011	rd	0010011	SLTIU
imm[11:0]		rs1	100	rd	0010011	XORI
imm[11:0]		rs1	110	rd	0010011	ORI
imm[11:0]		rs1	111	rd	0010011	ANDI
0000000	shamt	rs1	001	rd	0010011	SLLI
0000000	shamt	rs1	101	rd	0010011	SRLI
0100000	shamt	rs1	101	rd	0010011	SRAI

One of the higher-order immediate bits is used to distinguish "shift right logical" (SRLI) from "shift right arithmetic" (SRAI)

"Shift-by-immediate" instructions only use lower 5 bits of the immediate value for shift amount (can only shift by 0-31 bit positions)

Load Instructions are also I-Type



31 — 20	19 — 15	14 — 12	11 — 7	6 — 0
imm[11:0]	rs1	funct3	rd	opcode
12	5	3	5	7
offset[11:0]	base	width	dest	LOAD

- The 12-bit signed immediate (“offset”) is added to the base address in register rs1 to form the memory address
  - This is very similar to the add-immediate operation but used to create address not to create final result
- The value loaded from memory is stored in register rd

I-Format Load Example

- RISC-V Assembly Instruction:

```
lw x14, 8(x2)
```

31 20	19 15	14 12	11 7	6 0
imm[11:0]	rs1	funct3	rd	opcode
12	5	3	5	7

000000001000	00010	010	01110	0000011
imm=+8	rs1=2	LW	rd=14	LOAD

All RV32 Load Instructions



imm[11:0]	rs1	000	rd	0000011	LB
imm[11:0]	rs1	001	rd	0000011	LH
imm[11:0]	rs1	010	rd	0000011	LW
imm[11:0]	rs1	100	rd	0000011	LBU
imm[11:0]	rs1	101	rd	0000011	LHU

funct3 field encodes size and signedness of load data

- LBU is “load unsigned byte”
- LH is “load halfword”, which loads 16 bits (2 bytes) and sign-extends to fill destination 32-bit register
- LHU is “load unsigned halfword”, which zero-extends 16 bits to fill destination 32-bit register
- There is no LWU in RV32, because there is no sign/zero extension needed when copying 32 bits from a memory location into a 32-bit register

S-Format Used for Stores



31 – 25	24 – 20	19 – 15	14 – 12	11 – 7	6 – 0
imm[11:5]	rs2	rs1	funct3	imm[4:0]	opcode
7	5	5	3	5	7
offset[11:5]	src	base	width	offset[4:0]	STORE

- Store needs to read two registers, rs1 for base memory address, and rs2 for data to be stored, as well as need immediate offset!
- Can’t have both rs2 and immediate in same place as other instructions!
- Note that stores don’t write a value to the register file, ***no rd***!
- RISC-V design decision is move low 5 bits of immediate to where rd field was in other instructions – keep rs1/rs2 fields in same place
  - register names more critical than immediate bits in hardware design

S-Format Example

- RISC-V Assembly Instruction:

```
sw x14, 8(x2)
```

31 … 25	24 … 20	19 … 15	14 … 12	11 … 7	6 … 0
imm[11:5]	rs2	rs1	funct3	imm[4:0]	opcode
7	5	5	3	5	7
offset[11:5]	src	base	width	offset[4:0]	STORE

0000000	01110	00010	010	01000	0100011
offset[11:5] =0	rs2=14	rs1=2	SW	offset[4:0] =8	STORE



combined 12-bit offset = 8

All RV32 Store Instructions



imm[11:5]	rs2	rs1	000	imm[4:0]	0100011	SB
imm[11:5]	rs2	rs1	001	imm[4:0]	0100011	SH
imm[11:5]	rs2	rs1	010	imm[4:0]	0100011	SW

RISC-V Conditional Branches

- E.g., `BEQ x1, x2, Label`
- Branches read two registers but don’t write a register (similar to stores)
- How to encode label, i.e., where to branch to?

Branching Instruction Usage

- Branches typically used for loops (`if-else`, `while`, `for`)
  - Loops are generally small (< 50 instructions)
  - Function calls and unconditional jumps handled with jump instructions (J-Format)
- **Recall:** Instructions stored in a localized area of memory (Code/Text)
  - Largest branch distance limited by size of code
  - Address of current instruction stored in the program counter (PC)

PC-Relative Addressing

- PC-Relative Addressing: Use the `immediate` field as a two's-complement offset to PC
  - Branches generally change the PC by a small amount
  - Can specify $\pm 2^{11}$ addresses from the PC
- Why not use byte address offset from PC?

Scaling Branch Offset

- ~~One idea: To improve the reach of a single branch instruction, multiply the offset by four before adding to PC~~
- ~~This would allow one branch instruction to reach ± 2^{11} × 32-bit instructions either side of PC~~
  - ~~Four times greater reach than using byte offset~~

Not in RV32

Branch Calculation

Not in RV32

- If we don't take the branch:

  `PC = PC + 4` (i.e., next instruction)

- If we do take the branch:

  `PC = PC + immediate*4`

- **Observations:**
  - `immediate` is number of instructions to jump (remember, specifies words) either forward (+) or backwards (–)

RISC-V Feature, n×16-bit instructions

- Extensions to RISC-V base ISA support 16-bit compressed instructions and also variable-length instructions that are multiples of 16-bits in length
- To enable this, RISC-V scales the branch offset by 2 bytes even when there are no 16-bit instructions
- Reduces branch reach by half and means that ½ of possible targets will be errors on RISC-V processors that only support 32-bit instructions (as used in this class)
- RISC-V conditional branches can only reach $\pm 2^{10} \times$ 32-bit instructions either side of PC

RISC-V B-Format for Branches

31	30 25	24 20	19 15	14 12	11 8	7	6 0
imm[12]	imm[10:5]	rs2	rs1	funct3	imm[4:1]	imm[11]	opcode
1	6	5	5	3	4	1	7

- B-format is mostly same as S-Format, with two register sources (rs1/rs2) and a 12-bit immediate
- But now immediate represents values -4096 to +4094 in 2-byte increments
- The 12 immediate bits encode *even* 13-bit signed byte offsets
  – lowest bit of offset is always zero, so no need to store it

Branch Example, determine offset

- RISC-V Code:

```
Loop: beq  x19,x10,End
      add  x18,x18,x10
      addi x19,x19,-1
      j    Loop
End:  # target instruction
```



- Branch offset = 4×32-bit instructions = 16 bytes
- (Branch with offset of 0, branches to itself)

Branch Example, encode offset

- RISC-V Code:

```
Loop: beq   x19,x10,End
      add   x18,x18,x10
      addi  x19,x19,-1
      j     Loop
End: # target instruction
```

offset = 16 bytes = 8x2

???????	01010	10011	000	?????	1100011
imm	rs2=10	rs1=19	BEQ	imm	BRANCH

RISC-V Immediate Encoding

Instruction Encodings, inst[31:0]

31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type

32-bit immediates produced, imm[31:0]

31	30 20	19 12	11	10 5	4 1	0	
— inst[31] —				inst[30:25]	inst[24:21]	inst[20]	I-immediate
— inst[31] —				inst[30:25]	inst[11:8]	inst[7]	S-immediate
— inst[31] —			inst[7]	inst[30:25]	inst[11:8]	0	B-immediate

$\longleftrightarrow$

Upper bits sign-extended from inst[31] always

RISC-V Immediate Encoding



Instruction Encodings, inst[31:0]

31	30 ... 25	24 ... 21	20	19 ... 15	14 ... 12	11 ... 8	7	6 ... 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type

32-bit immediates produced, imm[31:0]

31	30 ... 20	19 ... 12	11	10 ... 5	4 ... 1	0	
— inst[31] —				inst[30:25]	inst[24:21]	inst[20]	I-immediate
— inst[31] —				inst[30:25]	inst[11:8]	inst[7]	S-immediate
— inst[31] —			inst[7]	inst[30:25]	inst[11:8]	0	B-immediate

RISC-V Immediate Encoding



Instruction Encodings, inst[31:0]

31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type

32-bit immediates produced, imm[31:0]

31	30 20	19 12	11	10 5	4 1	0	
— inst[31] —				inst[30:25]	inst[24:21]	inst[20]	I-immediate
inst[31]				inst[30:25]	inst[11:8]	inst[7]	S-immediate
— inst[31] —			inst[7]	inst[30:25]	inst[11:8]	0	B-immediate

RISC-V Immediate Encoding



Instruction Encodings, inst[31:0]

31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type

32-bit immediates produced, imm[31:0]

31	30 20	19 12	11	10 5	4 1	0	
— inst[31] —				inst[30:25]	inst[24:21]	inst[20]	I-immediate
— inst[31] —				inst[30:25]	inst[11:8]	inst[7]	S-immediate
— inst[31] —			inst[7]	inst[30:25]	inst[11:8]	0	B-immediate

Only bit 7 of instruction changes role in immediate between S and B

Branch Example, complete encoding

```
beq    x19,x10, offset = 16 bytes
```



All RISC-V Branch Instructions



imm[12|10:5]	rs2	rs1	000	imm[4:1|11]	1100011	BEQ
imm[12|10:5]	rs2	rs1	001	imm[4:1|11]	1100011	BNE
imm[12|10:5]	rs2	rs1	100	imm[4:1|11]	1100011	BLT
imm[12|10:5]	rs2	rs1	101	imm[4:1|11]	1100011	BGE
imm[12|10:5]	rs2	rs1	110	imm[4:1|11]	1100011	BLTU
imm[12|10:5]	rs2	rs1	111	imm[4:1|11]	1100011	BGEU

Questions on PC-addressing

- Does the value in branch immediate field change if we move the code?
  - If moving individual lines of code, then yes
  - If moving all of code, then no
- What do we do if destination is > 2^{10} instructions away from branch?
  - Other instructions save us

Questions on PC-addressing

- Does the value in branch immediate field change if we move the code?
  - If moving individual lines of code, then yes
  - If moving all of code, then no (because PC-relative offsets)
- What do we do if destination is > 2^{10} instructions away from branch?
  - Other instructions save us

  -
    ```
    beq x10,x0,far                  bne x10,x0,next
    # next instr      →             j   far
                              next: # next instr
    ```

U-Format for “Upper Immediate” instructions



31 — 12	11 — 7	6 — 0
imm[31:12]	rd	opcode
20	5	7
U-immediate[31:12]	dest	LUI
U-immediate[31:12]	dest	AUIPC

- Has 20-bit immediate in upper 20 bits of 32-bit instruction word
- One destination register, rd
- Used for two instructions
  - LUI – Load Upper Immediate
  - AUIPC – Add Upper Immediate to PC

LUI to create long immediates

- LUI writes the upper 20 bits of the destination with the immediate value, and clears the lower 12 bits.
- Together with an ADDI to set low 12 bits, can create any 32-bit value in a register using two instructions (LUI/ADDI).

```
LUI x10, 0x87654          # x10 = 0x87654000
ADDI x10, x10, 0x321      # x10 = 0x87654321
```

One Corner Case

How to set 0xDEADBEEF?

```
LUI x10, 0xDEADB          # x10 = 0xDEADB000
ADDI x10, x10, 0xEEF      # x10 = 0xDEADAEEF
```

ADDI 12-bit immediate is always sign-extended, if top bit is set, will subtract -1 from upper 20 bits

Solution

How to set 0xDEADBEEF?

```
LUI x10, 0xDEADC          # x10 = 0xDEADC000
ADDI x10, x10, 0xEEF  # x10 = 0xDEADBEEF
```

Pre-increment value placed in upper 20 bits, if sign bit will be set on immediate in lower 12 bits.

Assembler pseudo-op handles all of this:

```
li x10, 0xDEADBEEF # Creates two instructions
```

AUIPC

- Adds upper immediate value to PC and places result in destination register
- Used for PC-relative addressing

- `Label: AUIPC x10, 0 # Puts address of label in x10`

J-Format for Jump Instructions

31	30 21	20	19 12	11 7	6 0
imm[20]	imm[10:1]	imm[11]	imm[19:12]	rd	opcode
1	10	1	8	5	7
	offset[20:1]			dest	JAL

- JAL saves PC+4 in register rd (the return address)
  - Assembler "`j`" jump is pseudo-instruction, uses JAL but sets rd=x0 to discard return address
- Set PC = PC + offset (PC-relative jump)
- Target somewhere within $\pm 2^{19}$ locations, 2 bytes apart
  - $\pm 2^{18}$ 32-bit instructions
- Immediate encoding optimized similarly to branch instruction to reduce hardware cost
  - Offset field 20 bits. Append '0' bit. Resulting offset is 21 bits, even number

Uses of JAL

```
# j pseudo-instruction
j Label = jal x0, Label # Discard return address

# Call function within 2^18 instructions of PC
jal ra, FuncName
```

JALR Instruction (I-Format)



31 — 20	19 — 15	14 — 12	11 — 7	6 — 0
imm[11:0]	rs1	funct3	rd	opcode
12	5	3	5	7
offset[11:0]	base	0	dest	JALR

- JALR rd, rs, immediate
  - Writes PC+4 to rd (return address)
  - Sets PC = rs + immediate
  - Uses same immediates as arithmetic and loads
    - ***no*** multiplication by 2

Uses of JALR

```
# ret and jr psuedo-instructions
ret = jr ra = jalr x0, ra, 0
# Call function at any 32-bit absolute address
lui x1, <hi20bits>
jalr ra, x1, <lo12bits>
# Jump PC-relative with 32-bit offset
auipc x1, <hi20bits>
jalr x0, x1, <lo12bits>
```

Summary of RISC-V Instruction Formats



31	30 25	24 21	20	19 15	14 12	11 8	7	6 0	
funct7		rs2		rs1	funct3	rd		opcode	R-type
imm[11:0]				rs1	funct3	rd		opcode	I-type
imm[11:5]		rs2		rs1	funct3	imm[4:0]		opcode	S-type
imm[12]	imm[10:5]	rs2		rs1	funct3	imm[4:1]	imm[11]	opcode	B-type
imm[31:12]						rd		opcode	U-type
imm[20]	imm[10:1]		imm[11]	imm[19:12]		rd		opcode	J-type

Complete RV32I ISA



imm[31:12]				rd	0110111	LUI
imm[31:12]				rd	0010111	AUIPC
imm[20|10:1|11|19:12]				rd	1101111	JAL
imm[11:0]		rs1	000	rd	1100111	JALR
imm[12|10:5]	rs2	rs1	000	imm[4:1|11]	1100011	BEQ
imm[12|10:5]	rs2	rs1	001	imm[4:1|11]	1100011	BNE
imm[12|10:5]	rs2	rs1	100	imm[4:1|11]	1100011	BLT
imm[12|10:5]	rs2	rs1	101	imm[4:1|11]	1100011	BGE
imm[12|10:5]	rs2	rs1	110	imm[4:1|11]	1100011	BLTU
imm[12|10:5]	rs2	rs1	111	imm[4:1|11]	1100011	BGEU
imm[11:0]		rs1	000	rd	0000011	LB
imm[11:0]		rs1	001	rd	0000011	LH
imm[11:0]		rs1	010	rd	0000011	LW
imm[11:0]		rs1	100	rd	0000011	LBU
imm[11:0]		rs1	101	rd	0000011	LHU
imm[11:5]	rs2	rs1	000	imm[4:0]	0100011	SB
imm[11:5]	rs2	rs1	001	imm[4:0]	0100011	SH
imm[11:5]	rs2	rs1	010	imm[4:0]	0100011	SW
imm[11:0]		rs1	000	rd	0010011	ADDI
imm[11:0]		rs1	010	rd	0010011	SLTI
imm[11:0]		rs1	011	rd	0010011	SLTIU
imm[11:0]		rs1	100	rd	0010011	XORI
imm[11:0]		rs1	110	rd	0010011	ORI
imm[11:0]		rs1	111	rd	0010011	ANDI



0000000	shamt		rs1	001	rd	0010011	SLLI
0000000	shamt		rs1	101	rd	0010011	SRLI
0100000	shamt		rs1	101	rd	0010011	SRAI
0000000	rs2		rs1	000	rd	0110011	ADD
0100000	rs2		rs1	000	rd	0110011	SUB
0000000	rs2		rs1	001	rd	0110011	SLL
0000000	rs2		rs1	010	rd	0110011	SLT
0000000	rs2		rs1	011	rd	0110011	SLTU
0000000	rs2		rs1	100	rd	0110011	XOR
0000000	rs2		rs1	101	rd	0110011	SRL
0100000	rs2		rs1	101	rd	0110011	SRA
0000000	rs2		rs1	110	rd	0110011	OR
0000000	rs2		rs1	111	rd	0110011	AND
0000	pred	succ	00000	000	00000	0001111	FENCE
0000	0000	0000	00000	001	00000	0001111	FENCE.I
000000000000			00000	000	00000	1110011	ECALL
000000000001			00000	000	00000	1110011	EBREAK
csr			rs1	001	rd	1110011	CSRRW
csr			rs1	010	rd	1110011	CSRRS
csr			rs1	011	rd	1110011	CSRRC
csr			zimm	101	rd	1110011	CSRRWI
csr			zimm	110	rd	1110011	CSRRSI
csr			zimm	111	rd	1110011	CSRRCI

Not in 044252