

# Index

---

## A

*ABCD* ray matrix, 92,108  
  method of, 107-118,152-154,396-402  
  table of, 108  
Absorption (*see* Atmospheric scattering)  
Adaptive optics, 21,609  
  scintillation, 464  
  system components, 609  
Aerosol scattering, 12  
Airy disk, 615  
Amplitude, 87,88  
Angle-of-arrival, 199-201  
  variance, 200,492  
Angular frequency, 85  
Angular spectrum, 206-207  
Anisoplanatism, 493  
  (*See also*, Isoplanatic angle)  
Anisotropic turbulence, 480  
Annular beam, 720  
  mean irradiance, 724  
  scintillation index, 728  
Aperture-averaging, 24,281,409-410  
  array, 465-467  
    beam wave, 419-420  
    plane wave, 412-413,496  
    spherical wave, 415-416  
Array detector, 465-469  
Asymptotic theory, 330  
  for scintillation index, 330-332  
Atmospheric  
  absorption, 11  
  boundary layer, 480  
  coherence width,  $r_0$ , 194,272,492,608,617  
  scattering, 11  
  spectrum (*see* Power spectrum)  
  transmission, 12  
  turbulence, 14  
    (*See also*, Turbulence)  
Attenuation, 9,616  
Autocorrelation function (*see* Correlation function)  
Autocovariance function (*see* Covariance function)  
Average,  
  ensemble, 38  
  irradiance (*see* Mean irradiance)

time, 41-42

## B

Backscatter amplification effect, 535,546  
  correlation function, 546,549,551,553-554,  
    558-559,576-581,589  
Bandwidth, 16  
Beam  
  jitter, 272,503  
  spreading (*see* Beam radius)  
  waist, 9, 97-98,99-100  
  wave (*see* Gaussian-beam wave)  
Beam parameters,  
  effective, 242,349,681-682  
  input plane (transmitter), 92-94,96-98,183  
  output plane (receiver), 94-96,99-101,183  
Beam radius (spot size), 88,93,189-190,237-  
  238  
  double-pass, 551,553,557  
  higher-order modes, 101-107,715,717-719  
  long term, 189-190,238,404,494-495,500  
  partially coherent beam, 677,679  
  phase screen, 655  
  short term, 205-206  
Beam wander, 15,201-205,209-210,269-272,  
  501-502  
  effective pointing error, 272-274,503  
  filter function, 203,245  
  strong fluctuations, 245-246  
Bessel beam, 731-732  
Bessel function, 139,150  
  modified, 125,188  
Bistatic  
  channel, 536  
  system, 535,  
Bit error-rate (BER), 447,463,469-470,691-  
  692  
Born approximation, 141-143  
  first-order, 142  
  higher-order, 143  
  normalized, 144  
Bufton wind model, 481  
Bump spectrum (*see* Hill spectrum and  
  Modified spectrum)

**C**

Carrier-to-noise ratio (CNR),  
 Cell (*see* Eddy)  
 Channel models, 22  
 Clear-air turbulence, 480  
 Coherence,  
   bandwidth, 744  
   spatial, 15  
   time, 744  
 Coherence width (*see* Atmospheric coherence width,  $r_0$ )  
 Coherence radius, 161,192-199,208-209,491-492  
   double-pass, 571,581,590  
   Gaussian-beam wave, 198  
   partially coherent beam, 680  
   phase screen, 656  
   plane wave, 194  
   spherical wave, 196  
   strong fluctuations, 240,243  
 Coherent  
   detection, 24,443  
   transfer function (CFT), 611-613  
 Collimated beam, 88-89  
   (*See also*, Gaussian-beam wave)  
 Communication system (FSO), 15-17, 22-26  
   laser satellite, 17-19,478-479  
   terrestrial, 442-443  
 Complex  
   amplitude, 43,85,542  
   degree of coherence, 188  
 Complex phase perturbation, 143,183  
   folded path, 544  
   reciprocal path, 545  
   spectral representation for, 145-147,399-400  
 Conditional density function, 368  
 Confluent hypergeometric function, 71,187,758-759  
 Conformal transformation, 99  
 Convergent beam, 88-89  
   (*See also*, Gaussian-beam wave)  
 Correlation between incident and reflected waves (*see* Backscatter amplification effect)  
 Correlation function, 38  
 Correlation width (irradiance fluctuations), 281,498  
 Covariance function, 39  
   normalized, 39  
 Covariance function of irradiance, 261,279-281,361-364,498,509

  double-pass, 560,561,581  
   normalized, 281,362  
   phase screen, 658-659  
 Covariance function,  
   of log amplitude, 279  
   of phase, 294-296  
   of refractive index, 64,139  
 Cross-coherence function (*see* Fourth-order moment)  
 Crossings per second (*see* Number of crossings)  
 Cross-spectral purity, 669  
 Cumulants, 184  
 Cumulative probability density, 371,451-452

**D**

Decibel (dB), 451  
 Delta correlated, 139  
 Delta function, 44,87,139  
 Detector,  
   array, 465-469  
   coherent, 24,443  
   direct, 23,443-444  
   point, 23,281  
 Detector noise, 444  
 Diffraction, 8  
 Diffuser, 671  
   correlation radius, 672  
   correlation width, 671  
 Diffuse surface (*see* Lambertian surface)  
 Diffusivity, 63  
 Digital transmission, 447  
 Dissipation range, 59  
   diffusion, 62  
   viscous, 59  
 Divergent beam, 88-89  
   (*See also*, Gaussian-beam wave)  
 Doppler shift, 538

**E**

Earth's atmosphere, 479-480  
    $C_n^2$  profile of, 481-482  
   outer scale models of, 483  
 Echo signal, 536  
 Eddy, 59  
 Effective  
   beam parameters, 242,349  
   atmospheric spectrum, 327  
 Eikonal, 111,634  
 Electromagnetic spectrum, 6  
 Energy cascade theory, 59  
 Energy dissipation rate, 60

Enhanced backscatter, 535,546 (*See also*,  
Backscatter amplification effect)  
Ensemble, 36  
    average, 38  
Ergodic random process, 42  
Error function, 447,756  
Expected number of fades, 447-448,455-456,  
    513-514,519  
Exponential spectrum, 68,203,328  
Extended Huygens-Fresnel principle, 159,  
    234-241  
Extended medium model, 25  
Extended Rytov theory, 159-165,324-328  
Extinction coefficient, 12

**F**

Fade,  
    probability of, 445,451-452,511,518  
    threshold parameter, 451,511,518  
False alarm, 445  
    probability of, 447  
    rate (FAR), 448  
Far field, 98  
Femtosecond, 738,742  
Field, 84  
    coherent portion of, 182  
Field of view (FOV), 536,610  
Flattened Gaussian beam, 729-731  
Flow chart, 30,181,259  
Focused beam, 97,98,204,269  
Focusing parameter, 96  
Folded path, 117,543-544  
Four-frequency cross-coherence function, 746  
Fourier transform, 43  
    inverse, 43  
    propagation geometry for, 402  
Fourth-order moment, 182,235,260,559  
Fractional fade time (*see* Probability of fade)  
Free atmosphere, 480  
Free space optical (FSO) communication, 15-  
    17,442,478-479  
Frequency of fade (surge), 447-448,455-456,  
    513-514,519  
Fresnel zone size, 325  
Fried parameter (*see* Atmospheric coherence  
    width,  $r_0$ )  
Frozen turbulence hypothesis, 72,207

**G**

Gamma distribution, 368,370,449  
Gamma function, 75,755  
Gamma-gamma distribution, 370,450,510,

699

    cumulative, 371

## Gaussian

    aperture, 108,116,612  
    lens, 113  
    mirror, 117

## Gaussian-beam wave, 8,88,182-183

    definition of, 8,88  
    double-pass, 551,561,581-584  
    flattened, 729-731  
    free-space irradiance for, 94  
    higher-order Hermite, 101  
    higher-order Laguerre, 106  
    irradiance covariance function for  
        (*see* Covariance function of irradiance)  
    lowest order (TEM<sub>00</sub>), 88  
    mean irradiance for (*see* Mean irradiance)  
    mutual coherence function for, 188,191  
    scintillation index for, 262-263,352-353,  
        356  
    super, 729  
    waist, 97-98,99-100  
    wave structure function for, 196-199

## Gaussian

    distribution, 446-447  
    Schell-model, 671  
    spectrum, 673

## Geometric focus, 97-98,99-101

## Geometrical optics approximation, 165,330

Generalized hypergeometric  
function, 190,759-760

## Geostationary orbit (GEO), 484

## Geosynchronous orbit (GEO), 484

## Green's function, 90,142,151

    for Huygen's-Fresnel integral, 90

    generalized, 111,153

## Greenwood

    frequency, 622

    time constant, 622

**H**

## Hard aperture, 116,612

## Helmholtz equation, 85

    stochastic, 138,158

## Hermite equation, 103

## Hermite-Gaussian functions, 101,715

## Hermite polynomial, 101,715,731

    elegant, 129

## Hill spectrum, 69-70

## Hufnagle-Valley turbulence model, 481

## Huygens-Fresnel integral, 90,105

    extended, 159,234-241

generalized, 111  
 Hypergeometric function, 190,757-758  
   confluent, 71,187,758-759  
   generalized, 190,759-760

## I

Image,  
   blurring, 21,609  
   dancing, 21,609  
   displacement, 201  
   plane, 115  
   resolution, 116  
   short exposure, 609  
 Imaging, 21  
   adaptive optics, 609  
   coherent system, 610  
   hybrid techniques, 609  
   incoherent system, 614  
   speckle, 609  
 Impulse response function, 151,611,613  
 Index of refraction, 63-71  
   covariance function, 64,139  
   fluctuations, 63-71  
   inner scale for, 64  
   outer scale for, 64  
   spectrum models for, 66-71  
   structure constant, 64-65  
   structure function, 64-71  
 Inertial range, 59  
 Inertial-convective range, 62  
 Inner scale of turbulence, 59  
   index of refraction, 64  
   temperature, 63  
   velocity, 59  
 Intensity (*see* Irradiance)  
 Ionosphere, 11  
 Irradiance, 94  
   fluctuations, 9,15  
     (*See also*, scintillation index)  
   free space, 94,105,106  
   integrated, 686  
   mean (*see* Mean irradiance)  
   moments, 155,157,175  
   temporal spectrum, 282-288  
 Irradiance flux variance, 410  
 Isoplanatic angle, 493,622  
 Isotropic medium, 46,58

**K**  
 K distribution, 368  
 Kinematic viscosity, 59  
 Kolmogorov microscale, 60

Kolmogorov spectrum, 62,63,67,289  
 Kummer function (*see* Confluent  
   hypergeometric function)

## L

Laguerre-Gaussian functions, 106,718  
 Laguerre polynomial, 106,155,719,730  
 Lambertian surface, 539,589  
 Laminar flow, 58  
 Laplacian, 85,137  
 Laser  
   acronym, 4  
   beacon, 493,622  
   guide star, 493,622  
   wavelengths, 7  
 Laser radar, 20-21,534-539,693  
   imaging, 624  
 Laser satcom, 17-19,478-479  
 Lens,  
   Gaussian model, 113  
   law, 115  
 Lidar, 20,534  
 Locally homogeneous, 48  
 Log amplitude, 155,262  
   covariance, 279  
   mean, 310-311  
   variance, 157,259  
   structure function, 193,194  
 Log-irradiance variance, 259,262  
 Lognormal distribution, 155-157,451,510  
 Lognormal-Rician distribution, 369  
 Longitudinal phase shift, 93,96  
 Long-term spot size, 189-190,238,404,494-  
   495,500 (*See also*, Beam radius)  
 Low Earth orbit (LEO), 484

## M

Markov approximation, 138  
 Maser, 7  
 Mean field, 158,182,186-187,232  
 Mean irradiance, 189-190,208,237-238,404,  
   406,407,494,716  
   double-pass, 550,553,557,589  
   downlink, 494  
   partially coherent beam, 672,679  
   phase screen, 655  
   pulse, 743-744  
   strong fluctuations, 237-238  
   temporal, 742  
   uplink, 500  
 Mean fade time, 456  
   downlink, 515

terrestrial, 456  
 uplink, 520  
 Mesosphere, 11  
 Microscale of turbulence, 60  
 Mie scattering, 12  
 Miller-Zieske profile, 481  
 Mirror,  
     (See also, Target)  
     Gaussian, 117  
 Modified atmospheric spectrum, 68-69  
 Modified von Kármán spectrum (see Von Kármán spectrum)  
 Modulus of the complex degree of coherence, 193,655,672,679,697  
 Modulation process, 163,325,329  
 Modulation transfer function (MTF), 116,  
     614-618,624  
     short term, 620  
 Molniya orbit, 484  
 Moments,  
     fourth-order coherence function, 182,235,  
         260,559  
     irradiance, 155,157,175,208  
     long-time-average, 184  
     mean field, 182,186-187,232,235  
     mutual coherence function, 182,187-188,  
         232-233,547,653,674-675,678,696  
     temporal, 745  
 Monochromatic wave, 85  
 Monostatic  
     channel, 117,536  
     system, 117,535-536  
 Mutual coherence function (MCF), 158,182,  
     187-188,232-233  
     double-pass, 547  
     free space, 186  
     Gaussian-beam wave, 188,191  
     partially coherent beam, 674-676,678,696  
     phase screen, 653  
     plane wave, 190  
     spherical wave, 191  
     strong fluctuations, 232-233,239-241  
     two frequency, 740-742  
**N**  
 Narrowband, 742  
 Near field, 98  
 Negative exponential distribution, 368  
 Noise power, 445  
 Nonisotropic, 60,480  
 Number of crossings (fades and surges), 447-  
     448,455-456

**O**

Obukhov-Corrsin constant, 63  
 On-off keying (OOK), 447  
 Optical communications, 15-17  
     (See also, Communication systems)  
 Optical depth, 12  
 Optical transfer function (OTF), 115,614-615  
 Optical turbulence, 15,58  
     definition of, 15,58  
     profile, 481-482  
 Orbit, 484-485  
 Outer scale of turbulence, 59  
     model for, 483

**P**

Parabolic equation, 158,231  
     method of moments, 157-158,231-233  
 Paraxial  
     approximation, 85,109  
     wave equation, 85-86  
 Path amplitude weighting parameter, 146  
 Perturbation methods,  
     Born approximation, 141-143  
     Rytov approximation, 143-154  
 Phase, 88,288,301  
     covariance, 294-296  
     perturbation (see Complex phase  
         perturbation)  
     structure function, 193-195,291-294  
     temporal spectrum, 296-298  
     variance, 289-291,635-636  
 Phase front radius of curvature, 88,93  
 Phase screen, 25,649  
     multiple, 26,659-661  
     structure constant, 652  
     thin, 652  
 Photons, 6  
 Plane wave, 8,87  
     covariance function, 280,498  
     definition of, 8,87  
     double-pass, 557,568,576  
     mutual coherence function, 190-191  
     scintillation index, 264-265,336,340,497  
     structure function, 193  
 Pochhammer symbol, 220,756-757  
 Point ahead angle, 488,493  
 Point detector (receiver), 23,281  
 Point reflector (see Target, point)  
 Point spread function, 115,614-615  
     short term, 621  
 Pointing and tracking, 488  
     point ahead, 488,493

- Pointing error, 272,503
  - variance, 273-274,350,503
- Potential temperature, 62
- Power, 94
  - signal, 445
  - total average, 41
- Power spectral density (*see* Power spectrum)
- Power spectrum, 42-45
  - exponential, 68,203,308
  - Hill spectrum, 69-70
  - index of refraction, 66-71
  - Kolmogorov, 62,63,67
  - modified, 68-69
  - one-dimensional, 46
  - Tatarskii, 67
  - temporal (*see* Temporal spectrum)
  - three-dimensional, 47,139
  - two-dimensional, 47-48,140,148,164
  - von Kármán, 68
- Principle of reciprocity, 271
- Probability density function, 154,367
  - gamma distribution, 368,370,449
  - gamma-gamma distribution, 370,450,510, 691
  - gaussian distribution, 446-447
  - $K$  distribution, 368
  - lognormal distribution, 155-157,451,510
  - lognormal-Rician distribution, 369
  - modified Rician distribution, 154-155
  - negative exponential distribution, 368
  - Rayleigh distribution, 154
  - Rician distribution, 175
  - uniform distribution, 154
- Probability of
  - detection, 447,461-462
  - fade, 445,451-452,462,511,518
  - false alarm, 445,447,462
  - bit error-rate (BER), 446,463,469
- Propagation,
  - $ABCD$  optical system, 107-118
  - double-pass, 117
- Propagation paths,
  - folded, 117,543-544
  - reciprocal, 543-544
- Pulse,
  - arrival time, 745
  - coherence bandwidth, 744
  - duty cycle, 20,537,
  - Gaussian, 742
  - half-width, 742
  - length, 538-539
  - narrowband, 742
  - repetition frequency, 20,537
  - repetition interval, 20,537
  - spreading, 744
  - wideband, 742
- Q**
- Quantum efficiency, 445
- Quasi-frequency, 448,456
- R**
- Radar, 20
  - (*See also*, laser radar)
- Random phase screen (*see* Phase screen)
- Random process, 36
  - ergodic, 42
  - stationary, 38
  - wide-sense stationary, 39
  - with stationary increments, 40
- Random field, 45-49
  - homogeneous, 45
  - isotropic, 46
  - locally homogeneous, 48
- Range equation, 537-538
- Ray matrix (*see*  $ABCD$  ray matrix)
- Rayleigh
  - distribution, 154
  - range, 98
  - scattering, 11
- Receiver, 22-24
  - beam parameters, 94-96,99-101
  - coherent detection, 24
  - direct detection, 23
- Reciprocal path, 543-544
  - wave, 272
- Reduced wave equation, 85
- Reflection parameter, 589,696
- Reflector (*see* Target)
- Refractive index (*see* Index of refraction)
- Remote sensing, 21
- Resolution, 116
  - long-exposure, 616,619
  - maximum, 434,619
- Resolved target, 535
- Retroreflector,
  - (*see* Target, retroreflector)
- Reynolds number, 59
- Rice-Nakagami distribution (*see* Rician distribution)
- Rician distribution, 175
- Riemann-Stieltjes integral, 43,145,164
- Rytov approximation, 143-154,183-186,543, 649

- extended, 159-165,324-328
- first-order, 145-146
- second-order, 146-147
- spectral representations for, 145-147,399, 544-545
- statistical moments of, 147-150,401
- Rytov variance for,
  - beam wave, 35
  - phase screen, 653
  - plane wave, 140,189,263-264
  - spherical wave, 264
- S**
- Satellite
  - laser communication system, 17-19,478-479
  - orbits, 484-485
- Saturation regime, 140,323
- Scattering disk, 161,325
- Scintillation index, 261,299-301,405,406
  - double-pass, 547,561,565,581,584,591, 593,625
  - downlink channel, 495-496
  - focusing regime, 323
  - Gaussian-beam wave, 262-263,352,356
  - large-scale, 329
  - longitudinal component, 263,274-275,503
  - partially coherent beam, 682-684,685-688, 689-691,701-702
  - phase screen, 656-657
  - plane wave, 264-265,336,340
  - radial component, 263,349-350
  - saturation regime, 140,323
  - small-scale, 329
  - spherical wave, 264,342-343,345
  - temporal, 747
  - uplink channel, 503-504,506
- Seeing, 4,608,618
- Short exposure MTF, 620
- Short term beam spread, 205-206
- Signal current power, 445
- Signal-to-noise ratio (SNR), 445-446
  - mean, 460-461,466,627
- Slant paths, 207-210,299-301
- SLC models, 481
  - day, 482
  - night, 482
- Slew rate, 481
- Soft aperture (*see* Gaussian aperture)
- Source coherence parameter, 671
- Spatial
  - acquisition, 488
  - coherence radius (*see* Coherence radius)
  - diversity, 465
  - filters, 161-164,326-328
- Speckle
  - imaging, 609
  - reflection coefficient, 589,696
  - size, 673,677-678,697-700
- Speckle cells,
  - number of, 221,671,680,698-700
- Spectral representation, 145-147
  - first-order, 145-146
  - for *ABCD* system, 399-400
  - second-order, 146-147
- Spectrum (*See also*, Power spectrum),
  - electromagnetic, 6
  - temporal (*see* Temporal spectrum)
- Speed of light, 5
- Spherical wave, 8,87
  - covariance function, 280-281
  - definition of, 8,87
  - double-pass, 552,565,572,576
  - mutual coherence function, 191
  - scintillation index, 264,342-343,345
  - structure function, 195-196
- Spot size (*see* Beam radius)
- Stationary increments, 40
- Stationary random process, 38
  - wide-sense, 39
- Stratosphere, 10-11
- Strehl ratio, 407-408,501,623
- Stochastic process (*see* Random process)
- Strong fluctuations,
  - definition of, 140,230
- Structure constant,
  - Hufnagle-Valley model for, 481
  - index of refraction, 64-65
  - SLC day model for, 482
  - SLC night model for, 482
  - temperature, 63
  - velocity, 60
- Structure function, 40
  - definition of, 40
  - index of refraction, 64-71
  - log-amplitude, 193-194,196
  - phase, 193,195-196
  - temperature, 62
  - velocity, 60-61
  - wave (*see* Wave structure function)
- Structure parameter (*see* Structure constant)
- Super-Gaussian beam, 729
- System function, 151,739

**T**

- Target,
  - classification, 539
  - Lambert (diffuse), 539,589
  - plane mirror, 545,553,558,563,566,569
  - point, 575
  - retroreflector, 546,554,558,563,566,569
- Tatarskii spectrum, 67
- Taylor frozen turbulence hypothesis, 72,207
- Temperature fluctuations, 62-63
  - inner scale for, 63
  - spectrum for, 63
  - structure constant for, 63
  - structure function for, 62
- Temporal spectrum for
  - field, 207
  - irradiance, 282-288,365,421-424
  - phase, 296-298
- Temporal statistics, 72-73
- Thermosphere, 11
- Thin phase screen, 652
- Threshold detection, 445
- Threshold-to-noise ratio (TNR), 448
- Tilt, 272
- Time average, 41-42
- Tracking, 488,504
- Transceiver, 535
- Transmittance, 12
- Transmitter, 22
- Tropopause, 10
- Troposphere, 10
- Turbulence,
  - atmospheric boundary layer (ABL), 480
  - cascade theory, 59
  - clear-air, 480
  - dissipation range, 59
  - eddy, 59
  - homogeneous and isotropic, 60
  - inertial range, 59
  - inner scale, 59
  - Kolmogorov theory, 58-59
  - phase screen model, 648
  - outer scale, 59
- Two-frequency MCF, 740-742
- Two-thirds law, 60

**U**

- Uniform distribution, 154
- Units of measurements, 6
- Unit step function, 275
- Unresolved target, 535

**V**

- Variance for
  - angle-of-arrival fluctuations, 200
  - beam jitter, 272,503
  - beam wander, 201-205
  - log-amplitude fluctuations, 259,262
  - phase, 289-291
  - pointing error, 273-274,350
- Velocity fluctuations, 59-60
  - inner scale for, 59
  - spectrum, 62
  - structure constant, 60
  - structure function, 60,61
- Viscosity, 59
- Visual range, 12
- von Kármán spectrum, 68, 187

**W**

- Waist (*see* Beam waist)
- Wander (*see* Beam wander)
- Wave equation, 84
  - reduced, 85
  - stochastic, 137
- Wave front radius of curvature (*see* Phase front radius of curvature)
- Wave number, 85
- Wave structure function, 193-199
  - double-pass, 571-572
  - Gaussian-beam wave, 188,196-199
  - phase screen, 656
  - plane wave, 193-194
  - spherical wave, 195
- Wavelength, 85
- Weak fluctuations,
  - definition of, 140,230
- Wide-sense stationary, 39
- Wiener-Khintchine theorem, 44
- Wind model, 481

**Z**

- Zenith angle, 490
- Zernike
  - filter functions, 464,632-634
  - modes, 464,631
  - polynomials, 628,630
- Zero crossings (*see* Frequency of fade and Number of crossings)





**Larry C. Andrews** is a professor of mathematics at the University of Central Florida and an associate member of the College of Optics/CREOL. He is also an associate member of the Florida Space Institute (FSI). Previously, he held a faculty position at Tri-State University and was a staff mathematician with the Magnavox Company, antisubmarine warfare (ASW) operation. He received a doctoral degree in theoretical mechanics in 1970 from Michigan State University. Dr. Andrews has been an active researcher in optical wave propagation through random media for more than 25 years and is the author or co-author of ten textbooks on topics of differential equations, boundary value problems, special functions, integral transforms, wave propagation through random media, and mathematical techniques for engineers. Along

with wave propagation through random media, his research interests include special functions, random variables, atmospheric turbulence, and signal processing.



**Ronald L. Phillips** is Director of the Florida Space Institute (FSI) and a professor in the Department of Electrical and Computer Engineering at the University of Central Florida. Dr. Phillips is also a member of the Department of Mathematics and an associate member of the College of Optics/CREOL. He has held positions on the faculties at Arizona State University and the University of California, San Diego. He received a doctoral degree in Electrical Engineering in 1970 from Arizona State University. Dr. Phillips has been an active researcher in wave propagation through random media for more than 28 years. He was awarded a Senior NATO Postdoctoral Fellow

in 1977 and the American Society for Engineering Education 1983 Medal for outstanding contributions in research. Dr. Phillips is co-author of two textbooks on wave propagation through random media and mathematical techniques for engineers. In addition to optical wave propagation, his research interests include optical communications and imaging through atmospheric turbulence.