

Weekly Battery Maintenance Log

Date	Initial	Date	Initial	Date	Initial	Date	Initial

Charging Batteries

- 1. Remove cover on machine
- 2. Pull gray battery connectors apart
- Push the battery connector into the charger connector (separate battery charger) that leads to the batteries.

Battery Connector



When to Charge?

Charge batteries when . . .

- Machine is used for I hour or longer
- Battery Meter reads in red area

Filling Battery Cells

- Put on the goggles and gloves found in your store's Battery Care Kit
- Release the cover latches and lift up cover.
- Carefully pop off the battery caps (wearing protective gloves) and look into each battery cell to check the water level. If the water level in any battery cell is below the bottom of the filler tube, you will need to add water.
- Fill the pitcher (with pre-measured nozzle) with distilled or bottled water. DO NOT use tap water since it can corrode batteries.
- Hold the nozzle of the pitcher over the open battery cell. Using two fingers, pull up on the nozzle to release water into the battery cell(s). The water level should fill to the bottom of the filler tube. Do not overfill.
- Replace the battery caps securely on all batteries.
- 7. Put cover on & secure latches.

Safety Precautions



ALWAYS wear safety gloves and goggles when refilling batteries

- Check the fluid level in batteries after charging the batteries
- Keep sparks, flame, and smoking materials AWAY from batteries at all times
- Charge batteries only in well ventilated
- Avoid physical contact with batteries when connecting battery and charger connectors

Important!

Prior to charging activities, locate the eye wash station and ensure it is functional and easily accessible. Only designated associates should conduct the battery charging activities.

