

CS201- Lecture 8

IA32 Flow Control

RAOUL RIVAS


PORTLAND STATE UNIVERSITY

A solid green horizontal bar at the bottom of the slide.

Announcements

Processor State

- Information about currently executing program
 - Temporary data (**%rax**, ...)
 - Location of runtime stack (**%rsp**)
 - Location of current code control point (**%rip**, ...)
 - Status of recent tests (**CF**, **ZF**, **SF**, **OF**)



Condition Codes

- Single bit registers
 - **CF** Carry Flag (for unsigned) **SF** Sign Flag (for signed)
 - **ZF** Zero Flag **OF** Overflow Flag (for signed)
- Implicitly set (think of it as side effect) by arithmetic operations
Example: `addq Src, Dest` \leftrightarrow `t = a+b`
 - CF set** if carry out from most significant bit (unsigned overflow)
 - ZF set** if `t == 0`
 - SF set** if `t < 0` (as signed)
 - OF set** if two's-complement (signed) overflow
`(a>0 && b>0 && t<0) || (a<0 && b<0 && t>=0)`
- Not set by `leaq` instruction

Compare

- Explicit Setting by Compare Instruction
 - `cmpq Src2, Src1`
 - `cmpq b, a` like computing `a-b` without setting destination
 - **CF set** if carry out from most significant bit (used for unsigned comparisons)
 - **ZF set** if `a == b`
 - **SF set** if `(a-b) < 0` (as signed)
 - **OF set** if two's-complement (signed) overflow
`(a>0 && b<0 && (a-b)<0) || (a<0 && b>0 && (a-b)>0)`

Test

- Explicit Setting by Test instruction
 - `testq Src2, Src1`
 - `testq b, a` like computing `a&b` without setting destination
 - Sets condition codes based on value of *Src1* & *Src2*
 - Useful to have one of the operands be a mask
 - **ZF set** when `a&b == 0`
 - **SF set** when `a&b < 0`

Reading Condition Codes

- SetX Instructions

- Set low-order byte of destination to 0 or 1 based on combinations of condition codes
- Does not alter remaining 7 bytes

SetX	Condition	Description
sete	ZF	Equal / Zero
setne	~ZF	Not Equal / Not Zero
sets	SF	Negative
setns	~SF	Nonnegative
setg	~ (SF^OF) & ~ZF	Greater (Signed)
setge	~ (SF^OF)	Greater or Equal (Signed)
setl	(SF^OF)	Less (Signed)
setle	(SF^OF) ZF	Less or Equal (Signed)
seta	~CF & ~ZF	Above (unsigned)
setb	CF	Below (unsigned)

Reading Condition Codes

- SetX Instructions:
 - Set single byte based on combination of condition codes
- One of addressable byte registers
 - Does not alter remaining bytes
 - Typically use **movzbl** to finish job
 - 32-bit instructions also set upper 32 bits to 0

```
int gt (long x, long y)
{
    return x > y;
}
```

```
cmpq    %rsi, %rdi    # Compare x:y
setg     %al          # Set when >
movzbl   %al, %eax    # Zero rest of %rax
ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Jump

- jX Instructions
 - Jump to different part of code depending on condition codes

jX	Condition	Description
jmp	1	Unconditional
je	ZF	Equal / Zero
jne	$\sim ZF$	Not Equal / Not Zero
js	SF	Negative
jns	$\sim SF$	Nonnegative
jg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
jge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
jl	$(SF \wedge OF)$	Less (Signed)
jle	$(SF \wedge OF) \ \ ZF$	Less or Equal (Signed)
ja	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
jb	CF	Below (unsigned)



C Goto Statement

- C allows **goto** statement
- Jump to position designated by label

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j
(long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

C Goto Statement



Conditional Branches

```
long absdiff_j
(long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

```
absdiff:
    cmpq    %rsi, %rdi    # x:y
    jle     .L4
    movq    %rdi, %rax
    subq    %rsi, %rax
    ret
.L4:       # x <= y
    movq    %rsi, %rax
    subq    %rdi, %rax
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branches Recipe

C Code

```
val = Test ? Then_Expr : Else_Expr;
```

```
val = x>y ? x-y : y-x;
```

Goto Version

```
ntest = !Test;  
if (ntest) goto Else;  
val = Then_Expr;  
goto Done;  
Else:  
    val = Else_Expr;  
Done:  
    . . .
```

- Create separate code regions for then & else expressions
- Execute appropriate one

Conditional Move

■ Conditional Move Instructions (CMOVxx)

- Instruction supports:
if (Test) Dest \leftarrow Src
- Supported in post-1995 x86 processors
- GCC tries to use them
 - But, only when known to be safe

■ Why?

- Branches are very disruptive to instruction flow through pipelines
 - Modern Processors try to Predict the outcome of the Branch (Taken or Not Taken)
 - Easy for Loops. Hard for If/Else
- Conditional moves do not require control transfer

C Code

```
val = Test  
      ? Then_Expr  
      : Else_Expr;
```

Goto Version

```
result = Then_Expr ;  
eval = Else_Expr ;  
nt = !Test ;  
if (nt) result = eval ;  
return result ;
```

Conditional Move Example

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

absdiff:

```
movq    %rdi, %rax    # x
subq    %rsi, %rax    # result = x-y
movq    %rsi, %rdx
subq    %rdi, %rdx    # eval = y-x
cmpq    %rsi, %rdi    # x:y
cmovle  %rdx, %rax    # if <=, result = eval
ret
```

Do-While Loop

C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
    loop:
        result += x & 0x1;
        x >>= 1;
        if(x) goto loop;
    return result;
}
```

- Count number of 1's in argument x ("popcount")
- Use conditional branch to either continue looping or to exit loop

Do-While Loop Translation

C Code

```
do  
    Body  
while (Test) ;
```

Goto Version

```
loop:  
    Body  
    if (Test)  
        goto loop
```

Do-While Loop

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

```
        movl    $0, %eax    # result = 0
.L2:                                # loop:
        movq    %rdi, %rdx
        andl    $1, %edx    # t = x & 0x1
        addq    %rdx, %rax  # result += t
        shrq    %rdi        # x >>= 1
        jne     .L2        # if (x) goto loop
        rep; ret
```

While Translation

- “Jump-to-middle” translation
- Used with `-Og`

While version

```
while (Test)  
    Body
```



Goto Version

```
    goto test;  
loop:  
    Body  
test:  
    if (Test)  
        goto loop;  
done:
```

While Translation

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```

Optimized While Translation

While version

```
while (Test)  
    Body
```



Do-While Version

```
if (!Test)  
    goto done;  
do  
    Body  
    while (Test);  
done:
```



- “Do-while” conversion
- Used with **-O1**

Goto Version

```
if (!Test)  
    goto done;  
loop:  
    Body  
    if (Test)  
        goto loop;  
done:
```

For Loop

General Form

```
for (Init; Test; Update )  
    Body
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
#define WSIZE 8*sizeof(int)  
long pcount_for  
    (unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    for (i = 0; i < WSIZE; i++)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
    }  
    return result;  
}
```

For to While Conversion

For Version

```
for (Init; Test; Update )  
    Body
```



While Version

```
Init;  
while (Test) {  
    Body  
    Update;  
}
```

For to While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
long pcount_for_while  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    i = 0;  
    while (i < WSIZE)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
        i++;  
    }  
    return result;  
}
```


Switch Statement

- Multiple case labels
 - Here: 5 & 6
- Fall through cases
 - Here: 2
- Missing cases
 - Here: 4

```
long switch_eg
(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        case 1:
            w = y*z;
            break;
        case 2:
            w = y/z;
            /* Fall Through */
        case 3:
            w += z;
            break;
        case 5:
        case 6:
            w -= z;
            break;
        default:
            w = 2;
    }
    return w;
}
```

Switch to If/Else Conversion

- Convert each case to an If/Else

```
long switch_eg
(long x, long y, long z)
{
    long w = 1;
    If (x==1) w = y*z;
    Else If (x==2) w = y/z;
        ...

    Else w=2;

    return w;
}
```

```
long switch_eg
(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        case 1:
            w = y*z;
            break;
        case 2:
            w = y/z;
            /* Fall Through */
            ...

    default:
        w = 2;
    }
    return w;
}
```

Jump Table Optimization


Switch Form

```
switch(x) {  
  case val_0:  
    Block 0  
  case val_1:  
    Block 1  
    . . .  
  case val_n-1:  
    Block n-1  
}
```

Translation

```
goto *JTab[x];
```

Jump Table



Jump Targets

Targ0:

Code Block 0

Targ1:

Code Block 1

Targ2:

Code Block 2

•
•
•

Targn-1:

Code Block n-1


Pointer to Functions!

Switch Optimization Example

Jump table

```
.section .rodata
.align 8
.L4:
.quad .L8 # x = 0
.quad .L3 # x = 1
.quad .L5 # x = 2
.quad .L9 # x = 3
.quad .L8 # x = 4
.quad .L7 # x = 5
.quad .L7 # x = 6
```

```
switch(x) {
case 1:      // .L3
    w = y*z;
    break;
case 2:      // .L5
    w = y/z;
    /* Fall Through */
case 3:      // .L9
    w += z;
    break;
case 5:
case 6:      // .L7
    w -= z;
    break;
default:    // .L8
    w = 2;
}
```



Switch Optimization Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Jump table

```
.section      .rodata
    .align 8
.L4:
    .quad     .L8    # x = 0
    .quad     .L3    # x = 1
    .quad     .L5    # x = 2
    .quad     .L9    # x = 3
    .quad     .L8    # x = 4
    .quad     .L7    # x = 5
    .quad     .L7    # x = 6
```

Setup:

```
switch_eg:
    movq      %rdx, %rcx
    cmpq      $6, %rdi      # x:6
    ja       .L8            # Use default
    jmp       *.L4(,%rdi,8)  # goto *JTab[x]
```


**Indirect
jump**

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Switch Optimization Example

- Table Structure

- Each target requires 8 bytes
- Base address at `.L4`

- Jumping

- **Direct:** `jmp .L8`
- Jump target is denoted by label `.L8`
- **Indirect:** `jmp *.L4(, %rdi, 8)`
- Start of jump table: `.L4`
- Must scale by factor of 8 (addresses are 8 bytes)
- Fetch target from effective Address `.L4 + x*8`
 - Only for $0 \leq x \leq 6$

Jump table

```
.section      .rodata
    .align 8
.L4:
    .quad     .L8    # x = 0
    .quad     .L3    # x = 1
    .quad     .L5    # x = 2
    .quad     .L9    # x = 3
    .quad     .L8    # x = 4
    .quad     .L7    # x = 5
    .quad     .L7    # x = 6
```

Conclusion

- Most instruction modify condition codes
 - Side effect sometimes useful: Overflow check, avoid comparisons
- Compare and Test instruction used to set condition codes explicitly
- JMP – Unconditional Jump
- Conditional Jumps based on codes
- Structured programming is translated to assembly using conditional jumps and labels
- Large switches are implemented using jump tables
 - Indirect Jump