







HOME ABOUT XNOVA PRODUCTS DEALERS TEAM SPARE PARTS

,0

CONTACT

NEW! Xnova 2208 V2N LIGHTNING motor series. 2000Kv_1500kv_1700kv_1900kv_2300kv_2500kv and 2700kv

- Your choice for mindblowing racing performance
- High performance and finest CNC quality
- Ultimate efficiency
- Low cogging torque and smooth running
- Precisely balanced and fully tested

| Xnova Lightning 2208 V2 Data List | | | | | | | |
|-----------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|--|
| Xnova Lightning V2N | L2208-1500 V2 | L2208-1700 V2 | L2208-1900 V2 | L2208-2300 V2 | L2208-2500 V2 | L2208-2700 V2 | |
| RPM/Volt | 1500 | 1700 | 1900 | 2300 | 2500 | 2700 | |
| No-load Current (@10v) | 1. 2A | 1. 3A | 1. 6A | 2. 1A | 2, 3A | 2. 6A | |
| Weight(g) with 20cm wires | 36. 5g | 37. 3g | 36, 8g | 36, 8g | 36. 6g | 36. 6g | |
| Battery | 6S | 6S | 5-6S | 4-5S | 4S | 4S | |
| Resistance | 0. 078 Ω | 0. 066 Ω | 0. 058 Ω | 0. 045 Ω | 0. 040 Ω | 0. 036 Ω | |

| Xnova Lightning 2208-2 Xnova Lightning V2N | L2208-2000 V2 |
|-----------------------------------------------|---------------|
| | LZZ00-Z000 VZ |
| RPM/Volt | 2000 |
| No-load Current (@10v) | 1.7A |
| Weight(g) with 20cm wires | 37.7g |
| Battery | 5-6S |
| Resistance | 0. 055Ω |







| XNOVA Lightning V2N 2208 1700KV Propeller Datas | | | | | | | | |
|-------------------------------------------------|-----------|------------------|----------|------------|-----------|-----------|--|--|
| Motor | | L2208 V2N 1700KV | | | | | | |
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | | |
| | | 50% | 12.6 | 750 | 279.7 | 2.68 | | |
| | | | 15.4 | 880 | 341.9 | 2.57 | | |
| GF51466 | 22.2 | 70% | 18.1 | 993 | 401.8 | 2.47 | | |
| GI 31400 | 22.2 | 80% | 22.3 | 1185 | 495.1 | 2.39 | | |
| l . | l | 90% | 29.1 | 1450 | 646.0 | 2.24 | | |
| | | 100% | 31.6 | 1542 | 701.5 | 2.20 | | |


| | XNOVA Lightning V2N 2208 1900KV Propeller Datas | | | | | | | | |
|---|-------------------------------------------------|-----------|------------------|----------|------------|-----------|-----------|--|--|
| I | Motor | | L2208 V2N 1900KV | | | | | | |
| | Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | | |
| Γ | | | 50% | 16.5 | 880 | 366.3 | 2.40 | | |
| ı | | | 60% | 20.4 | 1027 | 452.9 | 2.27 | | |
| ı | GF51466 | 22.2 | 70% | 24.0 | 1170 | 532.8 | 2.20 | | |
| ı | GI 31400 | 22.2 | 80% | 28.5 | 1372 | 632.7 | 2.17 | | |
| 1 | | l | 90% | 37.7 | 1678 | 836.9 | 2.00 | | |
| L | | | 100% | 41.6 | 1816 | 923.5 | 1.97 | | |

| XNOVA Lightning V2N 2208 2300KV Propeller Datas | | | | | | | | |
|-------------------------------------------------|-----------|------------------|----------|------------|-----------|-----------|--|--|
| Motor | | L2208 V2N 2300KV | | | | | | |
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | | |
| | | 50% | 20.7 | 875 | 383.0 | 2.28 | | |
| | | 60% | 25.3 | 1025 | 468.1 | 2.19 | | |
| GF51466 | 18.5 | 70% | 29.5 | 1160 | 545.8 | 2.13 | | |
| GF51400 | 10.5 | 80% | 35.5 | 1360 | 656.8 | 2.07 | | |
| | | 90% | 45.5 | 1635 | 841.8 | 1.94 | | |
| | | 100% | 50.5 | 1773 | 934.3 | 1.90 | | |

| XNOVA Lightning V2N 2208 2500KV Propeller Datas | | | | | | | | |
|-------------------------------------------------|-----------|------------------|----------|------------|-----------|-----------|--|--|
| Motor | | L2208 V2N 2500KV | | | | | | |
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | | |
| | | 50% | 18.5 | 692 | 273.8 | 2.53 | | |
| | | 60% | 22.5 | 815 | 333.0 | 2.45 | | |
| GF51466 | 14.8 | 70% | 26.0 | 915 | 384.8 | 2.38 | | |
| GF51466 | 14.0 | 80% | 30.6 | 1050 | 452.9 | 2.32 | | |
| | | 90% | 39.2 | 1278 | 580.2 | 2.20 | | |
| | | 100% | 42.2 | 1350 | 624.6 | 2.16 | | |

| XNOVA Lightning V2N 2208 2700KV Propeller Datas | | | | | | | | |
|-------------------------------------------------|-----------|------------------|----------|------------|-----------|-----------|--|--|
| Motor | | L2208 V2N 2700KV | | | | | | |
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | | |
| | | 50% | 21.7 | 743 | 321.2 | 2.31 | | |
| | | 60% | 26.5 | 860 | 392.2 | 2.19 | | |
| GF51466 | 14.8 | 70% | 30.4 | 973 | 449.9 | 2.16 | | |
| GI 31400 | 14.0 | 80% | 36.0 | 1135 | 532.8 | 2.13 | | |
| | | 90% | 45.0 | 1350 | 666.0 | 2.03 | | |
| | l | 100% | 49.1 | 1450 | 726.7 | 2.00 | | |

| XNOVA Lightning V2N 2208 1500KV Propeller Datas | | | | | | | |
|-------------------------------------------------|-----------|--------------------------|----------------------------------|----------------------------|-----------------------------------------|----------------------------------|--|
| Motor | | L2208 V2N 1500KV | | | | | |
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) | |
| KINGKONG 6*4 2Blades | 22. 2 | 50% 60% 70% 80% | 10. 9 13. 5 16. 2 26. 9 | 770 915 1055 1298 | 241. 98 299. 7 359. 64 597. 18 | 3. 18 3. 05 2. 93 2. 17 | |
| | | 90% | 27. 1 28. 6 | 1580 1700 | 601. 62 634. 92 | 2. 17 2. 63 2. 68 | |



| Motor | | L2208 V2N 2000KV | | | | |
|-----------|-----------|------------------|----------|------------|-----------|--------------|
| Prop | Volts (V) | Throttle | Amps (A) | Thrust (g) | Watts (w) | Eff (g/w) |
| | | 50% | 18. 4 | 899 | 408. 48 | 2. 20 |
| | | 60% | 22.5 | 1055 | 499.5 | 2.11 |
| CDE 1 ACC | 22, 2 | 70% | 27.0 | 1200 | 599.4 | 2.00 |
| GF51466 | 22. 2 | 80% | 31.9 | 1405 | 708. 18 | 1.98 |
| | | 90% | 41.3 | 1690 | 916.86 | 1.84 |
| | | 100% | 46, 4 | 1803 | 1030, 08 | 1.75 |

| | Post | Share | |
|---------|------|-------|---------|
| | | | |
| ← LIGHT | | | Xnova → |

XNOVA MOTORS HIGH PERFORMANCE BRUSHLESS MOTORS

ELECTRIC BRUSHLESS MOTORS FOR RC HELICOPTERS - 3D, F3C, SCALE, MULTICOPTER AND QUADCOPTER.