

# Data Structures, Modern Operators & Strings

🎓 **CS Perspective:** This section covers JavaScript's built-in **data structures** (arrays, objects, Maps, Sets) and **pattern matching** through destructuring. Destructuring is a form of **structural pattern matching** common in functional languages like ML and Haskell. The spread/rest operators demonstrate **variadic functions** (functions accepting variable arguments). Maps provide O(1) average-case lookup (hash table implementation), while Sets enforce **uniqueness constraints**. Short-circuit evaluation (**&&**, **||**, **??**) relates to **lazy evaluation**—operands are only evaluated when necessary, which has implications for side effects and performance.

## 📌 Destructuring Arrays

Extract values from arrays into variables:

```
const arr = [2, 3, 4];

// Without destructuring
const a = arr[0];
const b = arr[1];

// With destructuring
const [x, y, z] = arr;
console.log(x, y, z); // 2, 3, 4
```

## Skip Elements

```
const [first, , third] = [1, 2, 3];
console.log(first, third); // 1, 3
```

## Swap Variables

```
let [main, secondary] = ['Pizza', 'Pasta'];
[main, secondary] = [secondary, main];
// main = 'Pasta', secondary = 'Pizza'
```

## Nested Destructuring

```
const nested = [2, 4, [5, 6]];
const [i, , [j, k]] = nested;
console.log(i, j, k); // 2, 5, 6
```

## Default Values

```
const [p = 1, q = 1, r = 1] = [8, 9];  
console.log(p, q, r); // 8, 9, 1
```

## Destructuring Objects

```
const restaurant = {  
  name: 'Italiano',  
  categories: ['Italian', 'Pizzeria'],  
  openingHours: { thu: { open: 12, close: 22 } }  
};  
  
// Basic  
const { name, categories } = restaurant;  
  
// Rename variables  
const { name: restaurantName, categories: tags } = restaurant;  
  
// Default values  
const { menu = [], starterMenu: starters = [] } = restaurant;  
  
// Nested objects  
const { openingHours: { thu: { open, close } } } = restaurant;
```

## Mutating Variables

```
let a = 111;  
let b = 999;  
const obj = { a: 23, b: 7 };  
  
// Must wrap in parentheses  
({ a, b } = obj);  
console.log(a, b); // 23, 7
```

## Spread Operator (...)

Expands an iterable into individual elements.

### Arrays

```
const arr = [7, 8, 9];  
const newArr = [1, 2, ...arr]; // [1, 2, 7, 8, 9]
```

```
// Copy array
const arrCopy = [...arr];

// Merge arrays
const merged = [...arr1, ...arr2];
```

## Strings

```
const str = 'Jonas';
const letters = [...str]; // ['J', 'o', 'n', 'a', 's']
```

## Objects (ES2018)

```
const newObj = { ...oldObj, newProp: 'value' };
```

## Function Arguments

```
const add = (a, b, c) => a + b + c;
const nums = [1, 2, 3];
add(...nums); // 6
```

---

## Rest Pattern (...)

Collects multiple elements into an array. **Opposite of spread!**

```
// SPREAD: Right side of =
const arr = [1, 2, ...[3, 4]];

// REST: Left side of =
const [a, b, ...others] = [1, 2, 3, 4, 5];
console.log(others); // [3, 4, 5]
```

## In Objects

```
const { sat, ...weekdays } = openingHours;
```

## Function Parameters (Rest Parameters)

```
const add = function(...numbers) {  
  let sum = 0;  
  for (let i = 0; i < numbers.length; i++) {  
    sum += numbers[i];  
  }  
  return sum;  
};  
  
add(2, 3);           // 5  
add(5, 3, 7, 2);    // 17
```

---

## Short Circuiting (&& and ||)

OR (||) - Returns first truthy value

```
console.log(3 || 'Jonas');    // 3  
console.log('' || 'Jonas');   // 'Jonas'  
console.log(undefined || null); // null  
console.log(undefined || 0 || '' || 'Hello'); // 'Hello'  
  
// Use for default values  
const guests = numGuests || 10;
```

AND (&&) - Returns first falsy value

```
console.log(0 && 'Jonas');    // 0  
console.log(7 && 'Jonas');    // 'Jonas'  
  
// Use to execute code conditionally  
restaurant.orderPizza && restaurant.orderPizza('mushrooms');
```

---

## Nullish Coalescing Operator (??)

Only considers `null` and `undefined` as falsy (NOT `0` or `''`).

```
restaurant.numGuests = 0;  
  
const guests1 = restaurant.numGuests || 10; // 10 ❌  
const guests2 = restaurant.numGuests ?? 10; // 0 ✅
```

---

## Logical Assignment Operators

```
const rest1 = { numGuests: 0 };
const rest2 = { owner: 'Giovanni' };

// OR assignment (||=)
rest1.numGuests ||= 10; // 10 (0 is falsy)
rest2.numGuests ||= 10; // 10

// Nullish assignment (??=)
rest1.numGuests ??= 10; // 0 (0 is not null/undefined)

// AND assignment (&&=)
rest2.owner &&= '<ANONYMOUS>'; // '<ANONYMOUS>'
rest1.owner &&= '<ANONYMOUS>'; // undefined (no change)
```

---

## Optional Chaining (?.)

Returns `undefined` if property doesn't exist instead of error.

```
// Without optional chaining
if (restaurant.openingHours && restaurant.openingHours.mon) {
  console.log(restaurant.openingHours.mon.open);
}

// With optional chaining
console.log(restaurant.openingHours?.mon?.open); // undefined

// With methods
console.log(restaurant.order?.(0, 1) ?? 'Method not found');

// With arrays
const users = [{ name: 'Jonas' }];
console.log(users[0]?.name ?? 'User not found');
```

---

## Looping Objects

```
const openingHours = {
  thu: { open: 12, close: 22 },
  fri: { open: 11, close: 23 }
};

// Keys
const days = Object.keys(openingHours); // ['thu', 'fri']

// Values
const hours = Object.values(openingHours);
```

```
// Entries (key-value pairs)
const entries = Object.entries(openingHours);

for (const [day, { open, close }] of entries) {
  console.log(`On ${day} we open at ${open}`);
}
```

---

## The for-of Loop

```
const menu = ['Pizza', 'Pasta', 'Risotto'];

for (const item of menu) {
  console.log(item);
}

// With index
for (const [index, item] of menu.entries()) {
  console.log(`${index + 1}: ${item}`);
}
```

---

## Sets

Collection of **unique** values.

```
const ordersSet = new Set(['Pasta', 'Pizza', 'Pizza', 'Risotto']);
console.log(ordersSet); // Set(3) {'Pasta', 'Pizza', 'Risotto'}
```

### Set Methods

```
ordersSet.size;           // 3
ordersSet.has('Pizza');   // true
ordersSet.add('Bread');
ordersSet.delete('Risotto');
ordersSet.clear();
```

### Convert Array to Unique Values

```
const staff = ['Waiter', 'Chef', 'Waiter', 'Manager'];
const uniqueStaff = [...new Set(staff)];
// ['Waiter', 'Chef', 'Manager']
```

## Set Operations (ES2024)

```
const setA = new Set([1, 2, 3]);
const setB = new Set([2, 3, 4]);

setA.intersection(setB);      // Set {2, 3}
setA.union(setB);             // Set {1, 2, 3, 4}
setA.difference(setB);        // Set {1}
setA.symmetricDifference(setB); // Set {1, 4}
setA.isDisjointFrom(setB);    // false
```

---

## Maps

Key-value pairs where keys can be **any type**.

```
const rest = new Map();

// Set values (chainable)
rest.set('name', 'Italiano')
  .set(1, 'Firenze')
  .set(true, 'We are open');

// Get values
rest.get('name'); // 'Italiano'
rest.get(true);   // 'We are open'

// Other methods
rest.has('name'); // true
rest.delete(1);
rest.size;        // 2
rest.clear();
```

## Create Map from Array

```
const question = new Map([
  ['question', 'Best language?'],
  [1, 'C'],
  [2, 'Java'],
  [3, 'JavaScript'],
  ['correct', 3],
  [true, 'Correct! 🎉'],
  [false, 'Try again!']
]);
```

## Convert Object to Map

```
const hoursMap = new Map(Object.entries(openingHours));
```

## Iterate Map

```
for (const [key, value] of question) {  
  if (typeof key === 'number') {  
    console.log(`Answer ${key}: ${value}`);  
  }  
}
```

## When to Use What

Data Structure	Use When
<b>Arrays</b>	Ordered list, may have duplicates
<b>Sets</b>	Unique values, high-performance lookup
<b>Objects</b>	"Traditional" key-value, methods, JSON
<b>Maps</b>	Keys can be any type, better performance

## Strings - Part 1

```
const airline = 'TAP Air Portugal';  
const plane = 'A320';  
  
// Access characters  
plane[0];           // 'A'  
'B737'[0];         // 'B'  
  
// Length  
airline.length;     // 16  
  
// Find position  
airline.indexOf('r'); // 6 (first)  
airline.lastIndexOf('r'); // 10 (last)  
airline.indexOf('Portugal'); // 8  
  
// Extract parts  
airline.slice(4);    // 'Air Portugal'  
airline.slice(4, 7); // 'Air'  
airline.slice(-2);   // 'al'  
airline.slice(1, -1); // 'AP Air Portuga'  
  
// First/last word
```



```
airline.slice(0, airline.indexOf(' ')); // 'TAP'  
airline.slice(airline.lastIndexOf(' ') + 1); // 'Portugal'
```

## 📌 Strings - Part 2

```
const airline = 'TAP Air Portugal';  
  
// Case  
airline.toLowerCase(); // 'tap air portugal'  
airline.toUpperCase(); // 'TAP AIR PORTUGAL'  
  
// Trim whitespace  
' Hello '.trim(); // 'Hello'  
' Hello '.trimStart(); // 'Hello '  
' Hello '.trimEnd(); // ' Hello'  
  
// Replace  
'288,97€'.replace('€', '$').replace(',', '.'); // '288.97$'  
'door door'.replace('door', 'gate'); // 'gate door'  
'door door'.replaceAll('door', 'gate'); // 'gate gate'  
  
// Booleans  
airline.includes('Air'); // true  
airline.startsWith('TAP'); // true  
airline.endsWith('Portugal'); // true
```

## 📌 Strings - Part 3

```
// Split  
'a+very+nice+string'.split('+'); // ['a', 'very', 'nice', 'string']  
'Jonas Schmedtmann'.split(' '); // ['Jonas', 'Schmedtmann']  
  
// Join  
['Mr.', 'Jonas', 'SCHMEDTMANN'].join(' '); // 'Mr. Jonas SCHMEDTMANN'  
  
// Padding  
'Jonas'.padStart(10, '+'); // '+++++Jonas'  
'Jonas'.padEnd(10, '+'); // 'Jonas+++++'  
  
// Repeat  
'Bad weather! '.repeat(3); // 'Bad weather! Bad weather! Bad weather! '
```

### Mask Credit Card

```
const maskCard = function(number) {  
  const str = number + '';  
  const last = str.slice(-4);  
  return last.padStart(str.length, '*');  
};  
  
maskCard(43378463864647384); // '*****7384'
```



## Quick Reference Cheatsheet

```
// Destructuring  
const [a, b] = [1, 2];  
const { name, age } = person;  
  
// Spread (expand)  
const newArr = [...arr1, ...arr2];  
const newObj = { ...obj, newProp: 'value' };  
  
// Rest (collect)  
const [first, ...rest] = arr;  
function fn(...args) {}  
  
// Short-circuit  
value || defaultValue; // OR  
condition && action(); // AND  
value ?? defaultValue; // Nullish  
  
// Optional chaining  
obj?.prop?.nested;  
  
// Sets  
new Set([1, 2, 2, 3]); // {1, 2, 3}  
  
// Maps  
const map = new Map([['key', 'value']]);  
map.set('key', 'value');  
map.get('key');  
  
// Strings  
str.slice(start, end);  
str.split(separator);  
arr.join(separator);  
str.padStart(length, char);  
str.includes(substring);  
str.replace(old, new);
```



## Exam Tips

1. **Spread** = expand (right side), **Rest** = collect (left side)
2. `||` returns first truthy, `&&` returns first falsy
3. `??` only treats `null/undefined` as falsy (not `0` or `' '`)
4. **Optional chaining** `?.` prevents errors on undefined properties
5. **Sets** are for unique values, **Maps** for any-type keys
6. `Object.entries()` converts object to array for iteration
7. **Strings are immutable** - methods return new strings
8. `split()` → array, `join()` → string
9. Use `for...of` for iterating arrays/strings
10. **Template literals** use backticks and `${}` for interpolation