# Filtrado Mediana

#### swap

- $\blacksquare$  m = |w|
- $T_{swap}(m) = c_1 + c_2 + c_3$
- $T_{swap}(m) \in O(1)$

### insert

- $\mathbf{m} = |w|$
- $T_{insert}(m) = c_1' + c_2' \cdot (m+1) + c_3' \cdot m + c_4' \cdot m$
- $T_{insert}(m) \in O(m)$

## insertionSort

- $\blacksquare m = |w|$
- $T_{insertSort}(m) = c_1'' + c_2'' \cdot (m+1) + c_3'' \cdot m^2 + c_4'' \cdot m + c_5''$
- $T_{insertSort}(m) \in O(m^2)$

## filtradoMediana

```
1
 _{\rm 1} void filtradoMediana(senial &s, int R, int prof, int freq) {
         vector < int > w((2 * R) + 1, 0);
                                                                                                                                          1
         vector<int> wOrdenada((2 * R) + 1);
 4
                                                                                                                                          1
         int j = 2 * R;
         while (j \ge 0) {
                                                                                                                                      m+1
 6
               w[j] = s[j];
                                                                                                                                         \mathbf{m}
               j--;
                                                                                                                                         \mathbf{m}
9
10
         int i = R;
                                                                                                                                         1
11
         int fin = s.size() - R;
while (i < fin) {</pre>
12
                                                                                                                                          1
13
                                                                                                                                      n-m+1
              if (i != R) {
   w[i - R - 1] = s[i + R];
14
                                                                                                                                       n-m
15
16
                                                                                                                                       n-m-1
               wOrdenada = insertionSort(w);
17
                                                                                                                         c_{12}^{\prime\prime\prime} \cdot m \\ c_{13}^{\prime\prime\prime} \\ c_{14}^{\prime\prime\prime}
               s[i] = wOrdenada[R];
18
                                                                                                                                        n-m
19
               i++;
                                                                                                                                        n-m
         }
20
                                                                                                                                        n-m
```

- $m = (2 * R) + 1 \wedge n = |s|$
- $= T_{filtradoMediana}(m) = c_1^{\prime\prime\prime} + c_2^{\prime\prime\prime} + c_3^{\prime\prime\prime} + c_4^{\prime\prime\prime} \cdot (m+1) + c_5^{\prime\prime\prime} \cdot m + c_6^{\prime\prime\prime} \cdot m + c_7^{\prime\prime\prime} + c_8^{\prime\prime\prime} + c_9^{\prime\prime\prime} \cdot (n-m+1) + c_{10}^{\prime\prime\prime} \cdot (n-m) + c_{11}^{\prime\prime\prime} \cdot (n-m-1) + c_{12}^{\prime\prime\prime} \cdot m \cdot (n-m) + c_{13}^{\prime\prime\prime} \cdot (n-m)$
- $T_{filtradoMediana}(m) \in O(m \cdot (n-m))$