

Evidencias CSS Retos

CSS Diner

Share

Facebook

Twitter

Select the plates

Help, I'm stuck!



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex -> "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate />
4 </div>
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 1 of 32

→

<

>

≡

Type Selector

Select elements by their type

A

Selects all elements of type **A**. Type refers to the type of tag, so `<div>`, `<p>` and `<a>` are all different element types.

Examples

`<div>` selects all `<div>` elements.

`<p>` selects all `<p>` elements.

CSS Diner

Share

Facebook

Twitter

Select the bento boxes

Help, I'm stuck!



CSS Editor

style.css

HTML Viewer

table.html

```
1 bento
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex -> "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento />
3   <plate />
4   <bento />
5 </div>
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 2 of 32

→

<

>

≡

Type Selector

Select elements by their type

A

Selects all elements of type **A**. Type refers to the type of tag, so `<div>`, `<p>` and `<a>` are all different element types.

Examples

`<div>` selects all `<div>` elements.

`<p>` selects all `<p>` elements.

CSS Diner

Share

Facebook

Twitter

Select the fancy plate

Help, I'm stuck!

CSS Editor

style.css

HTML Viewer

table.html

```
1 plate#fancy
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate id="fancy" />
3   <plate />
4   <plate />
5 </div>
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate id="fancy" />
3   <plate />
4   <plate />
5 </div>
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 3 of 32

< > ≡

ID Selector

Select elements with an ID

#id

Selects the element with a specific ID. You can also combine the ID selector with the type selector.

Examples

#cool selects any element with ID="cool"

ul#list selects any ul with ID="list"

CSS Diner

Share

Facebook

Twitter

Select the apple on the plate

CSS Editor

style.css

HTML Viewer

table.html

```
1 plate.apple
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate />
4   <apple />
5   <plate />
6   <apple />
7 </div>
8
9
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate />
4   <apple />
5   <plate />
6   <apple />
7 </div>
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 4 of 32

< > ≡

Descendant Selector

Select an element inside another element

A B

Selects all B inside of A. B is called a descendant because it is inside of another element.

Examples

p strong selects all strong elements that are inside of any p.

#fancy span selects any span elements that are inside of the element with ID="fancy"

Made by @flukeout - come say hi!

Have feedback or questions? Please let us know on the GitHub repo.

CSS Diner

Share

Facebook

Twitter

Select the pickle on the fancy plate



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate#fancy pickle
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex. + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <tr>
3     <td>orange />
4   </td>
5   <td><div class="fancy">
6     <div>
7       <div>
8         <div>
9           <div>
10            </div>
11          </div>
12        </div>
13      </div>
14    </td>
15  </tr>
16 </div>
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Level 5 of 32

Combine the Descendant & ID Selectors

#id A

You can combine any selector with the descendant selector.

Examples

#cool span selects all elements that are inside of elements with <div>#cool</div>

CSS Diner

Share

Facebook

Twitter

Select the small apples



CSS Editor

style.css

HTML Viewer

table.html

```
1 .small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex. + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <tr>
3     <td><div class="small">
4       <div>
5         <div>
6           <div>
7             <div>
8               <div>
9                 <div>
10                  </div>
11                </div>
12              </div>
13            </div>
14          </div>
15        </div>
16      </td>
17    </tr>
18 </div>
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Level 6 of 32

Class Selector

Select elements by their class

.classname

The class selector selects all elements with that class attribute. Elements can only have one ID, but many classes.

Examples

.heisto selects all elements with <div>class="heisto"</div>

CSS Diner

Share

Level 17 of 32

Select the small apple and the pickle



CSS Editor

```
1 :last-child.small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: #5 for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

style.css

```
1 (div class="table">
2   <plate id="fancy">
3     <apple class="small" />
4   </plate>
5   <plate />
6   <plate>
7     <orange class="small" />
8     <orange />
9   </plate>
10  <pickle class="small" />
11 </div>
12
13
14
15
16
17
18
19
20
```

HTML Viewer

table.html

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

Level 17 of 32

Last Child Pseudo-selector

Select the last element inside of another element

`:last-child`

You can use this selector to select an element that is the last child element inside of another element.

Pro Tip — In cases where there is only one element that element counts as the first-child, only-child and last-child

Examples

`:last-child` selects all last-child elements.

`:span:last-child` selects all last-child `span` elements.

`ul li:last-child` selects the last `li` elements inside of any `ul`.

CSS Diner

Share

Level 7 of 32

Select the small oranges



CSS Editor

```
1 orange.small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: #5 for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

style.css

```
1 (div class="table">
2   <apple />
3   <apple class="small" />
4   <bento>
5     <orange class="small" />
6   </bento>
7   <plate>
8     <orange />
9   </plate>
10  <plate>
11    <orange class="small" />
12    <orange class="small" />
13  </plate>
14 </div>
15
16
17
18
19
20
```

HTML Viewer

table.html

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

Level 7 of 32

Combine the Class Selector

`A.className`

You can combine the class selector with other selectors, like the type selector.

Examples

`ul li.important` selects all `li` elements that have `class="important"`

`img.wide` selects all elements with `id="img"` that also have `class="wide"`

CSS Diner

Share

Select the small oranges in the bentos



CSS Editor

style.css

HTML Viewer

table.html

```
1 bento <orange>.small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento>
3     <orange />
4   </bento>
5   <orange class="small" />
6   <bento>
7     <orange class="small" />
8   </bento>
9   <bento>
10    <apple class="small" />
11  </bento>
12  <bento>
13    <orange class="small" />
14  </bento>
15 </div>
16
17
18
19
20
```

```
1 <table>
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 8 of 32 ✓

You can do it...

Put your back into it!

Combine what you learned in the last few levels to solve this one!

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

CSS Diner

Share

Select all the plates and bentos



CSS Editor

style.css

HTML Viewer

table.html

```
1 .plate, bento
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <pickle class="small" />
3   <pickle />
4   <plate>
5     <pickle />
6   </plate>
7   <bento>
8     <pickle />
9   </bento>
10  <plate>
11    <pickle />
12  </plate>
13  <pickle />
14  <pickle class="small" />
15 </div>
16
17
18
19
20
```

```
1 <table>
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 9 of 32 ✓

Comma Combinator

Combine selectors with... comma!

A, B

Thanks to Shatner technology, this selects all A and B elements. You can combine any selectors this way, and you can specify more than two.

Examples

p, .foo selects all <p> elements as well as all elements with class="foo"

*.p, div selects all <div>, <p>, and <div> elements

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

CSS Diner

Share

Level 10 of 32

Select all the things!

CSS Editor

```
1 *
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

style.css

HTML Viewer

```
1 <div class="table">
2   <apple />
3   <plate />
4     <orange class="small" />
5   </plate>
6   <bento />
7     <bento />
8     <orange />
9   </bento>
10   <plate id="fancy" />
11 </div>
12
13
14
15
16
17
18
19
20
```

table.html

Made by @lukeout — come say hi!

The Universal Selector

You can select everything!

`*`

You can select all elements with the universal selector!

Examples

`p *` selects any element inside all `p` elements.

CSS Diner

Share

Level 11 of 32

Select everything on a plate!

CSS Editor

```
1 plate *
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

style.css

HTML Viewer

```
1 <div class="table">
2   <plate id="fancy">
3     <orange class="small" />
4   </plate>
5   <plate>
6     <apple />
7   </plate>
8   <apple class="small" />
9   <plate>
10     <apple />
11   </plate>
12 </div>
13
14
15
16
17
18
19
20
```

table.html

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo.

Combine the Universal Selector

`A *`

This selects all elements inside of `A`.

Examples

`p *` selects every element inside all `p` elements.

`ul.fancy *` selects every element inside all `ul` class="fancy" elements.

CSS Diner

Share

Facebook

Twitter

Select every apple that's next to a plate



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate ~ apple
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento>
3     <apple class="small" />
4   </bento>
5   <plate />
6   <apple class="small" />
7   <plate />
8   <apple />
9   <apple class="small" />
10  <apple class="small" />
11 </div>
12
13
14
15
16
17
18
19
20
```

Level 12 of 32 ✓

Adjacent Sibling Selector

Select an element that directly follows another element.

A + B

This selects all B elements that directly follow A. Elements that follow one another are called siblings. They're on the same level, or depth.

In the HTML markup for this level, elements that have the same indentation are siblings.

Examples

p + intro selects every element with class="intro" that directly follows a p.

div + a selects every a element that directly follows a div.

Made by @lukeout - come say hi!

Have feedback or questions? Please file an issue on the Github repo.

CSS Diner

Share

Facebook

Twitter

Select the pickles beside the bento



CSS Editor

style.css

HTML Viewer

table.html

```
1 bento ~ pickle
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <pickle />
3   <bento>
4     <orange class="small" />
5   </bento>
6   <pickle class="small" />
7   <pickle />
8   <plate>
9     <pickle />
10    <plate>
11      <plate>
12        <pickle class="small" />
13      </plate>
14    </plate>
15  </div>
16
17
18
19
20
```

Level 13 of 32 ✓

General Sibling Selector

Select elements that follows another element

A ~ B

You can select all siblings of an element that follow it. This is like the Adjacent Selector (A + B) except it gets all of the following elements instead of one.

Examples

A ~ B selects all B that follows A

Made by @lukeout - come say hi!

Have feedback or questions? Please file an issue on the Github repo.

CSS Diner

Share

Level 14 of 32

Select the apple directly on a plate

CSS Editor

style.css

HTML Viewer

table.html

```
1 plate > apple
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate>
3     <apple />
4   </plate>
5   <plate>
6     <apple />
7   </plate>
8   <plate>
9     <apple />
10  </plate>
11  <plate>
12    <apple class="small" />
13  </plate>
14 </div>
15
16
17
18
19
20
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

Child Selector

Select direct children of an element

A > B

You can select elements that are direct children of other elements. A child element is any element that is nested directly in another element.

Elements that are nested deeper than that are called descendant elements.

Examples

A > B selects all B that are a direct children of A

CSS Diner

Share

Level 15 of 32

Select the top orange

CSS Editor

style.css

HTML Viewer

table.html

```
1 plate :first-child
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <empty />
3   <plate />
4   <plate>
5     <orange />
6   </plate>
7   <plate>
8     <orange />
9   </plate>
10  <apple class="small" />
11 </div>
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

First Child Pseudo-selector

Select a first child element inside of another element

:first-child

You can select the first child element. A child element is any element that is directly nested in another element. You can combine this pseudo-selector with other selectors.

Examples

:first-child selects all first child elements.

p:first-child selects all first child p elements.

div p:first-child selects all first child p elements that are in a <div>.

CSS Diner

Share

Level 16 of 32

Select the apple and the pickle on the plates



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate :only-child
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate>
3     <apple />
4   </plate>
5   <plate>
6     <pickle />
7   </plate>
8   <plate>
9     <pickle />
10  </plate>
11  <plate>
12    <orange class="small" />
13    <orange />
14  </plate>
15  <pickle class="small" />
16 </div>
17
18
19
20
```

Made by @flukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo.

Only Child Pseudo-selector
Select an element that are the only element inside of another one.

`:only-child`

You can select any element that is the only element inside of another one.

Examples

`span:only-child` selects the `span` elements that are the only child of some other element.

`ul li:only-child` selects the only `li` element that are in a `ul`.

CSS Diner

Share

Level 17 of 32

Select the small apple and the pickle



CSS Editor

style.css

HTML Viewer

table.html

```
1 :last-child.small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate id="fancy">
3     <apple class="small" />
4   </plate>
5   <plate>
6     <orange class="small" />
7     <orange />
8   </plate>
9   <pickle class="small" />
10 </div>
11
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo.

Last Child Pseudo-selector
Select the last element inside of another element

`:last-child`

You can use this selector to select an element that is the last child element inside of another element.

Pro Tip → In cases where there is only one element, that element counts as the first-child, only-child and last-child

Examples

`:last-child` selects all last-child elements.

`span:last-child` selects all last-child `span` elements.

`ul li:last-child` selects the last `li` elements inside of any `ul`.

CSS Diner

Share

Facebook

Twitter

Select the 3rd plate



CSS Editor

style.css

HTML Viewer

Table.html

```
1 nth-child(3)
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex. + "3" for level 3
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate />
4   <plate />
5   <plate id="fancy" />
6 </div>
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

Level 18 of 32

< > ≡

Nth Child Pseudo-selector

Select an element by its order in another element

nth-child(A)

Selects the nth (Ex. 1st, 3rd, 12th etc.) child element in another element.

Examples

nth-child(8) selects every element that is the 8th child of another element.

div:nth-child(2) selects the second div in every div

CSS Diner

Share

Facebook

Twitter

Select the 1st bento



CSS Editor

style.css

HTML Viewer

Table.html

```
1 bento:nth-last-child(3)
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex. + "3" for level 3
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <bento />
4   <plate />
5   <orange />
6   <orange />
7   <plate />
8   <bento />
9   <bento />
10 </div>
11
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the GitHub repo

Level 19 of 32

< > ≡

Nth Last Child Selector

Select an element by its order in another element, counting from the back

nth-last-child(A)

Selects the children from the bottom of the parent. This is like nth-child, but counting from the back!

Examples

nth-last-child(2) selects all second-to-last child elements.

CSS Diner

Share

Facebook

Twitter

Select first apple



CSS Editor

style.css

HTML Viewer

table.html

```
1 apple:first-of-type
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <orange class="small" />
3   <apple />
4   <apple class="small" />
5   <apple />
6   <apple class="small" />
7   <plate>
8     <orange class="small" />
9     <orange />
10  </plate>
11 </div>
12
13
14
15
16
17
18
19
20
```

Level 20 of 32 ✓

First of Type Selector

Select the first element of a specific type

`first-of-type`

Selects the first element of that type within another element.

Examples

`span:first-of-type` selects the first `span` in any element.

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

CSS Diner

Share

Facebook

Twitter

Select all even plates



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate:nth-of-type(even)
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate />
4   <plate />
5   <plate />
6   <plate id="fancy" />
7   <plate />
8 </div>
9
10
11
12
13
14
15
16
17
18
19
20
```

Level 21 of 32 ✓

Nth of Type Selector

Selects a specific element based on its type and order in another element - or even or odd instances of that element.

Examples

`div:nth-of-type(2)` selects the second instance of a div.

`example:nth-of-type(odd)` selects all odd instances of a the example class.

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

CSS Diner

Share

Select every 2nd plate, starting from the 3rd



CSS Editor

style.css

HTML Viewer

table.html

```
1 nth-of-type(2n+3)
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "1" for level 1
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate />
3   <plate>
4     <pickle class="small" />
5   </plate>
6   <plate>
7     <pickle class="small" />
8   </plate>
9   <plate />
10  <plate>
11    <pickle />
12  </plate>
13  <plate />
14 </div>
15
16
17
18
19
20
```

```
<table>
  <tr>
    <td></td>
    <td></td>
    <td></td>
    <td></td>
    <td></td>
    <td></td>
  </tr>
</table>
```

Level 22 of 32

Nth-of-type Selector with Formula

nth-of-type(An+B)

The nth-of-type formula selects every nth element, starting the count at a specific instance of that element.

Examples

span:nth-of-type(2n+2) selects every 2nd instance of a , starting from (and including) the second instance.

Made by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

CSS Diner

Share

Level 23 of 32

Select the apple on the middle plate



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate apple:only-of-type
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate id="fancy">
3     <apple class="small" />
4   </apple>
5 </plate>
6 <plate>
7   <apple class="small" />
8 </plate>
9 <plate>
10  <pickle />
11 </plate>
12 </div>
13
14
15
16
17
18
19
20
```

table.html

Make by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Only of Type Selector

Select elements that are the only ones of their type within of their parent element

`only-of-type`

Selects the only element of its type within another element.

Examples

`p:only-of-type` selects a `<p>` within any `<div>` if it is the only `<p>` in there.

CSS Diner

Share

Level 24 of 32

Select the last apple and orange



CSS Editor

style.css

HTML Viewer

table.html

```
1 :last-of-type.small
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <orange class="small" />
3   <orange class="small" />
4   <pickle />
5   <pickle />
6   <apple class="small" />
7   <apple class="small" />
8 </div>
9
10
11
12
13
14
15
16
17
18
19
20
```

table.html

Make by @flukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Last of Type Selector

Select the last element of a specific type

`:last-of-type`

Selects each last element of that type within another element. Remember type refers the kind of tag so `<div>` and `<p>` are different types.

I wonder if this is how the last dinosaur was selected before it went extinct.

Examples

`div:last-of-type` selects the last `<div>` in every element.

`p:span:last-of-type` selects the last `<span>` in every `<p>`.

CSS Diner

Share

Facebook

Twitter

Level 25 of 32

Select the empty bentos



CSS Editor

style.css

HTML Viewer

table.html

```
1 bento:empty
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento />
3   <bento>
4     <pickle class="small" />
5   </bento>
6   <plate />
7   <bento />
8 </div>
9
10
11
12
13
14
15
16
17
18
19
20
```

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Empty Selector

Select elements that don't have children

`:empty`

Selects elements that don't have any other elements inside of them.

Examples

`div:empty` selects all empty `div` elements.

CSS Diner

Share

Facebook

Twitter

Level 26 of 32

Select the big apples



CSS Editor

style.css

HTML Viewer

table.html

```
1 :not(plate, .small)
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate id="fancy">
3     <apple class="small" />
4   </plate>
5   <plate>
6     <apple />
7   </plate>
8   <apple />
9   <plate>
10    <orange class="small" />
11  </plate>
12  <pickle class="small" />
13 </div>
14
15
16
17
18
19
20
```

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Negation Pseudo-class

Select all elements that don't match the negation selector

`:not(X)`

You can use this to select all elements that do not match selector `X`.

Examples

`:not(.fancy)` selects all elements that do not have `id="fancy"`.

`div:not(:first-child)` selects every `div` that is not a first child.

`:not(.big, .medium)` selects all elements that do not have `class="big"` or `class="medium"`.

CSS Diner

Share

Level 27 of 32

Select the items for someone



CSS Editor

style.css

HTML Viewer

table.html

```
1 {for}
2 {
3 /* Styles would go here. */
4 }
5
6 /*
7 Type a number to skip to a level.
8 Ex + "5" for level 5
9 */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento>
3     <apple class="small" />
4   </bento>
5   <apple for="Ethan" />
6   <plate for="Alice">
7     <pickle />
8   </plate>
9   <bento for="Clara">
10     <orange />
11   </bento>
12   <pickle />
13 </div>
14
15
16
17
18
19
20
```

table.html

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Attribute Selector

Select all elements that have a specific attribute

[attribute]

Attributes appear inside the opening tag of an element, like this: `<span attribute="value">`. An attribute does not always have a value, it can be blank!

Examples

`a[href]` selects all `a` elements that have a `href="anything"` attribute.

`[type]` selects all elements that have a `type="anything"` attribute

CSS Diner

Share

Level 28 of 32

Select the plates for someone



CSS Editor

style.css

HTML Viewer

table.html

```
1 plate{for}
2 {
3 /* Styles would go here. */
4 }
5
6 /*
7 Type a number to skip to a level.
8 Ex + "5" for level 5
9 */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate for="Sarah">
3     <pickle />
4   </plate>
5   <plate for="Luke">
6     <apple />
7   </plate>
8   <plate />
9   <bento for="Steve">
10     <orange />
11   </bento>
12 </div>
13
14
15
16
17
18
19
20
```

table.html

Made by @lukeout — come say hi!

Have feedback or questions? Please file an issue on the Github repo.

Attribute Selector

Select all elements that have a specific attribute

A[attribute]

Combine the attribute selector with another selector (like the tag name selector) by adding it to the end.

Examples

`[value]` selects all elements that have a `value="anything"` attribute.

`a[href]` selects all `a` elements that have a `href="anything"` attribute.

`input[disabled]` selects all `input` elements with the `disabled` attribute

CSS Director

Share

Level 29 of 32

Select Vitaly's meal



CSS Editor

style.css

HTML Viewer

table.html

```
1 bento(for="Vitaly")
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <apple for="Alexei" //
3   <bento for="Albina">
4     <apple //
5   </bento>
6   <bento for="Vitaly">
7     <orange //
8   </bento>
9   <apple //
10 </div>
11
12
13
14
15
16
17
18
19
20
```

Made by @lukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo.

Attribute Value Selector

Select all elements that have a specific attribute value

[attribute="value"]

Attribute selectors are case sensitive, each character must match exactly.

Examples

input[type="checkbox"] selects all checkbox input elements.

CSS Director

Share

Level 30 of 32

Select the items for names that start with 'Sa'



CSS Editor

style.css

HTML Viewer

table.html

```
1 [for="Sa"]
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex + "5" for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <plate for="Sam">
3     <apple //
4   </plate>
5   <bento for="Sarah">
6     <apple class="small" //
7   </bento>
8   <bento for="Mary">
9     <orange //
10 </bento>
11 </div>
12
13
14
15
16
17
18
19
20
```

Made by @lukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo.

Attribute Starts With Selector

Select all elements with an attribute value that starts with specific characters

[attribute^="value"]

Examples

tbody[category^="Swim"] selects elements with class tbody and either category="Swimwear" or category="Swimming".

css Diner

Share

Level 31 of 32

Select the items for names that end with 'ato'

CSS Editor

style.css

HTML Viewer

table.html

```
1 [for$="ato"]
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: #5 for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <apple class="small" />
3   <bento for="Hayato">
4     <pickle />
5   </bento>
6   <apple for="Ryota" />
7   <plate for="Minato">
8     <orange />
9   </plate>
10  <pickle class="small" />
11 </div>
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo

Attribute Ends With Selector

Select all elements with an attribute value that ends with specific characters

[attribute\$="value"]

Examples

selects all images display a .jpg image.

css Diner

Share

Level 32 of 32

Select the meals for names that contain 'obb'

CSS Editor

style.css

HTML Viewer

table.html

```
1 [for*="obb"]
2 {
3   /* Styles would go here. */
4 }
5
6 /*
7  Type a number to skip to a level.
8  Ex: #5 for level 5
9  */
10
11
12
13
14
15
16
17
18
19
20
```

```
1 <div class="table">
2   <bento for="Robbie">
3     <apple />
4   </bento>
5   <bento for="Timmy">
6     <pickle />
7   </bento>
8   <bento for="Bobby">
9     <orange />
10  </bento>
11 </div>
12
13
14
15
16
17
18
19
20
```

Made by @flukeout — come say hi!
Have feedback or questions? Please file an issue on the Github repo

Attribute Wildcard Selector

Select all elements with an attribute value that contains specific characters anywhere

[attribute*="value"]

Useful selector if you can identify a common pattern in things like `class`, `href` or `src` attributes.

Examples

selects all image elements that show images from the "thumbnails" folder.

`[class*="heading"]` selects all elements with "heading" in their class, like `class="main-heading"` and `class="sub-heading"`