

Documentation - Data Bases 2

Marco Fasanella

*MsC Computer Science, Polimi
C.P. 10617541*

Nicola Dean

*MsC Computer Science, Polimi
C.P. 106—*

This document describes design and implementation of Data Base 2 Project

1. Specifications

A telco company offers pre-paid online services to web users. Two client applications using the same database have been developed: a costumer application and an employee application.

1.1 Extra hypothesis

2. ER Diagram

3. SQL Description

Detailed description of SQL code used in the project.

3.1 Views

The following views are used for various Sales Reports.

Joining Orders and Rate_costs tables we performed a *selection* for each distinct package (depending on their month validity) and a *count* for their occurrences.

```
create view PurchasesCount as (  
    Select Packages.name as name,Rate_costs.monthValidity as validity, count(*) as count  
    from Orders as o join Packages  join Rate_costs  
    on o.packageId=Packages.id and Rate_costs.packageId=o.packageId  
    and o.rateId=Rate_costs.id  
    group by o.packageId, Rate_costs.id  
);
```

Then for a less detailed view, from *PurchasesCount* , a *group by* on the name of the package gives a count of each one.

Marco Fasanella, Nicola Dean, 2021




Figure 1. ER Diagram

```

create view PurchasesCountGrouped as (
    select p.name as name, sum(p.count) as count
    from PurchasesCount as p
    group by p.name
);

```

To count the Optional Products was necessary a *left join* because it could exist a Package without any Optional Product, and as a consequence it wouldn't be stored in *Orders_OptionalProducts* table.

```

create view OptionalProductsCount as(
    select o.packageId as packageId, count(opt.productId) as optcount
    from Orders as o left join Orders_OptionalProducts as opt
    on o.id=opt.orderId
    group by o.id
);

```

Then to have the average count of them, we performed an *avg* on the count of previous view.

```

create view OptionalProductsAverage as(
    select p.name as name, avg(opc.optcount) as avg
    from OptionalProductsCount as opc join Packages as p
    where opc.packageId=p.id

```

```

group by id
);

```

Following view sums the *totalPayment* of each Order grouped by *packageId*

```

create view ValueOfTotalSales as(
    select p.name as name, sum(o.totalPayment) as totalPayment
    from Orders as o join Packages as p
    where p.id=o.packageId
    group by o.packageId
);

```

Then in *OptionalProductsSales* the same method is used to get the totalCost of the Optional Products related to their corresponding Service Package in *Orderds*

```

create view OptionalProductsSales as(
    select p.name as name,sum(op.monthlyFee*r.monthValidity) as totalOptionalProductsSales
    from Orders_OptionalProducts as orderop join Orders as o
    join OptionalProducts as op join Packages as p join Rate_costs as r
    where o.id=orderop.orderId and orderop.productId=op.id
    and o.packageId=p.id and o.rateId=r.id
    group by p.id
);

```

And finally these two views are *left joined* to have both *totalPayment* with and without Optional Products. A *left join* is required because as mentioned before it could exist a service package without Optional Product. In this case *totalPaymentWithoutOP* will return *null*.

```

create view ValueOfSalesDetailed as(
    select vot.name as name, vot.totalPayment as totalPayment,
           (vot.totalPayment-ops.totalOptionalProductsSales) as totalPaymentWithoutOP
    from ValueOfTotalSales as vot left join OptionalProductsSales as ops
    on vot.name=ops.name
);

```

In *InsolventReport* are selected all Users with *having count(*)≥3* of insolvent orders stored in *FailedPayments*.

```

create view InsolventReport as(
    select u.id as id,u.username as username,u.email as email,
           (
            select max(fp1.faildate)
            from FailedPayments as fp1
            where fp1.userId=u.id) as lastDate,
           (

```

```

        select o.totalPayment
        from Orders as o join FailedPayments as fp2
        where o.id=fp2.orderId and lastdate=fp2.faildate) as amount
from FailedPayments as fp join Users as u
where fp.userId=u.id
group by u.id
having count(*)>=3
);

```

Last view *OptionalProductBestSeller* is used to have a count and the value of total sales of each Optional Product.

```

create view OptionalProductBestSeller as(
    select op.name as name,count(op.id) as amountSold,
           sum(op.monthlyFee*r.monthValidity) as value
    from Orders_OptionalProducts as ordop join OptionalProducts as op
    join Rate_costs as r join Orders as o
    where ordop.productId=op.id and o.rateId=r.id and o.id=ordop.orderId
    group by op.id
);

```

The using two distinct queries we performed the *OptionalProductBestSeller-ForValue*

```

select o
from OptionalProductBestSeller o
where o.value=(
select max(o2.value)
from OptionalProductBestSeller o2
);

```

and *OptionalProductBestSellerForAmount*

```

select o from OptionalProductBestSeller o
where o.amountSold=(
select max(o2.amountSold)
from OptionalProductBestSeller o2
);

```

■ 3.2 Triggers

```

create trigger INSOLVENT_USER
after insert on Orders
for each row
begin
    if ( new.status = false) then
        update Users set Users.insolvent = true where Users.id = new.userId;
        insert into FailedPayments (userId,orderId,faildate)

```

```

        values (new.userId,new.id,CURRENT_TIMESTAMP);
    end if;

    create trigger INSOLVENT_USER_REMOVAL
        after update on Orders
        for each row
    begin
        if (new.status = true) AND
            (select count(*) from Orders as o where o.userId=new.userId and o.status = false) = 0
        then
            update Users set Users.insolvent = false where Users.id = new.userId;
        end if;
        if (new.status = false AND old.status = new.status) then
            insert into FailedPayments (userId,orderId,faildate)
            values (new.userId,new.id,CURRENT_TIMESTAMP);
        end if;
    end if;

```

4. ORM Description

4.1 Entities

Optional Product

```

@Entity
@Table(name = "OptionalProducts", schema = "test")
public class OptionalProduct{

    @Id
    @GeneratedValue(strategy= GenerationType.IDENTITY)
    int id;
    String name;
    int monthlyFee;
}

```

Order The Orders entity

```

@Entity
@Table(name = "Orders", schema = "test")
@NamedQuery(name="Orders.Id", query="select o from Order o
    where o.Id = :orderId")
@NamedQuery(name="Orders.All", query="select o from Order o")
//TODO adjust query for only accepted orders
@NamedQuery(name="Orders.Suspended", query="select o from Order o
    where o.status=false")
@NamedQuery(name="Orders.RemoveSuspend", query="update Order o set
    o.status = true where o.Id=:orderId")
@NamedQuery(name="PurchasesByPackages", query = "select count
    (distinct o) from Order o group by o.pack")

```

```

@NamedQuery(name="PurchasesByPackagesID" , query = "select
    o.pack.name, count(o.pack) from Order o where o.status=true group
    by o.pack ")
@NamedQuery(name="Orders.UserInsolvances" , query = "select o from
    Order o where o.status=false and o.user.id = :userId")
//TODO think a new entity for statistical pourpose should be created
    to store pair "package-> quantity"

```

```

public class Order {

    @Id
    @GeneratedValue(strategy= GenerationType.IDENTITY)
    int Id;
    Date startDate;
    Date creationDate;
    float totalPayment;
    Boolean status =null;

```

RateCost

```

@Entity
@Table(name="Rate_costs", schema = "test")
public class RateCost {

    @Id
    @GeneratedValue(strategy= GenerationType.IDENTITY)
    int id;
    int monthValidity;
    int cost;
    int packageId;

```

Service

```

@Entity
@Inheritance(strategy = InheritanceType.JOINED)
@Table(name = "services", schema = "test")
public class Service {

    @Id
    @GeneratedValue(strategy=GenerationType.IDENTITY)
    int id;
    int packageId;
    @Column(name = "DTYPE")
    String type;

```

User

```

@Entity

```

```
@NamedQuery(name = "User.authentication", query = "select usr from
    User usr WHERE usr.username = :username and usr.password =
    :password")
@NamedQuery(name = "User.insolvent" , query = "select usr from User
    usr WHERE usr.insolvent = true")
@Table(name="Users", schema = "test")
public class User {
    @Id
    @GeneratedValue(strategy=GenerationType.IDENTITY)
    int id;

    String username;
    String password;
    String email;
    String type;
    boolean insolvent;
```

5. Application Components

6. UML sequence diagrams
