SINTEF

AI and cybersecurity: with a focus on LLM security

Nektaria Kaloudi

Research scientist at SINTEF Digital

Trondheim - Norway, 17 April 2026

AI hype

- AI market size is expected to reach **$407 billion by 2027**
- AI will have an estimated **21% net increase** on the United States GDP by 2030
- ChatGPT had **1M users** within the **first 5 days** of being available
- **One out of 10 cars** will be self-driving by 2030
- **64% of businesses** expect AI to increase productivity

Source: https://www.forbes.com/advisor/business/ai-statistics/

AI has surpassed humans at a number of tasks and the rate at which humans are being surpassed at new tasks is increasing

State-of-the-art AI performance on benchmarks, relative to human performance



For each benchmark, the maximally performing baseline reported in the benchmark paper is taken as the "starting point", which is set at 0%. Human performance number is set at 100%. Handwriting recognition = MNIST, Language understanding = GLUE, Image recognition = ImageNet, Reading comprehension = SQuAD 1.1, Reading comprehension = SQuAD 2.0, Speech recognition = Switchboard, Grade school math = GSK8k, Common sense completion = HellaSwag, Code generation = HumanEval.

Chart: Will Henshall for TIME • Source: ContextualAI

TIME

Source: https://time.com/6300942/ai-progress-charts/

AI and its terminology



Handcrafted knowledge with logic-based rules about a task

- reasoning capabilities
- limited learning and abstracting
- not good at handling complicated tasks in natural world



Statistical learning with all the current successes

- good at perceive the natural world
- learning and adaptive capabilities
- limited reasoning capabilities



Algorithm + Data + Computation

Melanie Mitchell "*Artificial Intelligence: A Guide for Thinking Humans*", 2019
Gary McGraw "*Security Engineering for Machine Learning*", 2022

AI evolution

Very fast evolving domain from deep learning to agentic AI



AI Agent is an **interactive system** that can **perceive environmentally-grounded data**, and can produce meaningful **action.** The system can self-**improve** by incorporating **external knowledge**, environment or **human feedback.**

Rise of AI impacting society

Self-driving car

Medical diagnosis

Customer service, chatbots

Virtual assistants

Financial trading

Artificial Intelligence ⇄ Cybersecurity

How do AI and cybersecurity relate?



AI and cybersecurity

Important research direction (covering all three dimensions): protecting AI systems and users from malicious AI using AI



AI is used to improve defensive cybersecurity

- ✅ Less time consuming
- ✅ Better cope with interconnected environment
- ✅ Learn weak signals unnoticed by humans

Cybersecurity is used to protect AI systems and users

- ✅ Secure, safe, fair design and operation of AI systems
- ✅ More robust AI

- ✅ Sophistication
- ✅ Speed
- ✅ Scale

malicious use of AI is used to enhance offensive cybersecurity, and **malicious abuse of AI** to manipulate capabilities of AI systems

Part II: LLM security

Why LLM security matters?

- LLMs are increasingly embedded in:
  - Chatbots and virtual assistants
  - Code assistants
  - Search and recommendation systems
  - Education and tutoring apps
  - Security analysis and log inspection tools
  - Research support and document analysis tools

- Failures in LLMs lead to security incidents, not just wrong answers.

- An LLM is not just a model, but it is part of an application and must be security-tested like any other critical component.

What is a Large Language Model (LLM)?

- A Large Language Model (LLM) is a type of AI designed to understand, summarize, and generate new content.
- It is a subset of generative AI specially designed to create text-based content.
- It is trained on vast amount of text with goal of generating coherent and contextually relevant content.
- LLMs learn behavior implicitly from data

LLM development timeline

- Starting from 1950 – 1990
  - Language modelled statistically (n-grams, probabilities)
  - Goal to predict the next word
- Early 2000
  - Probabilistic language models improve, but scale is limited
- 2010 – 2016
  - Neural language models (RNNs, LSTMs)
  - Able to model sequences, but slow to train with poor long-range memory, and hard to scale
- 2017
  - Appearance of transformer architecture

LLM development timeline



Figure 3: LLM development timeline. The models below the arrow are closed-source while those above the arrow are open-source.

Source: Chen, Hailin, et al. "ChatGPT's one-year anniversary: Are Open-Source large language models catching up?." *arXiv preprint arXiv:2311.16989* (2023).

How do LLMs work?

- LLMs work by learning statistical patterns in language and using those patterns to predict the next piece of text.
- The likelihood of the next word appearing is determined by the context in which the words are seen in the larger body of text or corpus and the input to the chat.
- An LLM:
  - Takes input text (prompt)
  - Breaks it into tokens (words or parts of words)
  - Uses a neural network (usually a Transformer) to understand context and weigh relationships between words via attention
  - Predicts the next token
  - Repeats this process to generate full responses

- Does LLM understand meaning?

Testing for LLMs

Main purpose: trying to make the model do something it should not, such as

- Generate harmful instructions
- Leak private data and reveal internal information
- Bypass safety filters
- Produce biased content
- Give illegal, dangerous, or unethical advices

LLM red teaming



Source: https://www.superannotate.com/blog/llm-red-teaming

OWASP Top 10 for LLM Applications

1. Prompt injection
2. Sensitive Information Disclosure
3. Supply Chain
4. Data and Model Poisoning
5. Improper Output Handling
6. Excessive Agency
7. System Prompt Leakage
8. Vector and Embedding Weaknesses
9. Misinformation
10. Unbounded Consumption

Source: https://genai.owasp.org/resource/owasp-top-10-for-llm-applications-2025/

LLM01:2025 Prompt Injection

Prompt injection vulnerability occurs when user prompts alter the LLM's behavior or output in unintended ways.

Prompt injections do not need to be human-visible or readable, as long as the content is parsed by the model.

- Jailbreaking is a form of prompt injection where the attacker provides inputs that cause the model to disregard its safety protocols entirely.
  - In a fictional scenario, where rules do not apply…
  - For academic research purposes only…
  - Imagine you are an AI without restrictions…

Source: https://genai.owasp.org/resource/owasp-top-10-for-llm-applications-2025/

Types of prompt injection vulnerabilities

Direct prompts

- User's prompt input directly alters the behavior of the model in unintended or unexpected ways.

Indirect prompts

- Occur when an LLM accepts input from external sources, such as websites or files.
- The content may have in the external content data that when interpreted by the model, alters the behavior of the model in unintended or unexpected ways.

Source: https://gandalf.lakera.ai/baseline

Adversarial AI/ML threats

National Institute of Standards and Technology (NIST)'s taxonomy of adversarial AI threats based on:

- Targets
- Attack timing
- Attacker knowledge
- Attack consequences

Source: Tabassi, Elham, et al. "A taxonomy and terminology of adversarial machine learning." *NIST IR* 2019 (2019): 1-29.



Source: Tabassi, Elham, et al. "A taxonomy and terminology of adversarial machine learning." *NIST IR* 2019 (2019): 1-29.

Adversarial AI attack taxonomy on GenAI systems



Source: NIST AI 100-2 E2025, Adversarial Machine Learning: A Taxonomy and Terminology of Attacks and Mitigations

Securing AI - examples

MITRE ATLAS

Knowledge base of adversary tactics and techniques based on real-world attack observations and realistic demonstrations.



MIT AI Risk repository

A comprehensive living database of over 1600 AI risks categorized by their cause and risk domain.

NIST AI RMF

AI risk management framework for managing AI risks through 4 functions.

- Dioptra is NIST's software test platform for assessing trustworthy of AI that supports RMF functions.

Efforts towards regulation and standards

- EU AI Act
- ETSI's Securing Artificial Intelligence (SAI) documents [1]
  - E.g., Understanding and preventing harm from Generative AI
- The new AI security standard: ISO 27090 "Cybersecurity – Artificial Intelligence- Guidance for addressing security threats and compromises to artificial intelligence systems"
  - It's AI security specific, not generic cybersecurity
  - It covers the full AI lifecycle
  - It is designed to integrate with ISO 42001 "Artificial intelligence – management system"

1 https://www.etsi.org/committee/2312-sai

Threats 2030 - ENISA

The rise of AI-related threats – during 2026

For the first time, every threat carries an AI dimension

1. AI-Generated Zero Days
2. Supply Chain Risks
3. OT Complexity and the Root Cause Crisis
4. The Dark Side of AI, Irresponsible Use in Digital Forensics and Incident Response
5. Find Evil, The Race to Autonomous Defense

Source: https://www.sans.org/press/announcements/rsac-2026-sans-institute-top-5-most-dangerous-new-attack-techniques

SINTEF

Thank you for your attention

nektaria.kaloudi@sintef.no