MOSFET

Metal Oxide Semiconductor Field Effect Transistor

OptiMOS™

OptiMOS™ 5 Power-Transistor, 80 V
IPT012N08N5

Data Sheet

Rev. 2.1
Final

Power Management & Multimarket

1 Description



Features

- Ideal for high frequency switching and sync. rec.
- Excellent gate charge x $R_{DS(on)}$ product (FOM)
- Very low on-resistance $R_{DS(on)}$
- N-channel, normal level
- 100% avalanche tested
- Pb-free plating; RoHS compliant
- Qualified according to JEDEC[1] for target applications
- Halogen-free according to IEC61249-2-21



Table 1 Key Performance Parameters

Parameter	Value	Unit
V_{DS}	80	V
$R_{DS(on),max}$	1.2	mΩ
I_D	300	A
Q_{oss}	208	nC
Q_G(0V..10V)	178	nC

Type / Ordering Code	Package	Marking	Related Links
IPT012N08N5	PG-HSOF-8-1	012N08N5	-

[1] J-STD20 and JESD22

Table of Contents

2 Maximum ratings

at T_j = 25 °C, unless otherwise specified

Table 2 Maximum ratings

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Continuous drain current	I_D	- - -	- - -	300 279 52	A	V_{GS}=10 V, T_C=25 °C V_{GS}=10 V, T_C=100 °C V_{GS}=10 V, T_C=25 °C, R_{thJA} =40 K/W[1)]
Pulsed drain current[2)]	$I_{D,pulse}$	-	-	1200	A	T_C=25 °C
Avalanche energy, single pulse[3)]	E_{AS}	-	-	817	mJ	I_D=150 A, R_{GS}=25 Ω
Gate source voltage	V_{GS}	-20	-	20	V	-
Power dissipation	P_{tot}	-	-	375	W	T_C=25 °C
Operating and storage temperature	T_j, T_{stg}	-55	-	175	°C	IEC climatic category; DIN IEC 68-1: 55/175/56

3 Thermal characteristics

Table 3 Thermal characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case	R_{thJC}	-	0.2	0.4	K/W	-
Device on PCB, minimal footprint	R_{thJA}	-	-	62	K/W	-
Device on PCB, 6 cm² cooling area[1)]	R_{thJA}	-	-	40	K/W	-

[1)] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm^2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.
[2)] See figure 3 for more detailed information
[3)] See figure 13 for more detailed information

4 Electrical characteristics

Table 4 Static characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	80	-	-	V	V_{GS}=0 V, I_D=1 mA
Gate threshold voltage	$V_{GS(th)}$	2.2	3.0	3.8	V	V_{DS}=V_{GS}, I_D=280 µA
Zero gate voltage drain current	I_{DSS}	- -	0.1 10	1 100	µA	V_{DS}=80 V, V_{GS}=0 V, T_j=25 °C V_{DS}=80 V, V_{GS}=0 V, T_j=125 °C
Gate-source leakage current	I_{GSS}	-	10	100	nA	V_{GS}=20 V, V_{DS}=0 V
Drain-source on-state resistance	$R_{DS(on)}$	- -	1.0 1.3	1.2 1.7	mΩ	V_{GS}=10 V, I_D=150 A V_{GS}=6 V, I_D=75 A
Gate resistance[1)]	R_G	-	1.6	2.4	Ω	-
Transconductance	g_{fs}	120	250	-	S	|V_{DS}|>2|I_D|$R_{DS(on)max}$, I_D=100 A

Table 5 Dynamic characteristics[1)]

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Input capacitance	C_{iss}	-	13000	17000	pF	V_{GS}=0 V, V_{DS}=40 V, f=1 MHz
Output capacitance	C_{oss}	-	2000	2600	pF	V_{GS}=0 V, V_{DS}=40 V, f=1 MHz
Reverse transfer capacitance	C_{rss}	-	86	150	pF	V_{GS}=0 V, V_{DS}=40 V, f=1 MHz
Turn-on delay time	$t_{d(on)}$	-	35	-	ns	V_{DD}=40 V, V_{GS}=10 V, I_D=100 A, $R_{G,ext}$=1.8 Ω
Rise time	t_r	-	31	-	ns	V_{DD}=40 V, V_{GS}=10 V, I_D=100 A, $R_{G,ext}$=1.8 Ω
Turn-off delay time	$t_{d(off)}$	-	82	-	ns	V_{DD}=40 V, V_{GS}=10 V, I_D=100 A, $R_{G,ext}$=1.8 Ω
Fall time	t_f	-	30	-	ns	V_{DD}=40 V, V_{GS}=10 V, I_D=100 A, $R_{G,ext}$=1.8 Ω

[1)] Defined by design. Not subject to production test.

Table 6 Gate charge characteristics[1)]

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Gate to source charge	Q_{gs}	-	56	-	nC	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Gate charge at threshold	$Q_{g(th)}$	-	38	-	nC	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Gate to drain charge[2)]	Q_{gd}	-	37	56	nC	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Switching charge	Q_{sw}	-	56	-	nC	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Gate charge total[2)]	Q_g	-	178	223	nC	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Gate plateau voltage	$V_{plateau}$	-	4.5	-	V	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V
Gate charge total, sync. FET	$Q_{g(sync)}$	-	154	-	nC	V_{DS}=0.1 V, V_{GS}=0 to 10 V
Output charge[2)]	Q_{oss}	-	208	276	nC	V_{DD}=40 V, V_{GS}=0 V

Table 7 Reverse diode

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Diode continuous forward current	I_S	-	-	300	A	T_C=25 °C
Diode pulse current	$I_{S,pulse}$	-	-	1200	A	T_C=25 °C
Diode forward voltage	V_{SD}	-	0.88	1.2	V	V_{GS}=0 V, I_F=150 A, T_j=25 °C
Reverse recovery time[2)]	t_{rr}	-	106	212	ns	V_R=40 V, I_F=100A, di_F/dt=100 A/µs
Reverse recovery charge[2)]	Q_{rr}	-	318	636	nC	V_R=40 V, I_F=100A, di_F/dt=100 A/µs

[1)] See ″Gate charge waveforms″ for parameter definition
[2)] Defined by design. Not subject to production test.

5 Electrical characteristics diagrams

Diagram 1: Power dissipation



$P_{tot}=f(T_C)$

Diagram 2: Drain current



$I_D=f(T_C)$; $V_{GS}\geq 10$ V

Diagram 3: Safe operating area



$I_D=f(V_{DS})$; $T_C=25$ °C; $D=0$; parameter: t_p

Diagram 4: Max. transient thermal impedance



$Z_{thJC}=f(t_p)$; parameter: $D=t_p/T$

Diagram 5: Typ. output characteristics



I_D=f(V_{DS}); T_j=25 °C; parameter: V_{GS}

Diagram 6: Typ. drain-source on resistance



$R_{DS(on)}$=f(I_D); T_j=25 °C; parameter: V_{GS}

Diagram 7: Typ. transfer characteristics



I_D=f(V_{GS}); |V_{DS}|>2|I_D|$R_{DS(on)max}$; parameter: T_j

Diagram 8: Typ. forward transconductance



g_{fs}=f(I_D); T_j=25 °C

Diagram 9: Drain-source on-state resistance



$R_{DS(on)}$=f(T_j); I_D=150 A; V_{GS}=10 V

Diagram 10: Typ. gate threshold voltage



$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}

Diagram 11: Typ. capacitances



C=f(V_{DS}); V_{GS}=0 V; f=1 MHz

Diagram 12: Forward characteristics of reverse diode



I_F=f(V_{SD}); parameter: T_j

Diagram 13: Avalanche characteristics



I_{AS}=f(t_{AV}); R_{GS}=25 Ω; parameter: $T_{j(start)}$

Diagram 14: Typ. gate charge



V_{GS}=f(Q_{gate}); I_D=100 A pulsed; parameter: V_{DD}

Diagram 15: Drain-source breakdown voltage



$V_{BR(DSS)}$=f(T_j); I_D=1 mA

Gate charge waveforms



6 Package Outlines



1) partially covered with Mold Flash

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.20	2.40	0.087	0.094
b	0.70	0.90	0.028	0.035
b1	9.70	9.90	0.382	0.390
b2	0.42	0.50	0.017	0.020
c	0.40	0.60	0.016	0.024
D	10.28	10.58	0.405	0.416
D2	3.30		0.130	
E	9.70	10.10	0.382	0.398
E1	7.50		0.295	
E4	8.50		0.335	
E5	9.46		0.372	
e	1.20 (BSC)		0.047 (BSC)	
H	11.48	11.88	0.452	0.468
H1	6.55	6.75	0.258	0.266
H2	7.15		0.281	
H3	3.59		0.141	
H4	3.26		0.128	
N	8		8	
K1	4.18		0.165	
L	1.60	2.10	0.063	0.083
L1	0.70		0.028	
L2	0.60		0.024	
L4	1.00	1.30	0.039	0.051

DOCUMENT NO.
Z8B00169619

SCALE
0 2
0 2 4mm

EUROPEAN PROJECTION

ISSUE DATE
20-02-2014

REVISION
02

Figure 1 Outline PG-HSOF-8-1

Revision History

IPT012N08N5

Revision: 2015-02-23, Rev. 2.1

Previous Revision		
Revision	Date	Subjects (major changes since last revision)
2.0	2014-12-17	Release of final version
2.1	2015-02-23	Update active area about 0.3%

We Listen to Your Comments
Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to:
erratum@infineon.com

Published by
Infineon Technologies AG
81726 München, Germany

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.