

Python Programming Fundamentals Cheat Sheet

Package/Method	Description	Syntax and Code Example
AND	Returns `True` if both statement1 and statement2 are `True`. Otherwise, returns `False`.	Syntax: <pre>statement1 and statement2</pre> Example: <pre>marks = 90 attendance_percentage = 87 if marks >= 80 and attendance_percentage >= 85: print("qualify for honors") else: print("Not qualified for honors") # Output = qualify for honors</pre>
Class Definition	Defines a blueprint for creating objects and defining their attributes and behaviors.	Syntax: <pre>class ClassName: # Class attributes and methods</pre> Example: <pre>class Person: def __init__(self, name, age): self.name = name self.age = age</pre>
Define Function	A `function` is a reusable block of code that performs a specific task or set of tasks when called.	Syntax: <pre>def function_name(parameters): # Function body</pre> Example: <pre>def greet(name): print("Hello,", name)</pre>
Equal(==)	Checks if two values are equal.	Syntax: <pre>variable1 == variable2</pre> Example 1: <pre>5 == 5</pre> returns True Example 2: <pre>age = 25 age == 30</pre> returns False
For Loop	A `for` loop repeatedly executes a block of code for a specified number of iterations or over a sequence of elements (list, range, string, etc.).	Syntax: <pre>for variable in sequence: # Code to repeat</pre> Example 1: <pre>for num in range(1, 10): print(num)</pre> Example 2: <pre>fruits = ["apple", "banana", "orange", "grape", "kiwi"] for fruit in fruits: print(fruit)</pre>
Function Call	A function call is the act of executing the code within the function using the provided arguments.	Syntax: <pre>function_name(arguments)</pre> Example: <pre>greet("Alice")</pre>
Greater Than or Equal To(>=)	Checks if the value of variable1 is greater than or equal to variable2.	Syntax: <pre>variable1 >= variable2</pre> Example 1: <pre>5 >= 5 and 9 >= 5</pre> returns True Example 2: <pre>quantity = 105 minimum = 100 quantity >= minimum</pre>

		returns True
Greater Than(>)	Checks if the value of variable1 is greater than variable2.	<p>Syntax:</p> <pre>variable1 > variable2</pre> <p>Example 1: 9 > 6</p> <p>returns True</p> <p>Example 2:</p> <pre>age = 20 max_age = 25 age > max_age</pre> <p>returns False</p>
If Statement	Executes code block `if` the condition is `True`.	<p>Syntax:</p> <pre>if condition: #code block for if statement</pre> <p>Example:</p> <pre>if temperature > 30: print("It's a hot day!")</pre>
If-Elif-Else	Executes the first code block if condition1 is `True`, otherwise checks condition2, and so on. If no condition is `True`, the else block is executed.	<p>Syntax:</p> <pre>if condition1: # Code if condition1 is True elif condition2: # Code if condition2 is True else: # Code if no condition is True</pre> <p>Example:</p> <pre>score = 85 # Example score if score >= 90: print("You got an A!") elif score >= 80: print("You got a B.") else: print("You need to work harder.") # Output = You got a B.</pre>
If-Else Statement	Executes the first code block if the condition is `True`, otherwise the second block.	<p>Syntax:</p> <pre>if condition: # Code, if condition is True else: # Code, if condition is False</pre> <p>Example:</p> <pre>if age >= 18: print("You're an adult.") else: print("You're not an adult yet.")</pre>
Less Than or Equal To(<=)	Checks if the value of variable1 is less than or equal to variable2.	<p>Syntax:</p> <pre>variable1 <= variable2</pre> <p>Example 1:</p> <pre>5 <= 5 and 3 <= 5</pre> <p>returns True</p> <p>Example 2:</p> <pre>size = 38 max_size = 40 size <= max_size</pre> <p>returns True</p>
Less Than(<)	Checks if the value of variable1 is less than variable2.	<p>Syntax:</p> <pre>variable1 < variable2</pre> <p>Example 1:</p> <pre>4 < 6</pre> <p>returns True</p> <p>Example 2:</p> <pre>score = 60 passing_score = 65 score < passing_score</pre> <p>returns True</p>

Loop Controls	<code>`break`</code> exits the loop prematurely. <code>`continue`</code> skips the rest of the current iteration and moves to the next iteration.	<p>Syntax:</p> <pre>for: # Code to repeat if # boolean statement break for: # Code to repeat if # boolean statement continue</pre> <p>Example 1:</p> <pre>for num in range(1, 6): if num == 3: break print(num)</pre> <p>Example 2:</p> <pre>for num in range(1, 6): if num == 3: continue print(num)</pre>
NOT	Returns <code>`True`</code> if variable is <code>`False`</code> , and vice versa.	<p>Syntax:</p> <pre>!variable</pre> <p>Example:</p> <pre>!isLocked</pre> <p>returns True if the variable is False (i.e., unlocked).</p>
Not Equal(!=)	Checks if two values are not equal.	<p>Syntax:</p> <pre>variable1 != variable2</pre> <p>Example:</p> <pre>a = 10 b = 20 a != b</pre> <p>returns True</p> <p>Example 2:</p> <pre>count=0 count != 0</pre> <p>returns False</p>
Object Creation	Creates an instance of a class (object) using the class constructor.	<p>Syntax:</p> <pre>object_name = ClassName(arguments)</pre> <p>Example:</p> <pre>person1 = Person("Alice", 25)</pre>
OR	Returns <code>`True`</code> if either statement1 or statement2 (or both) are <code>`True`</code> . Otherwise, returns <code>`False`</code> .	<p>Syntax:</p> <pre>statement1 statement2</pre> <p>Example:</p> <pre>"Farewell Party Invitation" Grade = 12 grade == 11 or grade == 12</pre> <p>returns True</p>
range()	Generates a sequence of numbers within a specified range.	<p>Syntax:</p> <pre>range(stop) range(start, stop) range(start, stop, step)</pre> <p>Example:</p> <pre>range(5) #generates a sequence of integers from 0 to 4. range(2, 10) #generates a sequence of integers from 2 to 9. range(1, 11, 2) #generates odd integers from 1 to 9.</pre>
Return Statement	<code>`Return`</code> is a keyword used to send a value back from a function to its caller.	<p>Syntax:</p> <pre>return value</pre> <p>Example:</p> <pre>def add(a, b): return a + b result = add(3, 5)</pre>
Try-Except Block	Tries to execute the code in the try block. If an exception of the specified type occurs, the code in the	<p>Syntax:</p> <pre>try: # Code that might raise an exception except</pre>

	except block is executed.	<p>ExceptionType: # Code to handle the exception</p> <p>Example:</p> <pre>try: num = int(input("Enter a number: ")) except ValueError: print("Invalid input. Please enter a valid number.")</pre>
Try-Except with Else Block	Code in the `else` block is executed if no exception occurs in the try block.	<p>Syntax:</p> <pre>try: # Code that might raise an exception except ExceptionType: # Code to handle the exception else: # Code to execute if no exception occurs</pre> <p>Example:</p> <pre>try: num = int(input("Enter a number: ")) except ValueError: print("Invalid input. Please enter a valid number") else: print("You entered:", num)</pre>
Try-Except with Finally Block	Code in the `finally` block always executes, regardless of whether an exception occurred.	<p>Syntax:</p> <pre>try: # Code that might raise an exception except ExceptionType: # Code to handle the exception finally: # Code that always executes</pre> <p>Example:</p> <pre>try: file = open("data.txt", "r") data = file.read() except FileNotFoundError: print("File not found.") finally: file.close()</pre>
While Loop	A `while` loop repeatedly executes a block of code as long as a specified condition remains `True`.	<p>Syntax:</p> <pre>while condition: # Code to repeat</pre> <p>Example:</p> <pre>count = 0 while count < 5: print(count) count += 1</pre>



Skills Network

© IBM Corporation. All rights reserved.