

GLOSSARY OF WEB APPLICATION DEVELOPMENT TERMS:

A Programming Language (APL): Is an expressive, symbolic programming language that uses a unique set of symbols and unconventional syntax, allowing for concise and powerful code.

Accounting: The work of preparing the financial records of people, companies, or organizations.

Access control: Mechanisms to manage who can view or use resources in a computing environment.

Active passive failover: A failover configuration where one system is actively handling traffic while another is on standby, ready to take over in case of failure.

Agenda: A list of matters to be discussed at a meeting.

Agile development: A methodology focused on iterative development, flexibility, and collaboration between teams.

Agreement: The situation in which people have the same opinion, or in which they approve of or accept something.

AJAX (Asynchronous JavaScript and XML): A technique for creating interactive web applications by exchanging data with a server without refreshing the page.

Algorithm: A set of step-by-step instructions used to solve a specific problem or perform a task.

Allocation: The process of giving someone their part of a total amount of something to use in a particular way.

Allowance: Money that you are given regularly, especially to pay for a particular thing.

Anchor tag: The HTML element <a> used to create hyperlinks.

Angel investor: A wealthy individual who provides capital to start-ups or early-stage companies in exchange for ownership equity or convertible debt, often offering mentorship, expertise, and networking opportunities.

Angular: A popular open-source web application framework developed by Google for building dynamic web apps.

Application Delivery Controller (ADC): A device or software that manages and optimizes the delivery of applications across networks.

Application layer: The top layer of the OSI model that provides network services directly to applications.

Application Programming Interface (API): A set of protocols and tools for building and interacting with software applications.

ARIA (Accessible Rich Internet Applications): A set of attributes for making web content and applications more accessible to people with disabilities.

Array: A collection of elements, typically of the same type, stored in contiguous memory locations.

ASCII (American Standard Code for Information Interchange): A character encoding standard for electronic communication.

Aspect ratio: The proportional relationship between the width and height of an element, often used in responsive design.

Assembler: A program that translates assembly language into machine code.

Asset: A useful or valuable quality, skill, or person.

Asset pipeline: A feature in some web development frameworks for managing and optimizing assets like images, CSS, and JavaScript.

Asynchronous programming: A programming model that allows functions to execute without waiting for others to complete.

Asynchronous Transfer Mode (ATM): A networking technology that uses fixed-size cells to transmit data, often used in high-speed networks.

Atom: An XML-based web syndication format used for content feeds.

Attributes: Properties added to HTML elements to provide additional information or functionality.

Audit: A systematic examination, review, or inspection of financial records, statements, or processes conducted by independent auditors to verify accuracy, compliance, and reliability, providing assurance to stakeholders and regulators.

Authentication: The process of verifying the identity of a user or system.

Authorization: The process of determining if a user has permission to perform a specific action.

Awareness: Knowledge that something exists, or understanding of a situation or subject at the present time based on information or experience.

B2B (Business-to-Business): Web applications designed to facilitate commerce or interactions between businesses.

B2C (Business-to-Consumer): Web applications designed for interactions or transactions between businesses and consumers.

Back-end: The server-side portion of a web application responsible for processing logic, database interactions, and server configuration.

Backbone: The principal data routes between large, strategically interconnected networks and core routers in a network.

Background: Used to refer to something that is done before, and in preparation for, something else.

Backup: A copy of data stored separately for recovery in case of data loss or corruption. Besides it can also refer to someone or something that provides support or help, or something that you have arranged in case your main plans, equipment, etc. go wrong.

Bandwidth: The maximum rate at which data can be transferred over a network connection.

Bandwidth management: Techniques used to control and allocate bandwidth usage on a network to ensure efficient operation.

Bandwidth throttling: The intentional slowing down of internet speed by an ISP or network administrator to manage network congestion.

Benchmark(ing): A standard or reference point used for comparison or evaluation of performance, returns, or investment results, such as market indices, peer groups, or predetermined metrics, serving as a basis for analysis and decision-making.

Bill: A request for payment of money owed, or the piece of paper on which it is written.

Binary: A base-2 number system used by computers to represent data using 0s and 1s.

BIOS (Basic Input/Output System): Firmware that initializes and tests hardware components during boot-up.

Bit: The smallest unit of data in computing, representing a binary value of 0 or 1.

Bit rate: The number of bits transmitted or received per unit of time, often measured in bits per second (bps).

Blockchain: A decentralized and distributed digital ledger used to record transactions across multiple computers.

Blue-sky: Using the imagination to think of ideas that do not yet have practical uses or make money.

Body tag: The HTML <body> element that contains the content of a webpage.

Boot: The process of starting up a computer and loading the operating system.

Boot sequence: The process a computer goes through to load the operating system and its associated files during startup.

Bootloader: Software that loads the operating system into memory when a computer starts up.

Boost: To increase or improve something.

Bootstrap: A popular front-end framework used to create responsive and mobile-first websites.

Bootstrap grid: A system of rows and columns used for creating flexible and responsive web layouts.

Border Gateway Protocol (BGP): A standardized exterior gateway protocol used to exchange routing information between different systems on the internet.

Branch: One of the offices or groups that form part of a large business organization.

Branding: The act of making a product, organization, person, or place easy to recognize as different from others by connecting it with a particular name, design, set of qualities, etc.

Breakpoint: A predefined point in responsive design where the layout changes to accommodate different screen sizes.

Bridge: A device that connects and filters traffic between two or more network segments, operating at the data link layer.

Briefing: Information that is given to someone just before they do something, or a meeting where this happens.

Brochure: A type of small magazine that contains pictures and information on a product or a company.

Browser: A software application used to access and display websites.

Budget: The amount of money you have available to spend.

Bug: An error or flaw in software that causes it to behave unexpectedly.

Bundle: A grouping of assets such as JavaScript and CSS files to optimize performance in web applications.

Bus: A communication system that transfers data between components inside or between computers.

Business: The activity of buying and selling goods and services.

Byte: A unit of digital information that consists of eight bits.

C2C (*abbreviation for Consumer-To-Consumer*): Relating to the buying and selling of products, services, and information between individual consumers, especially over the internet.

Cache: A hardware or software component that stores data to serve future requests more quickly.

Carbon Copy (CC): Written at the end of a business letter or in an email before the names of the people who will receive a copy.

Cash cow: A product or service that makes a lot of money over a long period of time for the company that sells it, often money that is used to support the company's other activities.

Chairman: A person in charge of a meeting or organization. President.

Checksum: A value used to verify the integrity of data by detecting errors.

Chief Executive Officer (CEO): The person with the most important position in a company.

Cipher: An algorithm for performing encryption or decryption.

Classless Inter-Domain Routing (CIDR): A method for allocating IP addresses and routing IP packets that replaces traditional class-based network addressing.

Client-server architecture: A network design where clients request resources or services from servers, which provide the requested resources.

Cloud computing: Delivery of computing services over the internet, including storage, processing, and networking.

Cloud Management Platform (CMP): Software tools that help manage and optimize cloud infrastructure and services.

Cloud storage: A service that stores data on remote servers accessed via the internet, providing scalability and redundancy.

Cluster: A group of similar things that are close together, sometimes surrounding something.

CMS (Content Management System): A software platform that allows users to create, manage, and modify content on a website without needing specialized technical knowledge.

Colleague: One of a group of people who work together.

Command Line Interface (CLI): A text-based interface used to interact with a computer by typing commands.

Commodity: A substance or product that can be traded, bought, or sold.

Compiler: A program that translates source code from a high-level programming language into machine code.

Compliance: The act of obeying a law or rule, especially one that controls a particular industry or type of work.

Configuration management: The discipline of managing and controlling the configurations of software and hardware systems.

Content Delivery Network (CDN): A network of distributed servers that deliver web content and services to users based on their geographic location.

Cookie: A small piece of data stored on a user's device by a website to remember information across sessions.

Core: The basic and most important part of something.

Corporate Social Responsibility (CSR): The voluntary commitment of businesses to integrate environmental, social, and ethical concerns into their operations, strategies, and interactions with stakeholders, aiming to create sustainable value for society and the environment, beyond financial profits.

CPU (Central Processing Unit): The primary component of a computer that performs most of the processing tasks.

Cross-browser compatibility: The ability of a website or application to function correctly across different web browsers.

Cross-site scripting (XSS): A type of security vulnerability in which an attacker injects malicious scripts into content that other users view.

CRUD (Create, Read, Update, Delete): The four basic operations that can be performed on data in a database.

CSS (Cascading Style Sheets): A style sheet language used for describing the presentation of a document written in HTML or XML.

CSS grid: A layout system in CSS that allows developers to create complex, responsive grid-based designs.

Customer: A person who buys goods or a service.

Customer Relationship Management (CRM): Ways that a company can encourage customers to like it and buy from it, for example by using software to look at information it has about its customers and by using social media.

Cutting-edge technology: Advanced or innovative technology that represents the latest developments in a particular field or industry.

CY: Abbreviation for *Current Year*.

Dashboard: Part of a device, a computer program, etc. that shows information and statistics (= numbers) about how the device, program, etc. is working, which you can use to control it.

Data center: A facility used to house computer systems and associated components, such as telecommunications and storage systems.

Data Loss Prevention (DLP): A strategy and tools used to prevent unauthorized access or loss of sensitive data.

Data Encryption Standard (DES): A symmetric-key algorithm used for data encryption, now considered insecure due to advances in computing power.

Data mining: The practice of analyzing large datasets to extract useful patterns and insights.

Data warehouse: A centralized repository for storing and analyzing large amounts of data from multiple sources.

Database: A structured collection of data stored electronically.

Deadline: A time or day by which something must be done.

Debugging: The process of finding and resolving errors or bugs in software.

Decapsulation: The process of removing headers or metadata from data packets to retrieve the original data.

Defragmentation: The process of reorganizing the data on a disk to reduce fragmentation and improve efficiency.

Demilitarized Zone (DMZ): A network segment that separates an internal network from an external network, providing an additional layer of security.

Dependency injection: A design pattern in which an object receives other objects it depends on, rather than creating them itself.

Deployment: The process of releasing a web application or update to a live server or production environment.

DevOps: A set of practices that combines software development and IT operations to shorten development cycles and improve reliability.

Directory service: A service that stores and manages information about resources on a network, including users and permissions.

Disaster recovery: Strategies and processes for recovering systems and data in the event of a catastrophic failure.

Distributed computing: A system in which computing resources are spread across multiple machines to work together.

DOM (Document Object Model): A programming interface for HTML and XML documents that defines the structure of a webpage as a tree of objects.

Domain: A group of networked computers and devices that are administered as a unit with common rules and procedures.

Domain Name System (DNS): A system that translates human-friendly domain names to IP addresses.

Downsizing: The practice of making a company or an organization smaller by reducing the number of people working for it, or an occasion when this is done.

Drive mapping: The process of assigning a drive letter to a shared network folder, making it accessible as if it were a local drive.

Driver: A program that controls or operates hardware attached to a computer.

Dynamic content: Web content that changes based on user interaction, time, or other factors, as opposed to static content.

Dynamic Host Configuration Protocol (DHCP): A network management protocol used to automatically assign IP addresses to devices on a network.

Dynamic Link Library (DLL): A file containing code that can be used by multiple programs simultaneously.

EJS (Embedded JavaScript): A simple templating language that lets you generate HTML markup with plain JavaScript.

Elastic Load Balancer (ELB): A service that automatically distributes incoming application traffic across multiple targets, such as EC2 (Elastic Compute Cloud) instances.

Elasticity: The capability of a system to dynamically allocate and deallocate resources based on demand.

Elevator pitch: A short but effective explanation that is intended to persuade someone to buy a product or accept an idea.

Encryption: The process of converting data into a coded form to prevent unauthorized access.

Endpoint: Any device that connects to a network, such as a computer, smartphone, or printer.

Endpoint Detection and Response (EDR): Security solutions that monitor and respond to threats on endpoint devices.

Endpoint protection: Security measures designed to protect end-user devices such as computers and smartphones from threats.

Entrepreneur: An individual who organizes, manages, and assumes the risks of a business venture or start-up, seeking to create value, innovate, and capitalize on opportunities by bringing together resources, ideas, and efforts to address market needs or solve problems.

Environmental, Social, and Governance (ESG): A set of criteria, principles, or standards used by investors, companies, and financial institutions to evaluate and integrate environmental, social, and governance factors into investment decisions, risk assessment, and corporate practices.

Error handling: The process of responding to and managing errors or exceptions that occur during the execution of a program.

Etag (Entity Tag): A unique identifier assigned by the server to a specific version of a resource, used to track changes and cache versions.

Ethernet: A network technology used for wired local area networks (LANs).

Event listener: A function in JavaScript that waits for a specific event, such as a mouse click or keypress, and responds to it.

Event log: A file or database that records system events and activities for monitoring and troubleshooting purposes.

Event propagation: The process by which an event is passed or "bubbled" through the DOM from the target element to its ancestors or vice versa.

Expense: The use of money, time, or effort.

Expertise: A high level of knowledge or skill.

Extranet: A private network that uses internet protocols and technologies to securely share part of an organization's information with external partners.

Facility: A place, especially including buildings, where a particular activity happens.

Failover: The process of switching to a redundant or standby server, system, or network in the event of a failure.

Favicon: A small icon associated with a website or webpage that appears in browser tabs and bookmarks.

Feature: A typical quality or an important part of something.

Fee: An amount of money paid for a particular piece of work or for a particular right or service.

Feedback: Information or statements of opinion about something, such as a new product, that can tell you if it is successful or liked.

Field: An area of activity or interest.

Figure: The symbol for a number or an amount expressed in numbers.

File Transfer Protocol (FTP): A standard network protocol used to transfer files between a client and server over a network.

Firewall: A network security system that monitors and controls incoming and outgoing network traffic based on predetermined security rules.

Firewall rules: Set of rules that define what traffic is allowed or blocked by a firewall.

Firewall policy: A set of rules configured in a firewall to control the traffic allowed to enter or leave a network.

Firmware: Software programmed into read-only memory (ROM) that controls hardware.

Firmware update: A software update for embedded systems that enhances functionality or fixes bugs.

Forecast: A statement of what is judged likely to happen in the future, especially in connection with a particular situation, or the expected weather conditions.

Form validation: The process of ensuring that user input in a form is valid before sending it to the server.

Forward proxy: A server that forwards requests from clients to other servers, often used for filtering and anonymization.

Frame: A digital data packet used in communication protocols.

Framework: A collection of tools, libraries, and best practices that developers use to build web applications more efficiently.

Franchise: A business model or arrangement in which an individual or entity (franchisee) is granted the right to operate a business or sell products or services under the brand, trademarks, and systems of another company (franchisor), in exchange for fees, royalties, and compliance with franchise standards.

Freeware: Software that is available for use at no cost.

Front-end: The client-side portion of a web application responsible for what users interact with directly.

Full Disk Encryption (FDE): The encryption of an entire disk to protect data at rest on a storage device.

Full duplex: A communication mode where data transmission can occur simultaneously in both directions.

Full-stack developer: A developer who works on both the front-end and back-end of a web application.

Function: A block of reusable code designed to perform a specific task in a program.

Funnel: Especially in e-commerce (= the business of selling things on the internet), the process that a customer goes through from first hearing about a product, for example through an internet search or advertisement, to buying the product, with a smaller number of customers at each stage of the process.

FYI: Abbreviation for *For Your Information*.

Game changer: Something such as a product or event that affects a situation or area of business very much.

Garbage collection: The process of automatically reclaiming memory that is no longer in use by a program.

Gartner: A global research and advisory firm that provides insights and analysis on various IT and business topics.

Gateway: A network device that connects two different networks and allows data to flow between them.

Gateway protocol: A protocol used by a gateway to manage and translate communication between different network protocols.

Giga: A prefix in the metric system denoting a factor of one billion (10^9), commonly used to describe data sizes and speeds.

Gigabit: A unit of data equal to one billion bits, used to measure network speed and bandwidth.

Gigabit ethernet: A version of Ethernet with a maximum data rate of 1 gigabit per second.

Git: A version control system used for tracking changes in source code during software development.

Golden handshake: A generous severance or retirement package offered to an executive or employee upon leaving a company, often as a reward for long service or as part of a merger or acquisition.

GPU (Graphics Processing Unit): A specialized processor used to render graphics in computers.

Graphical User Interface (GUI): An interface that allows users to interact with software through graphical elements such as windows, icons, and buttons.

Grid system: A layout system used to organize content on a webpage using rows and columns.

Group policy: A feature of Microsoft Windows that provides centralized management and configuration of operating systems, applications, and users' settings.

Group Policy Object (GPO): A collection of Group Policy settings that can be applied to users or computers.

Hard Drive: A device used to store data permanently in a computer system.

Hardware: The physical and electronic parts of a computer, or metal tools and equipment.

Hash Function: A function that converts input data into a fixed-size value or hash, often used for data verification.

Hashing: The process of converting data into a fixed-size string of characters, usually for secure storage or verification.

Heap Memory: A memory region used for dynamic memory allocation in programming.

Hop: the number of routers that a packet (a portion of data) passes through from its source to its destination.

Host: Any device connected to a network that has an IP address and can communicate with other devices on the network.

Hosting: The service of storing and serving web content from a server to make it accessible on the internet.

Hotfix: A software update designed to fix a specific issue or bug.

Hover State: A visual effect or style applied to an element when the user hovers over it with a mouse pointer.

HTML (Hypertext Markup Language): The standard markup language used to create and structure content on the web.

HTTP (Hypertext Transfer Protocol): The protocol used for transmitting web pages over the internet.

HTTP/2: The second major version of the HTTP network protocol used by the World Wide Web, designed to improve performance.

HTTPS (Hypertext Transfer Protocol Secure): An extension of HTTP that adds security through encryption using SSL/TLS.

Hub: A basic networking device that connects multiple computers or other devices in a network, allowing them to communicate with each other.

Hybrid app: A mobile application built using web technologies (HTML, CSS, and JavaScript) and then wrapped in a native container for mobile platforms.

Hyperlink: A reference or navigation element in a web page that directs users to another document or web page when clicked.

Hyper-V: Microsoft's virtualization technology that allows the creation and management of virtual machines on Windows servers.

Hypervisor: A software layer that enables multiple virtual machines to run on a single physical machine.

Hypervisor type 1: A hypervisor that runs directly on the host's hardware to manage guest operating systems, also known as a bare-metal hypervisor.

Hypervisor type 2: A hypervisor that runs on top of an existing operating system to manage guest operating systems, also known as a hosted hypervisor.

Icon fonts: Fonts that use symbols and pictograms in place of traditional alphanumeric characters to represent icons.

ID selector: A CSS selector that targets a specific element by its unique id attribute.

Image backup: A backup that captures the entire contents of a disk or partition, including the operating system and applications.

Image optimization: The process of reducing the file size of images without sacrificing quality to improve web performance.

Incident response: The process of detecting, managing, and mitigating security incidents or breaches.

Income: Money that is earned from doing work or received from investments.

Infinite scroll: A web design technique where more content is loaded as the user scrolls down the page.

Infrastructure as Code (IaC): The practice of managing and provisioning computing infrastructure through machine-readable configuration files.

Inheritance: A concept in object-oriented programming where one class takes on the properties and methods of another class.

Input: Something such as energy, money, or information that is put into a system, organization, or machine so that it can operate.

Input field: An HTML element that allows users to enter data into a form.

Insight: (The ability to have) a clear, deep, and sometimes sudden understanding of a complicated problem or situation.

Inspector: A developer tool in web browsers that allows you to inspect and modify the HTML and CSS of a webpage in real-time.

Instance: A single occurrence of an object created in memory during program execution.

Interface: A contract that defines the structure of a system, class, or API without specifying the implementation.

Internal linking: Hyperlinks that point to other pages within the same website, helping with navigation and SEO.

Internationalization (i18n): The process of designing and developing applications to support multiple languages and regions.

Internet Service Provider (ISP): A company that provides individuals and organizations access to the internet.

In the red: Refers to a situation in which a company or individual is operating at a financial loss or has negative net assets.

Intranet: A private network accessible only to an organization's staff.

Intrusion Detection System (IDS): A system that monitors network traffic for suspicious activity and potential threats.

Intrusion Prevention System (IPS): A system that monitors network traffic and takes action to block potential threats.

IoT (Internet of Things) - A network of interconnected devices that collect and share data.

IP (Internet Protocol): A set of rules that govern how data is sent and received over a network.

IP address: A unique address that identifies a device on a network.

IP Address Management (IPAM): The planning, managing, and tracking of IP address allocations in a network.

IPSec (Internet Protocol Security): A suite of protocols designed to ensure the integrity, authenticity, and confidentiality of data transmitted over IP networks.

ISDN (Integrated Services Digital Network): A set of communication standards for digital telephony and data transmission.

Invoice: a list of goods sent or services provided, with a statement of the sum due for these; a bill.

Java Virtual Machine (JVM): An engine that enables Java bytecode to run on any device or operating system that has a JVM installed.

JavaScript: A scripting language commonly used to create dynamic content on web pages.

Jitter: Variability in packet arrival times that can affect network performance.

Jitter buffer: A buffer used in VoIP and streaming to smooth out variations in packet arrival times.

Job queuing: The process of managing tasks or jobs in a queue to be processed by a system or application.

Job scheduler: A system tool that automates the execution of tasks at specified times or intervals.

JSON (JavaScript Object Notation): A lightweight data interchange format that is easy for humans to read and write and easy for machines to parse and generate.

Jumbo Frame: An Ethernet frame with a payload larger than the standard size, which can improve network performance.

Junction Point: A type of reparse point in Windows that creates a link to a directory, allowing it to appear in multiple locations.

Kerberos: A network authentication protocol designed to provide strong authentication for client-server applications.

Kernel: The core component of an operating system that manages system resources and allows communication between hardware and software.

Kerning: The process of adjusting the space between characters in text for better visual appearance.

Key management: The process of handling cryptographic keys in a secure manner, including their generation, distribution, and storage.

Key Performance Indicator (KPI): A measurable metric or data point that is used to evaluate the performance, progress, or success of an organization, project, or initiative against strategic objectives, goals, or benchmarks, guiding decision-making, accountability, and continuous improvement.

Keyframe animation: In CSS, a way to define the intermediate steps in an animation sequence.

Keylogger: A type of malware that records every keystroke a user makes to capture sensitive information.

Keystroke logger: A tool or software that records all the keys pressed on a keyboard, often used for monitoring or malicious purposes.

Keyword: A reserved word in a programming language that has a predefined meaning and cannot be used as a variable name.

Know-how: Practical knowledge and ability.

Knowledge base: A repository of information and solutions related to system administration and troubleshooting.

Kubernetes: An open-source platform for automating the deployment, scaling, and management of containerized applications.

KVM Switch (Keyboard, Video, Mouse Switch): A device that allows multiple computers to be controlled from a single set of peripherals.

LAN (Local Area Network): A network that connects devices within a limited geographic area, such as a home, office, or campus.

Landlord: A person or organization that owns a building or an area of land and is paid by other people for the use of it.

Lazy loading: A design pattern that delays the loading of resources (such as images) until they are needed to improve initial load performance.

LDAP (Lightweight Directory Access Protocol): A protocol used to access and manage directory information services over a network.

LDAP bind: The process of authenticating to an LDAP directory server to perform directory operations.

LDAP injection: A type of attack that exploits vulnerabilities in LDAP queries to access or modify directory services.

Lease: To make a legal agreement by which money is paid in order to use land, a building, a vehicle, or a piece of equipment for an agreed period of time.

Liability: The fact that someone is legally responsible for something.

Linting: The process of analyzing code to identify potential errors, bugs, or style issues.

Load balancer: A device or software that distributes network or application traffic across multiple servers to ensure no single server becomes overwhelmed.

Load testing: The process of testing a system's performance under a specific load to ensure it can handle expected user traffic.

Local storage: A web storage API that allows websites to store data locally within the user's browser, with no expiration time.

Localization (l10n): The process of adapting a product or content to meet the language, cultural, and other requirements of a specific region or locale.

Logging: The process of recording events, errors, and other significant information generated by system processes or applications.

Logical drive: A virtualized drive that represents a portion of a physical storage device.

Logical volume: A virtual storage unit created from one or more physical volumes in a logical volume management system.

Loop: A programming construct that repeats a block of code multiple times until a condition is met.

Loss: The fact that you no longer have something or have less of something.

LY: Abbreviation for *Last Year*.

MAC Address (Media Access Control Address): A unique identifier assigned to network interfaces for communications on the physical network segment.

Malware: Malicious software designed to harm or exploit any device, network, or service.

Managed Service Provider (MSP): A company that remotely manages a client's IT infrastructure and end-user systems on a proactive basis.

Manager: The person who is responsible for managing an organization.

Markdown: A lightweight markup language used to format plain text and convert it into HTML or other formats.

Meeting: A group of people who have met for a particular purpose.

Memory leak: A situation where a program consumes memory resources without releasing them, potentially leading to system performance issues.

Mergers and Acquisitions (M&A): The process of combining or integrating two or more companies through mergers, acquisitions, consolidations, or partnerships, often as strategic moves for growth, diversification, synergy, or market expansion, with implications for corporate finance, valuation, and competition.

MIB (Management Information Base): A database used for managing the entities in a communication network.

Microservices: An architectural style that structures an application as a collection of loosely coupled services, each responsible for a specific function.

Middleware: Software that provides common services and capabilities to applications beyond what the operating system offers.

Minification: The process of removing unnecessary characters from source code (like spaces and comments) to reduce file size and improve load times.

Mirroring: The process of copying data from one storage location to another for redundancy and fault tolerance.

Monitoring agent: A software component installed on a system to collect and report performance and health metrics to a monitoring system.

Motherboard: The main circuit board in a computer that connects the CPU, memory, and other components.

Namespace: A container that allows you to group related identifiers like classes, functions, and variables to avoid name collisions in code.

NAT (Network Address Translation): A method of remapping one IP address space into another, commonly used to allow multiple devices on a local network to share a single public IP address.

NAS (Network Attached Storage): A file-level storage device connected to a network that provides data access to various clients.

Nested routes: A feature in routing systems where routes can be nested within each other, allowing for complex navigation patterns in web apps.

NetFlow: A network protocol used for collecting IP traffic information and monitoring network traffic.

Network: A group of computers and devices connected together to share resources and communicate with each other.

Network interface: The point of connection between a computer and a network, typically provided by a network card or adapter.

Network latency: The time it takes for a packet of data to travel from its source to its destination across a network.

Network segmentation: The practice of dividing a network into smaller segments to improve performance and security.

Network topology: The arrangement of different elements (links, nodes, etc.) in a computer network.

Networking: The activity of meeting people who might be useful to know, especially in your job.

NIC (Network Interface Card): A hardware component that allows a computer to connect to a network.

NIC (Network Interface Controller): The hardware component that connects a computer to a network and enables communication.

Node: Any active electronic device attached to a network, such as a computer, router, or switch.

Normalization: The process of structuring a relational database to reduce redundancy and improve data integrity.

NTP (Network Time Protocol): A protocol used to synchronize the clocks of computers over a network.

Object storage: A storage architecture that manages data as objects, providing scalability and metadata capabilities.

Observer pattern: A design pattern in which an object, called the subject, maintains a list of its dependents, called observers, and notifies them of any state changes.

Octet: A group of eight bits, often used in networking to represent an 8-bit number.

OID (Object Identifier): A globally unique identifier used in networking and other fields to identify an object or entity.

On-demand service: A model where services are provided as needed, often used in cloud computing.

One-to-Many Relationship: A type of database relationship where a single record in one table can be related to multiple records in another table.

OOP (Object-Oriented Programming): A programming paradigm based on the concept of objects, which can contain data and code, such as fields and methods.

Open source: Software for which the original source code is made freely available and may be modified and distributed.

Operating System (OS): Software that manages computer hardware and software resources and provides common services for computer programs.

Operating System image: A snapshot of the operating system and installed software used for deployment or recovery purposes.

Optimization: The process of improving the performance, efficiency, or speed of a website or application.

ORM (Object-Relational Mapping): A technique for mapping object-oriented classes to relational database tables, allowing developers to interact with databases using objects.

OSI Model (Open Systems Interconnection Model): A conceptual framework used to understand and standardize network communication into seven layers.

Outage: A period when a system, service, or network is unavailable or not functioning correctly.

Out of the box: If something can be used out of the box, it can be used immediately, without a lot of effort being needed to prepare it.

Outbound traffic: Data sent from an internal network to an external network.

Outcome: A result or effect of an action, situation, etc.

Outperform: To do well in a particular job or activity compared to others of a similar type.

Output: The amount that is produced by a person, machine, factory, country, etc.

Outsourcing: The process of paying to have part of a company's work done by another company.

Overclocking: The practice of increasing the clock speed of a computer's CPU or GPU beyond its official limits to improve performance.

Overdue: Not done or happening when expected or when needed. Late.

Overflow: In CSS, this refers to how content is handled when it exceeds the size of its container.

Overprovisioning: Allocating more resources than needed to ensure that performance is maintained even under peak load conditions.

Owner: Someone who owns something.

PaaS (Platform as a Service): A cloud computing service that provides a platform allowing customers to develop, run, and manage applications.

Pagination: A user interface pattern that divides content into multiple pages, often used in data-heavy web applications.

Part time: If you work part-time or do part-time work, you work for only some of the day or the week.

Patch: A software update designed to fix bugs, vulnerabilities, or improve functionality.

Patch management: The process of managing updates and patches for software to address security vulnerabilities and bugs.

Payroll: The total amount of money paid to the people employed by a particular company.

Peanuts: Something so small it is not worth considering, especially an amount of money.

Performance: How successful an investment, company, software, etc. is and how much profit it makes.

Performance monitoring: The practice of observing and measuring the performance of systems and networks to ensure they are operating efficiently.

Performance tuning: Adjusting system settings and configurations to optimize performance and efficiency.

Ping: A network diagnostic tool used to test the reachability of a host and measure round-trip time for messages sent to that host.

Policy: A set of ideas or a plan of what to do in particular situations that has been agreed to officially by a group of people, a business organization, a government, or a political party.

Polyfill: A piece of code (or plugin) used to provide modern functionality in older browsers that do not support newer features.

Port: A communication endpoint in networking, often associated with specific services or protocols.

Port forwarding: A network configuration that redirects traffic from one port to another, often used to allow external access to internal services.

Preprocessing: The act of transforming source code, like Sass or LESS, into standard CSS or JavaScript before sending it to the browser.

Profit: Money that is earned in trade or business after paying the costs of producing and selling goods and services.

Progressive Web App (PWA): A type of web app that can work offline and offers features like push notifications, native-like performance, and installation on a device.

Promise: An object in JavaScript representing the eventual completion or failure of an asynchronous operation and its resulting value.

Proposal: A suggestion, sometimes a written one.

Protocol: A set of rules or standards that govern how data is transmitted and received over a network.

Prototype: In JavaScript, every object has a prototype from which it can inherit properties and methods.

Proxy: A server that acts as an intermediary between a client and another server, often used for security or performance reasons.

Public Key Infrastructure (PKI): A framework for managing digital keys and certificates used for secure communication and authentication.

Purchase: To buy something.

QBR: Abbreviation for *Quarterly Business Review*.

QoS (Quality of Service): A set of technologies and techniques to manage network traffic and ensure the performance of critical applications.

Quality Assurance (QA): The process of ensuring that a product or service meets certain quality standards before it is delivered to users.

Quality of Experience (QoE): A measure of user satisfaction with a service, considering factors such as performance, reliability, and usability.

Quarantine: A security measure that isolates infected or suspicious files to prevent the spread of malware.

Qubit: The basic unit of quantum information, analogous to a bit in classical computing but can represent both 0 and 1 simultaneously.

Query: A request for information from a database or network service.

Query language: A language used to make queries to databases, such as SQL for relational databases.

Query optimization: Techniques used to improve the efficiency of database queries, reducing execution time and resource usage.

Queue: A data structure used to manage tasks or data waiting to be processed.

Quick Response (QR) Code: A type of matrix barcode used to store information that can be read by smartphones and other devices.

RADIUS (Remote Authentication Dial-In User Service): A networking protocol that provides centralized Authentication, Authorization, and Accounting (AAA) management.

RAID (Redundant Array of Independent Disks): A data storage virtualization technology that combines multiple physical disk drive components into one or more logical units.

RAM (Random Access Memory): A type of volatile memory used by a computer to store data that is actively being used or processed.

Ransomware: A type of malware that encrypts a user's data and demands a ransom for its decryption.

Recursive function: A function that calls itself in order to solve smaller instances of a problem.

Red-black tree: A type of self-balancing binary search tree used in computer science to maintain sorted data.

Redundancy: The inclusion of extra components or systems to provide backup in case of failure, improving reliability and availability.

RegEx (Regular Expression): A sequence of characters that form a search pattern, used for string searching and manipulation.

Regression analysis: A statistical method or technique used to analyse the relationship between two or more variables by estimating the effect of one variable on another, identifying patterns, trends, or correlations in data, and making predictions or forecasts based on statistical models.

Regulatory compliance: The process or practice of ensuring that an organization, business, or individual follows laws, regulations, standards, and ethical guidelines relevant to their industry, operations, products, or services, to mitigate legal risks, liabilities, and penalties.

Relational database: A type of database that stores data in tables with predefined relationships between them.

Reliability: The quality of being able to be trusted or believed because of working or behaving well.

Remote desktop: A technology that allows users to access and control a computer from a remote location.

Remote Procedure Call (RPC): A protocol that allows a program to execute code on a remote server as if it were a local procedure call.

Rendering: The process of generating and displaying visual content from code, like turning HTML, CSS, and JavaScript into a web page.

Report: To give a description of something or information about it to someone.

Responsive design: A web design approach that ensures websites look good on all devices and screen sizes by adapting the layout.

Retail: The activity of selling goods to the public, usually in shops.

Return on Investment (ROI): A financial metric or performance measure that evaluates the profitability or efficiency of an investment by comparing the gain or return generated relative to the investment cost or initial capital outlay, calculated as a percentage of the investment amount.

Revenue: The total income or sales generated by a business or organization from its primary operations, activities, or sources, before deducting expenses, costs, and taxes, representing the top line of the income statement and a key measure of business performance.

Road map: A plan for how to achieve something.

Role-Based Access Control (RBAC): A method of restricting system access based on the roles assigned to users within an organization.

Root user: The superuser account in Unix and Linux systems with full administrative privileges.

Router: A device that forwards data packets between computer networks, directing traffic based on IP addresses.

Routing: The process of determining which content to display based on the current URL in a web application.

Runtime: The period during which a program is running, from start to finish.

Sale: An act of exchanging something for money.

Save the date: Tells someone the date of an event so they can keep that day free and be able to attend the event.

Schedule: A list of planned activities or things to be done showing the times or dates when they are intended to happen or be done.

Schema: The structure of a database, defining how data is organized and how relationships between entities are formed.

Scope: The range of a subject covered by a book, program, discussion, class, etc.

Script: A file containing a sequence of commands that are executed automatically by a certain program or engine.

SEM (Search Engine Marketing): A digital marketing strategy that uses paid ads to promote websites on search engines.

Seniority: Higher rank or advantage obtained as a result of the length of job service.

SEO (Search Engine Optimization) - The practice of optimizing a website to improve its visibility and ranking on search engines.

Server: A computer or system that provides resources, services, or data to other computers over a network.

Service discovery: The process of automatically detecting devices and services on a network.

Service Level Agreement (SLA): A contract that outlines the expected level of service between a service provider and a client.

Service worker: A script that runs in the background of a web application, enabling features like push notifications and offline functionality.

Session: A period during which a user interacts with a web application, often associated with session data stored on the server.

Share: One of the equal parts that the ownership of a company is divided into, and that can be bought by members of the public.

Shareholder: An individual, institution, or entity that owns shares or stock in a corporation or company, representing ownership interest in the company and entitling the shareholder to voting rights, dividends, and a share of the company's assets and profits.

Shell: A user interface that provides access to the operating system's services, either through a command-line interface (CLI) or a graphical user interface (GUI).

Shipping charge: The monetary amount that customers are charged to ship their orders.

Single Page Application (SPA): A type of web app that loads a single HTML page and dynamically updates content without reloading the page.

Single Sign-On (SSO): An authentication process that allows a user to access multiple applications with one set of login credentials.

Sitemap: A file that lists all the URLs on a website, used by search engines to crawl and index the site more efficiently.

SMTP (Simple Mail Transfer Protocol): A protocol used to send emails between servers.

Snapshot: A saved state of a system or virtual machine at a specific point in time.

SNMP (Simple Network Management Protocol): A protocol used for network management, monitoring, and configuration.

Software: A set of instructions, data, or programs used to operate computers and execute specific tasks.

Source control: A system for tracking changes to source code, allowing developers to collaborate on code and maintain version history.

Sponsorship: Money that is given, usually by a company, to support a person, organization or activity.

SSL (Secure Sockets Layer): A cryptographic protocol that provides secure communication over the internet.

Stack: A data structure that follows the Last-In-First-Out (LIFO) principle, used for managing function calls and other tasks.

Staff: The group of people who work for an organization.

Stakeholder: An employee, investor, customer, etc. who is involved in or buys from a business and has an interest in its success.

Static site: A website that consists of fixed content delivered as is to the user's browser, without dynamic content generation.

Subnet: A segment of a network that shares a common network address and is used to divide larger networks into smaller, manageable pieces.

Supplier: A company, person, etc. that provides things that people want or need, especially over a long period of time.

Supply chain: The network or system of interconnected entities, organizations, and processes involved in the production, distribution, and delivery of goods, products, or services from suppliers to customers, encompassing activities such as sourcing, manufacturing, logistics, and retailing.

Supply and demand: The fundamental economic principle or law that describes the relationship between the availability (supply) and desire (demand) for goods, products, or services in the market, determining prices, quantities, and allocation of resources.

Switch: A network device that connects devices within a LAN and uses MAC addresses to forward data only to the intended recipient.

System integration: The process of combining various subsystems or components into a unified system that functions as a whole.

Target: A person or a particular group of people that something is directed at, or that something is intended for.

Tax: (An amount of) money paid to the government that is based on your income or the cost of goods or services you have bought.

TBA: Abbreviation for *To Be Announced*.

TBC: Abbreviation for *To Be Confirmed*.

TBD: Abbreviation for *To Be Determined*.

TCP/IP (Transmission Control Protocol/Internet Protocol): A suite of communication protocols used to interconnect network devices on the internet.

Template engine: A tool that allows you to generate HTML dynamically by combining templates with data, e.g., Handlebars, Pug.

Tenant: A person who pays rent for the use of land or a building.

Terabyte (TB): A unit of digital information storage equivalent to 1,024 gigabytes (1 trillion bytes).

Test-Driven Development (TDD): A software development process where tests are written before writing the actual code to ensure it works as expected.

Thread: The smallest unit of a process that can be executed independently by a CPU.

Throttling: The practice of limiting the rate at which data is sent or received to manage network congestion and resource usage.

Throughput: The rate at which data is successfully transmitted through a network or system.

Time-to-Live (TTL): A field in IP packets that specifies the maximum number of hops a packet can make before being discarded.

Timestamps: Values representing a specific point in time, commonly used for logging and tracking events.

TLS (Transport Layer Security): A cryptographic protocol designed to provide secure communication over a computer network.

Token: In authentication, a token is a piece of data that is used to verify the identity of a user or process.

Token ring: A type of network protocol where devices are connected in a ring and pass a token to transmit data.

Traceroute: A network diagnostic tool used to track the path packets take from one network host to another.

Trade war: A situation of escalated trade tensions, disputes, or conflicts between two or more countries or trading blocs, characterized by tariffs, import restrictions, sanctions, or retaliatory measures, with implications for global trade, economic growth, and market volatility.

Traffic shaping: Techniques used to control the flow and speed of network traffic to ensure optimal performance and avoid congestion.

Transpiler: A tool that converts code written in one programming language into another, commonly used to transform modern JavaScript into backward-compatible versions.

Treasurer: A person who is responsible for an organization's money.

Tree shaking: A technique used in bundlers to eliminate unused code from the final output, optimizing file size.

Trojan Horse: A type of malicious software that disguises itself as a legitimate program to trick users into executing it.

Tunneling protocol: A protocol that encapsulates network packets to allow them to be transmitted over a different network.

Turnover: The amount of business that a company does in a period of time.

Two-Factor Authentication (2FA): An additional layer of security where users must provide two forms of verification before gaining access to a system.

Type coercion: The process of converting a value from one data type to another, either explicitly or implicitly.

UDP (User Datagram Protocol): A communication protocol that provides connectionless, unreliable data transmission.

UML (Unified Modeling Language): A standardized modeling language used to visualize and document the design of software systems.

Unified Communications (UC): The integration of various communication tools and technologies into a single, unified platform.

Unified Threat Management (UTM): A comprehensive security solution that integrates multiple security functions into a single device or service.

Unsubscribe: A mechanism allowing users to opt-out or stop receiving communications, often used in email or notification systems.

Update: To make something more modern or suitable for use now by adding new information or changing its design.

Uptime: The amount of time a system or service is operational and available.

URL (Uniform Resource Locator): The address used to access resources on the internet.

Usability testing: The process of evaluating a website or application by testing it with real users to identify usability issues.

Usage statistics: Data collected about how network resources or services are used, often for analysis and optimization.

User account: A profile that provides access to a computer system or network, with associated permissions and settings.

User Experience (UX): The overall experience and satisfaction a user gets when interacting with a website or application.

User Interface (UI): The means by which a user interacts with a computer, application, or device.

User provisioning: The process of creating and managing user accounts and access rights within an IT system.

UUID (Universally Unique Identifier): A 128-bit number used to uniquely identify information in computer systems.

VAT: Abbreviation for *Value Added Tax* (IVA in Spanish).

Version control: A system that records changes to files or code over time, allowing for tracking and management of different versions.

Version Control System (VCS): A tool that helps track changes to files and coordinate work among multiple contributors.

Viewport: The visible area of a web page within the user's browser window.

Virtual Machine (VM): A software emulation of a physical computer that runs an operating system and applications.

Virtual Private Cloud (VPC): A private cloud environment within a public cloud provider's infrastructure, offering enhanced control and security.

Virtualization: The process of creating virtual versions of physical resources, such as servers, storage, and networks.

Visual regression testing: A process of automatically comparing visual changes in web pages or user interfaces to identify unintended differences.

VLAN (Virtual Local Area Network): A network that partitions and isolates segments of a physical LAN into multiple logical networks.

VoIP (Voice over Internet Protocol): A technology that allows voice communication over the internet.

Volatile Memory: A type of computer memory that requires power to maintain stored data, such as RAM.

VPN (Virtual Private Network): A method of creating a secure network connection over a public network, such as the internet.

Wage: An amount of money that is paid, usually every week, to an employee for their work.

WAN (Wide Area Network): A telecommunications network that extends over a large geographic area, often connecting multiple LANs.

WAN acceleration: Technologies and techniques used to improve the performance and efficiency of data transmission across a WAN.

WAN optimization: Techniques used to improve the performance and efficiency of data transmission across a WAN.

WAN Optimization Controller (WOC): A device or software that enhances the performance of wide area networks through various optimization techniques.

Warehouse: A large building for storing things before they are sold, used or sent out to shops.

Web accessibility: The practice of designing and developing websites so that people with disabilities can use them easily.

Web Application Firewall (WAF): A security solution that protects web applications by filtering and monitoring HTTP traffic between a web application and the internet.

Web server: A server that delivers web pages and other content to clients over the internet using HTTP or HTTPS.

Web vitals: A set of specific metrics Google considers important for the overall user experience of a web page, such as loading, interactivity, and visual stability.

Webhook: A method of triggering an action or event by sending real-time data from one application to another over the web.

WebSocket: A protocol that provides full-duplex communication channels over a single TCP connection, commonly used in real-time web applications.

WFH: Abbreviation for *Working From Home*.

Wholesale: Of or for the selling of goods in large amounts at low prices to shops and businesses, rather than the selling of goods in shops to customers.

Widget: A small application or program that provides specific functionality, often embedded in other programs or on websites.

Wi-Fi: A wireless networking technology that allows devices to connect to a network using radio waves.

Win to Win: A result that is good for everyone who is involved in a situation.

Wireframe: A visual guide that represents the skeletal framework of a website or application, used in the planning phase of design.

Workshop: A meeting of people to discuss and/or perform practical work in a subject or activity.

Worm: A type of malware that spreads copies of itself from one computer to another without user intervention.

WPA (Wi-Fi Protected Access): A security protocol designed to protect wireless networks by improving encryption and authentication.

X.25: An older packet-switched network protocol used for WAN connections.

X.400: A standard for electronic messaging systems that specifies message formats and protocols for email.

X.500: A series of standards specified by the International Telecommunication Union for directory services.

Xen: An open-source hypervisor that allows multiple operating systems to run on a single physical machine.

X-Forwarded-For: An HTTP header used to identify the originating IP address of a client connecting to a web server through a proxy.

XML (Extensible Markup Language): A flexible text format used for creating structured documents and data interchange between systems.

XOR (Exclusive OR): A logical operation that returns true if only one of the inputs is true but not both.

XSS (Cross-Site Scripting): A security vulnerability that allows attackers to inject malicious scripts into web pages viewed by other users.

YAML (YAML Ain't Markup Language): A human-readable data serialization standard that can be used in conjunction with various programming languages.

Yield: In networking, the term might refer to the effective bandwidth or throughput achieved.

Yottabyte: A unit of digital information equal to 1 septillion bytes (10^{24} bytes).

YoY: Abbreviation for *Year On Year*. Interannual.

YTD: Abbreviation for *Year To Date*.

Zebra network: A network topology or configuration used for balancing and distributing network traffic.

Zero-day exploit: A security vulnerability that is exploited before the software vendor has released a fix.

Zero trust security: A security model that requires verification of every user and device, regardless of whether they are inside or outside the network perimeter.

Zettabyte (ZB): A unit of digital information storage equivalent to approximately 1 trillion gigabytes.

ZIP: A file format used for data compression and archiving

Zone transfer: The process of replicating DNS zone data between DNS servers to ensure consistency and availability.

Zoning: In storage area networks (SANs), the practice of partitioning the SAN to control access and isolate traffic between different devices.

Zookeeper: A centralized service for maintaining configuration information, naming, and providing distributed synchronization.