

# Package ‘spatialSPsurv’

June 2, 2020

**Type** Package  
**Title** Bayesian Spatial Split Population Survival Model  
**Version** 0.1.3  
**Description** Contains functions to fit Bayesian spatial survival model for split population.  
**License** MIT + file LICENSE  
**Encoding** UTF-8  
**LazyData** true  
**RoxygenNote** 7.1.0  
**LinkingTo** Rcpp,  
RcppArmadillo  
**Imports** MCMCpack,  
FastGP,  
stats,  
Rcpp,  
RcppArmadillo,  
coda

## R topics documented:

frailtySPsurv . . . . .	1
spatialSPsurv . . . . .	2
SPsurv . . . . .	4
<b>Index</b>	<b>5</b>

---

frailtySPsurv	<i>frailtySPsurv</i>
---------------	----------------------

---

## Description

Markov Chain Monte Carlo (MCMC) to run Bayesian non-spatial frailty split population survival model

**Usage**

```

frailtySPsurv(
  duration,
  immune,
  Y0,
  LY,
  S,
  data,
  N,
  burn,
  thin,
  w = c(1, 1, 1),
  m = 10,
  form = c("Weibull", "exponential", "loglog"),
  prop.var
)

```

**Arguments**

duration	...
immune	...
Y0	the elapsed time since inception until the beginning of time period (t-1)
LY	last observation year
S	spatial information (e.g. district ID) for each observation that matches the spatial matrix row/column information
data	...
N	number of MCMC iterations
burn	burn-in to be discarded
thin	thinning to prevent from autocorrelation
w	size of the slice in the slice sampling for (betas, gammas, rho). Write it as a vector. E.g. c(1,1,1)
m	limit on steps in the slice sampling. A vector of values for beta, gamma, rho.
form	type of parametric model (Exponential or Weibull)
prop.var	...

**Value**

chain of the variables of interest

---

spatialSPsurv

*spatialSPsurv*


---

**Description**

Markov Chain Monte Carlo (MCMC) to run Bayesian spatial split population survival model

**Usage**

```

spatialSPsurv(
  duration,
  immune,
  Y0,
  LY,
  S,
  A,
  data,
  N,
  burn,
  thin,
  w = c(1, 1, 1),
  m = 10,
  form = c("Weibull", "exponential", "loglog"),
  prop.var
)

```

**Arguments**

duration	...
immune	...
Y0	the elapsed time since inception until the beginning of time period (t-1)
LY	last observation year
S	spatial information (e.g. district ID) for each observation that matches the spatial matrix row/column information
A	Spatial Matrix (load separate spatial weights matrix file)
data	...
N	number of MCMC iterations
burn	burn-in to be discarded
thin	thinning to prevent from autocorrelation
w	size of the slice in the slice sampling for (betas, gammas, rho). Write it as a vector. E.g. c(1,1,1)
m	limit on steps in the slice sampling. A vector of values for beta, gamma, rho.
form	type of parametric model (Exponential or Weibull)
prop.var	proposal variance for Metropolis-Hastings

**Value**

chain of the variables of interest

---

 SPsurv

*SPsurv*


---

### Description

Markov Chain Monte Carlo (MCMC) to run Bayesian split population survival model with no frailties

### Usage

```
SPsurv(
  duration,
  immune,
  Y0,
  LY,
  data,
  N,
  burn,
  thin,
  w = c(1, 1, 1),
  m = 10,
  form = c("Weibull", "exponential", "loglog")
)
```

### Arguments

duration	...
immune	...
Y0	the elapsed time since inception until the beginning of time period (t-1)
LY	last observation year
data	...
N	number of MCMC iterations
burn	burn-in to be discarded
thin	thinning to prevent from autocorrelation
w	size of the slice in the slice sampling for (betas, gammas, rho). Write it as a vector. E.g. c(1,1,1)
m	limit on steps in the slice sampling. A vector of values for beta, gamma, rho.
form	type of parametric model (Exponential or Weibull)

### Value

chain of the variables of interest

# Index

frailtySPsurv, [1](#)

spatialSPsurv, [2](#)

SPsurv, [4](#)