Automatic Cache Aware Roofline Model Building and Validation Using Topology Detection

Nicolas Denoyelle - Aleksandar Ilic - Brice Goglin - Leonel Sousa - Emmanuel Jeannot

Inria (France) - INESC-ID (Portugal) - Inria (France) - INESC-ID (Portugal) - Inria (France)

October 3, 2016

NESUS
Network for Sustainable Ultrascale Computing

1 Introduction

2 The Cache Aware Roofline Model

3 Tool and Validation

4 Conclusion & Future Work

NESUS
Network for Sustainable Ultrascale Computing

Hardware Complexity is Growing

- ↗ Cores: up to 72 on Intel KNL.
- ↘ Memory per Core.
- ↗ Cache Sharing .
- ↗ Cache Hierarchy: several levels, side cache *etc. . .*



NESUS
Network for Sustainable Ultrascale Computing

1 Introduction

2 The Cache Aware Roofline Model

3 Tool and Validation

4 Conclusion & Future Work

NESUS
Network for Sustainable Ultrascale Computing

The Cache Aware Roofline Model (CARM)

The Cache Aware Roofline Model (CARM) simplifies this for you !

- What is the best you can get from the chip ? [Platform Model]
- Is it worth investing in code optimization ? [Application Model]

Platform Model

Improvement over the Original Roofline Model (ORM).

Assumptions:

- The machine is bound whether by the memory unit or by the compute unit.
- Both unit are not dependent on each other.



NESUS
Network for Sustainable Ultrascale Computing

Application Model

$$ddot = ddot + b[i] * c[i] \quad (1)$$

- memory: $b[i], c[i] = 8 + 8 Bytes$
- compute: $+, * = 2 flops$
- arithmetic intensity: $2^{-3} Flops/Bytes$
- performance: $Flops/Time$

ORM versus CARM



Bytes transferred from DRAM to last level cache



Bytes issued from Cores.

NESUS
Network for Sustainable Ultrascale Computing

1 Introduction

2 The Cache Aware Roofline Model

3 Tool and Validation

4 Conclusion & Future Work

NESUS
Network for Sustainable Ultrascale Computing

A Tool to Build and Validate the Model

Build Model from Portable Blocks

- Hwloc gives the machine informations: cache structure and attributes, cores.
- The compiler gives architecture type and let us select the best instruction set.

Micro-Benchmark Each Unit

- Bandwidth benchmark each cache level, and several stream types: Load, Store, 2Loads/Store.
- Floating Point peak benchmark: MUL, ADD, MAD, FMA.
- Micro Benchmarks of several operational intensity for validation.

NESUS
Network for Sustainable Ultrascale Computing

A Tool for Non Experts

Easy steps

- Build the model for the target platform.
- Collect CARM metrics from your application with our library (Hardware counters: PAPI).
- Plot this on a chart and get insights on your application.

Quick Glance if the Model is Wrong

- Validation matches model ?
- Micro-Benchmarks matches theoretical throughput ?

NESUS
Network for Sustainable Ultrascale Computing

1 Introduction

2 The Cache Aware Roofline Model

3 Tool and Validation

4 Conclusion & Future Work

NESUS
Network for Sustainable Ultrascale Computing

Conclusion

We provide a Tool to build the CARM and model applications.
It is portable and easy to use. It reaches near theoretical architecture throughput.

Future Work

The CARM gives insight over Caches (i.e temporal locality).
We will use it to model system heteogeneous memory, and give insights on data locality.

NESUS
Network for Sustainable Ultrascale Computing

Thank you !

https://github.com/NicolasDenoyelle/LARM-Locality-Aware-Roofline-Model-

Automatic Cache Aware Roofline Model Building and Validation Using Topology Detection

Nicolas Denoyelle - Aleksandar Ilic - Brice Goglin - Leonel Sousa - Emmanuel Jeannot

Inria (France) - INESC-ID (Portugal) - Inria (France) - INESC-ID (Portugal) - Inria (France)

October 3, 2016